


DRAWING INDEX

DRAWING No.	DESCRIPTION
C 1.0	COVER SHEET, SITE LOCATION, AND DRAWING INDEX
C 1.1	STANDARD LEGEND AND ABBREVIATIONS
C 1.2	GENERAL NOTES
C 2.0	EXISTING SURVEY
C 2.1	DEMOLITION PLAN
C 3.0	SITE PLAN
C 4.0	GRADING PLAN
C 5.0	DRAINAGE PLAN
C 5.1	EROSION CONTROL PLAN
C 6.0	UTILITES PLAN
C 7.0	LANDSCAPING PLAN
C 8.0	EROSION CONTROL DETAILS
C 8.1	MISCELLANEOUS DETAILS
C 8.2	MISCELLANEOUS DETAILS
C 9.0	ADS PLAN
C 9.1	ADS PLAN
C 9.2	ADS PLAN
C 9.3	ADS PLAN
C 9.4	ADS PLAN
C 9.5	ADS PLAN
C 9.6	ADS PLAN

APPENDIX


DRAWING No.	DESCRIPTION
AP 1	ACCESS PERMIT PLAN
AP 2	TRAFFIC CONTROL DETAILS
AP 3	TRAFFIC CONTROL DETAILS
AP 4	TRAFFIC CONTROL DETAILS



EXPRESS OIL CHANGE
NORTHPORT


1803 27TH ST
NORTHPORT, ALABAMA

PREPARED BY:



INSITE
ENGINEERING

INSITE ENGINEERING, LLC.
5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-9696
FAX (205) 733-9697



LOCATION MAP

SCALE: NONE



**INSITE
ENGINEERING**

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-9696
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL


CONSTRUCTION PLANS FOR:

**EXPRESS OIL CHANGE
NORTHPORT**

NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24




THIS SHEET CONTAINS:
COVER SHEET,
SITE LOCATION,
AND DRAWING
INDEX

C 1.0

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING OR ITS CONTENTS MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT PERMISSION IN WRITING FROM INSITE ENGINEERING, LLC.

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING IS TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT PERMISSION IN WRITING FROM INSITE ENGINEERING, LLC. COPYRIGHT © 2023 INSITE ENGINEERING, LLC.



**INSITE
ENGINEERING**

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE: (205) 733-0698
www.insiteengineering.org


CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:
**EXPRESS OIL CHANGE
NORTHPORT**
NORTHPORT, ALABAMA

**REVIEW
DRAWING**
(NOT FOR CONSTRUCTION)

PROJECT INFO:

INSITE JOB No. 24041.00
PLOTTED: 12/2/24



THIS SHEET CONTAINS:
GENERAL NOTES

C 1.2

PROJECT SPECIFIC NOTES

1. FLOOD HAZARD RISK, IF ANY, ASSOCIATED WITH THIS PROPERTY MAY BE FOUND IN THE DETAILED DRAINAGE REPORT. THIS INFORMATION HAS BEEN OBTAINED FROM THE FEMA MAPPING SERVICE AND FOR FURTHER INFORMATION SEE THE APPROPRIATE FEMA FLOOD PANEL.
2. A SUBSURFACE INVESTIGATION HAS BEEN PREFORMED BY TERRACON ON MAY 6 2024. WORK SHALL BE DONE IN ACCORDANCE WITH GEOTECHNICAL REPORT DATED MAY 6 2024.
3. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE CURRENT SUBDIVISION REGULATIONS AND DESIGN STANDARDS OF THE GOVERNING AUTHORITY.
4. CONTRACTOR IS RESPONSIBLE FOR BUILDING SITES FREE OF DRAINAGE PROBLEMS DUE TO ANY DEVIATION FROM THE DESIGN PLANS.
5. GOVERNING AUTHORITIES ARE NOT RESPONSIBLE FOR ANY DRAINAGE EASEMENT OUTSIDE THE PUBLIC RIGHT-OF-WAY.
6. THE GOVERINING AUTHORITY IS NOT, NOR EVER WILL BE RESPONSIBLE FOR MAINTENANCE OF PRIVATE ROADS, EASEMENTS, OR AREAS OFF PUBLIC RIGHTS OF WAY.
7. CONTRACTOR SHALL NOTIFY GOVERNING AUTHORITIES A MINIMUM OF 24 HOURS PRIOR TO BEGINNING ANY WORK WITHIN THE RIGHT-OF-WAY OF EXISTING ROADS.
8. ALL FEMA, USACE, COUNTY, AND/OR STATE PERMITS SHALL BE IN HAND AND ON SITE DURING THE CONSTRUCTION OF THE PROJECT.
9. A SIGNED AND SEALED COPY OF THE PLANS SHALL BE MAINTAINED ON SITE AND MADE READILY AVAILABLE FOR THE DURATION OF THE CONSTRUCTION.
10. CONTRACTOR SHALL KEEP A MARKED UP SET OF PLANS SHOWING ALL CHANGES, DIMENSIONS, ETC. TO PROVIDE TO THE ENGINEER AFTER THE JOB IS COMPLETE AND CAPABLE OF BEING UTILIZED AS AS-BUILT DRAWINGS FOR FUTURE LOCATES.

GENERAL NOTES

1. CONTRACTOR SHALL COORDINATE BETWEEN ARCHITECTURAL, MECHANICAL, STRUCTURAL, ELECTRICAL, AND OTHER DRAWINGS. ANY DISCREPANCIES BETWEEN DRAWINGS OF DIFFERENT DISCIPLINES SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE ENGINEER.
2. UNDERGROUND UTILITY LOCATIONS SHOWN ARE FROM UTILITY COMPANY RECORDS OR FROM LINE LOCATOR MARKS AND ARE SHOWN IN APPROXIMATE MANNER ONLY. CONTRACTOR SHALL FIELD VERIFY THE EXISTENCE, LOCATION, SIZE, AND TYPE OF ANY AND ALL UTILITY LINES PRIOR TO BEGINNING ANY CONSTRUCTION. CONTRACTOR IS RESPONSIBLE FOR ANY DAMAGE TO EXISTING UTILITIES AS A RESULT OF HIS CONSTRUCTION OPERATIONS.
3. CONTRACTOR IS SOLELY RESPONSIBLE FOR CONSTRUCTION METHODS, SEQUENCES, PROCEDURES, AND JOB SITE SAFETY. THE CONTRACTOR SHALL TAKE ALL MEANS NECESSARY TO MAINTAIN AND PROTECT THE INTEGRITY OF ALL CONSTRUCTION (NEW AND EXISTING) AT ALL STAGES. ENGINEER ASSUMES NO LIABILITY FOR SAFETY ON THE JOB SITE.
4. ALL UTILITIES WITHIN ROADWAY SHALL BE BACKFILLED COMPLETELY WITH STONE UNLESS OTHERWISE DIRECTED BY THE GEOTECHINAL ENGINEER OR THE GOVERNING AUTHORITY.
5. ALL AREAS WHICH WILL LIE UNDER NEW STRUCTURES, PAVING, CONCRETE, OR WALKWAYS SHALL BE COMPACTED TO 98% STANDARD PROCTOR DENSITY.
6. ALL PERMITS, OTHER THAN THOSE LISTED IN THE SPECIFICATIONS, FOR THE DEVELOPMENT OF THESE PLANS ARE THE CONTRACTORS RESPONSIBILITY AND SHOULD BE OBTAINED PRIOR TO DISTURBING ANY AREAS OR BEGINNING ANY CONSTRUCTION.
7. CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVAL AND LEGAL DISPOSAL OF ALL MATERIALS AND DEBRIS NOT ACCEPTABLE TO THE OWNER.
8. CONTRACTOR SHALL COORDINATE HIS WORK WITH ALL OTHER CONCURRENT WORK BEING PERFORMED IN THE AREA.

GRADING NOTES

1. EMBANKMENTS WITHIN THE RIGHT-OF-WAY SHALL BE CONSTRUCTED IN MAX. 10" LIFTS AND MIN. 98% COMPACTION (AASHTO T - 180) UNLESS OTHERWISE DIRECTED BY GEOTECHNICAL ENGINEER.
2. NO WORK TO BE DONE IN EITHER ALDOT OR COUNTY RIGHT-OF-WAY UNTIL ALL APPROPRIATE PERMITS ARE PROVIDED TO THE CITY.
3. CITY ENGINEER TO BE PROVIDED AT LEAST 24 HOURS NOTICE PRIOR TO THE STARTING OF EACH PHASE OF WORK.
4. ALL PERMITS/APPROVALS BY ADEM, ALDOT, FEMA, CORPS OF ENGINEERS WILL BE REQUIRED PRIOR TO DISTURBING AREAS UNDER JURISDICTIONS OF SUCH PERMITS.
5. THERE SHALL BE NO LAND DISTURBING ACTIVITY UNTIL PROOF OF ADEM NOR COVERAGE IS PROVIDED TO THE CITY AND ADEQUATE EROSION CONTROL MEASURES ARE IN PLACE.
6. ELEVATIONS SHOWN ARE FINISHED GRADE. THE CALCULATION OF THE APPROPRIATE SUBGRADE ELEVATIONS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. SUBGRADE ELEVATIONS SHALL VARY IN ACCORDANCE WITH THE SURFACE TREATMENT CALL FOR ON THESE PLANS (I. E. ASPHALT PAVEMENT, CONCRETE PAVEMENT, SIDEWALK, TOPSOIL, ETC.) AND THE RELATED SECTIONS OR DETAILS.
7. CONTRACTOR SHALL TIE PROPOSED PAVING INTO EDGE OF EXISTING PAVING. CONTRACTOR SHALL ADJUST CROSS SECTION AS REQUIRED TO ENSURE SMOOTH PAVEMENT TRANSITIONS AND POSITIVE DRAINAGE. CURB AND GUTTER SHALL BE WORKMANLIKE, SMOOTH, AND ENSURE POSITIVE DRAINAGE.
8. ALL CUT AND FILL SIDE SLOPES ARE 2:1 UNLESS NOTED OTHERWISE. UNLESS OTHERWISE DIRECTED BY GEOTECHNICAL ENGINEER.
9. CLEARING LIMITS TO BE 5' OUTSIDE OF TOE AND TOP OF SLOPE.
10. CONTRACTOR SHALL OVER EXCAVATE ALL PONDS BY ADEQUATE AMOUNT IN ORDER TO ALLOW FOR SEDIMENTATION OF THE WATER ENTERING THE DETENTION FACILITIES.
11. DIMENSIONS AND RADII ARE SHOWN TO EDGE OF PAVEMENT, UNLESS OTHERWISE NOTED.
12. ELEVATION SPOTS ARE TO EDGE OF PAVEMENT UNLESS OTHERWISE NOTED

EROSION CONTROL NOTES

1. ALL EROSION CONTROL PERMITS FOR THE DEVELOPMENT OF THESE PLANS SHALL BE OBTAINED BY THE CONTRACTOR PRIOR TO ANY GROUND DISTURBANCE.
2. EROSION CONTROL MEASURES ARE TO BE INSTALLED PRIOR TO BEGINNING ANY OTHER CONSTRUCTION ON THE JOB SITE.
3. CONTRACTOR IS RESPONSIBLE FOR INSTALLING, MAINTAINING, AND REMOVING ALL EROSION AND SEDIMENT CONTROLS IN ACCORDANCE WITH BEST MANAGEMENT PRACTICES AS SHOWN ON THESE DRAWINGS OR REQUIRED BY LOCAL, STATE, AND/OR FEDERAL REGULATORY AUTHORITIES.
4. THE EROSION AND SEDIMENT CONTROL MEASURES SHOWN ON THESE DRAWINGS ARE CONSIDERED THE MINIMUM ACCEPTABLE AND SHALL BE MODIFIED IN THE FIELD AS NECESSARY TO COMPLY WITH LOCAL, STATE, AND/OR FEDERAL REQUIREMENTS.
5. EROSION CONTROL MEASURES MUST BE MAINTAINED UNTIL PERMANENT GROUND COVER IS ESTABLISHED AND THE NPDES PERMIT IS TERMINATED.
6. ALL DISTURBED AREAS NOT SHOWN TO BE LANDSCAPED SHALL BE SEEDED & MULCHED AS PER LOCAL STANDARDS AND SPECIFICATIONS.
7. CONTRACTOR SHALL COMPLY WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS RELATING TO THE ONSITE STORAGE OF FUEL, OIL, AND GREASE. AN SPCC PLAN MUST BE MAINTANED AND IMPLEMENTED ON SITE.
8. STREAMS SHALL NOT BE USED AS TRANSPORTATION ROUTES FOR HEAVY EQUIPMENT. CROSSINGS SHALL BE LIMITED TO ONE POINT AND EROSION CONTROL MEASURES MUST BE UTILIZED WHERE STREAM BANKS AND DRAINAGE DITCHES ARE DISTURBED.

EROSION CONTROL SEQUENCE

ALL CONSTRUCTION SHALL BE DONE IN A LOGICAL SEQUENCE SO TO MINIMIZE THE AREA OF DISTURBANCE.

1. OBTAIN REQUIRED PERMITS.
2. STAKE PROPERTY LINES AND CLEARING LIMITS.
3. SELECTIVELY CLEAR PATH AS REQUIRED TO INSTALL SILT FENCING AND PERIMETER EROSION CONTROL MEASURES.
4. INSTALL SILT FENCES ALONG SIDE SLOPE BOUNDARIES.
5. INSTALL STONE ENTRANCE DRIVE.
6. PROTECT STORM DRAIN INLETS DOWNSTREAM OF CONSTRUCTION WITH HAY BALES, WATTLES, SILT FENCE AND/OR OTHER PROTECTIVE MEASURES.
7. INSTALL OTHER REQUIRED EROSION CONTROL MEASURES DOWNSTREAM OF PROJECT AREA.
8. PERFORM CLEARING AND GRUBBING.
9. INSTALL SILT FENCE AROUND STOCKPILES.
10. BEGIN EARTHWORK AND CONSTRUCT PROJECT.
11. MODIFY AND MAINTAIN EROSION CONTROL AS REQUIRED DURING CONSTRUCTION.
12. INSPECT ALL EROSION CONTROL MEASURES AFTER EVERY 0.50" RAINFALL. COPIES OF ALL INSPECTION REPORTS SHALL BE SUBMITTED TO THE PROPER AUTHORITIES IN ACCORDANCE WITH APPLICABLE PERMITS.
13. TEMPORARILY OR PERMANENTLY STABILIZE STRIPPED AREAS AND STOCKPILES LEFT INACTIVE FOR 14 OR MORE CALENDAR DAYS.
14. REMOVE ANY SEDIMENT REACHING PUBLIC OR PRIVATE ROADWAYS BY STREET CLEANING BEFORE THE END OF EACH DAY. FLUSHING OF STREETS WILL NOT BE ALLOWED
15. INSTALL TEMPORARY SEDIMENTATION PONDS OR DIVERSION BERMS AS NEEDED TO CONTROL THE FLOW OF WATER AND COLLECTION OF SEDIMENT DURING THE PROJECT.
16. COMPLETE FINE GRADING AND INSTALL PERMANENT SEEDING AND PLANTING.
17. COMPLETE FINAL PAVING FOR ROADS.
18. REMOVE SILT FENCE UPON COMPLETION OF ALL CONSTRUCTION ACTIVITY.
19. RESEED AND STABILIZE ANY BARE SPOTS OR WASHOUTS.
20. TERMINATE ALL PERMITS.

**EROSION CONTROL PLAN
AND PERFORMANCE STANDARDS**

1. THE EROSION CONTROL PLAN SHALL CONTAIN A DESCRIPTION OF THE EXISTING SITE CONDITIONS, A DESCRIPTION OF ADJACENT TOPOGRAPHICAL FEATURES, INFORMATION NECESSARY TO DETERMINE THE EROSION QUALITIES OF THE SOIL ON THE SITE, POTENTIAL PROBLEM AREAS OF SOIL EROSION AND SEDIMENTATION, SOIL STABILIZATION SPECIFICATIONS, STORM WATER MANAGEMENT CONSIDERATIONS, PROJECTED TIME SCHEDULE FOR COMMENCEMENT AND COMPLETION OF THE LAND-DISTURBING ACTIVITY, SPECIFICATIONS FOR BMP PLAN MAINTENANCE DURING THE PROJECT AND AFTER THE COMPLETION OF THE PROJECT, CLEARING AND GRADING LIMITS, AND ALL OTHER INFORMATION NEEDED TO DEPICT ACCURATELY THE SOLUTIONS TO POTENTIAL SOIL EROSION AND SEDIMENTATION PROBLEMS TO THE MS4. THE CONTROL PLAN SHALL INCLUDE THE SERIES OF BMP'S AND SHALL BE REVIEWED BY, AND SUBJECT TO THE APPROVAL OF, THE OFFICIAL PRIOR TO THE ISSUANCE OF THE PERMIT.
2. CONTROL MEASURES SHALL BE MAINTAINED AS AN EFFECTIVE BARRIER TO SEDIMENTATION AND EROSION IN ACCORDANCE WITH THIS PLAN.
3. THERE SHALL BE NO DISTINCTLY VISIBLE FLOATING SCUM, OIL OR OTHER MATTER CONTAINED IN THE STORM WATER DISCHARGE. THE STORM WATER DISCHARGE TO AN MS4 MUST NOT CAUSE AN UNNATURAL COLOR (EXCEPT DYES OR OTHER SUBSTANCES DISCHARGED TO AN MS4 FOR THE PURPOSE OF ENVIRONMENTAL STUDIES AND WHICH DO NOT HAVE HARMFUL EFFECT ON THE BODIES OF WATER WITHIN THE MS4) OR ODOR IN THE COMMUNITY WATERS. THE STORM WATER DISCHARGE TO THE MS4 MUST RESULT IN NO MATERIALS IN CONCENTRATIONS SUFFICIENT TO BE HAZARDOUS OR OTHERWISE DETRIMENTAL TO HUMANS, LIVESTOCK, WILDLIFE, PLANT LIFE OR FISH AND AQUATIC LIFE IN THE COMMUNITY WATERS.

- TABLE A
- Monuments shown on survey.
 - Property address:
 - Flood zone: ZONE X FIRM MAP NUMBER 01125C0502F EFFECTIVE DATE SEPTEMBER 28, 2007
 - Gross land area 0.51 ACRES
 - vertical relief: 1' contour
 - Zoning noted on survey: N/A
 - Setback requirements: N/A
 - Exterior dimensions of all buildings are shown on survey:
 - Square footage of exterior footprint of buildings are ground level N/A
 - Measured height of building above grade is noted on survey. N/A
 - Substantial features shown on the survey.
 - Number of parking spaces and disabled, none
 - As designated by client a determination of the relationship and location of certain division of party walls with respect to adjoining properties.
 - Evidence of underground utilities existing on or serving the surveyed property is based online location 811.
 - N/A
 - Name of adjoining landowners is shown on the survey.
 - N/A
 - N/A
 - No Evidence of recent earth moving work, building construction, or building additions observed in the process of conducting the fieldwork.
 - NO proposed changes in street right of ways lines, NO evidence of recent street or sidewalk construction or repairs.
 - No plottable offsite (i.e., appurtenant) easements disclosed in documents provided to or obtained by the surveyor.

TITLE COMMITMENT

To:
This is to certify that this map or plat and the survey on which it is based were made in accordance with the 2021 Minimum Standard Detail Requirements for ALTA/NSPS Land Title Surveys, jointly established and adopted by ALTA and NSPS, and includes items 1,2,3,4,8,10,11a,13,16,17, of Table A thereof. The fieldwork was completed on APRIL 11 2024.

James M. Ray PLS
Reg#18383

Account Pin STR 43932 1 57956 10-215-10W
Parcel No: 63 31 02 10 3 015 001.000
Prop. Addr: 1803 27TH ST
Tax Dist 05 - Northport Exemption/Not Exempt
Deeded Acres: 0.0000 Calc 05-15-2003
Deed Bk/Pg Date: 2003 0873 05-15-2003
Plat Info: Book 0002 Page 0036
Sub InfoSub Block 6 Lot 9
Subdivisions: KENNEDY ADD
Owner: L ETANG & MARTIN LLC
Address: PO BOX 944
City, State, ZIP: NORTHPORT, AL 35476

BEARING BASED ON STATE PLANE
WEST ZONE NAD83
ELEVATION IS BASED ON NAVD 88

LEGEND

- SS - SS - SS - SS - SS - SS - SS
E - E - E - E - E - E - E
W - W - W - W - W - W - W
G - G - G - G - G - G - G
F - F - F - F - F - F - F
M - MEASURED BY SURVEY
R - PER A RECORD DOCUMENT
- ⊕ LIGHT POLE
⊙ POWER POLE
⊙ GUY ANCHOR
⊙ WATER METER
⊙ WATER VALVE
⊙ SEWER MANHOLE
⊙ FIRE HYDRANT
⊙ PHONE PEDESTAL

- SEWER LINE
AERIAL POWER LINE
WATER LINE
NATURAL GAS
FIBER LINE
M-MEASURED BY SURVEY
R-PER A RECORD DOCUMENT

SSMH
TOP RIM EL. 224.81
INV EL. 221.31

Account Pin STR 49214 1 72247 10-215-10W
Parcel No: 63 31 02 10 3 015 001.000
Prop. Addr: 2401 LURLEEN B WALLACE BLVD
Tax Dist 05 - Northport Exemption/Not Exempt
Deeded Acres: 0.0000 Calc 05-15-2003
Deed Bk/Pg Date: 2003 0873 05-15-2003
Plat Info: Book 0002 Page 0036
Sub InfoSub Block 6 Lot 9
Subdivisions: KENNEDY ADD
Owner: BYRDS FOUR SOME LLC
Address: 3333 FAIRFAX RD
City, State, ZIP: BIRMINGHAM, AL 35223

Account Pin STR 47358 1 35157 10-215-10W
Parcel No: 63 31 02 10 3 007 005.000
Prop. Addr: 1701 LURLEEN B WALLACE BLVD
Tax Dist 05 - Northport Exemption/Not Exempt
Deeded Acres: 0.0000 Calc 05-15-2003
Deed Bk/Pg Date: 2003 0873 05-15-2003
Plat Info: Book 0002 Page 0036
Sub InfoSub Block 6 Lot 9
Subdivisions: KENNEDY ADD
Owner: BUDDYS RESTAURANT PROPERTIES LLC
Address: 2501 REDDUB LN
City, State, ZIP: TUSCALOOSA, AL 35405

Account Pin STR 46328 1 71598 10-215-10W
Parcel No: 63 31 02 10 3 015 001.000
Prop. Addr: 1803 27TH ST
Tax Dist 05 - Northport Exemption/Not Exempt
Deeded Acres: 0.0000 Calc 05-15-2003
Deed Bk/Pg Date: 2003 0873 05-15-2003
Plat Info: Book 0002 Page 0036
Sub InfoSub Block 6 Lot 9
Subdivisions: KENNEDY ADD
Owner: BECKER LAND & TIMBER COMPANY
Address: PO BOX 2507
City, State, ZIP: TUSCALOOSA, AL 35403


Account Pin STR 46328 1 71598 10-215-10W
Parcel No: 63 31 02 10 3 015 001.000
Prop. Addr: 1803 27TH ST
Tax Dist 05 - Northport Exemption/Not Exempt
Deeded Acres: 0.0000 Calc 05-15-2003
Deed Bk/Pg Date: 2003 0873 05-15-2003
Plat Info: Book 0002 Page 0036
Sub InfoSub Block 6 Lot 9
Subdivisions: KENNEDY ADD
Owner: BECKER LAND & TIMBER COMPANY
Address: PO BOX 2507
City, State, ZIP: TUSCALOOSA, AL 35403

Account Pin STR 46842 1 25404 10-215-10W
Parcel No: 63 31 02 10 3 015 001.000
Prop. Addr: 2612 18TH AVE
Tax Dist 05 - Northport Exemption/Not Exempt
Deeded Acres: 0.0000 Calc 05-15-1988
Deed Bk/Pg Date: 1988 00607 05-15-1988
Plat Info: Book 0002 Page 0036
Sub InfoSub Block 6 Lot 9
Subdivisions: KENNEDY ADD
Owner: FIRST FREE WILL BAPTIST CHURCH
Address: 2401 LURLEEN B WALLACE BLVD
City, State, ZIP: NORTHPORT, AL 35476

Account Pin STR 46597 1 72742 10-215-10W
Parcel No: 63 31 02 10 3 014 003.000
Prop. Addr: 2615 18TH AVE
Tax Dist 05 - Northport Exemption/Not Exempt
Deeded Acres: 0.0000 Calc 05-15-1993
Deed Bk/Pg Date: 1993 00225 05-15-1993
Plat Info: Book 0002 Page 0036
Sub InfoSub Block 6 Lot 9
Subdivisions: KENNEDY ADD
Owner: RAY GLADYS M ETAL
Address: 3914 NORTHWOOD LAKE DR W
City, State, ZIP: NORTHPORT, AL 35473

Account Pin STR 4807 1 25618 10-215-10W
Parcel No: 63 31 02 10 3 014 002.000
Prop. Addr: 2655 18TH AVE
Tax Dist 05 - Northport Exemption/Not Exempt
Deeded Acres: 0.0000 Calc 05-15-2003
Deed Bk/Pg Date: 2003 00265 05-15-2003
Plat Info: Book 0002 Page 0036
Sub InfoSub Block 6 Lot 9
Subdivisions: KENNEDY ADD
Owner: KE EMMA J
Address: 2655 18TH AVE
City, State, ZIP: NORTHPORT, AL 35476

Account Pin STR 101217 1 345 10-215-10W
Parcel No: 63 31 02 10 3 006 002.000
Prop. Addr: 2705 18TH AVE
Tax Dist 05 - Northport Exemption/Not Exempt
Deeded Acres: 0.0000 Calc 05-09-2022
Deed Bk/Pg Date: 2022 05443 05-09-2022
Plat Info: Book 0002 Page 0036
Sub InfoSub Block 6 Lot 9
Subdivisions: KENNEDY ADD
Owner: OMEGA REZ 6B LLC
Address: 2518 VALLEYDALE RD
City, State, ZIP: BIRMINGHAM, AL 35242



INSITE ENGINEERING

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-0696
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE NORTHPORT

NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24

THIS SHEET CONTAINS:
EXISTING SURVEY

SCALE: 1"= 20'

C 2.0

ALTA/NSPS LAND TITLE SURVEY
APRIL 12 2024

NORTHPORT AL
TUSCALOOSA COUNTY

INSITE ENGINEERING
5800 FELDSPAR WAY
HOOVER, ALABAMA

RAY & GILLILAND, P.C.	
122 NORTH CALHOUN STREET P.O. BOX 1183 SYLACAUGA, ALABAMA 35150 DRAWN BY: JMR	TEL NO. (256) 245-3243 FAX NO. (256) 245-3202 FILE: EXPRESSOILNORTHPORT
ALTA SURVEY	APRIL 2024

ALL NOTIFICATIONS ARE TO GO BE SENT TO:
ENGINEERINGINSPECTIONS@CITYOFNORTHPORT.ORG



NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:
 INSITE JOB No. 24041.00
 PLOTTED: 12/2/24



SCALE: 1"= 20'

C 2.1

THIS DRAWING AND THE DESIGN SHOWN IS THE PROPERTY OF INSITE ENGINEERING, LLC
THE REPRODUCTION, COPYING, OR USE OF THIS DRAWING WITHOUT THEIR WRITTEN
CONSENT IS PROHIBITED AND ANY INFRINGEMENT WILL BE SUBJECT TO LEGAL ACTION.
COPYRIGHT © 2024, INSITE ENGINEERING, LLC


NOTE:
THE CITY OF NORTHPORT MUST BE NOTIFIED AT LEAST ONE BUSINESS DAY PRIOR TO EACH OF THE FOLLOWING ACTIVITIES:
- COMMENCEMENT OF CONSTRUCTION
- CLEARING AND GRUBBING
- CONSTRUCTION OF ANY PUBLIC INFRASTRUCTURE
- UNDER CURB COMPACTION TEST ON PUBLIC INFRASTRUCTURE
- SUB-GRADE COMPACTION TEST ON PUBLIC INFRASTRUCTURE
- BASE COMPACTION TEST ON PUBLIC INFRASTRUCTURE
- AIR AND MANDREL TEST ON PUBLIC SANITARY SEWER LINES
ALL NOTIFICATIONS ARE TO GO BE SENT TO:
ENGINEERINGINSPECTIONS@CITYOFNORTHPORT.ORG

CITY OF NORTHPORT MAIN CONTACT:
HOLLY PHILLIPS | (205) 333-7000 | HPHILLIPS@CITYOFNORTHPORT.ORG

PARKING CALCULATIONS:
SECTION 610.02.B.70 OF ZONING ORDINANCE:
1 SPACE / 400 SF OF OFFICE AND INDOOR DISPLAY AREA + 1 SPACE PER BAY
920 SF OF OFFICE AND INDOOR DISPLAY AREA / 400 SF + 8 BAYS = 11 REQUIRED
PROVIDED = 11 PARKING SPOTS

LAND USE: RESTAURANT
ZONING: C3

LAND USE: MULTIFAMILY
ZONING: RM



20' 0 20' 40'
GRAPHIC SCALE
1" = 20'

LEGEND

- HEAVY DUTY CONCRETE
- MEDIUM DUTY ASPHALT
- STANDARD DUTY ASPHALT
- EXISTING ASPHALT

NOTES:

- 4" BOLLARDS BETWEEN ALL BAY DOORS AND BUILDING CORNERS WHERE PAVEMENT MEETS BUILDING
- ADDITIONAL COORDINATES CAN BE REQUESTED IF NEEDED DURING CONSTRUCTION.
- REFER TO SHEETS AP 2, AP 3, AND AP 4 FOR TRAFFIC CONTROL DETAILS FOR CONNECTIONS TO 27TH STREET AND 18TH AVENUE.

LAND USE: HOUSE
ZONING: RS3

LAND USE: DOCTOR
ZONING: C3

LAND USE: BUSINESS
ZONING: C3

LAND USE: BUSINESS
ZONING: C3

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING IS TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT PERMISSION IN WRITING FROM INSITE ENGINEERING, LLC.



5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE: (205) 733-0698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:


EXPRESS OIL CHANGE NORTHPORT

NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:

INSITE JOB No. 24041.00
PLOTTED: 12/2/24




THIS SHEET CONTAINS:
SITE PLAN

SCALE: 1"= 20'

C 3.0

NOTE:
THE CITY OF NORTHPORT MUST BE NOTIFIED AT LEAST ONE BUSINESS DAY PRIOR TO EACH OF THE FOLLOWING ACTIVITIES:
- COMMENCEMENT OF CONSTRUCTION
- CLEARING AND GRUBBING
- CONSTRUCTION OF ANY PUBLIC INFRASTRUCTURE
- UNDER CURB COMPACTION TEST ON PUBLIC INFRASTRUCTURE
- SUB-GRADE COMPACTION TEST ON PUBLIC INFRASTRUCTURE
- BASE COMPACTION TEST ON PUBLIC INFRASTRUCTURE
- AIR AND MANDREL TEST ON PUBLIC SANITARY SEWER LINES
ALL NOTIFICATIONS ARE TO GO BE SENT TO:
ENGINEERINGINSPECTIONS@CITYOFNORTHPORT.ORG





**INSITE
ENGINEERING**

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-0698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL


CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE NORTHPORT

NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)


PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24



THIS SHEET CONTAINS:
GRADING PLAN

SCALE: 1"= 20'

C 4.0



NOTES:
1. CONTRACTOR SHALL ENSURE POSITIVE DRAINAGE TO INLETS OR OUTFALL LOCATIONS. NO PONDING OF WATER IS PERMITTED.

CONTRACTOR TO ENSURE ALL WATER DRAINS AWAY FROM BUILDING AND TOWARDS PROPOSED INLETS.

SLOPES LESS THAN 3:1 POSE NO STRUCTURAL RISK TO THE SITE.

SEE ARCH PLANS FOR WATER PROOFING ALONG BUILDING FOUNDATION

STORM DRAIN SEE C5.0 FOR INFO


THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING IS TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF INSITE ENGINEERING, LLC.

NOTE:

THE CITY OF NORTHPORT MUST BE NOTIFIED AT LEAST ONE BUSINESS DAY PRIOR TO EACH OF THE FOLLOWING ACTIVITIES:



- COMMENCEMENT OF CONSTRUCTION
- CLEARING AND GRUBBING
- CONSTRUCTION OF ANY PUBLIC INFRASTRUCTURE
- INTER CURB COMPACTION TEST ON PUBLIC INFRASTRUCTURE
- SUBGRADE COMPACTION TEST ON PUBLIC INFRASTRUCTURE
- BASE COMPACTION TEST ON PUBLIC INFRASTRUCTURE
- AIR AND MANDEL TEST ON PUBLIC SANITARY SEWER LINES

ALL NOTIFICATIONS ARE TO GO BE SENT TO:
ENGINEERINGINSPECTIONS@CITYOFNORTHPORT.ORG




NOTE:

1. THAT ALL UNDERGROUND UTILITIES REQUIRE AS-BUILT SURVEY. GC RESPONSIBLE TO COORDINATE WITH LOCAL AHJ ON AS-BUILT REQUIREMENTS.



DETAIL - OUTLET STRUCTURE

SCALE: NONE



5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-9696
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:


**EXPRESS OIL CHANGE
NORTHPORT**

NORTHPORT, ALABAMA

**REVIEW
DRAWING**
(NOT FOR CONSTRUCTION)

PROJECT INFO:

INSITE JOB No. 24041.00
PLOTTED: 12/2/24





THIS SHEET CONTAINS:
DRAINAGE PLAN

SCALE: 1"= 20'

C 5.0

THIS DRAWING AND THE DESIGN SHOWN IS THE PROPERTY OF INSITE ENGINEERING, LLC
THE REPRODUCTION, COPYING, OR USE OF THIS DRAWING WITHOUT THEIR WRITTEN
CONSENT IS PROHIBITED AND ANY INFRINGEMENT WILL BE SUBJECT TO LEGAL ACTION.
COPYRIGHT © 2024, INSITE ENGINEERING, LLC

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING OR ITS CONTENTS MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT PERMISSION IN WRITING FROM INSITE ENGINEERING, LLC. COPYRIGHT © 2024, INSITE ENGINEERING, LLC.



INSITE ENGINEERING
5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-0698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL


CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE NORTHPORT

NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24





THIS SHEET CONTAINS:
EROSION CONTROL
PLAN

SCALE: 1"= 20'

C 5.1

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING OR ITS CONTENTS MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT PERMISSION IN WRITING FROM INSITE ENGINEERING, LLC.





**INSITE
ENGINEERING**

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-0698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE
NORTHPORT


NORTHPORT, ALABAMA

REVIEW
DRAWING

(NOT FOR CONSTRUCTION)

PROJECT INFO:

INSITE JOB No. 24041.00
PLOTTED: 12/2/24




12/2/24

THIS SHEET CONTAINS:
UTILITIES PLAN

SCALE: 1"= 20'

C 6.0



CONSTRUCTION PLANS FOR:


**EXPRESS OIL CHANGE
NORTHPORT**

NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:














INSITE JOB No. 24041.00
PLOTTED: 12/2/24



THIS SHEET CONTAINS:
LANDSCAPING PLAN

SCALE: 1"= 20'

C 7.0



INSITE ENGINEERING

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-0698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE NORTHPORT

NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)


PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24

ALABAMA
LICENSED PROFESSIONAL ENGINEER
JOHN L. JETTON
12/2/24


THIS SHEET CONTAINS:
EROSION CONTROL
DETAILS

SCALE: NONE


C 8.0




DETAIL - TYPICAL WATER SERVICE ASSEMBLY
SCALE: NONE




DETAIL - TYPICAL VALVE
BOX SETTING
SCALE: NONE



DETAIL - SANITARY
SEWER LATERAL
SCALE: NONE



DETAIL - TYPICAL CLEANOUT DETAIL
(IN PAVEMENT OR OUT OF PAVEMENT)
SCALE: NONE



SECTION

DETAIL - LATERAL CONNECTION TO MANHOLE
SCALE: NONE


NOTES:
1. ALL MANHOLES WITH PIPE ENTERING WITH DIAMETER OF 18" D.I.P. OR LESS SHALL BE SUPPLIED WITH KOR-N-SEAL FLEXIBLE BOOTS OR APPROVED EQUAL.
2. WHERE THE DIFFERENCE IN THE INVERT ELEVATION IS >6" A STANDARD LENGTH OF DUCTILE IRON PIPE SHALL BE INSTALLED TO BRIDGE THE FILL AREA BETWEEN THE MANHOLE AND THE UNDISTURBED PIPE TRENCH.

INSITE ENGINEERING
5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-0696
www.insiteengineering.org
CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:
**EXPRESS OIL CHANGE
NORTHPORT**
NORTHPORT, ALABAMA

**REVIEW
DRAWING**
(NOT FOR CONSTRUCTION)











PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24



THIS SHEET CONTAINS:
MISCELLANEOUS
DETAILS

SCALE: NONE

C 8.1



INSITE ENGINEERING

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-0698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE NORTHPORT

NORTHPORT, ALABAMA

REVIEW DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24

ALABAMA
LICENSED
PROFESSIONAL
ENGINEER
JOHN L. JETTON
12/2/24

THIS SHEET CONTAINS:
MISCELLANEOUS
DETAILS

SCALE: NONE

C 8.2

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING OR ITS CONTENTS MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT PERMISSION IN WRITING FROM INSITE ENGINEERING, LLC.

PROJECT INFORMATION	
ENGINEERED PRODUCT MANAGER:	JOSEPH LEACH 470-432-1615 JOSEPH.LEACH@ADSPIPE.COM
ADS SALES REP:	BRAGG KNOTT 205-504-3745 BRAGG.KNOTT@ADSPIPE.COM
PROJECT NO:	S438167



EXPRESS OIL CHANGE

NORTHPORT, AL

MC-3500 STORMTECH CHAMBER SPECIFICATIONS

- CHAMBERS SHALL BE STORMTECH MC-3500.
- CHAMBERS SHALL BE ARCH-SHAPED AND SHALL BE MANUFACTURED FROM VIRGIN, IMPACT-MODIFIED POLYPROPYLENE COPOLYMERS.
- CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS" CHAMBER CLASSIFICATION 45x76 DESIGNATION SS.
- CHAMBER ROWS SHALL PROVIDE CONTINUOUS, UNOBSTRUCTED INTERNAL SPACE WITH NO INTERNAL SUPPORTS THAT WOULD IMPEDE FLOW OR LIMIT ACCESS FOR INSPECTION.
- THE STRUCTURAL DESIGN OF THE CHAMBERS, THE STRUCTURAL BACKFILL, AND THE INSTALLATION REQUIREMENTS SHALL ENSURE THAT THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET FOR: 1) LONG-DURATION DEAD LOADS AND 2) SHORT-DURATION LIVE LOADS, BASED ON THE AASHTO DESIGN TRUCK WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCES.
- CHAMBERS SHALL BE DESIGNED, TESTED AND ALLOWABLE LOAD CONFIGURATIONS DETERMINED IN ACCORDANCE WITH ASTM F2787, "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS". LOAD CONFIGURATIONS SHALL INCLUDE: 1) INSTANTANEOUS (<1 MIN) AASHTO DESIGN TRUCK LIVE LOAD ON MINIMUM COVER 2) MAXIMUM PERMANENT (75-YR) COVER LOAD AND 3) ALLOWABLE COVER WITH PARKED (1-WEEK) AASHTO DESIGN TRUCK.
- REQUIREMENTS FOR HANDLING AND INSTALLATION:
 - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
 - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 3".
 - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, a) THE ARCH STIFFNESS CONSTANT SHALL BE GREATER THAN OR EQUAL TO 450 LBS/FT/%. THE ASC IS DEFINED IN SECTION 6.2.8 OF ASTM F2418. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.
- ONLY CHAMBERS THAT ARE APPROVED BY THE SITE DESIGN ENGINEER WILL BE ALLOWED. UPON REQUEST BY THE SITE DESIGN ENGINEER OR OWNER, THE CHAMBER MANUFACTURER SHALL SUBMIT A STRUCTURAL EVALUATION FOR APPROVAL BEFORE DELIVERING CHAMBERS TO THE PROJECT SITE AS FOLLOWS:
 - THE STRUCTURAL EVALUATION SHALL BE SEALED BY A REGISTERED PROFESSIONAL ENGINEER.
 - THE STRUCTURAL EVALUATION SHALL DEMONSTRATE THAT THE SAFETY FACTORS ARE GREATER THAN OR EQUAL TO 1.95 FOR DEAD LOAD AND 1.75 FOR LIVE LOAD, THE MINIMUM REQUIRED BY ASTM F2787 AND BY SECTIONS 3 AND 12.12 OF THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS FOR THERMOPLASTIC PIPE.
 - THE TEST DERIVED CREEP MODULUS AS SPECIFIED IN ASTM F2418 SHALL BE USED FOR PERMANENT DEAD LOAD DESIGN EXCEPT THAT IT SHALL BE THE 75-YEAR MODULUS USED FOR DESIGN.
- CHAMBERS AND END CAPS SHALL BE PRODUCED AT AN ISO 9001 CERTIFIED MANUFACTURING FACILITY.
- MANIFOLD SIZE TO BE DETERMINED BY SITE DESIGN ENGINEER. SEE TECHNICAL NOTE 6.32 FOR MANIFOLD SIZING GUIDANCE. DUE TO THE ADAPTATION OF THIS CHAMBER SYSTEM TO SPECIFIC SITE AND DESIGN CONSTRAINTS, IT MAY BE NECESSARY TO CUT AND COUPLE ADDITIONAL PIPE TO STANDARD MANIFOLD COMPONENTS IN THE FIELD.
- ADS DOES NOT DESIGN OR PROVIDE MEMBRANE LINER SYSTEMS. TO MINIMIZE THE LEAKAGE POTENTIAL OF LINER SYSTEMS, THE MEMBRANE LINER SYSTEM SHOULD BE DESIGNED BY A KNOWLEDGEABLE GEOTEXTILE PROFESSIONAL AND INSTALLED BY A QUALIFIED CONTRACTOR.

IMPORTANT - NOTES FOR THE BIDDING AND INSTALLATION OF MC-3500 CHAMBER SYSTEM

- STORMTECH MC-3500 CHAMBERS SHALL NOT BE INSTALLED UNTIL THE MANUFACTURER'S REPRESENTATIVE HAS COMPLETED A PRE-CONSTRUCTION MEETING WITH THE INSTALLERS.
- STORMTECH MC-3500 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH MC-3500/MC-4500 CONSTRUCTION GUIDE".
- CHAMBERS ARE NOT TO BE BACKFILLED WITH A DOZER OR AN EXCAVATOR SITUATED OVER THE CHAMBERS. STORMTECH RECOMMENDS 3 BACKFILL METHODS:
 - STONESHOOTER LOCATED OFF THE CHAMBER BED.
 - BACKFILL AS ROWS ARE BUILT USING AN EXCAVATOR ON THE FOUNDATION STONE OR SUBGRADE.
 - BACKFILL FROM OUTSIDE THE EXCAVATION USING A LONG BOOM HOE OR EXCAVATOR.
- THE FOUNDATION STONE SHALL BE LEVELED AND COMPACTED PRIOR TO PLACING CHAMBERS.
- JOINTS BETWEEN CHAMBERS SHALL BE PROPERLY SEATED PRIOR TO PLACING STONE.
- MAINTAIN MINIMUM - 6" (150 mm) SPACING BETWEEN THE CHAMBER ROWS.
- INLET AND OUTLET MANIFOLDS MUST BE INSERTED A MINIMUM OF 12" (300 mm) INTO CHAMBER END CAPS.
- EMBEDMENT STONE SURROUNDING CHAMBERS MUST BE A CLEAN, CRUSHED, ANGULAR STONE OR RECYCLED CONCRETE; AASHTO M43 #3, 357, 4, 467, 5, 56, OR 57.
- STONE MUST BE PLACED ON THE TOP CENTER OF THE CHAMBER TO ANCHOR THE CHAMBERS IN PLACE AND PRESERVE ROW SPACING.
- THE CONTRACTOR MUST REPORT ANY DISCREPANCIES WITH CHAMBER FOUNDATION MATERIALS BEARING CAPACITIES TO THE SITE DESIGN ENGINEER.
- ADS RECOMMENDS THE USE OF "FLEXSTORM CATCH IT" INSERTS DURING CONSTRUCTION FOR ALL INLETS TO PROTECT THE SUBSURFACE STORMWATER MANAGEMENT SYSTEM FROM CONSTRUCTION SITE RUNOFF.

NOTES FOR CONSTRUCTION EQUIPMENT

- STORMTECH MC-3500 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH MC-3500/MC-4500 CONSTRUCTION GUIDE".
- THE USE OF EQUIPMENT OVER MC-3500 CHAMBERS IS LIMITED:
 - NO EQUIPMENT IS ALLOWED ON BARE CHAMBERS.
 - NO RUBBER TIRED LOADER, DUMP TRUCK, OR EXCAVATORS ARE ALLOWED UNTIL PROPER FILL DEPTHS ARE REACHED IN ACCORDANCE WITH THE "STORMTECH MC-3500/MC-4500 CONSTRUCTION GUIDE".
 - WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT CAN BE FOUND IN THE "STORMTECH MC-3500/MC-4500 CONSTRUCTION GUIDE".
- FULL 36" (900 mm) OF STABILIZED COVER MATERIALS OVER THE CHAMBERS IS REQUIRED FOR DUMP TRUCK TRAVEL OR DUMPING.

USE OF A DOZER TO PUSH EMBEDMENT STONE BETWEEN THE ROWS OF CHAMBERS MAY CAUSE DAMAGE TO CHAMBERS AND IS NOT AN ACCEPTABLE BACKFILL METHOD. ANY CHAMBERS DAMAGED BY USING THE "DUMP AND PUSH" METHOD ARE NOT COVERED UNDER THE STORMTECH STANDARD WARRANTY.

CONTACT STORMTECH AT 1-800-821-6710 WITH ANY QUESTIONS ON INSTALLATION REQUIREMENTS OR WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT.

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-0698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE
NORTHPORT

NORTHPORT, ALABAMA

REVIEW
DRAWING

(NOT FOR CONSTRUCTION)

PROJECT INFO:

INSITE JOB No. 24041.00
PLOTTED: 12/2/24

THIS SHEET CONTAINS:
ADS PLAN

SCALE: NONE

C 9.0

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING IS TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF INSITE ENGINEERING, LLC.

CONCEPTUAL LAYOUT (SYSTEM 1)


68	STORMTECH MC-3500 CHAMBERS
30	STORMTECH MC-3500 END CAPS
12	STONE ABOVE (in)
9	STONE BELOW (in)
40	% STONE VOID
15,249	INSTALLED SYSTEM VOLUME (CF) (PERIMETER STONE INCLUDED)
4770	SYSTEM AREA (ft²)
277	SYSTEM PERIMETER (ft)

CONCEPTUAL ELEVATIONS (SYSTEM 1)

227.50	MAXIMUM ALLOWABLE GRADE (TOP OF PAVEMENT/UNPAVED)
221.50	MINIMUM ALLOWABLE GRADE (UNPAVED WITH TRAFFIC)
221.00	MINIMUM ALLOWABLE GRADE (UNPAVED NO TRAFFIC)
221.00	MINIMUM ALLOWABLE GRADE (BASE OF FLEXIBLE PAVEMENT)
221.00	MINIMUM ALLOWABLE GRADE (TOP OF RIGID PAVEMENT)
220.50	TOP OF STONE
219.50	TOP OF MC-3500 CHAMBER
217.42	18" TOP MANIFOLD INVERT
215.92	24" ISOLATOR ROW PLUS CONNECTION INVERT
215.90	18" BOTTOM MANIFOLD INVERT
215.75	BOTTOM OF MC-3500 CHAMBER
215.00	UNDERDRAIN INVERT
215.00	BOTTOM OF STONE

NOTES

- THE SITE DESIGN ENGINEER MUST CONSIDER THE EFFECTS OF POSSIBLE SATURATED SOILS ON NEARBY SYSTEMS, INCLUDING BUT NOT LIMITED TO, RETAINING WALLS, SLOPE CONSTRUCTION/STABILITY, OR BUILDINGS/STRUCTURES. NO FOUNDATION LOADS SHALL BE TRANSMITTED TO THE CHAMBERS.
- NOT FOR CONSTRUCTION:** THIS LAYOUT IS FOR DIMENSIONAL PURPOSES ONLY TO PROVE CONCEPT & THE REQUIRED STORAGE VOLUME CAN BE ACHIEVED ON SITE.



EXPRESS OIL CHANGE

NORTHPORT, AL

DATE: 10-21-24

DRAWN: SLS

CHECKED: XXX

PROJECT #: S438167

THIS DRAWING IS NOT INTENDED FOR USE IN BIDDING OR CONSTRUCTION WITHOUT THE EOR'S PRIOR APPROVAL. EOR SHALL REVIEW THIS DRAWING PRIOR TO BIDDING AND/OR CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE EOR TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.

StormTech®

Chamber System

1-800-821-6710 | WWW.STORMTECH.COM

4640 TRUEMAN BLVD
HILLIARD, OH 43026

0 20' 40'

2

SHEET

OF

7

CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE
NORTHPORT

NORTHPORT, ALABAMA


REVIEW
DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24

THIS SHEET CONTAINS:
ADS PLAN

SCALE: NONE

C 9.1



INSITE
ENGINEERING

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-9698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING IS TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF INSITE ENGINEERING, LLC.

CONCEPTUAL LAYOUT (SYSTEM 2)


40	STORMTECH MC-3500 CHAMBERS
18	STORMTECH MC-3500 END CAPS
12	STONE ABOVE (in)
9	STONE BELOW (in)
40	% STONE VOID
9,975	INSTALLED SYSTEM VOLUME (CF) (PERIMETER STONE INCLUDED)
3261	SYSTEM AREA (ft²)
233	SYSTEM PERIMETER (ft)




CONCEPTUAL ELEVATIONS (SYSTEM 2)

227.50	MAXIMUM ALLOWABLE GRADE (TOP OF PAVEMENT/UNPAVED)
221.50	MINIMUM ALLOWABLE GRADE (UNPAVED WITH TRAFFIC)
221.00	MINIMUM ALLOWABLE GRADE (UNPAVED NO TRAFFIC)
221.00	MINIMUM ALLOWABLE GRADE (BASE OF FLEXIBLE PAVEMENT)
221.00	MINIMUM ALLOWABLE GRADE (TOP OF RIGID PAVEMENT)
220.50	TOP OF STONE
219.50	TOP OF MC-3500 CHAMBER
217.42	18" TOP MANIFOLD INVERT
215.92	24" ISOLATOR ROW PLUS CONNECTION INVERT
215.90	18" BOTTOM MANIFOLD/CONNECTION INVERT
215.75	BOTTOM OF MC-3500 CHAMBER
215.00	UNDERDRAIN INVERT
215.00	BOTTOM OF STONE

NOTES

- THE SITE DESIGN ENGINEER MUST CONSIDER THE EFFECTS OF POSSIBLE SATURATED SOILS ON NEARBY SYSTEMS, INCLUDING BUT NOT LIMITED TO, RETAINING WALLS, SLOPE CONSTRUCTION/STABILITY, OR BUILDINGS/STRUCTURES. NO FOUNDATION LOADS SHALL BE TRANSMITTED TO THE CHAMBERS.
- NOT FOR CONSTRUCTION:** THIS LAYOUT IS FOR DIMENSIONAL PURPOSES ONLY TO PROVE CONCEPT & THE REQUIRED STORAGE VOLUME CAN BE ACHIEVED ON SITE.



-  ISOLATOR ROW PLUS (SEE DETAIL)
-  PLACE MINIMUM 17.5' OF ADSPLUS125 WOVEN GEOTEXTILE OVER BEDDING STONE AND UNDERNEATH CHAMBER FEET FOR SCOUR PROTECTION AT ALL CHAMBER INLET ROWS
-  BED LIMITS

EXPRESS OIL CHANGE		NORTHPORT, AL		DATE: 10-21-24	DRAWN: SLS	CHECKED: XXX
StormTech® Chamber System		1-800-821-6710 WWW.STORMTECH.COM		DATE: 11/15/24	DRWN: EEH	CHKD: JPR
4640 TRUEMAN BLVD HILLIARD, OH 43026		0 20' 40'		THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS/STORMTECH UNDER THE DIRECTION OF THE PROJECT'S ENGINEER OR OTHER PROJECT REPRESENTATIVE. THIS DRAWING IS NOT INTENDED FOR USE IN BIDDING OR CONSTRUCTION WITHOUT THE EOR'S PRIOR APPROVAL. EOR SHALL REVIEW THIS DRAWING PRIOR TO BIDDING AND/OR CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE EOR TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.		
3 SHEET OF 7						


**INSITE
ENGINEERING**
5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-9698
www.insiteengineering.org
CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE NORTHPORT

NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24

THIS SHEET CONTAINS:
ADS PLAN

SCALE: NONE

C 9.2


THIS DRAWING AND THE DESIGN THEREOF IS THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING OR THE DESIGN THEREOF MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF INSITE ENGINEERING, LLC.

ACCEPTABLE FILL MATERIALS: STORMTECH MC-3500 CHAMBER SYSTEMS

MATERIAL LOCATION	DESCRIPTION	AASHTO MATERIAL CLASSIFICATIONS	COMPACTION / DENSITY REQUIREMENT
D	FINAL FILL: FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'D' LAYER	N/A	PREPARE PER SITE DESIGN ENGINEER'S PLANS. PAVED INSTALLATIONS MAY HAVE STRINGENT MATERIAL AND PREPARATION REQUIREMENTS.
C	INITIAL FILL: FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 18" (450 mm) ABOVE THE TOP OF THE CHAMBER. NOTE THAT PAVEMENT SUBBASE MAY BE A PART OF THE 'C' LAYER.	AASHTO M145 ¹ A-1, A-2-4, A-3 OR AASHTO M43 ¹ 3, 357, 4, 467, 5, 56, 57, 6, 67, 68, 7, 78, 8, 89, 9, 10	BEGIN COMPACTIONS AFTER 18" (450 mm) OF MATERIAL OVER THE CHAMBERS IS REACHED. COMPACT ADDITIONAL LAYERS IN 12" (300 mm) MAX LIFTS TO A MIN. 95% PROCTOR DENSITY FOR WELL GRADED MATERIAL AND 95% RELATIVE DENSITY FOR PROCESSED AGGREGATE MATERIALS.
B	EMBEDMENT STONE: FILL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.	AASHTO M43 ¹ 3, 357, 4, 467, 5, 56, 57	NO COMPACTION REQUIRED
A	FOUNDATION STONE: FILL BELOW CHAMBERS FROM THE SUBGRADE UP TO THE FOOT (BOTTOM) OF THE CHAMBER.	AASHTO M43 ¹ 3, 357, 4, 467, 5, 56, 57	PLATE COMPACT OR ROLL TO ACHIEVE A FLAT SURFACE. ^{2,3}

PLEASE NOTE:

- THE LISTED AASHTO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR. FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE".
- STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTED IN 9" (230 mm) (MAX) LIFTS USING TWO FULL COVERAGES WITH A VIBRATORY COMPACTOR.
- WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD DESIGN LOAD CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAKING OR DRAGGING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.
- ONCE LAYER 'C' IS PLACED, ANY SOIL/MATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.
- WHERE RECYCLED CONCRETE AGGREGATE IS USED IN LAYERS 'A' OR 'B' THE MATERIAL SHOULD ALSO MEET THE ACCEPTABILITY CRITERIA OUTLINED IN TECHNICAL NOTE 6.20 "RECYCLED CONCRETE STRUCTURAL BACKFILL".



NOTES:

- CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS" CHAMBER CLASSIFICATION 45x76 DESIGNATION SS.
- MC-3500 CHAMBERS SHALL BE DESIGNED IN ACCORDANCE WITH ASTM F2787 "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR ASSESSING THE BEARING RESISTANCE (ALLOWABLE BEARING CAPACITY) OF THE SUBGRADE SOILS AND THE DEPTH OF FOUNDATION STONE WITH CONSIDERATION FOR THE RANGE OF EXPECTED SOIL MOISTURE CONDITIONS. REFERENCE STORMTECH DESIGN MANUAL FOR BEARING CAPACITY GUIDANCE.
- PERIMETER STONE MUST BE EXTENDED HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH VERTICAL AND SLOPED EXCAVATION WALLS.
- REQUIREMENTS FOR HANDLING AND INSTALLATION:
 - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
 - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 3".
 - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, a) THE ARCH STIFFNESS CONSTANT AS DEFINED IN SECTION 6.2.8 OF ASTM F2418 SHALL BE GREATER THAN OR EQUAL TO 500 LBS/FT/%. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.

EXPRESS OIL CHANGE

NORTHPORT, AL

DATE: 10-21-24
PROJECT #: S438167
DRAWN: SLS
CHECKED: XXX

StormTech®
Chamber System

1-800-821-6710 | WWW.STORMTECH.COM

4640 TRUEMAN BLVD
HILLIARD, OH 43026

ADS

4 SHEET
OF 7

THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS/STORMTECH UNDER THE DIRECTION OF THE PROJECT'S ENGINEER OF RECORD (EOR) OR OTHER PROJECT REPRESENTATIVE. THIS DRAWING IS NOT INTENDED FOR USE IN BIDDING OR CONSTRUCTION WITHOUT THE EOR'S PRIOR APPROVAL. EOR SHALL REVIEW THIS DRAWING PRIOR TO BIDDING AND/OR CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE EOR TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.



5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-9698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE
NORTHPORT

NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)


PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24

THIS SHEET CONTAINS:
ADS PLAN

SCALE: NONE

C 9.3

THIS DRAWING AND THE DESIGN THEREOF IS THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING OR THE DESIGN THEREOF MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF INSITE ENGINEERING, LLC.




MC-3500 ISOLATOR ROW PLUS DETAIL
NTS

INSPECTION & MAINTENANCE

- STEP 1) INSPECT ISOLATOR ROW PLUS FOR SEDIMENT
- A. INSPECTION PORTS (IF PRESENT)
- A.1. REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN
- A.2. REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED
- A.3. USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
- A.4. LOWER A CAMERA INTO ISOLATOR ROW PLUS FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
- A.5. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- B. ALL ISOLATOR PLUS ROWS
- B.1. REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW PLUS
- B.2. USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW PLUS THROUGH OUTLET PIPE
- i) MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
- ii) FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
- B.3. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW PLUS USING THE JETVAC PROCESS
- A. A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45° (1.1 m) OR MORE IS PREFERRED
- B. APPLY MULTIPLE PASSES OF JETVAC UNTIL BACKFLUSH WATER IS CLEAN
- C. VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS.
- STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.

NOTES

1. INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION. ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
2. CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.



NOTE:
INSPECTION PORTS MAY BE CONNECTED THROUGH ANY CHAMBER CORRUGATION VALLEY.

4" PVC INSPECTION PORT DETAIL
(MC SERIES CHAMBER)
NTS

EXPRESS OIL CHANGE		NORTHPORT, AL	
DATE: 10-21-24		DRAWN: SLS	
PROJECT #: S438167		CHECKED: XXX	
11/15/24	EEH	JPR	REVISE PER MTD WIEOR
DATE	DRWN	CHKD	DESCRIPTION
StormTech® Chamber System		1-800-821-6710 WWW.STORMTECH.COM	
4640 TRUEMAN BLVD HILLIARD, OH 43026		ADS®	
5	SHEET OF	7	

THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS/STORMTECH UNDER THE DIRECTION OF THE PROJECT'S ENGINEER OF RECORD. EOR OR OTHER PROJECT REPRESENTATIVE. THIS DRAWING IS NOT INTENDED FOR USE IN BIDDING OR CONSTRUCTION WITHOUT THE EOR'S PRIOR APPROVAL. EOR SHALL REVIEW THIS DRAWING PRIOR TO BIDDING AND/OR CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE EOR TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.



**INSITE
ENGINEERING**

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-9698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE
NORTHPORT

NORTHPORT, ALABAMA

REVIEW
DRAWING

(NOT FOR CONSTRUCTION)

PROJECT INFO:

INSITE JOB No. 24041.00
PLOTTED: 12/2/24




THIS SHEET CONTAINS:

ADS PLAN

SCALE: NONE

C 9.4

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING OR ITS CONTENTS MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT PERMISSION IN WRITING FROM INSITE ENGINEERING, LLC. COPYRIGHT © 2023 INSITE ENGINEERING, LLC.



PARTIAL CUT HOLES AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B"
PARTIAL CUT HOLES AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T"
END CAPS WITH A PREFABRICATED WELDED STUB END WITH "W"
END CAPS WITH A WELDED CROWN PLATE END WITH "C"

PART #	STUB	B	C
MC3500IEPP06T	6" (150 mm)	33.21" (844 mm)	---
MC3500IEPP06B	---	---	0.66" (17 mm)
MC3500IEPP08T	8" (200 mm)	31.16" (791 mm)	---
MC3500IEPP08B	---	---	0.81" (21 mm)
MC3500IEPP10T	10" (250 mm)	29.04" (738 mm)	---
MC3500IEPP10B	---	---	0.93" (24 mm)
MC3500IEPP12T	12" (300 mm)	26.36" (670 mm)	---
MC3500IEPP12B	---	---	1.35" (34 mm)
MC3500IEPP15T	15" (375 mm)	23.39" (594 mm)	---
MC3500IEPP15B	---	---	1.50" (38 mm)
MC3500IEPP18TC	---	20.03" (509 mm)	---
MC3500IEPP18TW	18" (450 mm)	---	---
MC3500IEPP18BC	---	---	1.77" (45 mm)
MC3500IEPP18BW	---	---	---
MC3500IEPP24TC	---	14.48" (368 mm)	---
MC3500IEPP24TW	24" (600 mm)	---	---
MC3500IEPP24BC	---	---	2.06" (52 mm)
MC3500IEPP24BW	---	---	---
MC3500IEPP30BC	30" (750 mm)	---	2.75" (70 mm)

NOTE: ALL DIMENSIONS ARE NOMINAL

CUSTOM PARTIAL CUT INVERTS ARE AVAILABLE UPON REQUEST. INVENTORIED MANIFOLDS INCLUDE 12-24" (300-600 mm) SIZE ON SIZE AND 15-48" (375-1200 mm) ECCENTRIC MANIFOLDS. CUSTOM INVERT LOCATIONS ON THE MC-3500 END CAP CUT IN THE FIELD ARE NOT RECOMMENDED FOR PIPE SIZES GREATER THAN 10" (250 mm). THE INVERT LOCATION IN COLUMN 'B' ARE THE HIGHEST POSSIBLE FOR THE PIPE SIZE.

EXPRESS OIL CHANGE		NORTHPORT, AL		DATE: 10-21-24	DRAWN: SLS	CHECKED: XXX
StormTech® Chamber System		1-800-821-6710 WWW.STORMTECH.COM		DATE: 11/15/24	DRWN: EEH	CHKD: JPR
4640 TRUEMAN BLVD HILLIARD, OH 43026		ADS		SHEET 6 OF 7		

THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS/STORMTECH UNDER THE DIRECTION OF THE PROJECT'S ENGINEER OF RECORD. EOR SHALL REVIEW THIS DRAWING PRIOR TO BIDDING AND/OR CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE EOR TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS. PRIOR APPROVAL EOR SHALL REVIEW THIS DRAWING PRIOR TO BIDDING AND/OR CONSTRUCTION.

INSITE ENGINEERING
5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-9698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:
**EXPRESS OIL CHANGE
NORTHPORT**
NORTHPORT, ALABAMA

**REVIEW
DRAWING**
(NOT FOR CONSTRUCTION)


PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24

THIS SHEET CONTAINS:
ADS PLAN

SCALE: NONE

C 9.5

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING IS TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF INSITE ENGINEERING, LLC.



NOTES

- 8-30" (200-750 mm) GRATES/SOLID COVERS SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
- 12-30" (300-750 mm) FRAMES SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
- DRAIN BASIN TO BE CUSTOM MANUFACTURED ACCORDING TO PLAN DETAILS
- DRAINAGE CONNECTION STUB JOINT TIGHTNESS SHALL CONFORM TO ASTM D3212 FOR CORRUGATED HDPE (ADS & HANCOR DUAL WALL) & SDR 35 PVC
- FOR COMPLETE DESIGN AND PRODUCT INFORMATION: WWW.NYLOPLAST-US.COM
- TO ORDER CALL: **800-821-6710**

A	PART #	GRATE/SOLID COVER OPTIONS		
8" (200 mm)	2808AG	PEDESTRIAN LIGHT DUTY	STANDARD LIGHT DUTY	SOLID LIGHT DUTY
10" (250 mm)	2810AG	PEDESTRIAN LIGHT DUTY	STANDARD LIGHT DUTY	SOLID LIGHT DUTY
12" (300 mm)	2812AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
15" (375 mm)	2815AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
18" (450 mm)	2818AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
24" (600 mm)	2824AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
30" (750 mm)	2830AG	PEDESTRIAN AASHTO H-20	STANDARD AASHTO H-20	SOLID AASHTO H-20

EXPRESS OIL CHANGE

NORTHPORT, AL

DATE: 10-21-24

DRAWN: SLS

CHECKED: XXX

PROJECT #: S438167

NYLOPLAST®

770-932-2443 | WWW.NYLOPLAST-US.COM

ADS

4640 TRUEMAN BLVD
HILLIARD, OH 43026

7 SHEET OF 7

THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS/STORMTECH UNDER THE DIRECTION OF THE PROJECT'S ENGINEER OF RECORD (EOR) OR OTHER PROJECT REPRESENTATIVE. THIS DRAWING IS NOT INTENDED FOR USE IN BIDDING OR CONSTRUCTION WITHOUT THE EOR'S PRIOR APPROVAL. EOR SHALL REVIEW THIS DRAWING PRIOR TO BIDDING AND/OR CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE EOR TO ENSURE THAT THE PRODUCT(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.

INSITE
ENGINEERING

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE: (205) 733-9698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE
NORTHPORT

NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:


INSITE JOB No. 24041.00
PLOTTED: 12/2/24

THIS SHEET CONTAINS:
ADS PLAN

SCALE: NONE

C 9.6

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING OR ITS CONTENTS MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT PERMISSION IN WRITING FROM INSITE ENGINEERING, LLC. COPYRIGHT © 2024, INSITE ENGINEERING, LLC.



INSITE ENGINEERING

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-0698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL


CONSTRUCTION PLANS FOR:

EXPRESS OIL CHANGE NORTHPORT

NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24



THIS SHEET CONTAINS:
ACCESS PERMIT
PLAN


SCALE: 1"= 20'

AP-1

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING OR ITS CONTENTS MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT PERMISSION IN WRITING FROM INSITE ENGINEERING, LLC.

TEMPORARY TRAFFIC CONTROL PLAN SHEET

REFERENCE PROJECT NO	FISCAL YEAR	SHEET NO




(FOR USE WHERE EXCAVATION HAS BEEN DONE, BUT WIDENING IS NOT COMPLETED BY NIGHTFALL OR WHERE PAVEMENT DROP OFF OF RESURFACING PROJECTS IS 3" OR MORE AT NIGHTFALL)

TYPICAL FOR DROP-OFF AT EDGE OF PAVEMENT

NOTE:
THE CONTRACTOR IS TO CONSTRUCT A WEDGE OF UNCLASSIFIED EXCAVATION OR CRUSHED AGGREGATE BASE. THE COST OF PLACING AND REMOVAL SHALL BE A SUBSIDIARY OBLIGATION OF THE ADJACENT LAYER.


CHANNELIZING DRUMS SHALL BE PLACED AT 50 FT INTERVALS.




NOTES:

- SEE ALDOT'S GENERAL TRAFFIC CONTROL PLAN NOTE NO. 702.
- DRUMS TO BE AS FAR AS PRACTICAL FROM EDGE OF PAVEMENT, MINIMUM DESIRABLE DISTANCE IS 15 FEET FOR FREEWAY TYPE FACILITIES AND 10 FEET FOR OTHER FACILITIES. FOR UNUSUAL CONDITIONS, SUCH AS SPECIAL EQUIPMENT OR LIMITED AVAILABLE SPACE, DIMENSIONS LESS THAN DESIRABLE SHALL BE AS DIRECTED BY THE ENGINEER.
- ALL DEVICES TO BE FURNISHED BY THE CONTRACTOR WITHOUT COST TO THE ALDOT.

DELINEATING DETAIL FOR EQUIPMENT PARKING OR STORING AREA




DETAILS FOR TYPICAL PLACEMENT OF TYPE III BARRICADES INSIDE OF CLEAR ZONE



DETAILS FOR TYPICAL PLACEMENT OF TYPE III BARRICADES OUTSIDE OF CLEAR ZONE

NOTES

- SLOPE OF STRIPES ON BARRICADES SHALL BE IN ACCORDANCE WITH SECTION 6F.68 OF THE MUTCD AND DRAWING B-107-2.
- IF SIGNS ARE REQUIRED TO BE USED IN CONJUNCTION WITH TYPE III BARRICADES TO BE PLACED INSIDE THE CLEAR ZONE, THEY SHALL BE POST MOUNTED TO THE SIDE OF THE BARRICADES AS SHOWN.
- IF ROAD CLOSED OR DETOUR SIGNS ARE REQUIRED TO BE USED WITH TYPE III BARRICADES TO BE PLACED OUTSIDE THE CLEAR ZONE, THEY SHALL BE PLACED ON THE TOP OF THE BARRICADES NEAREST THE DETOUR.



ALABAMA DEPARTMENT
OF TRANSPORTATION
1409 COLISEUM BOULEVARD
MONTGOMERY, AL 36130-9050

THIS DRAWING REPRESENTS DESIGNS PREPARED FOR USE BY THE ALABAMA DEPARTMENT OF TRANSPORTATION AND IS NOT TO BE COPIED, REPRODUCED, ALTERED, OR USED BY ANYONE, OR ANY ORGANIZATION, WITHOUT THE EXPRESSED WRITTEN CONSENT OF THE ALABAMA DEPARTMENT OF TRANSPORTATION REPRESENTATIVE AUTHORIZED TO APPROVE THIS USE. ANYONE MAKING UNAUTHORIZED USE OF THIS DRAWING MAY BE PROSECUTED TO THE FULLEST EXTENT OF THE LAW.

REVISIONS:

1. Corrected text overlap on 12-8-2021 by D.J.W.

Drawn Std. Fig.: D.J.W.
DRAWN BY:
DATE DRAWN:
REVISED DATE: 12-8-2021

DESIGN BUREAU SPECIAL DRAWING
STANDARD DETAILS FOR
TRAFFIC CONTROL PLANS

NOT TO SCALE

--SPECIFICATIONS--
CURRENT ALABAMA DEPARTMENT OF TRANSPORTATION
SPECIAL DRAWING NO
SPECIAL PROJECT DETAIL
INDEX NO
2001




5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-0698
www.insiteengineering.org

CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:
**EXPRESS OIL CHANGE
NORTHPORT**
NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:
INSITE JOB No. 24041.00
PLOTTED: 12/2/24




THIS SHEET CONTAINS:
TRAFFIC CONTROL
DETAILS

SCALE: NONE


AP-2

TEMPORARY TRAFFIC CONTROL PLAN SHEET


REFERENCE PROJECT NO	FISCAL YEAR	SHEET NO




TYPICAL METHOD FOR INSTALLING OR REMOVING CONSTRUCTION SIGNS



HEIGHT AND LATERAL LOCATION OF POST MOUNTED CONSTRUCTION SIGNS



DETAIL FOR DRUM MOUNTED CONSTRUCTION SIGNS



ALABAMA DEPARTMENT
OF TRANSPORTATION
1409 COLISEUM BOULEVARD
MONTGOMERY, AL 36130-3090

THIS DRAWING REPRESENTS DESIGNS PREPARED FOR USE BY THE ALABAMA DEPARTMENT OF TRANSPORTATION AND IS NOT TO BE COPIED, REPRODUCED, ALTERED, OR USED BY ANYONE, OR ANY ORGANIZATION, WITHOUT THE EXPRESSED WRITTEN CONSENT OF THE ALABAMA DEPARTMENT OF TRANSPORTATION REPRESENTATIVE AUTHORIZED TO APPROVE THIS USE. ANYONE MAKING UNAUTHORIZED USE OF THIS DRAWING MAY BE PROSECUTED TO THE FULLEST EXTENT OF THE LAW.

REVISIONS:


1.

Drawn By: D.J.W.
DATE DRAWN: 6-12-2019
REVISED DATE: 6-12-2019

DESIGN BUREAU SPECIAL DRAWING
STANDARD DETAILS
FOR TRAFFIC CONTROL PLANS

NOT TO SCALE

--SPECIFICATIONS--
CURRENT ALABAMA DEPARTMENT OF TRANSPORTATION
SPECIAL DRAWING NO
INDEX NO
SPECIAL PROJECT DETAIL
2001A



INSITE
ENGINEERING

5800 FELDSPAR WAY
HOOVER, ALABAMA 35244
OFFICE (205) 733-0698
www.insiteengineering.org


CIVIL / GIS
INFRASTRUCTURE
ENVIRONMENTAL
PLANNING
COMMERCIAL
RESIDENTIAL

CONSTRUCTION PLANS FOR:
**EXPRESS OIL CHANGE
NORTHPORT**
NORTHPORT, ALABAMA

REVIEW
DRAWING
(NOT FOR CONSTRUCTION)

PROJECT INFO:

INSITE JOB No. 24041.00
PLOTTED: 12/2/24




THIS SHEET CONTAINS:
TRAFFIC CONTROL
DETAILS

SCALE: NONE

AP-3

THIS DRAWING AND ITS CONTENTS ARE THE PROPERTY OF INSITE ENGINEERING, LLC. NO PART OF THIS DRAWING MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF INSITE ENGINEERING, LLC. COPYRIGHT © 2022 INSITE ENGINEERING, LLC.





1855 Data Drive, Suite 150
Hoover, Alabama 35244
T: 205-983-6000 F: 205-983-6001
www.ahoarch.com

AHO ARCHITECTS, LLC

A R C H I T E C T ' S S U P P L E M E N T A L I N S T R U C T I O N S

ASI NUMBER: **1**

PROJECT NUMBER: 24028

PROJECT: Express Oil Change & Tire Engineers
Two Building / Left Hand Oil Change / Five Bay Service Building
Northport, AL

DATE OF ISSUANCE: 1/16/2025

DESCRIPTION: **Revisions to Construction Documents**

1. Sheet OC-E700 Site plan – Photometrics dated 01/09/2025 was added in response to the planning and zoning comments received by the civil engineers, Dated 12/23/24.

COPIES TO: Express Oil Change & Tire Engineers

SIGNED: _____

Anna Kate Simmons
Intern Interior Designer

EXPRESS OIL CHANGE & TIRE ENGINEERS

LEFT HAND OIL CHANGE BUILDING

HWY 43 LURLEEN B WALLACE & 27th STREET
NORTHPORT, AL 35476

ATTENTION AUTHORITY HAVING JURISDICTION

Notice is hereby given that Aho Architects, LLC, the Architect of Record on the above referenced project, will be providing construction administration services on a limited basis, supplemented by a third-party independent engineering consulting service as described below.

This project has been designed by the Architect and Engineers ("Design Team") for its specific location, or adapted from prototypical designs, to comply with the following codes, ordinances, and similar requirements adopted by the Authority Having Jurisdiction ("AHJ"):

- See codes listed on Sheet LS100.

During the Construction Administration Phase of the Project:

- General: The Design Team will respond to inquiries or requests from the Owner or Contractor, specifically related to documents prepared by the Design Team. As is standard in Construction Law and Professional Service Agreements, the Design Team shall not have control over, charge of, or responsibility for the construction means, methods, techniques, sequences or procedures, or for safety precautions and programs in connection with the Project(s), nor shall the Architect be responsible for the Owner's or Contractor's failure to perform the work in accordance with the requirements of the Permit Set Documents. The Architect shall be responsible for the Architect's negligent acts or omissions, but shall not have control over or charge of, and shall not be responsible for, acts or omissions of the Owner, Contractor, or of any other persons or entities performing portions of the work.
- Experienced Contractor: The Owner will use experienced and licensed Contractors familiar with the construction of Projects of this type and in similar locations, and experienced with the applicable building codes, selection of materials and systems, and methods of installation and construction; and able to implement the Permit Set Documents through completion of the Project(s).
- Submittals: The Design Team's Basic Construction Administration Services include review of critical submittals (e.g. shop drawings) by engineering disciplines (Structural). The Design Team shall also review, approve or take other appropriate action on any submittal for which the AHJ requires approval by the Architect/Engineer, as Additional Services.
- Site Visits: The Architect and Design Engineers typically will not be making any site visits unless specifically required to do so.
 - The Owner has been advised and acknowledges that some States and AHJs require the Architect to perform at least some site visits or provide a notice such as this statement.
 - In consideration of this, the Owner will provide site visits, observation, testing, and related work by a third party independent engineering consulting service:
 - The Owner has an agreement with Terracon, a provider of geotechnical, environmental, construction materials and facilities engineering
 - Experienced Professional Engineers or field technicians under the responsible control of a Professional Engineer will perform site observation, construction materials testing, and required Special Inspections (per IBC Chapter 17; see Schedule of Special Inspections on structural drawings provided) including review of construction for conformance with the permit drawings, supplemental drawings, shop drawings/submittals, and similar relevant documents. Written reports shall be provided, with the Design Team included on the distribution list and involved in resolving any deficiencies noted or other items requiring the Design Team's input.
 - If the above provisions are not acceptable to the AHJ and the AHJ gives notice requiring the Architect to make site visit(s), the Owner has agreed to authorize the Architect's Additional Services and Reimbursable Expenses to comply with the AHJ's requirements.

If you have any questions, or if there is anything else we can do for you, please do not hesitate to contact April Cain, the project manager or Tim Aho, Architect at the address/phone listed below, or by email at [HYPERLINK "mailto:acain@ahoarch.com"](mailto:acain@ahoarch.com) acain@ahoarch.com or [HYPERLINK "mailto:taho@ahoarch.com"](mailto:taho@ahoarch.com) taho@ahoarch.com. Thank you very much, and we appreciate the opportunity to be involved in this project in your jurisdiction.



*Image above is generic. See Civil for actual site conditions

ARCHITECT

AHO ARCHITECTS, LLC
1855 DATA DRIVE, SUITE 150
HOOVER, ALABAMA 35244
205-983-6000

CIVIL ENGINEER

INSITE ENGINEERING
5800 FELDSPAR WAY
HOOVER, AL 35244
205-733-9696

STRUCTURAL ENGINEER

BARNETT-JONES-WILSON, LLC
125 18TH STREET NORTH
PELL CITY, ALABAMA 35125
205-884-5334

MECHANICAL / PLUMBING ENGINEER

PINNACLE ENGINEERING, INC.
2031 SHADY CREST DRIVE
HOOVER, ALABAMA 35216
205-733-6912

ELECTRICAL ENGINEER

GW ENGINEERING, LLC
4120 OVERLOOK CIRCLE
TRUSSVILLE, ALABAMA 35173
205-413-4112

FINAL



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Title Sheet

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A
T100	
Scale	12" = 1'-0"

GENERAL PROJECT NOTES

1. These documents are considered accurate and true to the best knowledge of the Architect at this time, but do not necessarily represent, nor are they intended to represent, actual existing conditions, dimensions, and tolerances. Contractor shall field-verify existing conditions including, but not limited to materials, construction, elevations, and dimensions prior to bidding and undertaking the work. Items of concern shall be brought to the attention of the Architect. Submittal of a proposal (bid) by a Contractor and their Subcontractors shall constitute an acknowledgement and confirmation of having complied with these requirements.
2. All work shall comply with all applicable local, state, and national codes, rules, ordinances and regulations and authorities having jurisdiction.
3. The Contractor shall comply with all applicable provisions of the specifications, including, but not limited to all general conditions, supplementary general conditions, special conditions, and material and construction provisions, which apply to materials or construction methods required by this project.
4. Where warranties are concerned, Contractor shall follow manufacturer's standards and recommendations unless specifically directed otherwise. Any conditions which might negatively affect the warranty shall be brought to the attention of the Architect in advance.
5. The Owner and Contractor shall promptly report to the Architect any defects, suspected defects, or discrepancies in the Architect's work or services of which the Owner or Contractor may become aware, so that the Architect may take measures to minimize the consequences of such a defect. Failure to notify the Architect shall relieve the Architect of costs of remedying the defects above the sum such remedy would have cost had prompt notification been given.
6. Neither the professional activities of the Architect, nor the presence of the Architect or its employees and consultants at a construction site shall relieve the Contractor or others of their obligations, duties, and responsibilities including, but not limited to: construction means and methods, sequence, techniques, or procedures necessary for performing, superintending, or coordinating all portions of the work in accordance with the contract documents and any health and safety precautions required by agencies having jurisdictional authority over the project. The Architect and its personnel have no authority to exercise control over any Contractor or other entity or their employees in connection with their means, methods, or safety precautions. The Contractor is solely responsible for jobsite safety. The Owner, Architect, and their Consultants shall be indemnified and shall be made additional insureds under the Contractor's general liability insurance policy.
7. All work, unless specifically indicated otherwise, shall be the responsibility of the General Contractor and shall be performed by the tradesmen skilled in the required field.
8. "Provide" shall mean to furnish and install, complete and ready for intended use.
9. Provide pressure treated wood where in contact with concrete or masonry.
10. The Contractor shall be responsible for all cutting, fitting, and patching that may be required to complete the work.
11. Dimensions of existing construction and repetitive dimensions are sometimes omitted. Detailed dimensions not indicated may be found on large-scale drawings of the same areas. Drawings are intended to reflect the existing conditions as closely as possible, however, the Contractor shall field verify and accept all existing conditions and dimensions. Notify Architect of any discrepancies affecting the work.
12. Provide all temporary services required to facilitate the work indicated, including but not limited to the following: power, lighting, heat, and water.
13. The Contractor(s) shall provide all barriers, shoring, warning lights, etc. as required to conduct the work and maintain the site in a safe condition consistent with good construction practices and with all applicable rules and regulations.
14. All exist. utility services including domestic water, sanitary sewer, electricity, fuel oil and/or gas shall be disconnected and made safe prior to any demolition work. Any work which might require interruption of utility services to Owner or other tenants, shall be approved and coordinated beforehand with the Owner.
15. It is the intent of the bid and construction documents to indicate complete and fully operational systems (i.e. structural, HVAC, plumbing, electrical, roofing, etc.). The Contractor shall provide operational systems and testing which comply with applicable codes, regulations, and requirements of authorities having jurisdiction.
16. Any work or utility outages which might disrupt the operations of the Owner or others shall be approved and coordinated in advance with the Owner and the Architect. The Contractor shall give the Owner and Architect at least three days advance notice prior to undertaking work which might cause disruption. Activities which produce utility outages, excessive noise, dust and other disruption shall be coordinated with the Owner and Architect. Some of these activities may need to occur at "off hours" to minimize disruption of the Owner's operations.
17. All wood blocking, trim, decking, etc. shall be decay-resistant treated, or as specified.
18. To prepare substrate for all wall mounted items, wall fixture, toilet accessories, etc. - fill all voids in the CMU surface to provide a sound base (provide blocking in stud walls) for all new wall mounted items, fixtures, etc. Install per manufacturer's specifications and recommendations.
19. Do not paint any caulking or sealants which are subject to movement. Control joints shall be caulked after paint and special coating applications. Provide caulking or sealants in colors which match adjacent finished surface as approved by the Architect.
20. Bidders shall be responsible for obtaining a copy of the Geotech Report from the Owner.
21. The project may include some items that are delegated design. Bidders shall ensure these items are covered in their base bid.
22. All questions that affect cost, time, etc. shall be presented in the form of RFI's to the Architect prior to bid.

ENERGY CODE EXEMPTION

Per 2015 International Energy Conservation Code:

C402.1.1 Low Energy Buildings. The following low-energy buildings, or portions thereof, separated from the remainder of the building by building thermal envelope assemblies complying with this section, shall be exempt from the building thermal envelope provisions of Section C402:

1. Those with a peak design rate of energy usage less than 3.4 Btu/h x ft2 or 1.0 watt/ft2 of floor area for space conditioning purposes.
2. Those that do not contain "conditioned space".
3. Greenhouses

Per Chapter 2:

Definition of Conditioned Space: An area, room or space that is **enclosed** within the building thermal envelope and is directly or indirectly heated or cooled. Spaces are indirectly heated or cooled where they communicate through openings with conditioned spaces, where they are separated from conditioned spaces by uninsulated walls, floors, or ceilings, or where they contain uninsulated ducts, piping or other sources of heating or cooling.

While the Oil Change do have radiant heaters,during normal operations, the Oil Change and Pit areas are **not enclosed** and are outside the building thermal envelope assembly. These areas are separated from the remainder of the building by building thermal envelope assemblies complying with this code. Later versions of the IECC (2018 and 2021) allow radiant heaters to be installed outside the building thermal envelope. Therefore, these areas shall be exempt from the building thermal envelope provisions of this code.

GENERAL ACCESSIBILITY NOTES

1. All door hardware shall be accessible type per section 404 of the 2017 ICC A117.1 / 2010 ADA Standards.
2. All walking surfaces shall have a maximum slope of 1:20 per section 405 of the 2017 ICC A117.1 / 2010 ADA Standards
3. All floor or ground surfaces shall be stable, firm, and slip resistant per section 302 of the 2017 ICC A117.1 / 2010 ADA Standards
4. Changes in level of 1/4" high maximum shall be permitted to be vertical per section 303 of the 2017 ICC A117.1 / 2010 ADA Standards
5. Provide maneuvering clearances at manual swinging doors per section 404 of the 2017 ICC A117.1 / 2010 ADA Standards
6. ADA mounting heights, dimensions, tolerances, etc. shall apply to all construction and the location of all fixtures, etc. unless specifically noted otherwise.


GENERAL INTERIOR NOTES

1. Quantities (area, perimeter, etc.) shown on finish schedule are approximate and are provided as a convenience to the Contractor. Actual quantities may vary and it is the responsibility of the Contractor to field verify.
2. Anything specified with a directional pattern (e.g. brushed aluminum, wood grain laminate, etc.) the pattern shall go in the same direction as directed by Architect.
3. The Contractor shall provide all necessary blocking in walls for support of all equipment, shelving, accessories, grab bars, and other required elements.
4. Provide pressure treated wood where in contact with concrete or masonry.
5. Ease all edges on casework to prevent sharp corners.
6. Paint all HVAC wall grilles to match adjacent surface color unless otherwise noted or instructed by the Architect.
7. Use moisture resistant gypsum board at all walls subject to moisture unless wall will be subject to standing water or frequent wetting in which case you shall use cementitious backer.
8. Provide thresholds where required. All shall be ADA compliant.
9. All gypsum board to have a level 4 finish unless otherwise indicated.

BIDDING INQUIRES


Company: Express Oil Change
Contact: Chris Plummer
E-Mail: chris.plummer@expressoil.com
Phone: 205-945-1771

Note: Sub-contractors to call bidding General Contractor for questions



Express Oil Change & Tire Engineers
Hwy 43 Lurleen B Wallace & 27th Street
Northport, AL 35476

NORTH



Sheet Index	
Sheet Number	Sheet Name
T100	Title Sheet
G100	General Information
G200	Architectural Specifications
G201	Architectural Specifications
G202	Architectural Specifications
G300	EOC Standards - Exterior
G301	EOC Standards - Interior
G400	Building COMCheck
LS100	Life Safety / Code Summary
LS101	Life Safety / Code Summary
LS102	Life Safety Plan - Main
LS103	Life Safety - Pit
AS100	Architectural Site Plan
A100	Floor Plan - Main
A101	Pit Floor Plan and Site Details
A102	Foundation Details
A103	Enlarged Floor Plans and Details
A104	Reflected Ceiling Plan - Main
A105	Reflected Ceiling Plan - Pit
A106	Floor Plan - Equipment Platform
A107	Reflected Ceiling Plan - Equipment Platform
A108	Roof Plan
A200	Exterior Elevation - Front (West)
A201	Exterior Elevation - Rear (East)
A202	Exterior Elevation - Left (North)
A203	Exterior Elevation - Right (South)
A300	Building Sections
A301	Building Sections
A302	Building Sections
A400	Wall Types
A600	Interior Elevations
A601	Interior Elevations
A602	Interior Elevations
A605	Interior Dimensional Info.
A610	Floor Finishes - Main
A611	Floor Finishes - Pit
A620	Schedules
A621	Finish Schedules & Head, Jamb, and Sill Details
R100	3D Views
S0.1	General Notes and Special Inspections
S0.2	Typical Details
S1.1	Foundation Plan
S3.1	Roof Framing Plan
S5.1	Sections and Details
S5.2	Sections and Details
M0.01	Mechanical Legend, Abbreviations and Schedules
M0.02	Mechanical Specifications
M0.03	Mechanical Specifications
M0.04	Mechanical ComCheck
M1.01	Mechanical Floor Plan
M1.02	Partial Mechanical Plans - Pit and Platform
M2.01	Mechanical Details
M2.02	Mechanical Details
P0.01	Plumbing Legend, Abbreviations, and Schedules
P0.02	Plumbing Specifications
P0.03	Plumbing Specifications
P1.01	Plumbing Floor Plan - Gravity
P1.02	Plumbing Floor Plan - Pressure
P1.03	Partial Plumbing Plans - Pit and Platform
P2.01	Gravity Riser
P2.02	Pressure Riser
P2.03	Plumbing Details
E100	General Notes and Fixture Schedules
E101	Symbol Legends and Details
E102	Single Line Diagram and Panelboard Schedules
E103	Details
E104	Site Plan - Electrical
E200	Main Level Floor Plan - Lighting
E201	Pit Level & Equipment Platform Floor Plan - Lighting
E300	Main Level Plan - Power & Voice/Data
E301	Pit Level Equipment Plan - Power & Voice/ Data
E400	Main Level Floor Plan - Elec. Conn. to Mech.
E401	Equip. Platform Plan - Elec. Conn. to Mech.
E500	Specifications
E600	ComCheck



Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

General Information

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A
G100	
Scale	12" = 1'-0"

GENERAL NOTES

1. **GENERAL CONTRACTOR SHALL ENSURE EACH OF THE FOLLOWING HAVE BEEN REVIEWED BY THE MANUFACTURER FOR COMPLIANCE WITH LOCAL CONDITIONS/REQUIREMENTS PRIOR TO BIDDING/ORDERING/INSTALLING: ROOFING, DOORS, WINDOWS/STOREFRONT, GLAZING, DOOR HARDWARE, PAINT, AND FIRE EXTINGUISHERS.**

2. **GENERAL CONTRACTOR SHALL PROVIDE SUBMITTALS / SHOP DRAWINGS FOR EACH PRODUCT LISTED UNDER ARCHITECTURAL SPECIFICATIONS. ALL SUBMITTALS / SHOP DRAWINGS ARE TO BE APPROVED BY THE OWNER AND/OR THE A/E PRIOR TO ORDERING.**

3. **PROVIDE MANUFACTURER'S STANDARD WARRANTY FOR ALL SPECIFIED PRODUCTS.**

4. **ALL EXTERIOR SIGNAGE AND SCONCES BY OTHERS.**

5. **ALL FURNITURE AND EQUIPMENT BY OTHERS. COORDINATE PLACEMENT WITH OWNER PRIOR TO ROUGHING IN REQUIRED UTILITIES.**

6. **ALL COMPARABLE PRODUCTS TO BE REVIEWED AND APPROVED BY THE OWNER PRIOR TO BID.**

7. **GC SHALL BE RESPONSIBLE FOR CHECKING WITH THE LOCAL AHJ ON ANY DEFERRED SUBMITTALS THAT MAY BE REQUIRED TO BE APPROVED BY THE AHJ PRIOR TO CONSTRUCTION.**

DIVISION 4 - MASONRY

042200 - Concrete Unit Masonry

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Block USA or a comparable product by an approved manufacturer.

Products

A. Concrete Masonry Units

1. Finish: Smooth and split-face

2. Min. Compressive Strength: See Structural

3. Density Classification: See Structural

4. Provide types, shapes and sizes as indicated

5. Integral Water Repellent: Provide RainBloc 80 by ACM Chemistries or a comparable product by an approved manufacturer.

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Concrete Products Group or Echelon Masonry or approved comparable product by an approved manufacturer.

Products

B. Structural Half-Highs

1. Spec-Brik (CPG) or Quik-Brik (Echelon)

2. Size: 8x4x16

3. Color: Stanton Blend (CPG) or Richfield Blend (Echelon) with flash.

*Provide full mock-up for Owner's Approval prior to ordering.

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Argos or an approved comparable product by an approved manufacturer.

Products

C. Mortar

1. Type: See Structural

2. Color: Argos Magnolia Dark at cmu and structural half-highs

3. Liquid Mortar Additive: Provide RainBloc for Mortar or a comparable product by an approved manufacturer.

Subject to compliance with requirements, provide products indicated below:

Products

D. Joint Reinforcement

1. Type: Hot dipped galvanized, carbon steel (truss)

2. Size: 0.187" diameter

3. Length: Not less than 10'

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Mortar Net Solutions or an approved comparable products by an approved manufacturer.

Subject to compliance with requirements, provide products indicated below:

E. Single Wythe Concrete Masonry Unit Drainage System

1. BlockFlash

055000- Metal Fabrications

Products

A. Concrete-filled Steel Pipe Bollards

1. Material: Schedule 40 steel pipe

2. Height: 3'-6"

3. Diameter: 4"

4. Finish: Painted (See Finish Schedule)

Installation:

See drawings for installation details.

055113- Metal Pan Stairs

Delegated Design: Engage a qualified professional engineer to design stairs and railings and provide sealed calculations and drawings.

Products:

A. Metal Pan Stairs

1. Steel Sheet Thickness: 0.067" minimum

2. Uniform Load: 100 lbf/sf

3. Concentrated Load: 300 lbf applied on an area of 4 sq. in.

4. Finish: Painted (See Finish Schedule)

5. Uniform and concentrated loads need not be assumed to act concurrently.

6. Stair Framing: Capable of withstanding stresses resulting from railing loads in addition to loads specified above.

B. Stair Tread Bar Ribbed Abrasive Nosing

1. Basis of Design: Nystrom Model V951

2. Extents: Install Nosing to the full length of steps

3. Color: Safety Yellow

4. Type: Short Nose, Aluminum Extruded Anchor

C. Stair Railings

1. Rails and Posts: 1 5/8" diameter

2. Picket Infill: 1/2" round pickets spaced less than 4 inches clear.

D. Installation: Install per manufacturer's standard written instructions.

E. Warranty: Provide manufacturer's standard material warranty.

055133 - Ladders

Manufacturers:

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Grainger, or a comparable product by an approved manufacturer:

Product:

A. Fixed Welded-Steel Ladder by Grainger

1. Model F14S C-1 Cottenman Fixed (Pit Ladder)

a. Width: 20 Inches

b. Height: 13 feet

Installation:

Install ladder according to manufacturer's written instructions.

055213- Pipe and Tube Railings

Delegated Design: Engage a qualified professional engineer to design stairs and railings and provide sealed calculations and drawings.

A. Handrails & Top Rails of Guards

1. Rails and Posts: 1 1/2" diameter

2. Uniform Load: 50lbf/ft in any direction.

3. Concentrated Load: 200 lbf applied in any direction

4. Uniform and concentrated loads need not be assumed to act concurrently.

5. Type: F or S

6. Material: Schedule 40

7. Finish: Painted (See Finish Schedule)

8. Seismic Performance: See Structural

B. Infill of Guards

1. Concentrated Load: 50 lbf applied horizontally on an area of 1 SF.

2. Infill load and other loads need not be assumed to act concurrently.

Installation:

Install stairs and railings according to manufacturers' written instructions and with welded connections.

DIVISION 6 - WOOD, PLASTICS AND COMPOSITES

061000- Rough Carpentry

Products:

A. Framing with Dimensional Lumber (Interior Non-Load-Bearing)

1. Thoroughly Dried

2. No. 2 Southern Yellow Pine or No. 2 Douglas Fir

3. Of sizes, shapes, and lengths required.

4. Moisture content shall not exceed 19% at time of installation

B. Miscellaneous Lumber (e.g. Blocking, Furring, etc.)

1. Thoroughly Dried

2. No. 2 Southern Yellow Pine or No. 2 Douglas Fir

3. Of sizes, shapes, and lengths required.

4. Moisture content shall not exceed 19% at time of installation

C. Temporary Bracing, Shoring, etc. as required

1. Thoroughly Dried

2. No. 2 Southern Yellow Pine or No. 2 Douglas Fir

3. Of sizes, shapes, and lengths required.

4. Moisture content shall not exceed 19% at time of installation

D. Wood Fascia Board (inc. frieze board)

1. Thouroughly dried

2. No. 2 Southern Yellow Pine or No. 2 Douglas Fir

3. Of sizes, shapes, and lengths required.

4. Moisture content shall not exceed 19% at time of installation.

5. Painted (see Finish Schedule)

E. Plywood decking (Equipment Platform)

1. Plywood Type: Exposure 1

2. Plywood Grade: BC

3. Thickness: As indicated on drawings

4. Square Edge

5. Class: C Fire Rating

6. Flame Spread Rating 76-200 / Smoke Developed Index <450

F. Plywood decking (Dumpster Roof)

1. Plywood Type: Exposure 1

2. Plywood Grade: BC

3. Thickness: As indicated on drawings

4. Square Edge

Note:

1. All plywood which has any edge or surface permanently exposed to the weather shall be of the exterior type.

2. All wood exposed to weather and/or in contact with masonry or concrete shall be pressure-treated lumber.

061533- Composite Decking

Products

A. Plastic Decking for Dumpster Enclosure Doors

1. Composite plastic lumber

2. Solid shapes made from a mixture of cellulose fiber and polyethylene or polypropylene.

3. Surface Texture: Smooth

4. Color: See Finish Schedule.

5. Size: See dumpster details.

Installation:

Install plastic decking according to manufacturers' written instructions.

Warranty:

Provide manufacturer's standard material warranty.

066400 Plastic Paneling (Fiberglass Reinforced Panels)

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Marlite Wall Systems, or a comparable product by one of the following:

1. Kal-Lite

2. Crane Composites

3. Panolam

Product Requirements:

A. Provide standard FRP (Fiber Reinforced Plastic) panels in 4' x 8' textured panels.

B. Color: As indicated on the Finish Schedule

C. Conform to all building code requirements for interior finish for smoke and flame spread requirements tested in accordance with ASTM 84

D. Wall required Rating - Class A

Submittals:

Submit shop drawings (elevations of each wall) showing location of paneling and trim members.

Installation:

A. Install per manufacturer's written standards.

Warranty:

A. Provide manufacturer's standard warranty.

DIVISION 7 - THERMAL AND MOISTURE PROTECTION

071900- Water Repellents

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Ghostshield or a comparable product from an approved manufacturer.

Products

A. Water Repellant

1. ISO-Tek 8540

2. Color: Clear

Installation:

Install water repellents according to manufacturers' written instructions.

Warranty:

Provide manufacturers' standard product warranty.

072100- Thermal Insulation

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Owens Corning, or a comparable product by one of the following:

1. Johns Manville

2. CertainTeed

Products:

A. Kraft Faced (Vapor Retarder) Batt Insulation:

1. EcoTouch PINK Fiberglass Insulation

2. R-20; where indicated

B. Unfaced Batt Insulation:

1. EcoTouch PINK Fiberglass Insulation

2. R-38; where indicated.

C. Eave Ventilation Troughs:

1. Preformed, rigid fiberboard or plastic sheets designed and sized to fit between roof framing members and to provide ventilation between insulated attic space and vented eaves.

Installation:

Install insulation and accessories according to manufacturers' written instructions.

Warranty:

Provide manufacturers' standard material warranty.

072600 Vapor Retarders

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Reef Industries, or a comparable product by an approved manufacturer.

Products:

A. Reinforced Under Slab Vapor Retarder:

1. Griffolyn 10 Mil Green

2. Thickness: 10 mil

3. Max Perm Rating: 0.1 perm

4. Lap: 12" and tape with manufacturer recommended tape

Installation:

Install vapor retarders according to manufacturers' written instructions.

Warranty:

Provide manufacturers' standard product warranty.

072726- Fluid-Applied Membrane Air Barrier

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by W.R. Meadows, or a comparable product by an approved manufacturer.

Products:

A. Liquid Membrane Air/Vapor & Liquid Moisture Barrier

1. Air-Shield LMP

Installation:

Install fluid applied membrane air barriers according to manufacturers' written instructions.

Warranty:

Provide manufacturer's standard product warranty.

074113.16- Standing-Seam Metal Roof Panels (Standard)

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Berridge Manufacturing Co. or comparable product by an approved manufacturer.

Products:

A. Metal Panel: Cee-Lock

1. Structural Performance: Provide metal panel systems capable of withstanding the effects of the following loads, based on testing according to ASTM E 1592.

a. Wind Loads: See Structural.

b. Other Design Loads: See Structural.

c. Deflection Limits: See Structural.

2. Air Infiltration: Air leakage of not more than 0.06 cfm/sq. ft when tested according to ASTM E 1680 and ASTM E 283 at the following test-pressure difference:

a. Test-Pressure Difference: 6.24 lbf/sq. ft.

3. Water Penetration under Static Pressure: No water penetration when tested according to ASTM E 1646 and ASTM E 331 at the following test-pressure difference:

a. Test-Pressure Difference: 15 lbf/sq. ft.

4. Wind-Uplift Resistance: Provide metal roof panel assemblies that comply with UL 580 for wind-uplift-resistance class indicated.

a. Uplift Rating: UL 90.

Thermal Movements: Allow for thermal movements from ambient and surface temperature changes by preventing buckling, opening of joints, overstreessing of components, failure of joint sealants, failure of connections, and other detrimental effects.

6. Material: Metallic coated steel

7. Nominal Thickness: 24 gauge

8. Finish: Two-coat fluoropolymer.

9. Color: See Finish Schedule (verify sample with Owner prior to ordering)

10. Panel Coverage: 16.5 inches

11. Panel Height: 1.5 inches

12. Slope: As indicated on roof plan

B. Underlayment

1. Two layers of 15# felt.

C. Snowguards

1. Provide snowguards if required by AHJ.

D. Ridge/Hip Cap

1. Provide preformed ridge/hip cap by roofing manufacturer.

2. Color: Match Roof Color.

3. Material: Match Roof.

Installation:

Install metal panels, underlayment, vents, and accessories according to manufacturers' written instructions.

Warranty:

Provide manufacturers' standard material and product warranties.

074293 Soffit Panels (Standard)

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by James Hardie Building Products, Inc., or a comparable product by an approved manufacturer.

Products:

A. Smooth Vented Soffits

1. Structural Performance: Provide soffit systems capable of withstanding the effects of the following loads:

a. Wind Loads: See Structural.

b. Deflection Limits: See Structural.

2. Net Free Area: 5 sq. in. per linear foot.

3. Width: 12"

4. Thickness: 0.25"

5. Color: Painted. (See Finish Schedule)

6. Jointing: Provide paintable PVC "H" Jointer between panels.

Installation:

Install soffit panels and accessories according to manufacturers' written instructions.

Warranty:

Provide manufacturers' standard material warranty.

077100- Roof Specialties (Standard)

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Roof Drainage Components & Accessories, Inc. or a comparable product by an approved manufacturer.

Products:

A. Gutters (alum.):

1. Style:Smooth Box Gutter - "F" Style

2. Size: 5"

3. Color: Match Roof Color

B. Downspouts (alum.):

1. Style: Smooth Box Downspout

2. Size: 3"x4"

3. Color: Match Roof Color

C. Downspout elbow - Match downspout color

D. Straps

1. Smooth Box Downspout Strap.

2. Color: Match Roof Color.

E. Gutter Guard

1. Continuous screened leaf guard w/ frame.

2. Material: Stainless Steel

Installation:

Install roof specialties according to manufacturers' written instructions.

Warranty:

Provide manufacturers' standard material warranty.

077100- Roof Specialties (Standard)

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Metal-Era Roofing Products or comparable product by an approved manufacturer.

A. Coping Cap

1. Product: Creative Design Series - Creative Design Reveal Coping

2. 22 gauge w/ kynar finish

3. Color : To be selected from Manufacturer's Full Range of colors

4. Face & Back Dimension: 4 inches minimum (Dumpster / HVAC Enclosure)

Installation:

Install roof specialties according to manufacturers' written instructions.

Warranty:

Provide manufacturers' standard material warranty.

079200- Joint Sealants

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Tremco, or a comparable product by one of the following:

1. BASF Building Systems

2. Pecora Corporation

3. Dow Corning Corp.

Products:

A. Silicone (for use around plumbing fixtures and around glazing):

1. Spectrem 2

2. Color: Clear

B. Urethane (for use at masonry, control joints, and rough openings)

1. Dymonic 100

2. Color: To match adjacent material color (color and paintable)

C. Joint Sealant Backing:

1. Closed cell material with a surface skin or as approved by sealant manufacturer

Installation:

Install sealants and proper backing according to manufacturers' written instructions.

Warranty:

Provide manufacturers' standard product warranty.

079219- Acoustical Joint Sealants

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by USG or a comparable product by an approved manufacturer.

Products:

A. Acoustical Joint Sealant


1. USG Sheetrock Brand Acoustical Sealant

Installation:

Install sealants according to manufacturers' written instructions.

Warranty:

Provide manufacturer's standard warranty.



Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Architectural Specifications	
Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A
G200	
Scale	12" = 1'-0"

087100- Door Hardware (Oil Change Building)			
Manufacturers:			
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by the following manufacturers, or approved equal:			
1.	MK- McKinney		
2.	AD- Adams Rite		
3.	YA- Yale		
4.	RO- Rockwood		
5.	NO- Norton		
6.	PE- Pemko		
General Notes:			
1.	Hardware listed for design criteria, confirm with specific door manufacturer.		
2.	Finishes for all door hardware are to be as indicated on Finish Schedule.		
Hardware Sets:			
Set: 1.0			
Doors: 1			
Description: EXT - ALUM			
1	Continuous Hinge	MCK-25HD	MK
1	Deadlatch	4900 x 4591	AD
1	Cylinder	Mort / Cyl as required	YA
2	Pull	BF168	RO
1	Surface Closer	CLP8501	NO
1	Mtg Plate	as required	NO
1	Threshold	271A Pemkote MSES25SS	PE
1	Gasketing	by door / frame mfg	
1	Sweep	315CN	PE
Set: 2.0			
Doors: 3, 15, 16			
Description: WAITING ROOM / STORAGE ROOM / PIT LADDER			
4	Hinge	TA2714 4-1/2" x 4-1/2"	MK
1	Cylindrical Lock (classroom)	PB 5408LN	YA
1	Surface Closer	8501 Reg / PA	NO
1	Kick Plate	K1050 8" X 2" LDW 4BE CSK	RO
1	Door Stop	409 / 446 [as required]	RO
1	Gasketing	S773D	PE
Set: 3			
Doors: 7, 11			
Description: EXT - BAY			
4	Hinge (heavy weight)	T4A3386 NRP 4-1/2" x 4-1/2"	MK
1	Exit Device (rim, nightlatch)	7150 WS PB627F	YA
1	Cylinder	Mort / Cyl as required	YA
1	Surface Closer	CLP8501	NO
1	Threshold	271A Pemkote MSES25SS	PE
1	Gasketing	S773D	PE
1	Rain Guard	348C x LAR	PE
1	Sweep	315CN	PE
Set: 4.0			
Doors: 2			
Description: TOILET			
4	Hinge	TA2714 4-1/2" x 4-1/2"	MK
1	Cylindrical Lock (privacy)	PB 5402LN	YA
1	Mop Plate	K1050 4" X 1" LDW 4BE CSK	RO
1	Door Stop	409 / 446 [as required]	RO
1	Gasketing	S773D	PE
1	Surface Closer	8501 Reg / PA	NO
Set: 5.0			
Doors: 14			
Description: OFFICE			
4	Hinge	TA2714 4-1/2" x 4-1/2"	MK
1	Cylindrical Lock (entry)	PB 5407LN	YA
1	Door Stop	409 / 446 [as required]	RO
1	Threshold	271A Pemkote MSES25SS	PE
1	Gasketing	S773D	PE
1	Sweep	315CN	PE
1	Surface Closer	8501 Reg / PA	NO
Set: 6.0			
Doors: 13			
Description: BREAK			
4	Hinge	TA2714 4-1/2" x 4-1/2"	MK
1	Passage Set	PB 5401LN	YA
1	Surface Closer	8501 Reg / PA	NO
1	Mop Plate	K1050 4" X 1" LDW 4BE CSK	RO
1	Kick Plate	K1050 8" X 2" LDW 4BE CSK	RO
1	Door Stop	409 / 446 [as required]	RO
1	Gasketing	S773D	PE
Set: 7.0			
Doors: 12			
Description: SHOP TOILET			
4	Hinge	TA2714 4-1/2" x 4-1/2"	MK
1	Cylindrical Lock (privacy)	PB 5402LN	YA
1	Mop Plate	K1050 4" X 1" LDW 4BE CSK	RO
1	Door Stop	409 / 446 [as required]	RO
1	Threshold	271A Pemkote MSES25SS	PE
1	Gasketing	S773D	PE
1	Sweep	315CN	PE
1	Surface Closer	8501 Reg / PA	NO
Set: 8.0			
Doors: 4, 5, 6, 8, 9, 10			
Description: OH DOOR			
1	Hardware	By door mfg	
Installation:			
Install door hardware according to manufacturers' written instructions.			
All door hardware (Interior and Exterior) to be keyed alike.			
Warranty:			
Provide manufacturers' standard product warranty.			

088000- Glazing (IGU) Standard and Hurricane Non-Impact			
Manufacturers:			
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Vitro</u> , or a comparable product by one of the following:			
1.	Guardian Industries Corp.		
2.	Or Approved equal		
Products:			
Notes:			
1.)	All glazing to have proper labels as required by local AHJ and building codes.		
2.)	All glazing shall be reviewed and approved by the local distributor to meet the requirements for the region in which the glazing is being installed. Any issues with items specified shall be brought to the attention of the Architect prior to bid.		
A.	GL-1 Insulated Glass Unit		
	Double Glazed Clear Solar Control Insulating Glass Unit Solarban® 90 on Clear 6mm (2) Air 1/2" (12.7mm) Clear 6mm		
1.	Conformance: ASTM E 2190		
2.	Outdoor Lite: Clear Float Glass as manufactured by Vitro Architectural Glass		
	a. Conformance: ASTM C 1036, Type 1, Class 1, Quality q3.		
	b. Glass Thickness: 6mm (1/4")		
	c. Magnetic Sputter Vacuum Deposition Coating (MSVD): ASTM C 1376.		
	d. Coating: Solarban® 90 on Surface # 2		
	e. Heat-Treatment: Tempered; ASTM C 1048, Kind FT; Safety Glazing meets ANSI Z97.1 and CPSC 16CFR-1201		
3.	Interspace Content: Air 1/2" (12.7mm)		
4.	Indoor Lite: Clear float glass as manufactured by Vitro Architectural Glass		
	a. Conformance: ASTM C 1036, Type 1, Class 1, Quality q3.		
	b. Heat-Treatment: Tempered; ASTM C 1048, Kind FT; Safety Glazing meets ANSI Z97.1 and CPSC 16CFR-1201		
	c. Glass Thickness: 6mm (1/4")		
5.	Performance Requirements:		
	a. Visible Light Transmittance: 51 percent minimum.		
	b. Winter Nighttime U-Factor: 0.23 (Btu/hr*ft²°F) maximum.		
	c. Summer daytime U-Factor: 0.27 (Btu/hr*ft²°F) maximum.		
	d. Shading Coefficient: 0.27 maximum.		
	e. Solar Heat Gain Coefficient: 0.23 maximum.		
	f. Outdoor Visible Light Reflectance: 12 percent maximum.		
B.	GL-2 Monolithic Single-Glaze Float-Glass:		
	Monolithic Clear Glass Clear 6mm		
1.	Clear float glass as manufactured by Vitro Architectural Glass		
	a. Conformance: ASTM C 1036, Type 1, Class 1, Quality q3.		
	b. Heat-Treatment: Tempered; ASTM C 1048, Kind FT; Safety Glazing meets ANSI Z97.1 and CPSC 16CFR-1201		
	c. Glass Thickness: 6mm (1/4")		
2.	Performance Requirements:		
	a. Visible Light Transmittance: 89 percent minimum.		
	b. Winter Nighttime U-Factor: 0.102 (Btu/hr*ft²°F) maximum.		
	c. Summer daytime U-Factor: 0.92 (Btu/hr*ft²°F) maximum.		
	d. Shading Coefficient: 0.94 maximum.		
	e. Solar Heat Gain Coefficient: 0.82 maximum.		
	f. Outdoor Visible Light Reflectance: 8 percent maximum.		
C.	Glazing Installation		
	1. Install per manufacturers' standard written instructions.		
D.	Glazing warranty		
	1. Provide manufacturers' standard product warranty.		
DIVISION 9 - FINISHES			
092900- Gypsum Board			
Manufacturers:			
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Lafarge</u> unless otherwise indicated, or a comparable product by one of the following:			
1.	Georgia-Pacific		
2.	USG		
3.	National Gypsum		
Products:			
A.	Moisture and Mold-Resistant Type: Mold Defense		
	1. Thickness: 1/2 inch		
	2. Long Edges: Tapered		
B.	Water-resistant Type: Watercheck (@ Toilet Rooms and behind plumbing fixtures)		
	1. Thickness: 1/2 inch		
	2. Long Edges: Tapered		
	3. Finish: Level 4		
	4. Cuts: All cuts in board shall be covered with special waterproofing sealant as recommended by the manufacturer.		
C.	Type X: Firecheck (As Required)		
	1. Thickness: 5/8"		
	2. Long Edges: Tapered		
	3. Finish: Level 4		
	4. All penetrations and joints to be sealed with fire caulk as recommended by the manufacturer.		
Installation:			
Install gypsum board and accessories according to manufacturers' written instructions.			
Warranty:			
Provide manufacturers' standard product warranty.			
093013- Ceramic Tiling			
Manufacturer:			
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below:			
Products:			
A.	Ceramic Tile: Volume 1.0 by Daltile		
	1. Size: 12"x12"		
	2. Color: Intensity Pebble VL72		
B.	Epoxy Grout: Kerapoxy by MAPEI		
	1. Color: 47 Charcoal		
C.	Transition Strip: RENO-U 3/8" /10 mm by Schluter Systems		
	1. Type: ADA Compliant		
	2. Finish: Satin Anodized Aluminum		
Installation:			
Install ceramic tile and accessories according to manufacturers' written instructions.			
Warranty:			
Provide manufacturers' standard product warranty.			

096513- Resilient Base and Accessories			
Manufacturers:			
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Roppe</u> , or a comparable product by one of the following:			
1.	Johnsontite, a Tarkett Company		
2.	Armstrong World Industries		
3.	Or Approved equal		
Products:			
A.	Rubber Base: Pinnacle Rubber by Roppe		
	1. Height: 4"		
	2. Length: Coils in manufacturer's standard length		
	3. Outside Corners: Job formed		
	4. Inside Corners: Job formed		
	5. Color as indicated on finish schedule.		
B.	Adhesives: As recommended by the manufacturer		
Installation:			
Install resilient base according to manufacturers' written instructions.			
Warranty:			
Provide manufacturers' standard product warranty.			
099113- Exterior Painting			
Manufacturer:			
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Sherwin Williams</u> .			
Products:			
A.	Masonry: Pro Industrial Urethane Alkyd Enamel Gloss, B54-150 Series		
B.	Steel: Pro Industrial Urethane Alkyd Enamel Gloss, B54-150 Series		
C.	Wood: Pro Industrial Urethane Alkyd Enamel Gloss, B54-150 Series		
D.	Aluminum: Pro Industrial Urethane Alkyd Enamel Gloss, B54-150 Series		
Note: Use 1 coat primer as recommended by manufacturer and 2 finish coats unless otherwise recommended by the manufacturer.			
Installation:			
Install exterior paint according to manufacturers' written instructions.			
Warranty:			
Provide manufacturers' standard product warranty.			
099123- Interior Painting			
Manufacturer:			
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Sherwin Williams</u> .			
Products:			
A.	Masonry: Pro Industrial Pre-Catalyzed Water Based Epoxy Semi-Gloss, K46W151 Series		
B.	Steel: Pro Industrial Urethane Alkyd Enamel Gloss, B54-150 Series		
C.	Wood: Pro Industrial Urethane Alkyd Enamel Gloss, B54-150 Series		
D.	Gypsum Board in Office Area: ProMar 200 Zero VOC Interior Latex Egshel, B20W2600 Series. Use extreme bond primer at vinyl graphics.		
E.	Gypsum Board in Bay Area: ProMar 200 Zero VOC Interior Latex Egshel, B20W2600 Series. Use extreme bond primer at vinyl graphics.		
F.	Gypsum Board Ceilings: ProMar 200 Zero VOC Interior Latex Flat, B30W2650 Series		
G.	Sealed Concrete Floors: ArmorSeal Rextthane I Floor Coating + Shark Grip (1000 HS primer)		
Note: Use 1 coat primer as recommended by manufacturer and 2 finish coats unless otherwise recommended by the manufacturer.			
Installation:			
Install interior paint according to manufacturers' written instructions.			
Warranty:			
Provide manufacturers' standard product warranty.			
DIVISION 10 - SPECIALTIES			
101419- Dimensional Letter Signage - By others.			
101423.13 Room-Identification Signage			
See drawing on A602.			
102600 - Wall and Door Protection			
Manufacturer:			
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>InPro Corporation</u> :			
Products:			
A.	Stainless Steel Flush Mount Corner Guards		
B.	Corner Radius: 1/8"		
C.	Height: 4'-0"		
D.	Width: 1 1/2"		
E.	Materials: Stainless Steel: Type 430, 16 gauge		
F.	Attachment: Pre-drilled beveled holes and Phillips head screws.		
G.	Finish: Stainless Steel No. 4 satin finish.		
H.	Location: As indicated on drawings.		
J.	Installation: Install per manufacturer's standard written instructions.		
K.	Warranty: Provide manufacturers' standard product warranty.		
102800- Toilet, Bath, and Laundry Accessories			
The following list of accessories is essentially complete; however, the Contractor shall examine the drawings carefully and shall supply such items not specifically called for to provide a complete installation.			
Manufacturers:			
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Bradley Corporation</u> or a comparable product by one of the following:			
1.	Bobrick Washroom Equipment, Inc.		
2.	American Specialties, Inc.		
3.	Or Approved Equal		
Products:			
A.	Robe Hook: Bradley Model 915.		
B.	Grab Bars: Bradley Model 812-001-42, Model 812-001-36, and Model 812-001-24		
C.	Toilet Tissue Dispenser: Bradley Model 5425 (By Others)		
D.	Mirror: Bradley Model 780-2436		
E.	Soap Dispenser: Bradley Model 6563 (By Others)		
F.	Paper Towel Dispenser: Bradley Model 2494 (By Others)		
G.	Under Lavatory Guard: Truebro Lav Guard 2 by IPS Corporation		
H.	Baby Changing Station: Bradley Model 9631 (Light Gray)		

102800- Toilet, Bath, and Laundry Accessories (continued):	
<u>Installation:</u>	
1. Install accessories according to manufacturers' written instructions, using fasteners appropriate to substrate indicated and recommended by unit manufacturer. Install units level, plumb, and firmly anchored in locations and heights indicated.	
2. Install grab bars to withstand a downward load of at least 250 lbf, when tested according to ASTM F 446.	
<u>Warranty:</u>	
Provide manufacturers' standard product warranty.	
104413- Fire Department Lock Box	
<u>Manufacturers:</u>	
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Knox</u> , or a comparable product by one of the following:	
1.	Kidde
2.	Or Approved Equal
<u>Products:</u>	
A.	Lock Box: 3200 Series Hinged Door Surface Mount
i.	Color: As indicated on Finish Schedule
<u>Installation:</u>	
1. Install fire department lock box in location and height as required by the authorities having jurisdiction.	
2. Install per manufacturer's written installation instructions.	
<u>Warranty:</u>	
Provide manufacturers' standard product warranty.	
104416- Fire Extinguishers	
<u>Manufacturers:</u>	
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Amerex Corporation</u> , or a comparable product by one of the following:	
1.	Larsens Manufacturing Company
2.	JL Industries
3.	Or Approved Equal
<u>Products:</u>	
A.	ABC Dry Chemical Extinguisher: Amerex Model B456
B.	Wall Bracket: Amerex Model 0546 Wall
C.	UL and ULC Rating: 4A-80BC
<u>Installation:</u>	
1. Install fire extinguishers in locations and heights indicated and in compliance with requirements of authorities having jurisdiction.	
2. Install fire extinguishers and brackets according to manufacturers' written instructions.	
<u>Warranty:</u>	
Provide manufacturers' standard product warranty.	
DIVISION 12- FURNISHINGS	
123623.13 Plastic-Laminate-Clad Countertops	
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Wilsonart</u> .	
<u>Products:</u>	
A.	Plastic Laminate #1
i.	High pressure decorative laminate: NEMA LD3
ii.	Grade: HGS
iii.	Color: 4880-38 Carbon Mesh
B.	Adhesives: as recommended by the manufacturer
<u>Installation:</u>	
Install plastic laminate according to manufacturers' written instructions.	
<u>Warranty:</u>	
Provide manufacturers' standard product warranty.	
DIVISION 31- EARTHWORK	
313116- Termite Control	
Provide EPA Registered termiticide acceptable to authorities having jurisdiction, in an aqueous solution formulated to prevent termite infestation.	
DIVISION 33 - UTILITIES	
334600- Subdrainage	
Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Carlisle</u> .	
<u>Products:</u>	
A.	CCW MiraDrain 6200 and 9800
B.	CCW MiraStop
C.	CCW MiraClay Woven Geotextile
D.	CCW MiraClay Granules or Mastic
<u>Installation:</u>	
Install subdrainage products according to manufacturers' written instructions.	

EXPRESS OIL CHANGE & TIRE ENGINEER STANDARDS - EXTERIOR

EXTERIOR

RED BRICK
On newer prototype buildings, the red brick is left unpainted. The Blue Blood stripe extends all the way up to the flashing on the roof down to the top of the bay doors and all the way around the building's. On Peak buildings, the peak is painted summit gray.
The Bay Doors are painted a bright white. The hollows that protect the bay doors are painted Blue Blood. Downspouts and gutters to be painted Blue Blood.
If the building does not have a Peak, you must use the GRAY BRICK color scheme. Must have a Gray, Black, or Blue Roof



3

PAINTED GRAY BRICK

PAINTED GRAY BRICK
Painted buildings include all of the same specs as the RED BRICK buildings except the red brick is painted Summit Gray. Downspouts are painted to match the background of the building.
If the building does not have a Peak, the blue stripe will go all the way around the building.
Must have a Gray, Black, or Blue Roof



4

EXTERIOR

EOC & TE SIGN FOR PEAK BUILDINGS




5

Signage by Others

EXTERIOR

CUSTOM LIGHTBAR (OPTIONAL)
The new lightbar sits underneath the letters and is an aesthetic architectural complement during the day and catches the viewers attention at night.
The lightbar is to sit even with the top of the bay doors and span across all bay doors.



7

Lightbar by Others

EXTERIOR

AWNING
The new metal awning adds a nice modern, industrial look to the buildings and features built-in lighting for customers entering and exiting in late afternoons. Standard size is 12' for most buildings.




9

Awnings by General Contractor. See Details

BRANDED SCONCES

BRANDED SCONCES
40"x24" aluminum sconces light up your building from top to bottom with a glowing logo in center. E sconces are to be placed on oil change side. TE sconces are to be placed on mechanical side. Sconces to be evenly spaced between the bay doors, and vertically centered with the bay doors.



10

Branded Sconces by Others

CHANNEL LETTERS

CHANNEL LETTERS
While channel letters with 3" depth. Channel letter sizing is dictated by space and also may change due to the local sign regulations. In most cases, these letters are treated as directional signage. In most cases, sizes vary from 18" to 24".


FONT
Interstate Bold Condensed - Slant tracking



8

Letters by Others

Note: Items shown on this page are EOC standards. See Finish Schedule for actual materials to be used on this project.



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC. All Rights Reserved.

EOC Standards - Exterior	
Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A
G300	
Scale	12" = 1'-0"

11/16/2025 9:00:24 AM

COMcheck Software Version COMcheckWeb
Envelope Compliance Certificate

Project Information

Energy Code: 2015 IECC
Project Title: 24028_EOC Northport, AL
Location: Northport, Alabama
Climate Zone: 3a
Project Type: New Construction
Vertical Cladding / Wall Area: 13%

Construction Site: Hwy 43 Unleashed Wallace Northport, Alabama 35476
Owner/Agent: Express Oil Change & Tire Engineers 1880 Southpark Drive Birmingham, Alabama 35244 20594521771 jrovis@expressoil.com
Designer/Contractor: Aho Architects, LLC 1855 Data Drive, Ste. 150 Hoover, Alabama 35344 205-983-6000 ahoarch@ahoarch.com

Additional Efficiency Package(s): Credits: 1.0 Required, 1.0 Proposed
Reduced Lighting Power, 1.0 Credit

Building Area: 1-Automotive Facility, Nonresidential
Floor Area: 682

Envelope Assemblies

Assembly	Gross Area or Perimeter	Cavity R-Value	Cont. R-Value	Proposed U-Factor	Budget U- Factor
Roof: ATFC Roof, Wood joists, (Bldg. Use 1 - Automotive Facility) Floor: Unheated Slab-On-Grade, Vertical 2 ft., (Bldg. Use 1 - Automotive Facility) (c)	882 110	36.0 —	0.0 0.0	0.007 0.730	0.027 0.730
WALLS Ext. Wall g Oil Change: Wood-Framed, 16in. o.c., (Bldg. Use 1 - Automotive Facility) Window A: Metal Frame: Fixed, Perf. Specs.: Product ID Solarban 90 on clear, SHGC 0.23, PF 3.67, (Bldg. Use 1 - Automotive Facility) (b) Window D: Metal Frame: Fixed, Perf. Specs.: Product ID Solarban 90 on clear, SHGC 0.23, PF 3.67, (Bldg. Use 1 - Automotive Facility) (b) Door #5: Wood, Swinging, (Bldg. Use 1 - Automotive Facility) Door #2: Wood, Swinging, (Bldg. Use 1 - Automotive Facility)	454 12 8 21 21	20.0 — — — —	0.0 — — — —	0.061 0.270 0.460 0.500 0.500	0.064 0.460 0.460 0.610 0.610
EAST Ext. Wall g Corridor: Wood-Framed, 16in. o.c., (Bldg. Use 1 - Automotive Facility) Door #14: Wood, Swinging, (Bldg. Use 1 - Automotive Facility) Door #15: Wood, Swinging, (Bldg. Use 1 - Automotive Facility)	278 21 21	20.0 — —	0.0 — —	0.061 0.500 0.600	0.064 0.610 0.610
SOUTH Ext. Wall g Walking/Trailer 3&B: Wood-Framed, 16in. o.c., (Bldg. Use 1 - Automotive Facility)	439	26.0	0.0	0.064	0.064

Project Title: 24028_EOC Northport, AL
Data Filename: Report date: 11/07/24
Page: 1 of 8

Assembly	Gross Area or Perimeter	Cavity R-Value	Cont. R-Value	Proposed U-Factor	Budget U- Factor
WEST Ext. Wall g Service Wiring & Wiring: Wood-Framed, 16in. o.c., (Bldg. Use 1 - Automotive Facility) Sidelight B: Metal Frame with Thermal Break: Fixed, Perf. Specs.: Product ID Solarban 90 on Clear, SHGC 0.23, PF 0.63, (Bldg. Use 1 - Automotive Facility) (b) Sidelight C: Metal Frame with Thermal Break: Fixed, Perf. Specs.: Product ID Solarban 90 on Clear, SHGC 0.23, PF 0.63, (Bldg. Use 1 - Automotive Facility) (b) Door #1: Glass (over 50% glazing): Metal Frame, Entrance Door, Perf. Specs.: Product ID Solarban 90 on Clear, SHGC 0.23, PF 0.63, (Bldg. Use 1 - Automotive Facility) (b)	209 31 43 21	20.0 — — —	0.0 — — —	0.064 0.270 0.460 0.270	0.064 0.460 0.460 0.770

Envelope PASS(ES): Design 10% Better than code
Envelope Compliance Statement
Consistency Statement: The proposed envelope design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed envelope systems have been designed to meet the 2015 IECC requirements in COMcheck Version COMcheckWeb and to comply with any applicable mandatory requirements listed in the Inspection Checklist.

Name: Tisa Issler-Ingles Signature: Date: 11/07/24

Project Title: 24028_EOC Northport, AL
Data Filename: Report date: 11/07/24
Page: 2 of 8

COMcheck Software Version COMcheckWeb
Inspection Checklist

Energy Code: 2015 IECC

Requirements: 3.0% were addressed directly in the COMcheck software.
Text in the "Comments/Assumptions" column is provided by the user in the COMcheck Requirements screen. For each requirement, the user certifies that a code requirement will be met and how that is documented, or that an exception is being claimed. Where compliance is itemized in a separate table, a reference to that table is provided.

Section # & Req ID	Plan Review	Complies?	Comments/Assumptions
C103.2 (R112)	Plans and/or specifications provide all information with which compliance can be determined for the building envelope and document where exceptions to the standard are claimed.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C402.4.1 (R110)	The vertical fenestration area <= 30 percent of the gross above-grade wall area.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C402.4.1 (R111)	The skylight area <= 3 percent of the gross roof area.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C402.4.2 (R114)	In enclosed spaces > 2,000 sq ft directly under a roof with ceiling heights > 8 ft and used as an office, lobby, atrium, concourse, corridor, storage, gymnasium/fitness center, convention center, automotive service, manufacturing, non-refrigerated warehouse, retail store, distribution/loading area, transportation, or workshop, the following requirements apply: (a) the skylight area under skylight is the half the floor area; (b) the skylight area is daylight zone <= 3 percent with a skylight VT >= 0.40; or a minimum skylight effective aperture >= 1 percent.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C406 (R93)	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the additional energy efficiency package options.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)
Project Title: 24028_EOC Northport, AL
Data Filename: Report date: 11/07/24
Page: 3 of 8

Section # & Req ID	Footings / Foundation Inspection	Complies?	Comments/Assumptions
C103.2 (R14)	Slab edge insulation installed per manufacturer's instructions.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C103.2.1 (R16)	Exterior insulation protected against damage, sunlight, moisture, wind, landscaping and equipment.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C108 (R23)	Installed slab-on-grade insulation type and R-value consistent with insulation specifications reported in plans and COMcheck reports.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	See the Envelope Assemblies table for values.
C402.2.6 (R112)	Radiant heating systems panels installed to >= 48.3.5 on face opposite space being heated.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	See the Envelope Assemblies table for values.

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)
Project Title: 24028_EOC Northport, AL
Data Filename: Report date: 11/07/24
Page: 4 of 8

Section # & Req ID	Insulation Inspection	Complies?	Comments/Assumptions
C103.1.3 (R121)	Fenestration products rated in accordance with NFRC.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C103.1.3 (R121)	Fenestration products are certified to performance labels or certificates provided.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C402.4.3 (R110)	Vertical fenestration SHGC value.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	See the Envelope Assemblies table for values.
C402.4.3 (R111)	Vertical fenestration U-Factor.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	See the Envelope Assemblies table for values.
C402.4.4 (R114)	U-factor of opaque doors associated with the building thermal envelope meets requirements.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	See the Envelope Assemblies table for values.
C402.5.1 (R116)	The building envelope contains a continuous air barrier that is sealed in an approved manner and either constructed or tested in an approved manner. Air barrier penetrations are sealed in an approved manner.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C402.5.2 (R110)	Factory-built fenestration and doors are labeled as meeting air leakage requirements.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C402.5.7 (R111)	Weatherstrips are installed on all building entrances. Doors have self-closing devices.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)
Project Title: 24028_EOC Northport, AL
Data Filename: Report date: 11/07/24
Page: 5 of 8

Section # & Req ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C402.5.5 (R121)	Duct and evaporator coil vents have motorized dampers that automatically close.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)
Project Title: 24028_EOC Northport, AL
Data Filename: Report date: 11/07/24
Page: 6 of 8

Section # & Req ID	Insulation Inspection	Complies?	Comments/Assumptions
C103.1.1 (R12)	Roof insulation installed per manufacturer's instructions. Blown or poured loose-fill insulation is installed only where the roof slope is <=3 in 12.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C103.1.1 (R12)	Building envelope insulation is labeled with R-value or insulation certificate providing R-value and other relevant data.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C103.2 (R17)	Above-grade wall insulation installed per manufacturer's instructions.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C103.2.1 (R14)	Exterior insulation is protected from damage with a protective material. Verification for exposed foundation insulation may need to occur during Foundation Inspection.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C402.2.1 (R111)	Insulation intended to meet the roof insulation requirements cannot be installed on top of a suspended ceiling. Mark this requirement compliant if insulation is installed accordingly.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C104 (R16)	Installed above-grade wall insulation type and R-value consistent with insulation specifications reported in plans and COMcheck reports.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	See the Envelope Assemblies table for values.
C104 (R16)	Installed floor insulation type and R-value consistent with insulation specifications reported in plans and COMcheck reports.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	See the Envelope Assemblies table for values.
C402.2.6 (R116)	Radiant panels and associated components, designed for heat transfer from the panel surfaces to the occupants or indoor space and insulated with a minimum of R-5.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C402.3 (R12)	High-albedo roofs satisfy one of the following: 3-year-aged solar reflectance >= 0.75 or 3-year-aged solar reflectance index >= 44.0.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C104 (R12)	Installed roof insulation type and R-value consistent with insulation specifications reported in plans and COMcheck reports. For some ceiling systems, verification may need to occur during Framing Inspection.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	See the Envelope Assemblies table for values.
C402.5.1 (R11)	All sources of air leakage in the building thermal envelope are sealed, caulked, gasketed, weather stripped or equipped with moisture vapor-permeable wrapping material to minimize air leakage.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	


Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)
Project Title: 24028_EOC Northport, AL
Data Filename: Report date: 11/07/24
Page: 7 of 8

Section # & Req ID	Final Inspection	Complies?	Comments/Assumptions
C402.2.3 (R15)	Where open combustion air ducts provide combustion air to open combustion fuel burning appliances, the appliances and combustion air openings are located outside the building thermal envelope or enclosed in a room, isolated from inside the thermal envelope. Such rooms are sealed and insulated.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C402.5.6 (R11)	Weatherstrips installed on all loading dock cargo doors.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	
C402.5.8 (R16)	Recessed luminaires in thermal envelope to limit infiltration and be IC rated and labeled. Seal between interior finish and luminaire housing.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)
Project Title: 24028_EOC Northport, AL
Data Filename: Report date: 11/07/24
Page: 8 of 8



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Building
COMCheck

Project number: 24028
Date: 11/8/2024
Drawn by: ARC
Checked by: N/A

G400

Scale

1

General Information

PROJECT INFORMATION

Name of Project:

Two Building / Left Hand Oil Change

Client:

Express Oil Change & Tire Engineers

Location:

Northport, AL

Authority Having Jurisdiction (AHJ):

City: Northport

County:

N/A

State:

N/A

Square Footage / Stories / Height:

Main Level G.S.F. = 2,228

Pit Level G.S.F. = 1,420

Total G.S.F. = 3,648

Stories = 1 + Pit

Height = 26'- 4"

PROJECT TYPE

☒ New Construction

☐ Addition

☐ Other

☐ Alteration

☐ Change of Occupancy

BUILDING USE

☐ Single Use

☐ Mixed Use (Separated)

☒ Mixed Use (Non-Separated)

Description: Automotive repair garage used for general service on automobiles.

SPRINKLERED

☐ Yes

☐ Partial

☒ No

4

Special Detailed Requirements Based On Use and Occupancy (2021 IBC)

406.8 Repair Garages

☒ Project complies with 406.8 through 406.8.3

413 Combustible Storage

413.1 High-piled storage of combustible materials over 12'-0" or high-hazard commodities over 6'-0"

☐ Yes

☒ No

413.2 Storage of combustible materials in attics, under-floor, and concealed spaces

☐ Yes

☒ No

414 Hazardous Materials

☒ Project complies with 414.2.1 through 414.2.5 (IFC)Control Areas

☒ Number of Control Areas Provided: Entire Building is one control area

Location

☐ Inside

☐ Outside

Use

☒ Open

☐ Closed

☒ Storage Only

Types of Hazardous Materials (Table 307.1.(1) of IBC and 3206.2 of IFC)

☒ Class IIIB Liquids

☒ Actual Storage per control area: 4040.13 gallons

☒ Class IA Flammable Liquids

☒ Actual Storage per control area: 0.94 gallons

☒ Class IB Flammable Liquids

☒ Actual Storage per control area: 3.25 gallons

☒ High-Hazard Commodities per IFC 2018 3203.6 / 3206.2 (Rubber Tires)

☒ Allowable Quantity: 0-500 s.f.

☒ Actual Quantity: 0 s.f.

2

Codes

☒ 2021 International Building Code

☒ 2021 International Plumbing Code

☒ 2015 International Energy Conservation Code

☒ 2017 ICC/ANSI 117.1

☒ 2021 International Fire Code

☒ 2020 National Electrical Code

☒ 2021 International Fuel Gas Code

☒ 2021 International Mechanical Code

5

General Building Heights and Areas (2021 IBC)

504 Building Height and Areas and 506 Building Area (Per Table 504.3, 504.4, and 506.2)

☐ Allowable Building Height = 40'-0"

☒ Actual Building Height = 26'- 4"

☐ Allowable Number of Stories Above Grade Plane = 1

☒ Actual Number of Stories Above Grade Plane = 1

☐ Allowable Area Factor = 9,000 s.f.

☒ Actual Area = 3648 s.f. (2228 Main Level + 1420 Pit)

505.3 Equipment Platforms

☒ Project complies with 505.3 through 505.3.3

508 Mixed Use and Occupancy

☐ Mixed Use Occupancy (Separated)

☒ Mixed Use Occupancy (Non-Separated)

☐ Does not apply

No separation required between Group B and Group S-1 Occupancies

3

Use and Occupancy Classification(s) (2021 IBC)

☐ Assembly Group A-1

☐ High-Hazard Group H-2

☐ Residential Group R-2

☐ Assembly Group A-2

☐ High-Hazard Group H-3

☐ Residential Group R-3

☐ Assembly Group A-3

☐ High-Hazard Group H-4

☐ Residential Group R-4

☐ Assembly Group A-4

☐ High-Hazard Group H-5

☒ Storage Group S-1

☐ Assembly Group A-5

☐ Institutional Group I-1

☐ Storage Group S-2

☒ Business Group B

☐ Institutional Group I-2

☐ Utility & Misc Group U

☐ Educational Group E

☐ Institutional Group I-3

☐ Factory Group F-1

☐ Institutional Group I-4

☐ Factory Group F-2

☐ Mercantile Group M

☐ High-Hazard Group H-1

☐ Residential Group R-1

6

Types of Construction (2021 IBC)

601 General and 602 Construction Classification

☐ Type IA

☐ Type IB

☐ Type IIA

☐ Type IIB

☐ Type IIIA

☐ Type IIIB

☐ Type IV

☐ Type VA

☒ Type VB

Table 601 Fire Resistance Rating Requirements for Building Elements

Building Elements	Hours Required	Hours Provided
Primary Structural Frame	0	0
Bearing Walls (Exterior)	0	0
Bearing Walls (Interior)	0	N/A
Nonbearing Walls & Partitions (Exterior)	0	0
Nonbearing Walls & Partitions (Interior)	0	0
Floor Construction & Associated Secondary Members	0	0
Roof Construction & Associated Secondary Members	0	0

Table 705.5 Fire Resistance Requirements for Exterior Walls Based on Fire Separation Distance

Fire Separation Distance	Rear (East)	Right (South)	Front (West)	Left (North)
X < 5				
5 ≤ X < 10				
10 ≤ X < 30	= 20'	=10'		= 20'
X ≥ 30			>30'	

X≥30' for Group B and S-1 = 0 hours

10≤X<30' for Group B and S-1 = 0 hours

7

Fire And Smoke Protection Systems (2021 IBC)

718.4 Draftstopping in Attics

☐ Yes

☐ No

☒ Not Required

☐ Openings in the partitions shall be protected by self-closing doors with automatic latches constructed as required for the partitions.

☐ Installed in attics and concealed roof spaces such that any horizontal area does not exceed 3,000 s.f.

8

Interior Finishes (2021 IBC)

Table 803.13 Interior Wall and Ceiling Finish Requirements by Occupancy

Group	Exit Enclosures and Exit Passageways	Corridors	Rooms and Enclosed Spaces
S-1	B	B	C
B	A	B	C

804.4.2 Minimum Critical Radiant Flux

☐ Class I

☒ Class II

9

Fire Protection Systems (2021 IBC)

903 Automatic Sprinkler Systems

903.2.9.1 Repair Garages

☐ Yes

☐ Partial

☒ Not Required

906 Portable Fire Extinguishers

☒ Yes

☐ No

☒ Project complies with 906.1 through 906.10

☒ Project complies NFPA 10

907 Fire Alarm and Detection System

☐ Yes

☒ Not Required

10

Means of Egress (2021 IBC)

DT_2021 IBC Sections 1005.3.1 & 1005.3.2 Egress width Stairways and Other Egress Components (Group S-1)

Occupancy Classification	Name	Number	No. of Occupants	Egress - Stairways	Required Stairway Width	Other Egress Components	Required Capacity in Inches
S-1	Oil Change	3	6.36			0.2	1.27
S-1	Storage	4	0.24			0.2	0.05
S-1	Corridor	6	0.59			0.2	0.12
S-1	Pit	9	6.42	0.3	1.93	0.2	1.28
Subtotal			13.61		1.93		2.72

DT_2021 IBC Table 1005.3.2 Egress width Other Egress Components (Group B)

Occupancy Classification	Name	Number	No. of Occupants	Other Egress Components	Required Capacity in Inches
B	Service Writing	1	1.97	0.2	0.39
B	Toilet	2	0.33	0.2	0.07
B	Manager	5	0.37	0.2	0.07
B	Break Room	7	0.44	0.2	0.09
B	Toilet	8	0.33	0.2	0.07
Subtotal			3.45		0.69

Tables 1006.2.1 Spaces with One Exit or Exit Access Doorway

Occupancy	Max Occupant Load	Max Occupant Load Provided	Number of Exits Required	Number of Exits Provided	Max. Common Path of Travel Allowable (Nonsprinkled)	Max. Provided Common Path of Travel (Nonsprinkled)
S-1	29	13.61	1	2	100'-0"	≤ 100' -0"
B	49	3.45	1	1	100'-0"	≤ 100' -0"

Table 1006.3.3 Minimum Number of Exits or Access to Exits Per Story

Occupant Load Per Story	Minimum Number of Exits or Access to Exits from Story	Number of Exits or Access to Exits from Story Provided
1-500	2	3

Table 1017.2 Exit Access Travel Distance

Occupancy	Without Sprinkler System (Feet)	With Sprinkler System	Max Travel Distance Provided (Feet)
S-1	200	N/A	71'-1"
B	200	N/A	24'-4"

11

Fire Protection Systems (2021 IBC)

12

Interior Environment (2021 IBC)

1208.1 Minimum Room Widths

Habitable spaces are not less than 7 feet in any plan dimension

☒ Yes

☐ No

1208.2 Minimum Ceiling Heights

Occupiable spaces, habitable spaces, and corridors have a ceiling height of not less than 7 feet 6 inches. Bathrooms, toilet rooms, kitchens, storage rooms, and laundry rooms have a ceiling height of not less than 7 feet.

☒ Yes

☐ No

1209.2 Attic spaces

Opening not less than 20 inches by 30 inches is provided for attic area with clear height over 30 inches. 30" headroom provided at or above access opening

☒ Yes

☐ Not Required

Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC. All Rights Reserved.

Life Safety / Code Summary

Project number

24028

Date

11/8/2024

Drawn by

ARC

Checked by

N/A

LS100

Scale

12" = 1'-0"

11/19/2025 9:00:45 AM

29 Plumbing Systems (2021 IBC)

DT_Plumbing Fixture_Group S-1												
Total Occupant Load	Male	Female	Required Water Closets		Water Closets Provided	Required Lavatories		Lavatories Provided	Required Drinking Fountains	Drinking Fountains Provided	Required Service Sinks	Service Sinks Provided
			Male	Female		Male	Female					
13.61	6.81	6.81	0.07	0.07	1	0.07	0.07	1	0.01	1	1	1

DT_Plumbing Fixture_Group B												
Total Occupant Load	Male	Female	Required Water Closets		Water Closets Provided	Required Lavatories		Lavatories Provided	Required Drinking Fountains	Drinking Fountains Provided	Required Service Sinks	Service Sinks Provided
			Male	Female		Male	Female					
3.45	1.725	1.725	0.07	0.07	1	0.04	0.04	1	0.03	1	1	1

2902.2 Separate Facilities

Separate facilities provided for each sex

☐ Yes ☒ Not Required per 2902.2 Exception 2

2902.2.1 Family or assisted use toilet facilities serving as separate facilities

☐ Yes ☐ No ☒ Not Required

2902.3 Employee and public toilet facilities

☒ Employee toilet combined with public toilet facilities

2902.3.1 Access

Route to public toilet facilities does not pass through kitchens, storage rooms, or closets and is accessible.

☒ Yes ☐ No

2902.3.3 Location of toilet facilities in occupancies other than covered mall buildings

Located not more than one story above or below the space required to be provided with toilet facilities

☒ Yes ☐ No

Path of travel to such facilities does not exceed 500 feet

☒ Yes ☐ No

2902.4 Signage

☒ Yes ☐ No

Legible sign designating the sex provided in visible location near entrance to toilet facility

☐ Yes ☒ Not Required per 2902.2.1

Plumbing Fixture Notes:

- (1) High / Low drinking fountain provided for the entire building.
(1) Service Sink provided for the entire building.
(2) Family Assisted-Use Toilet Room each containing (1) lavatory and (1) water closet provided for the entire building.

5 Fire Service Features (2021 IFC)

505.1 Address Identification

☒ Yes ☐ No ☐ Not Required

☒ Project complies 505.1 Address Identification

506 Key Boxes

☒ Yes ☐ No ☐ Not Required

☒ Project complies 506.1 Where Required

23 Motor Fuel-Dispensing Facilities and Repair Garages (2021 IFC)

2311.2.2 Waste oil, motor oil and other Class IIIB Liquids

☒ Project complies with 2311.2.2 Waste oil, motor oil and other Class IIIB liquids.

2311.2.2.1 Tank Location

☒ Project complies with 2311.2.2.1 tank location ☐ Not Applicable

2311.2.3 Drainage and disposal of liquid and oil-soaked waste

☐ Yes ☐ No ☒ Not Required

☒ Garage floors do not contain floor drains.

2311.4 Below-grade areas

☒ Project complies with 2311.4.1 through 2311.4.3 ☐ Not Applicable

2311.7 Fire Extinguishers

☒ Project complies with 2311.7 fire extinguishers (See Section 9 Fire Protection Systems)

50 Hazardous Materials - General Provisions (2021 IFC)

Table 5003.1.1 (1) Maximum Allowable Quantity Per Control Area of Hazardous Materials Posing a Physical Hazard

☒ Project complies with Table 5003.1.1 (1).

☒ Project contains Class IIIB Liquid Storage that does not exceed 13,200 liquid gallons per control area.

☒ Project contains Class IIIB Liquid Open-System that does not exceed 3,300 liquid gallons per control area.

☒ Project contains Flammable Liquid IA Storage that does not exceed 30 liquid gallons per control area.

☒ Project contains Flammable Liquid IA Open System that does not exceed 10 liquid gallons per control area.

☒ Project contains Flammable Liquid IB Storage that does not exceed 120 liquid gallons per control area.

☒ Project contains Flammable Liquid IB Open System that does not exceed 30 liquid gallons per control area.

☒ Project complies 5003.8.3.1 through 5003.8.3.4

☒ Entire building is one single control area.

57 Flammable and Combustible Liquids (2021 IFC)


5703.2 Fire Protection

☒ Project complies with 5703.2.1 portable fire extinguishers an hose lines. (See Section 9 Fire Protection Systems).

5703.4 Spill Control and Secondary Containment

☒ Not required. Project does not exceed maximum allowable quantity per control area.

☒ Though not required, the pit itself acts as a secondary containment. There are no drains in the pit.



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL






No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Life Safety / Code Summary


Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A
LS101	
Scale	12" = 1'-0"

LIFE SAFETY SYMBOL LEGEND

	Exit Sign		Maneuvering clearances at manual swinging doors
	Handicap Accessible Egress Width		Travel Distance
	32\" data-bbox="128 718 178 748"/> Exit from room (# = minimum clear width in inches)		



Keynote Schedule	
Tag	Text
3	Location of 30" wide refrigerator (By Others).
26	Fire Department Lock Box. Locate as directed by the Local Fire Marshal or AHJ. See Specification 104413 Fire Department Lock Box.
33	ADA compliant room / exit sign. See Details.
35	Submersible foundation sump pump. Provide Zoeller M98 or comparable product. Coordinate location with Civil and tie into Civil's storm drainage system.
38	Eyewash station. See Plumbing.
51	Provide 20"x30" insulated attic access panel.
58	Verify location and size of pit exhaust opening with Structural and Mechanical drawings.
59	Gas meter. See Plumbing.
60	Coffee cabinet. See Details on sheet G301.
63	Service Desk. See Details on sheet G301.
66	Wall mounted ladder. See Details. See Specification 055133 Ladders. See Finish Schedule for color.
108	Gray shading indicates these walls are the boundaries for the building thermal envelope assembly.
144	Electrical meter. See Electrical.
212	HVAC condensing unit. See Mechanical.
219	Air compressor (By Others).
225	Lube console (By Others).
226	Computer podium (By Others).
227	Cashier computer station (By Others).
229	Rolling drain pan (By Others).
230	Tool cart (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

[illegible]


© 2024 Aho Architects, LLC.
All Rights Reserved.

Life Safety Plan - Main

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

LS102

Scale $1/4" = 1'-0"$



LIFE SAFETY SYMBOL LEGEND

Exit Sign

HC
EXIT
32"


32"

Handicap Accessible
Egress Width

Exit from room
(# = minimum clear
width in inches)

Maneuvering
clearances at
manual swinging
doors

Travel Distance



10_Life Safety Plan_Pit
1/4" = 1'-0"

Keynote Schedule	
Tag	Text
35	Submersible foundation sump pump. Provide Zoeller M98 or comparable product. Coordinate location with Civil and tie into Civil's storm drainage system.
38	Eyewash station. See Plumbing.
46	Oil tank stairs (By Others).
66	Wall mounted ladder. See Details. See Specification 055133 Ladders. See Finish Schedule for color.
223	Work bench (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.
233	275-gallon Class IIIB new oil tank (By Others).
234	928-gallon Class IIIB new oil tank (By Others). Provide a 2" concrete walkway cap with non-slip surface over (oil tank By Others). Coordinate with equipment supplier prior to installation.
235	928-gallon Class IIB waste oil tank (By Others). Provide a 2" concrete walkway cap with non-slip surface over (oil tank By Others). Coordinate with equipment supplier prior to installation.

AHO ARCHITECTS, LLC

www.ahoarch.com

STATE OF ALABAMA

TIMOTHY ARNOLD AHO

5099

BIRMINGHAM, ALABAMA

REGISTERED ARCHITECT

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.


Life Safety - Pit

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

LS103

Scale 1/4" = 1'-0"





NOTE:
THIS PLAN IS TO SHOW THE BUILDING AS IT RELATES TO THE SITE. A COMPLETE SET OF CIVIL DRAWINGS ARE TO BE SUBMITTED TO THE AHJ INDEPENDENT OF THIS SUBMITTAL. REFER TO THOSE DRAWINGS FOR ACTUAL INFORMATION.



AHO ARCHITECTS, LLC

www.ahoarch.com



Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.


Architectural Site
Plan

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

AS100



Scale N.T.S.





Keynote Schedule	
Tag	Text
1	Pull down attic access and ladder. See Specification 083113 Access Doors and Frames.
3	Location of 30" wide refrigerator (By Others).
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
20	4" diameter painted concrete-filled steel pipe bollard. Color as indicated on Finish Schedule. Paint embedded portion of bollard. Use primer and two finish coats. See Details on sheet A101. See Specification 055000 Metal Fabrications.
26	Fire Department Lock Box. Locate as directed by the Local Fire Marshal or AHJ. See Specification 104413 Fire Department Lock Box.
33	ADA compliant room / exit sign. See Details.
35	Submersible foundation sump pump. Provide Zoeller M98 or comparable product. Coordinate location with Civil and tie into Civil's storm drainage system.
38	Eyewash station. See Plumbing.
45	See Structural for jamb reinforcing as required.
51	Provide 20"x30" insulated attic access panel.
58	Verify location and size of pit exhaust opening with Structural and Mechanical drawings.
59	Gas meter. See Plumbing.
60	Coffee cabinet. See Details on sheet G301.
63	Service Desk. See Details on sheet G301.
66	Wall mounted ladder. See Details. See Specification 055133 Ladders. See Finish Schedule for color.
70	4'-0" high FRP on wet wall. See Specification 066400 Plastic Paneling (Fiberglass Reinforced Panels).
108	Gray shading indicates these walls are the boundaries for the building thermal envelope assembly.
144	Electrical meter. See Electrical.
212	HVAC condensing unit. See Mechanical.
219	Air compressor (By Others).
225	Lube console (By Others).
226	Computer podium (By Others).
227	Cashier computer station (By Others).
229	Rolling drain pan (By Others).
230	Tool cart (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.

1 01 Floor Plan Main
1/4" = 1'-0"



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date






© 2024 Aho Architects, LLC.
All Rights Reserved.

Floor Plan - Main



Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A100

Scale 1/4" = 1'-0"



Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above Oil doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
20	4" diameter painted concrete-filled steel pipe bollard. Color as indicated on Finish Schedule. Paint embedded portion of bollard. Use primer and two finish coats. See Details on sheet A101. See Specification 055000 Metal Fabrications.
27	Pre-finished metal coping at exposed tops only over self-adhered membrane flashing and pressure treated wood blocking Slope to drain. Color to match roof.
34	4" perforated perimeter drain with silt filtration fabric. See Details on Sheet A102.
35	Submersible foundation sump pump. Provide Zoeller M98 or comparable product. Coordinate location with Civil and tie into Civil's storm drainage system.
38	Eyewash station. See Plumbing.
46	Oil tank stairs (By Others).
58	Verify location and size of pit exhaust opening with Structural and Mechanical drawings.
66	Wall mounted ladder. See Details. See Specification 055133 Ladders. See Finish Schedule for color.
72	Painted concrete cap for pipe bollard. Color as indicated on Finish Schedule.
73	1/2" diameter x 4" long metal studs. Provide a total of 4.
74	1/2" expansion joint with backer rod and sealant.
75	1/4" x 6" painted steel bracket with continuous fillet weld to painted steel collar hinge and frame.
76	2"x2"x1/4" painted steel gate frame with welded connections.
78	6" diameter painted steel dumpster post. See Finish Schedule for color.
79	Wrap front face and underside of dumpster roof joists with metal panels to match standing seam metal roof.
80	Hinge collar with grease fitting. Collar welded all around to post. Typical.
81	2"x2"x1/4" painted steel cross bracing with horizontal bracing in thirds (beyond).
223	Work bench (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.
233	275-gallon Class IIIB new oil tank (By Others).
234	928-gallon Class IIIB new oil tank (By Others). Provide a 2" concrete walkway cap with non-slip surface over (oil tank By Others). Coordinate with equipment supplier prior to installation.
235	928-gallon Class IIB waste oil tank (By Others). Provide a 2" concrete walkway cap with non-slip surface over (oil tank By Others). Coordinate with equipment supplier prior to installation.
236	1x6 painted Trex slats secured to frame. See Finish Schedule for color.
237	Dumpster (By Others).
238	Cane bolts with stops.
268	Hold bottom of gate above grade as necessary to clear adjacent curb height to ensure gates can swing 180 degrees. Coordinate with Civil drawings for clearance needed.




Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama


FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.


Pit Floor Plan and Site Details	
Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A
A101	
Scale	As indicated




1 DT_Sheet A102_Sump Pump Detail w/ Mud Slab
1/4" = 1'-0"



2 DT_Sheet A102_Foundation Construction Joint w/ Mud Slab
1 1/2" = 1'-0"




3 DT_Sheet A102_Sump Pump Section
3/4" = 1'-0"



4 DT_Sheet A102_Foundation Waterproofing with Gravel Fill w/ Mud Slab
1 1/2" = 1'-0"

Keynote Schedule	
Tag	Text
21	Cast-in-place concrete wall. See Structural. Membrane waterproofing at perimeter of foundation wall as specified. See Specification 334600 Subdrainage.
34	4" perforated perimeter drain with silt filtration fabric. See Details on Sheet A102.
35	Submersible foundation sump pump. Provide Zoeller M98 or comparable product. Coordinate location with Civil and tie into Civil's storm drainage system.
85	18" diameter black corrugated pipe with inlet fittings and solid heavy duty corrugated locking pipe cover set in concrete with power grommet, or Nyloplast drain basin with inlet fittings and lockable cover and power grommet. Contractor's Option. Set pipe in concrete 2'x2'x1'. Embed pipe 6" into concrete.
86	4" discharge pipe to sump pump.
87	2" discharge pipe from sump pump to storm drainage system. Coordinate with Civil.
88	Install union at serviceable depth.
89	Concrete foundation. See Structural.
91	Provide power for sump pump. See Electrical.
92	Power cord for sump pump to be run in conduit from outlet to sump below grade.
93	2" - 3" vent pipe
94	Fasteners at 12" max o.c. for securing subdrainage to pit wall. Follow manufacturer's installation instructions.
95	Pull rope or wire for submersible sump pump.
96	CCW MiraClay woven geotextile against wall/slab.
97	CCW MiraDrain 6200.
98	CCW MiraClay granules or CCW MiraClay mastic.
99	CCW MiraStop.
100	Concrete slab. See Structural.
101	4" mud slab. See Structural.
103	Construction joint.
104	CCW MiraDrain 9800.
105	3" washed #57 stone wrapped in silt filtration fabric.
107	CCW MiraClay 12" Reinforcing Angle Strip at all outside corners.
245	Lockable cover @ sump pump.



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date




© 2024 Aho Architects, LLC.
All Rights Reserved.

Foundation Details

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A102

Scale As indicated



Keynote Schedule	
Tag	Text
1	Pull down attic access and ladder. See Specification 083113 Access Doors and Frames.
3	Location of 30" wide refrigerator (By Others).
5	42" grab bar with blocking in walls as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
26	Fire Department Lock Box. Locate as directed by the Local Fire Marshal or AHJ. See Specification 104413 Fire Department Lock Box.
28	Framed mirror. See Specification 102800 Toilet, Bath, and Laundry Accessories.
29	Automatic Towel Dispenser (By others). Provide blocking in wall as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
30	Wall mounted soap dispenser (By Others). Provide blocking in wall as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
31	Jumbo Dual Roll Toilet Tissue dispenser (By Others). Provide blocking in wall as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
32	36" grab bar with blocking in walls as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
33	ADA compliant room / exit sign. See Details.
36	Surface mounted baby changing station with blocking in walls as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
38	Eyewash station. See Plumbing.
43	24" vertical grab bar with blocking in walls as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
59	Gas meter. See Plumbing.
60	Coffee cabinet. See Details on sheet G301.
63	Service Desk. See Details on sheet G301.
66	Wall mounted ladder. See Details. See Specification 055133 Ladders. See Finish Schedule for color.
70	4'-0" high FRP on wet wall. See Specification 066400 Plastic Paneling (Fiberglass Reinforced Panels).
108	Gray shading indicates these walls are the boundaries for the building thermal envelope assembly.
112	Painted 1/2" gypsum board on 2x6 wood studs at 16" o.c. with kraft-face R-20 batt insulation (kraft in contact with gypsum board). See Details on sheet A400.
113	Fluid applied vapor permeable air barrier. See Specification 072726 Fluid Applied Membrane Air Barrier.
144	Electrical meter. See Electrical.
185	Flush valve on transfer side of water closet.
212	HVAC condensing unit. See Mechanical.
219	Air compressor (By Others).
227	Cashier computer station (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Enlarged Floor
Plans and Details

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A103

Scale As indicated



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Reflected Ceiling
Plan - Main


Project number 24028
Date 11/8/2024
Drawn by ARC
Checked by N/A

A104

Scale 1/4" = 1'-0"


11/8/2025 9:04:19 AM

Keynote Schedule	
Tag	Text
1	Pull down attic access and ladder. See Specification 083113 Access Doors and Frames.
6	Painted 1/2" thick fire-rated plywood with 1/4" x 1 1/4" fire-rated painted wood batten strips at seams, secured to underside of roof trusses. Provide painted 1"x4" fire-rated wood trim at perimeter.
7	Painted 1/2" gypsum board ceiling. 5/8" Type X where indicated. See Specification Section 061000 Rough Carpentry.
11	Pre-finished metal canopy. See Details.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
24	Lightbar (By Others). Provide blocking as required. See Electrical.
51	Provide 20"x30" insulated attic access panel.
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
108	Gray shading indicates these walls are the boundaries for the building thermal envelope assembly.
114	Contractor to ensure overhead door, track, etc. meets the minimum vertical clearance required for equipment (By Others). Typical.
115	Dashed line indicates extent of overhead doors. Typical.
116	See Engineering drawings for Mechanical/Electrical/Plumbing fixtures and equipment. Typical.
228	Convex mirrors (By Others).




1 01_RCP_Main
1/4" = 1'-0"

Keynote Schedule	
Tag	Text
8	Exposed to structure above.
58	Verify location and size of pit exhaust opening with Structural and Mechanical drawings.
116	See Engineering drawings for Mechanical/Electrical/Plumbing fixtures and equipment. Typical.



① 00_RCP_Pit
1/4" = 1'-0"





www.ahoarch.com



Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Reflected Ceiling
Plan - Pit

Project number

24028

Date

11/8/2024

Drawn by

ARC

Checked by

N/A

A105


Scale

1/4" = 1'-0"


NOTES:

1. Equipment platform is designed for mechanical equipment only. This space is not intended for occupants other than during general maintenance.

Keynote Schedule	
Tag	Text
1	Pull down attic access and ladder. See Specification 083113 Access Doors and Frames.
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
11	Pre-finished metal canopy. See Details.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
24	Lightbar (By Others). Provide blocking as required. See Electrical.
49	Telephone backboard. See Electrical.
51	Provide 20"x30" insulated attic access panel.
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
108	Gray shading indicates these walls are the boundaries for the building thermal envelope assembly.
116	See Engineering drawings for Mechanical/Electrical/Plumbing fixtures and equipment. Typical.
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.



02 Floor Plan Equip. Platform
1/4" = 1'-0"



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Floor Plan -
Equipment
Platform


Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A106

Scale 1/4" = 1'-0"



Keynote Schedule	
Tag	Text
7	Painted 1/2" gypsum board ceiling, 5/8" Type X where indicated. See Specification Section 061000 Rough Carpentry.
51	Provide 20"x30" insulated attic access panel.



① 02_RCP_Equip. Platform
1/4" = 1'-0"



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.


Reflected Ceiling
Plan - Equipment
Platform

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A


A107

Scale 1/4" = 1'-0"







2 DT_Sheet A106_SSMR Roof Penetration Detail
1 1/2" = 1'-0"




3 DT_Sheet A106_SSMR Roof Curb Detail
1 1/2" = 1'-0"



4 Draft Template_Typical Ridge-Hip Detail
1" = 1'-0"



Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
11	Pre-finished metal canopy. See Details.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
14	Pre-finished metal valley flashing. Color to match roof.
27	Pre-finished metal coping at exposed tops only over self-adhered membrane flashing and pressure treated wood blocking Slope to drain. Color to match roof.
42	Paint all roof penetrations to match roof color.
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
118	Stainless steel draw band.
119	Metal storm collar. Finish to match roof.
120	Rubber boot. Cut to suit pipe penetration.
121	Rivet boot to panel with continuous bead of sealant between boot and panel.
122	When pipe is fixed to structure and not designed to float with roof panel, cut hole in panel to allow for thermal expansion.



1 03_Roof Plan
1/4" = 1'-0"



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Roof Plan


Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A108

Scale As indicated




EXTERIOR FINISH MATERIAL LEGEND




PAINTED SPLIT-FACE CMU

Color: SW7669 Summit Gray
Manuf: Sherwin Williams




STRUCTURAL HALF-HIGHS

Color: Richfield Blend
Manuf: Echelon



EXTERIOR PAINT

Color: SW6966 Blueblood
Manuf: Sherwin Williams



ROOF

Color: Royal Blue
Manuf: Berridge



HM DOORS

Color: SW7669 Summit Gray
Manuf: Sherwin Williams



STOREFRONT DOORS


Color: Clear Anodized Aluminum
Manuf: YKK

NOTE:
Align top of exterior wall packs with bottom of banding at 12'-0" a.f.f. Do not locate exterior wall packs on side of building that contains illuminated lightbars or sconces by others, unless at exit doors as indicated on the Electrical Drawings.



01 Exterior Elevation_Front (West)
1/4" = 1'-0"

Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
11	Pre-finished metal canopy. See Details.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
15	1x pressure treated painted fascia board, continuous.
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
20	4" diameter painted concrete-filled steel pipe bollard. Color as indicated on Finish Schedule. Paint embedded portion of bollard. Use primer and two finish coats. See Details on sheet A101. See Specification 055000 Metal Fabrications.
21	Cast-in-place concrete wall. See Structural. Membrane waterproofing at perimeter of foundation wall as specified. See Specification 334600 Subdrainage.
22	Signage (By Others). Provide blocking as required. See Electrical.
23	Wall sconce (By Others). Provide blocking as required. See Electrical. Locate junction box for sconces 5'-0" a.f.f. vertically and 4" from center horizontally. Verify with sign company prior to rough-in.
24	Lightbar (By Others). Provide blocking as required. See Electrical.
25	Control joint. For control joints in concrete floor slabs, coordinate location with equipment layout by others. Max. distance between control joints in slabs not to exceed 12'-0". Control joints in walls shall be 4'-0" max from wall intersection or corner and every 20'-0".
26	Fire Department Lock Box. Locate as directed by the Local Fire Marshal or AHJ. See Specification 104413 Fire Department Lock Box.
27	Pre-finished metal coping at exposed tops only over self-adhered membrane flashing and pressure treated wood blocking Slope to drain. Color to match roof.
35	Submersible foundation sump pump. Provide Zoeller M98 or comparable product. Coordinate location with Civil and tie into Civil's storm drainage system.
47	Provide address identification as directed by the Local Fire Marshal or AHJ.
53	Conduit to be centered horizontally for lights in canopy. Verify with sign company prior to rough-in.
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
68	1x pressure treated painted frieze board, continuous.



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Exterior Elevation -
Front (West)


Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A200

Scale As indicated


11/16/2025 9:04:48 AM

EXTERIOR FINISH MATERIAL LEGEND




PAINTED SPLIT-FACE CMU

Color: SW7669 Summit Gray
Manuf: Sherwin Williams




STRUCTURAL HALF-HIGHS

Color: Richfield Blend
Manuf: Echelon



EXTERIOR PAINT

Color: SW6966 Blueblood
Manuf: Sherwin Williams



ROOF

Color: Royal Blue
Manuf: Berridge



HM DOORS

Color: SW7669 Summit Gray
Manuf: Sherwin Williams



STOREFRONT DOORS

Color: Clear Anodized Aluminum
Manuf: YKK

Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
15	1x pressure treated painted fascia board, continuous.
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
20	4" diameter painted concrete-filled steel pipe bollard. Color as indicated on Finish Schedule. Paint embedded portion of bollard. Use primer and two finish coats. See Details on sheet A101. See Specification 055000 Metal Fabrications.
21	Cast-in-place concrete wall. See Structural. Membrane waterproofing at perimeter of foundation wall as specified. See Specification 334600 Subdrainage.
25	Control joint. For control joints in concrete floor slabs, coordinate location with equipment layout by others. Max. distance between control joints in slabs not to exceed 12'-0". Control joints in walls shall be 4'-0" max from wall intersection or corner and every 20'-0".
27	Pre-finished metal coping at exposed tops only over self-adhered membrane flashing and pressure treated wood blocking Slope to drain. Color to match roof.
35	Submersible foundation sump pump. Provide Zoeller M98 or comparable product. Coordinate location with Civil and tie into Civil's storm drainage system.
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
68	1x pressure treated painted frieze board, continuous.
102	Provide opening in wall to allow water to drain.

NOTE:

Align top of exterior wall packs with bottom of banding at 12'-0" a.f.f. Do not locate exterior wall packs on side of building that contains illuminated lightbars or sconces by others, unless at exit doors as indicated on the Electrical Drawings.



02 Exterior Elevation_Rear (East)
1/4" = 1'-0"

www.ahoarch.com

Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC. All Rights Reserved.

Exterior Elevation - Rear (East)


Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A201

Scale As indicated


11/16/2025 9:05:08 AM

EXTERIOR FINISH MATERIAL LEGEND




PAINTED SPLIT-FACE CMU

Color: SW7669 Summit Gray
Manuf: Sherwin Williams




STRUCTURAL HALF-HIGHS

Color: Richfield Blend
Manuf: Echelon



EXTERIOR PAINT

Color: SW6966 Blueblood
Manuf: Sherwin Williams



ROOF

Color: Royal Blue
Manuf: Berridge



HM DOORS

Color: SW7669 Summit Gray
Manuf: Sherwin Williams




STOREFRONT DOORS

Color: Clear Anodized Aluminum
Manuf: YKK

NOTE:
Align top of exterior wall packs with bottom of banding at 12'-0" a.f.f. Do not locate exterior wall packs on side of building that contains illuminated lightbars or sconces by others, unless at exit doors as indicated on the Electrical Drawings.

Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
11	Pre-finished metal canopy. See Details.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
15	1x pressure treated painted fascia board, continuous.
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
20	4" diameter painted concrete-filled steel pipe bollard. Color as indicated on Finish Schedule. Paint embedded portion of bollard. Use primer and two finish coats. See Details on sheet A101. See Specification 055000 Metal Fabrications.
21	Cast-in-place concrete wall. See Structural. Membrane waterproofing at perimeter of foundation wall as specified. See Specification 334600 Subdrainage.
22	Signage (By Others). Provide blocking as required. See Electrical.
24	Lightbar (By Others). Provide blocking as required. See Electrical.
25	Control joint. For control joints in concrete floor slabs, coordinate location with equipment layout by others. Max. distance between control joints in slabs not to exceed 12'-0". Control joints in walls shall be 4'-0" max from wall intersection or corner and every 20'-0".
26	Fire Department Lock Box. Locate as directed by the Local Fire Marshal or AHJ. See Specification 104413 Fire Department Lock Box.
27	Pre-finished metal coping at exposed tops only over self-adhered membrane flashing and pressure treated wood blocking Slope to drain. Color to match roof.
35	Submersible foundation sump pump. Provide Zoeller M98 or comparable product. Coordinate location with Civil and tie into Civil's storm drainage system.
47	Provide address identification as directed by the Local Fire Marshal or AHJ.
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
68	1x pressure treated painted frieze board, continuous.
144	Electrical meter. See Electrical.
212	HVAC condensing unit. See Mechanical.
219	Air compressor (By Others).



03 Exterior Elevation_Left (North)
1/4" = 1'-0"

www.ahoarch.com

Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC. All Rights Reserved.

Exterior Elevation - Left (North)


Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A202

Scale As indicated


1/16/2025 9:05:22 AM

EXTERIOR FINISH MATERIAL LEGEND




PAINTED SPLIT-FACE CMU

Color: SW7669 Summit Gray
Manuf: Sherwin Williams




STRUCTURAL HALF-HIGHS

Color: Richfield Blend
Manuf: Echelon



EXTERIOR PAINT

Color: SW6966 Blueblood
Manuf: Sherwin Williams



ROOF

Color: Royal Blue
Manuf: Berridge



HM DOORS

Color: SW7669 Summit Gray
Manuf: Sherwin Williams




STOREFRONT DOORS

Color: Clear Anodized Aluminum
Manuf: YKK


Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
11	Pre-finished metal canopy. See Details.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
15	1x pressure treated painted fascia board, continuous.
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
21	Cast-in-place concrete wall. See Structural. Membrane waterproofing at perimeter of foundation wall as specified. See Specification 334600 Subdrainage.
25	Control joint. For control joints in concrete floor slabs, coordinate location with equipment layout by others. Max. distance between control joints in slabs not to exceed 12'-0". Control joints in walls shall be 4'-0" max from wall intersection or corner and every 20'-0".
26	Fire Department Lock Box. Locate as directed by the Local Fire Marshal or AHJ. See Specification 104413 Fire Department Lock Box.
27	Pre-finished metal coping at exposed tops only over self-adhered membrane flashing and pressure treated wood blocking Slope to drain. Color to match roof.
47	Provide address identification as directed by the Local Fire Marshal or AHJ.
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
68	1x pressure treated painted frieze board, continuous.
219	Air compressor (By Others).

NOTE:

Align top of exterior wall packs with bottom of banding at 12'-0" a.f.f. Do not locate exterior wall packs on side of building that contains illuminated lightbars or sconces by others, unless at exit doors as indicated on the Electrical Drawings.



04 Exterior Elevation Right (South)
1/4" = 1'-0"



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date



© 2024 Aho Architects, LLC.
All Rights Reserved.

Exterior Elevation -
Right (South)


Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A203

Scale As indicated



Keynote Schedule	
Tag	Text
6	Painted 1/2" thick fire-rated plywood with 1/4" x 1 1/4" fire-rated painted wood batten strips at seams, secured to underside of roof trusses. Provide painted 1"x4" fire-rated wood trim at perimeter.
7	Painted 1/2" gypsum board ceiling. 5/8" Type X where indicated. See Specification Section 061000 Rough Carpentry.
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
15	1x pressure treated painted fascia board, continuous.
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
21	Cast-in-place concrete wall. See Structural. Membrane waterproofing at perimeter of foundation wall as specified. See Specification 334600 Subdrainage.
25	Control joint. For control joints in concrete floor slabs, coordinate location with equipment layout by others. Max. distance between control joints in slabs not to exceed 12'-0". Control joints in walls shall be 4'-0" max from wall intersection or corner and every 20'-0".
33	ADA compliant room / exit sign. See Details.
35	Submersible foundation sump pump. Provide Zoeller M98 or comparable product. Coordinate location with Civil and tie into Civil's storm drainage system.
38	Eyewash station. See Plumbing.
44	Concrete apron. See Civil. Slope away from building with 3% slope.
46	Oil tank stairs (By Others).
49	Telephone backboard. See Electrical.
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
68	1x pressure treated painted frieze board, continuous.
74	1/2" expansion joint with backer rod and sealant.
94	Fasteners at 12" max o.c. for securing subdrainage to pit wall. Follow manufacturer's installation instructions.
96	CCW MiraClay woven geotextile against wall/slab.
97	CCW MiraDrain 6200.
99	CCW MiraStop.
109	Horizontal joint reinforcement at 16" o.c. vertical.
123	Blocking. See Structural.
124	Pre-engineered wood roof truss. See Structural.
125	Insulation baffle.
126	Unfaced R-38 batt insulation. See Specification 072100 Thermal Insulation.
127	2x pressure treated wood nailer.
128	Painted smooth-face 8" concrete-filled "U" block bond beam. Condition varies. See Structural.
129	"H" clips at mid-span on standing seam metal roof.
130	2 layers of #15 roofing felt.
131	5/8" pressure treated plywood decking. See Structural.
132	2x wood sub-fascia, continuous.
133	Field cut seam and form pan around eave flashing.
134	Eave flashing with drip edge.
135	Painted vented soffit with paintable PVC "H" jointers between panels, fastened to pressure treated 2"x4" wood blocking. See Specification Section 074293 Soffit Panels.
136	Pea gravel above through wall flashing.
137	Base flashing between first and second course to utilize BlockFlash. In addition to the pea gravel specified, provide a drainage mat in open masonry cell directly above the BlockFlash pan.
138	Drainable weeps at every third mortar joint.
139	10 mil vapor barrier. See Specification 072600 Vapor Retarders.
140	4" porous fill. See Geotechnical Report.
141	3/4" tongue and groove plywood on wood joists. See Structural.
145	2x pressure treated wood sill plate.
170	Fill first course of CMU with grout.
205	1 layer of 1/2" painted gypsum board on both sides of 2"x6" wood studs at 16" o.c. Infill with kraft-faced R-20 batt insulation. Kraft in contact with gypsum board.
223	Work bench (By Others).
225	Lube console (By Others).
226	Computer podium (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.
234	928-gallon Class IIB new oil tank (By Others). Provide a 2" concrete walkway cap with non-slip surface over (oil tank By Others). Coordinate with equipment supplier prior to installation.
235	928-gallon Class IIB waste oil tank (By Others). Provide a 2" concrete walkway cap with non-slip surface over (oil tank By Others). Coordinate with equipment supplier prior to installation.
242	2x pressure treated wood top plate.



Express Oil Change & Tire Engineers







Left Hand Oil Change Building

Northport, Alabama


FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Building Sections	
Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A
A300	
Scale	As indicated



Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
11	Pre-finished metal canopy. See Details.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
15	1x pressure treated painted fascia board, continuous.
16	Painted structural half-hiis. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-hiis. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
20	4" diameter painted concrete-filled steel pipe bollard. Color as indicated on Finish Schedule. Paint embedded portion of bollard. Use primer and two finish coats. See Details on sheet A101. See Specification 055000 Metal Fabrications.
21	Cast-in-place concrete wall. See Structural. Membrane waterproofing at perimeter of foundation wall as specified. See Specification 334600 Subdrainage.
22	Signage (By Others). Provide blocking as required. See Electrical.
24	Lightbar (By Others). Provide blocking as required. See Electrical.
26	Fire Department Lock Box. Locate as directed by the Local Fire Marshal or AHJ. See Specification 104413 Fire Department Lock Box.
27	Pre-finished metal coping at exposed tops only over self-adhered membrane flashing and pressure treated wood blocking Slope to drain. Color to match roof.
38	Eyewash station. See Plumbing.
44	Concrete apron. See Civil. Slope away from building with 3% slope.
47	Provide address identification as directed by the Local Fire Marshal or AHJ.
66	Wall mounted ladder. See Details. See Specification 055133 Ladders. See Finish Schedule for color.
68	1x pressure treated painted frieze board, continuous.
74	1/2" expansion joint with backer rod and sealant.
89	Concrete foundation. See Structural.
94	Fasteners at 12" max o.c. for securing subdrainage to pit wall. Follow manufacturer's installation instructions.
96	CCW MiraClay woven geotextile against wall/slab.
97	CCW MiraDrain 6200.
99	CCW MiraStop.
100	Concrete slab. See Structural.
105	3" washed #57 stone wrapped in silt filtration fabric.
109	Horizontal joint reinforcement at 16" o.c. vertical.
113	Fluid applied vapor permeable air barrier. See Specification 072726 Fluid Applied Membrane Air Barrier.
136	Pea gravel above through wall flashing.
137	Base flashing between first and second course to utilize BlockFlash. In addition to the pea gravel specified, provide a drainage mat in open masonry cell directly above the BlockFlash pan.
138	Drainable weeps at every third mortar joint.
139	10 mil vapor barrier. See Specification 072600 Vapor Retarders.
140	4" porous fill. See Geotechnical Report.
144	Electrical meter. See Electrical.
149	1/2" recess at scheduled door. See Structural.
150	Painted guardrail with painted 1/2" round trucks at 4" max o.c. See Finish Schedule for color. See Specification 055213 Pipe and Tube Railings.
151	Painted 1-1/2" outside diameter pipe handrail. Return handrail to guard/wall. Typical. See Finish Schedule for color. See Specification 055213 Pipe and Tube Railings.
152	Paint all structural steel P-5 Safety Yellow.
154	Concrete filled pre-fabricated metal pan stair treads with safety yellow abrasive nosing, full grit, full length, adhered and fastened. Typical. See Finish Schedule for color. See Specification 055113 Metal Pan Stairs.
155	1-1/4" steel angle clips.
156	10" steel channel stringer. See Finish Schedule for color. See Specification 055113 Metal Pan Stairs.
157	3"x3"x3-1/4" angle floor clip.
158	Vinyl letters (By Others).
172	Ensure paint line occurs at top of door and window frames. Ensure all openings, alcoves and windows align with top of door frame. Typical in Oil and Service Bays.
194	Scheduled door. See plans for details.
205	1 layer of 1/2" painted gypsum board on both sides of 2"x6" wood studs at 16" o.c. Infill with kraft-faced R-20 batt insulation. Kraft in contact with gypsum board.
219	Air compressor (By Others).
225	Lube console (By Others).
226	Computer podium (By Others).
227	Cashier computer station (By Others).
228	Convex mirrors (By Others).
230	Tool cart (By Others).
233	275-gallon Class IIIB new oil tank (By Others).
234	928-gallon Class IIIB new oil tank (By Others). Provide a 2" concrete walkway cap with non-slip surface over (oil tank By Others). Coordinate with equipment supplier prior to installation.
256	Prefinished metal flashing and counterflashing. Match adjacent wall color.



Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL

[illegible]




© 2024 Aho Architects, LLC.
All Rights Reserved.

Building Sections

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A




A301

Scale	As indicated
-------	--------------



Keynote Schedule	
Tag	Text
74	1/2" expansion joint with backer rod and sealant.
89	Concrete foundation. See Structural.
100	Concrete slab. See Structural.
109	Horizontal joint reinforcement at 16" o.c. vertical.
110	Sealant with backer rod. Match adjacent material color.
111	Aluminum storefront with insulated glazing. See Details on sheet A620.
112	Painted 1/2" gypsum board on 2x6 wood studs at 16" o.c. with kraft-face R-20 batt insulation (kraft in contact with gypsum board). See Details on sheet A400.
113	Fluid applied vapor permeable air barrier. See Specification 072726 Fluid Applied Membrane Air Barrier.
130	2 layers of #15 roofing felt.
131	5/8" pressure treated plywood decking. See Structural.
134	Eave flashing with drip edge.
136	Pea gravel above through wall flashing.
137	Base flashing between first and second course to utilize BlockFlash. In addition to the pea gravel specified, provide a drainage mat in open masonry cell directly above the BlockFlash pan.
138	Drainable weeps at every third mortar joint.
139	10 mil vapor barrier. See Specification 072600 Vapor Retarders.
140	4" porous fill. See Geotechnical Report.
141	3/4" tongue and groove plywood on wood joists. See Structural.
144	Electrical meter. See Electrical.
159	Painted smooth-face grout-filled CMU where canopy attaches to wall construction. See Structural.
160	Pre-finished aluminum flashing to match color of canopy. Turn out onto canopy.
162	Pre-finished 8"x8"x1/4" steel plate anchored to wall using through wall fasteners by Canopy manufacturer's designated design.
163	Pre-finished 1" cast steel turnbuckle with 1" threaded steel rod and 1" pins.

Keynote Schedule	
Tag	Text
164	Anchor canopy to wall using through wall fasteners by Canopy manufacturer's designated design.
165	Provide a 1" flexible conduit extending 12" beyond the face of the wall for canopy lighting. See Electrical.
167	Pre-finished hinged panel for mounting access. Color to match canopy.
168	1"x2" aluminum tube. Typical.
169	Pre-finished metal over 1/2" pressure treated plywood. Terminate at aluminum storefront. Turn up pre-finished metal 1" at edge where metal meets canopy. Secure panel to plywood with fasteners compatible with type and color of metal being used.
170	Fill first course of CMU with grout.
225	Lube console (By Others).
230	Tool cart (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.
246	3"x12" aluminum channel.
252	Prefinished metal flashing "Z" closure. Provide non-curing butyl sealant at ends to fill in all gaps.
256	Prefinished metal flashing and counterflashing.
269	1" drain tube beyond. Slope top panel of canopy toward the drain tube at the front of the canopy.
287	2x joists. See Structural.
303	Roof joists, see Structural.
309	Sealant with Backer rod continuous around wood column.
311	Simpson post base embedded in grout filled masonry. See Structural.
312	P.T. square wood post, painted (P-1). See Structural.
313	Double 2x P.T. header beam, painted (P-1). See Structural.
314	H3 Simpson hanger at each rafter, see Structural.
315	Paving, see Civil drawings for extents and details.



Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL		
No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Building Sections	
Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A
A302	
Scale	As indicated

E1

Refer to structural drawings for reinforcing and other information

Install all waterproofing per manufacturer's recommendations.




Wall Type No.	Description	Width	Ref Test
E1	As shown	10"	-

E2

Install siloxane on the exterior side of wall construction

Refer to structural drawings for reinforcing, grouting, and other information




Wall Type No.	Description	Width	Ref Test
E2	As shown	7 5/8"	-

E3

Install siloxane on the exterior side of wall construction


Refer to structural drawings for reinforcing and other information



Wall Type No.	Description	Width	Ref Test
E3	As shown	7 5/8"	-
E3a	As shown, except with 1x8 painted frieze board at top	7 5/8"	

E5


Refer to structural drawings for reinforcing, grouting, and other information



Wall Type No.	Description	Width
E5	As shown	7 5/8"
E5a	As shown, except without coping and painted structural half-highs to roof. See Elevations on A101.	7 5/8"

E6


Refer to structural drawings for reinforcing, grouting, and other information



Wall Type No.	Description	Width
E6	As shown	7 5/8"

I1


Note: Stagger electrical outlet boxes, switches, etc. Seal around all penetrations in wall with acoustical sealant.



Wall Type No.	Description	Width	Ref Test
I1	As shown	4 1/2"	-

I2


Masonry construction




Wall Type No.	Description	Width	Ref Test
I2	As shown	6"	-

I3


Note: Stagger electrical outlet boxes, switches, etc. Seal around all penetrations in wall with acoustical sealant.




Wall Type No.	Description	Width	Ref Test
I3	As shown	6 1/2"	-



① DT_Sheet A400_Gypsum Board Control Joint
1 1/2" = 1'-0"



② DT_Sheet A400_Masonry Control Joint
1 1/2" = 1'-0"



③ DT_Sheet A400_Sealant Detail
6" = 1'-0"

Tag	Text
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
21	Cast-in-place concrete wall. See Structural. Membrane waterproofing at perimeter of foundation wall as specified. See Specification 334600 Subdrainage.
27	Pre-finished metal coping at exposed tops only over self-adhered membrane flashing and pressure treated wood blocking Slope to drain. Color to match roof.
68	1x pressure treated painted frieze board, continuous.
94	Fasteners at 12" max o.c. for securing subdrainage to pit wall. Follow manufacturer's installation instructions.
96	CCW MiraClay woven geotextile against wall/slab.
97	CCW MiraDrain 6200.
109	Horizontal joint reinforcement at 16" o.c. vertical.

Tag	Text
112	Painted 1/2" gypsum board on 2x6 wood studs at 16" o.c. with kraft-face R-20 batt insulation (kraft in contact with gypsum board). See Details on sheet A400.
113	Fluid applied vapor permeable air barrier. See Specification 072726 Fluid Applied Membrane Air Barrier.
127	2x pressure treated wood nailer.
136	Pea gravel above through wall flashing.
137	Base flashing between first and second course to utilize BlockFlash. In addition to the pea gravel specified, provide a drainage mat in open masonry cell directly above the BlockFlash pan.
138	Drainable weeps at every third mortar joint.
145	2x pressure treated wood sill plate.
170	Fill first course of CMU with grout.
202	1 layer of 1/2" painted gypsum board on both sides of 2"x4" wood studs at 16" o.c. Infill with kraft-face R-13 batt insulation. Kraft in contact with gypsum board.
203	Acoustical sealant and backer rod. See Specification 079219 Acoustical Joint Sealants.
205	1 layer of 1/2" painted gypsum board on both sides of 2"x6" wood studs at 16" o.c. Infill with kraft-faced R-20 batt insulation. Kraft in contact with gypsum board.
242	2x pressure treated wood top plate.



www.ahoarch.com



Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.



Wall Types

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A






A400

Scale As indicated

1/16/2025 9:12:31 AM



Keynote Schedule	
Tag	Text
21	Cast-in-place concrete wall. See Structural. Membrane waterproofing at perimeter of foundation wall as specified. See Specification 334600 Subdrainage.
33	ADA compliant room / exit sign. See Details.
38	Eyewash station. See Plumbing.
46	Oil tank stairs (By Others).
58	Verify location and size of pit exhaust opening with Structural and Mechanical drawings.
66	Wall mounted ladder. See Details. See Specification 055133 Ladders. See Finish Schedule for color.
158	Vinyl letters (By Others).
172	Ensure paint line occurs at top of door and window frames. Ensure all openings, alcoves and windows align with top of door frame. Typical in Oil and Service Bays.
173	Pit ladder to comply fully with OSHA 1910.23 and 1926.1053.
174	Rungs shall be capable of supporting a single concentrated load of at least 250 lbs. applied to the middle of the rung.
175	Rungs shall be corrugated, knurled, dimpled, coated with skid-resistant material or otherwise treated to minimize slipping.
176	Rungs to be uniformly spaced 10" min. to 14" max. as measured between centerline of rungs.
177	Extend ladder above landing surface to ensure proper grip.
223	Work bench (By Others).
225	Lube console (By Others).
226	Computer podium (By Others).
227	Cashier computer station (By Others).
228	Convex mirrors (By Others).
230	Tool cart (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.
233	275-gallon Class IIIB new oil tank (By Others).
234	928-gallon Class IIIB new oil tank (By Others). Provide a 2" concrete walkway cap with non-slip surface over (oil tank By Others). Coordinate with equipment supplier prior to installation.
235	928-gallon Class IIIB waste oil tank (By Others). Provide a 2" concrete walkway cap with non-slip surface over (oil tank By Others). Coordinate with equipment supplier prior to installation.
266	Pit ladder to be painted P-5 Safety Yellow.



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

[illegible]


© 2024 Aho Architects, LLC.
All Rights Reserved.

Interior Elevations


Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A600


Scale	As indicated
-------	--------------




1 Toilet #2 Interior Elevation A
1/2" = 1'-0"




2 Toilet #2 Interior Elevation B
1/2" = 1'-0"




3 Toilet #2 Interior Elevation C
1/2" = 1'-0"




4 Toilet #2 Interior Elevation D
1/2" = 1'-0"




5 Toilet #8 Interior Elevation A
1/2" = 1'-0"



6 Toilet #8 Interior Elevation B
1/2" = 1'-0"



7 Toilet #8 Interior Elevation C
1/2" = 1'-0"



8 Toilet #8 Interior Elevation D
1/2" = 1'-0"

Keynote Schedule	
Tag	Text
4	Robe hook mounted at 48" A.F.F. See Specification 102800 Toilet, Bath, and Laundry Accessories.
5	42" grab bar with blocking in walls as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
28	Framed mirror. See Specification 102800 Toilet, Bath, and Laundry Accessories.
29	Automatic Towel Dispenser (By others). Provide blocking in wall as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
30	Wall mounted soap dispenser (By Others). Provide blocking in wall as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
31	Jumbo Dual Roll Toilet Tissue dispenser (By Others). Provide blocking in wall as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
32	36" grab bar with blocking in walls as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
36	Surface mounted baby changing station with blocking in walls as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
40	Under lavatory guard. See Specification 102800 Toilet, Bath, and Laundry Accessories.
43	24" vertical grab bar with blocking in walls as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
185	Flush valve on transfer side of water closet.



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.


Interior Elevations

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A601

Scale 1/2" = 1'-0"

Keynote Schedule	
Tag	Text
179	Plastic laminate over 1x wood blocking. See Specification 123623.13 Plastic-Laminate-Clad Countertops. See Finish Schedule for color.
180	Plastic laminate over 3/4" plywood. See Specification 123623.13 Plastic-Laminate-Clad Countertops. See Finish Schedule for color.
181	1x wood blocking.
182	Concealed countertop bracket.
183	2x wood cleat.
184	Finish base. See Specification Section 096513 Resilient Base Accessories. See Finish Schedule for color.



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama


FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Interior Elevations


Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A
A602	
Scale	As indicated



1 DT_Sheet A602_Countertop Section @ Wall
1" = 1'-0"



2 DT_Sheet A602_Signage @ OC Building
3" = 1'-0"



Signage shall comply with
Section 703 of the 2017
ICC/ANSI A117.1

FLOOR FINISH LEGEND


Tile

Sealed Concrete

Stonehard Flooring (By Others)

Safety Yellow Paint

Keynote Schedule	
Tag	Text
41	Paint structural steel at openings P-5 Safety Yellow. Typical for all pit and stairwell openings.
55	Stainless steel corner guard. See Specification 102600 Wall and Door Protection.
57	Transition strip. See Specification 093013 Ceramic Tiling.
187	Paint 12" P-5 Safety Yellow around pit openings. Verify paint is compatible with floor finish.



21. Floor Finish Plan Main
1/4" = 1'-0"



www.ahoarch.com



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Floor Finishes - Main


Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A610

Scale 1/4" = 1'-0"




FLOOR FINISH LEGEND




Tile




Sealed
Concrete





Stonehard
Flooring
(By Others)



Safety Yellow
Paint



1 20_Floor Finish Plan_Pit
1/4" = 1'-0"



www.ahoarch.com



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Floor Finishes - Pit


Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A611


Scale 1/4" = 1'-0"

Door and Frame Schedule												
Number	Door						Frame			Glass	UL Label	Notes
	Width	Height	Thickness	Door Type	Door Material	Door Finish	Frame Type	Frame Material	Frame Finish			
1	3' - 0"	7' - 0"	0' - 1 3/4"	SF	Aluminum / Glass	Factory Finish	3	Aluminum	Factory Finish	Tempered		If required by the Fire Marshal or AHJ, add lettering that reads," This door must remain unlocked when business is occupied."
2	3' - 0"	7' - 0"	0' - 1 3/4"	F	Wood	Painted	1	Hollow Metal	Painted	N/A		
3	3' - 0"	7' - 0"	0' - 1 3/4"	FV	Wood / Glass	Painted	1	Hollow Metal	Painted	Tempered		
4	10' - 0"	12' - 0"	0' - 2 1/8"	OH	Metal / Glass	Factory Finish	N/A	N/A	Factory Finish	Tempered		
5	10' - 0"	12' - 0"	0' - 2 1/8"	OH	Metal / Glass	Factory Finish	N/A	N/A	Factory Finish	Tempered		
6	10' - 0"	12' - 0"	0' - 2 1/8"	OH	Metal / Glass	Factory Finish	N/A	N/A	Factory Finish	Tempered		
7	3' - 0"	7' - 0"	0' - 1 3/4"	F	Hollow Metal	Painted	2	Hollow Metal	Painted	N/A		
8	10' - 0"	12' - 0"	0' - 2 1/8"	OH	Metal / Glass	Factory Finish	N/A	N/A	Factory Finish	Tempered		
9	10' - 0"	12' - 0"	0' - 2 1/8"	OH	Metal / Glass	Factory Finish	N/A	N/A	Factory Finish	Tempered		
10	10' - 0"	12' - 0"	0' - 2 1/8"	OH	Metal / Glass	Factory Finish	N/A	N/A	Factory Finish	Tempered		
11	3' - 0"	7' - 0"	0' - 1 3/4"	F	Hollow Metal	Painted	2	Hollow Metal	Painted	N/A		
12	3' - 0"	7' - 0"	0' - 1 3/4"	F	Wood	Painted	1	Hollow Metal	Painted	N/A		
13	3' - 0"	7' - 0"	0' - 1 3/4"	FV	Wood / Glass	Painted	1	Hollow Metal	Painted	Tempered		
14	3' - 0"	7' - 0"	0' - 1 3/4"	FV	Wood / Glass	Painted	1	Hollow Metal	Painted	Tempered		
15	3' - 0"	7' - 0"	0' - 1 3/4"	F	Wood	Painted	1	Hollow Metal	Painted	N/A		
16	3' - 0"	7' - 0"	0' - 1 3/4"	F	Wood	Painted	1	Hollow Metal	Painted	N/A		

WINDOW LEGEND



DOOR AND FRAME LEGEND



NOTE: Refer to floor plan for direction of door swing.



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC. All Rights Reserved.

Schedules


Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A620


Scale 1/4" = 1'-0"



1 DT_Sheet A621_Door Head Detail_Wood
3" = 1'-0"




2 DT_Sheet A621_Door Head Detail_Masonry
3" = 1'-0"




9 DT_Sheet A621_Door Head Detail_Masonry (Interior)
3" = 1'-0"

Keynote Schedule	
Tag	Text
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
109	Horizontal joint reinforcement at 16" o.c. vertical.
123	Blocking. See Structural.
128	Painted smooth-face 8" concrete-filled "U" block bond beam. Condition varies. See Structural.
188	Kraft-faced batt insulation. Kraft in contact with gypsum board.
189	2x wood studs at 16" o.c.
190	1/2" painted gypsum board.
191	Double 2"x8" wood header.
192	Caulk all around on both sides.
193	Painted hollow metal frame with returns. See Finish Schedule for color.
194	Scheduled door. See plans for details.
196	Closed bottom structural half-high bond beam. See Structural.
197	Painted hollow metal frame, grouted solid.
198	Jamb anchors. Provide 3 per jamb.



3 DT_Sheet A621_Door Jamb Detail_Wood
3" = 1'-0"



4 DT_Sheet A621_Door Jamb Detail_Masonry
3" = 1'-0"

Material Schedule							
Abbreviation	Material Description	Manufacturer	Style Name or Number	Color (Description)	Size	Finish	Material Notes
CT-1	Ceramic Tile	Dal-Tile	Volume 1.0	BL72 Intensity Pebble	12"x12"	N/A	Use MAPEI 47 Epoxy Grout
P-1	Paint - Color 1	Sherwin Williams	See Paint Schedule on G202	SW6966 Blueblood	N/A	See Paint Schedule on G202	
P-2	Paint - Color 2	Sherwin Williams	See Paint Schedule on G202	Custom Color (Dover Gray)	N/A	See Paint Schedule on G202	
P-3	Paint - Color 3	Sherwin Williams	See Paint Schedule on G202	SW7669 Summit Gray	N/A	See Paint Schedule on G202	
P-4	Paint - Color 4	Sherwin Williams	See Paint Schedule on G202	SW6959 Bluechip	N/A	See Paint Schedule on G202	
P-5	Paint - Color 5	Sherwin Williams	See Paint Schedule on G202	Safety Yellow	N/A	See Paint Schedule on G202	
P-6	Paint - Color 6	Sherwin Williams	See Paint Schedule on G202	Safety Red	N/A	See Paint Schedule on G202	
P-7	Paint - Color 7	Sherwin Williams	See Paint Schedule on G202	SW7006 Extra White	N/A	See Paint Schedule on G202	
PL-1	Plastic Laminate - Color 1	Wilsonart	4880-38	Carbon Mesh	N/A	N/A	
RB	Rubber Base	Ropee	Pinnacle	175 Slate	4"	N/A	
SC	Sealed Concrete	Sherwin Williams	See Paint Schedule on G202	Haze Gray	N/A	See Paint Schedule on G202	Add SharkGrip for added slip resistance
SH	StonHard Flooring	StonHard	N/A	N/A	N/A	N/A	Provided and installed by (Others)
FRP-1	Fiberglass Reinforced Panels	Marlite	4'X8' Textured Panels	P430N Medium Gray	4'X8'	Pebbled	

Finish Schedule for Additional Items							
1.	Doors & Frames: Paint P-3	9.	Keynote 15, 16 & 17: P-1	17.	Overhead Door: White	25.	Dumpster Gate / Frame: P-3
2.	Bollards & Dumpster Posts: P-6	10.	Keynote 19: P-3	18.	Lintel at OH Doors: P-1	26.	Countertop Carbon Mesh: PL1
3.	Exterior Pole Sign: By others.	11.	Coping Cap @ Dumpster: Match Roof Color	19.	Exterior Aluminum Storefront & Door: Clear Anodized	27.	SSMR @ Dumpster: Royal Blue
4.	Downspouts and Gutters: Match Roof Color	12.	Coping Cap @ Bldg: Match Roof Color	20.	Abrasive Nosing: Safety Yellow	28.	Soffit: P-1
5.	Electrical covers to be brushed aluminum	13.	Knox Box: Aluminum	21.	Interior Aluminum Storefront & Door: Clear Anodized	29.	Frieze Board: P-1
6.	Paint all louvers to match adjacent finish	14.	Roof: Royal Blue (Berridge)	22.	Chair Rail: Stainless Steel by others		
7.	Epoxy Floor Grout used with CT: MAPEI 47 Charcoal	15.	Door Hardware: Satin Chrome	23.	Word Wall: P-3		
8.	Stairs & Railings, Swing Gate & Interior Ladder (if req'd): P-5	16.	Window Gaskets: Light Gray	24.	Canopy: Pantone 425C		

Finish Schedule										
Number	Name	Area	Floor Finish	Base Finish	Walls				Ceiling Finish	Remarks
					Rear (East)	Left (North)	Front (West)	Right (South)		
1	Service Writing	296 SF	CT	CT	P-3 & Vinyl Graphics (By Others)	P-1, P-2, P-3	Storefront & P-1, P-2, P-3	P-1, P-2, P-3	P-7	See G301 for paint patterns
2	Toilet	50 SF	CT	CT	CT / P-3	CT / P-3	CT / P-3	CT / P-3	P-7	Ceramic tile wainscot 4'-4" high all walls
3	Oil Change	1271 SF	SH	None / RB	P-3	P-1, P-4	P-3	P-1, P-4 & Vinyl Graphics (By Others)	P-7	Rubber base on gypsum board walls only. See G301 for paint patterns.
4	Storage	73 SF	SC	RB	P-3	P-3	P-3	P-3	P-7	
5	Manager	56 SF	SC	RB	P-3	P-3	P-3	P-3	P-7	
6	Corridor	118 SF	SC	None / RB	P-3	P-1	P-1	P-1	P-7	
7	Break Room	65 SF	SC	RB	P-3	P-3	P-3	P-3	P-7	
8	Toilet	50 SF	CT	CT	CT / P-3	CT / P-3	CT / P-3	CT / P-3	P-7	Ceramic tile wainscot 4'-4" high all walls
9	Pit	1284 SF	SC	None	None	None	None	None	N/A	Paint all structural steel in Pit P-5 Safety Yellow.



www.ahoarch.com



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Finish Schedules &
Head, Jamb, and
Sill Details

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

A621


Scale As indicated

11/16/2025 9:15:39 AM



① 02_3D View_Front (West)

*See Civil for actual site conditions, including dumpster enclosure location.



② 03_3D View_Rear (East)

*See Civil for actual site conditions, including dumpster enclosure location.

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

3D Views

Project number	24028
Date	11/8/2024
Drawn by	ARC
Checked by	N/A

R100

Scale

SCHEDULE OF SPECIAL INSPECTIONS			
Item	Inspection/Test/Certification	C or P	Extent/Comments
1000.00	General Conditions		
1000.01	Review of Structural Documents and Shop Drawings to determine differences not approved by Architect or Engineer of Record	Continuous	Structural Documents should take precedence over any shop drawings. Special Inspector should use the Architectural and Structural Documents as the primary documents for review of construction. Shop drawing should be used as secondary document to review details not shown on the Architectural and Structural Documents. Any discrepancy between the two documents should be resolved by the Architect or Engineer of Record before proceeding with construction.
1000.02	The Special Inspector duties for missing details, conflicting details or coordination issues.	Continuous	Reasonable attempts have been made on the part of the design team to properly coordinate drawings. However in the event that a question arises on the project the Special Inspector shall obtain clarification from the Architect on all items. No changes shall be made to the drawings or construction without written conformation.
1400.00	Fabricators		
1400.01	Review the quality control procedures of the following fabricators for completeness and adequacy relative to the fabricator's scope of work: steel fabricator, lightgage truss fabricator, wood truss fabricator.	Periodic	
1400.02	The following fabricators, if registered and approved by the building official, may submit "Certificates of Compliance" at the completion of their scope of work that their fabricated items were constructed in accordance with the approved construction documents: steel fabricator, lightgage truss fabricator, wood truss fabricator. Fabricators having successfully completed no fewer than 5 similar projects may also submit for approval with documentation of similar projects.	Periodic	
2300.00	Soils and Deep Foundations		
2300.01	Verify bearing capacities of soils beneath footings.	Periodic	As recommended in approved soils report and specified in earthwork specifications.
2300.02	Verify assumed bearing capacities and determine settlements of soils beneath footings and building pad.	Periodic	As noted on the drawings, recommended by the geotechnical engineer, and specified in earthwork specifications.
2300.03	Verify site preparation prior to beginning fill placement. Verify fill material type, placement method, lift thickness, and compaction of fill material. Verify in-place density of compacted fill.	Periodic	As recommended in approved soils report and specified in earthwork specifications.
2300.04	Inspect installation of pile foundations including installation of test piles.	Continuous	As recommended in approved soils report and specified in pile specifications.
2300.05	Inspect installation of drilled pier foundations and installation of test piers. Inspect reinforcing in each pier and test concrete.	Continuous	As recommended in approved soils report and specified in pile specifications.
2300.06	Inspect helical pile installation.	Continuous	Record installation equipment used, pile dimensions, tip elevations, final depth, final installation torque.
3300.00	Concrete Construction		
3300.06	Inspect concrete formwork except as noted above for proper dimensions. Verify that construction joints are properly keyed. Verify that slab recesses, if any, have been installed.	Periodic	Prior to each pour.
3300.07	Inspect reinforcing steel except as noted above for installation including size, spacing and bar clearances. Verify that lap splices and embedment lengths are per the construction documents. Verify that dowels for work above are properly aligned and spaced to match other work.	Periodic	Prior to each pour.
3300.13	Inspect bolts	Periodic	
3300.15	Verify each proposed concrete mix for the project.	Periodic	For each proposed mix
3300.16	Sample all concrete for strength tests and test concrete for slump, air content, temperature, and other tests.	Continuous	During placement operations. Reference concrete specifications for specific tests and frequencies.
3300.17	Inspect concrete placement except as noted above.	Continuous	
3300.18	Inspect all concrete curing operations as noted in the extents column.	Periodic	Monitor during hot, cold and windy conditions. Reference concrete specifications.
3300.25	Verify sawed joints in slabs on grade are completed within 4 hours of the final set of the concrete	Continuous	
4810.00	Masonry Construction		
4810.03	Inspect proportions of site prepared mortar and grout. Inspect construction of mortar joints. Inspect reinforcement for correct size and spacing. Inspect work for correct location and type of embeds and anchor bolts. Inspect work for size and location of structural elements.	Periodic	At beginning of masonry construction and every _____ square feet of masonry thereafter.
4810.05	Inspect masonry cells and cleanouts prior to placement of grout. Inspect grout proportions. Inspect placement of reinforcement.	Periodic	Prior to grouting of masonry.
4810.06	Inspect grouting operations to ensure compliance with code and construction documents.	Continuous	During grouting.
4810.12	Inspect protection of masonry during cold weather and hot weather.	Periodic	During periods with temperatures below 40 degrees or above 90 degrees.
4810.13	Inspect preparation of grout specimens, mortar specimens and / or prisms.	Continuous	During preparation of all specimens.
4810.14	Verify compliance with all required inspection provisions of the construction documents and approved submittals.	Periodic	As required for duration of project.
5120.00	Steel Construction		
5120.01	Inspection of the steel pieces		
5120.02	Inspection of frame		
5120.03	Inspect high-strength bolts, nuts and washers: a. Identify markings to conform to ASTM standards specified in the construction documents. b. Inspect manufacturer's certificate of compliance.	Periodic	Reference project specifications and ASTM material specifications; AISC 335, (Sect A3.4); AISC LRFD (Sect A3.3).
5120.05	Inspect high-strength bolting: Bearing-type connections.	Periodic	
5120.07	Inspect and verify structural steel material: a. Identification markings to conform to ASTM standards specified in the approved construction documents. b. Manufacturers' certified mill test reports.	Periodic	Confirm that materials meet applicable ASTM specifications noted in construction documents.
5120.08	Inspect and verify weld filler materials: a. Identification markings to conform to AWS specification in the approved construction documents. b. Manufacturer's certificate of compliance required.	Periodic	Confirm that materials meet applicable ASTM specifications noted in construction documents.
5120.09	"Inspect welding: Structural Steel: 1) Complete and partial penetration groove 2) Multipass fillet welds. 3) Single-pass fillet welds > 5/16 ⌀ "	Continuous	Per specifications and AWS D1.1
5120.10	"Inspect welding: Structural Steel: 1) Single-pass fillet welds ≤ 5/16 ⌀ 2) Floor and deck welds. "	Periodic	Per specifications and AWS D1.1
5120.11			
5120.12	"6. Inspect steel frame joint details for compliance with approved construction documents: a. Details such as bracing and stiffening. b. Member locations. c. Application of joint details at each connection."	Periodic	Inspect complete frame.
5301.03	Verify deck support angles are provided for all opening greater than 100 square inches.	Periodic	
5310.00	Metal Deck		
5310.01	Verify depth and gauge of all deck elements	Periodic	
5310.02	Verify adequate bearing of ends of decking	Periodic	
6000.00	Wood		
6000.01	Inspect fabricated wood trusses and shop built components.	Periodic	Inspect truss production in shop unless fabricator is approved by building official and submits certification of compliance at end of scope of work. Inspect _____% of trusses. Inspect 100% of trusses if discrepancies are observed.
6000.02	Inspect site-built assemblies including site built trusses. Inspect erected trusses including bridging and attachments.	Periodic	Inspect all site-built trusses. Inspect erected trusses and installation of bridging.
8000.00	Special Inspections for Wind Resistance		
8000.01	Roof Cladding and Roof Framing Connections	Periodic	
8000.02	Wall Connections to Roof and Floor Diaphragms and Framing	Periodic	
8000.03	Roof and Floor Diaphragm Systems, including Collectors, Drag Struts, and Boundary Elements.	Periodic	
8000.04	Vertical Windforce-Resisting Systems, including Braced Frames, Moment Frames, and Shearwalls	Periodic	
8000.05	Windforce-Resisting System Connections to the Foundation.	Periodic	
8000.06	Fabrication and installation of components and assemblies required to meet the impact-resistance requirements of Section 1609.1.4.	Periodic	

GENERAL NOTES

- Contractor shall compare structural drawings and architectural drawings. Any omissions or discrepancies between plans, details, and specifications shall be brought to the attention of the Architect or Engineer before bidding. In all cases, more stringent requirement governs. Architectural dimensions and elevations will control.
- Structural drawings or parts of the structural drawings may not be used as shop drawings without prior written approval.
- All or parts of these drawings were produced with computer aided drafting. Drawings are available from the Engineer in DWG format on request.
- Contractor proposed changes to details must be clearly noted on the first sheet of all shop drawings.
- Construction shown is stable after the building is complete including interior and exterior finishes. The Contractor is responsible for temporary bracing of the structure during construction.
- Review of submittal information shall be for general compliance with the contract documents and shall not include checking of detailed dimensions or detailed quantities.

DESIGN LOADS

- Reference code for loading 2021 IBC.
 - Building Classification II
 - Wind Load
 - Basic Wind Speed (3 sec gust) 108 mph
 - Wind Exposure C
 - Internal Pressure Coefficient +/- 0.18
 - Velocity Pressure (qz) --- psf
 - Roof Snow Load
 - Flat Roof Snow Load (Pf) 5 psf
 - Snow Exposure (Ce) 1.0
 - Importance Factor 1.0
 - Thermal Factor (Ct) 1.0
 - Seismic Load
 - Importance Factor 1.0
 - Mapped Spectral Response Accelerations
 - Ss 0.296
 - S1 0.103
 - Site Class D
 - Spectral Response Coefficients
 - Sds 0.309
 - Sd1 0.164
 - Seismic Design Category C
 - Base Seismic Force-Resisting System(s) and Response Modification Factor
 - Intermediate Reinforced Masonry Shear Walls 3.5
 - Design Base Shear x x kips
 - Seismic Response Coefficient (Cs) 0.xx
 - Analysis Procedure = Equivalent Lateral Force
 - Live Load
 - Roof Load 20 psf
 - Service Bay and slabs on grade 100 psf
 - Mezzanine 50 psf

FOUNDATIONS

- Foundation design for this project was based on soils information provided by Terracon
- Assumed bearing capacity----- 2500 psf
- All footings are to bear on engineered fill.
- Install corner bars at all footing intersections and corners (Provide lap length e.w.)
- All footing elevations are given to the top of the footings.
- Footing steps shown on the plans are furnished as a guide for estimating quantities. Final elevations are to be set in the field. Bearing elevations must be approved by a Soils Engineer before any concrete is placed.
- Coordinate foundation elevations with plumbing requirements. Step footings as required to clear plumbing lines.
- Provide drainage for all retaining walls, see architectural for notes and details.

MASONRY

- All masonry work to be in accordance with "Building Code Requirements for Concrete Masonry Structures" TMS 402-2016 and "Specifications for Masonry Structures" TMS 602-2016.
- Fill all concrete masonry units with concrete or grout from the top of the footing to the finish floor or to 8" above finish grade whichever is higher.
- Use ladder type joint reinforcement (Dur-O-Wall SW DA3100 or better) at 16" on center in all cavity walls where brick is used for one or more of the wythes
- Use truss type joint reinforcement (Dur-O-Wall SW DA3100 or better) at 16" o/c. in all other masonry walls.
- Provide joint reinforcement at 8" o/c. for all walls constructed with stack bond.
- Use Type "M" or Type "S" mortar in accordance with IBC Table 2103.7(1).
- Minimum compressive strength of concrete masonry f'm = 2500 psi. Submit for review test data on strength of units before starting any masonry work.
- Minimum compressive strength of grout f'm = 2500 psi. Use 3/8" max size aggregate. See Special Inspection Schedule for any testing requirements. Grout slump shall be 8" to 11".
- Use "Fine" grout for all reinforced piers and reinforced wall in accordance with ASTM C 476.
- Each grout lift shall not exceed 5'-0" unless cleanouts are provided in the bottom course.
- Fill cells under all lintels with grout.
- Provide lintels over all openings through wall. See lintel details for reinforcement.
- Unless otherwise noted provide control joints in all walls 4'-0" from wall intersections or corners and at 20'-0"
- Extend all horizontal steel and bond beams thru control joints.
- Vertical Reinforcement shall extend into the bond beam.
- Unless noted, all bars are to be located at the center of cell. Where bars are specified at each face, provide minimum ¾" clear space between reinforcement and CMU face shell.
- Anchor bolt into grouted cell locations only, unless noted otherwise.

REINFORCING STEEL AND CONCRETE

- All concrete work is to be in accordance with the "Building Code Requirements for Reinforced Concrete" (ACI 318-19).
- All detailing is to be in accordance with "ACI Detailing Manual" SP-66
- Use of Calcium Chloride, Chloride Ions, or other salts in concrete are prohibited.
- Concrete Properties: See Schedule
 - All concrete must obtain 7 day strength of 70% of design strength.
 - Concrete mixes may use up to 25% of cementitious weight as fly ash.
 - Concrete mixes may use water reducers, accelerators or retarders with prior approval.
 - Do not provide air entrainment in concrete mixes for interior slabs.
- All steel reinforcement shall be of deformed bars of billet steel conforming to ASTM A615, Grade 60 in all concrete.
- Welded wire fabric shall be ASTM 185 and shall lap 2 cross wires or 6" whichever is greater on all sides. All laps shall be wired together.
- Provide (2) #4 bars x 4'-0" at re-entrant corner locations Typical. Locate 3" away from corner and space 1'-0" apart.
- All slabs on grade are 6", unless noted. Slabs are to be placed on 10 Mil, PVC vapor barrier over 4" of porous fill. Reinforce slabs with 6x6 W2.9 x W2.9 WWF placed 1" from top of slab. Unless otherwise noted slabs shall have joints placed a 12'-0" on centers. Joints may be control joints or construction joints. See Architectural Plans for floor slopes and recesses for hard tile.
- Minimum concrete cover for reinforcement:
 - Footings 3" bottom, 2" sides
 - Cast-In-Place WallsSurfaces exposed to weather or soil 2" - #6 and greater, 1-1/2" - #5 and smallerOther surfaces 3/4"
- Provide corner bars at all wall and footing intersections.
- No openings shall be allowed to penetrate any concrete work, unless it is shown on the structural framing plans without prior written approval. Contractor shall submit for review locations of proposed openings not shown 30 days prior to pouring any concrete.
- Provide a continuous water bar at all wall construction joints below ground level.
- Use 3/4" chamfer for all exposed corners unless noted.
- Testing samples for preparing strength test specimens of each concrete mixture placed each day shall be taken in accordance with (1) through (3).
 - At least once a day
 - At least once for each 150yd^3 of concrete
 - At least once for each 5000ft^2 of surface area for walls or slabs.

STRUCTURAL STEEL

- All detailing, fabricating, and erection of structural steel shall be in accordance with the AISC 360-10 "Specifications for Structural Steel Buildings". All reactions shown are ASD loads.
- All connections are to be detailed as Type 2 "simple frame connections".
- All structural steel W shapes shall be ASTM A992.
- All structural steel Tube sections shall be ASTM A500 Grade B.
- All structural steel Pipe sections shall be ASTM A501.
- All structural steel channels, angles and other sections shall be ASTM A36, unless noted.
- Headed Studs shall be Type B Shear Connectors.
- Shop and field connections shall be welded with E-70XX electrodes or bolted with 3/4" dia. A-325N or A-325F bolts, unless noted.
- Use 3/4" cap and bearing plates, unless noted.
- Use 3/4" dia x 1'-0" long ASTM 1554 Grade 36 anchor bolts, unless noted. In lieu of cast bolts, 3/4"x1'-0" long HAS rods epoxied with Hilti HVA epoxy, or equal, may be used with prior approval.
- Grout under baseplates with ASTM C 1107 cementitious 6000 psi Non-Shrink Grout.
- Structural steel shall be shop primed per SSPC paint system No. 7. Primer shall be SSPC paint with a minimum thickness of 2.0 MILS. Omit Paint at surfaces to be fireproofed.
- Provide L 3"x3"x1/4" frames around all roof opening through metal decking.

WOOD (STRUCTURAL)

- All floor framing and roof framing shall be #2KD SYP or approved equal.
- All floor framing shall be horizontally braced/blocked at midspan unless noted otherwise.
- All vertical framing shall be Sparce-Pine Fir, #2.
- All wood exposed to weather or in contact with CMU or concrete shall be pressure treated in accordance with American Wood Preservers Association Manual of Recommended Practice.
- All Fasteners and Nails in contact with pressure treated lumber shall be stainless steel Type 304. Submit all alternates for approval.
- Furnish design calculations sealed by a Professional Engineer licensed in the State of Project for all truss members.
- Truss connections to walls and framing shall be Designed and Specified by Truss Supplier.
- Field Modification or Fabrication of trusses is not allowed unless written approval is provided by Truss Supplier.
- Provide (4) studs at all beam and girder truss bearing locations.
- Roof decking shall be 5/8" APA rated sheathing. Exposure 1 with 32/16 span rating. Provide plyclips at all roof sheathing connections, unless noted otherwise.
- Floor and roof sheathing shall be nailed with 8d rinks Hank nails at 6" o.c.
- All bolts connecting continuous horizontal sill plates to concrete, masonry, or steel shall have 3" flat washers.

CONCRETE SCHEDULE						
Concrete Use	Design Strength	Max W/C Ratio	Slump Limits	Entrained Air Range	Weight	Notes
Basement Walls	4000 psi	n/a	6" to 8"	3% to 5%	150 pcf	Use HRWR
Slabs on Composite Metal Deck	4000 psi	n/a	6" to 8"	---	150 pcf	Use HRWR
Slabs on Grade/Grade Beams	4000 psi	n/a	6" to 8"	---	150 pcf	Use HRWR

BJW

STRUCTURAL
ENGINEERS

BARNETT JONES WILSON, LLC • PELL CITY • TUSCALOOSA • CHATTANOOGA • WWW.STRUCTENGS.COM

AHO ARCHITECTS, LLC

www.ahoarch.com

REGISTERED
No. 22742
PROFESSIONAL
ENGINEER
JOHN CAMPBELL

11/8/2024

Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

General Notes & Special Inspections

Project number24028

Date11/8/2024

Drawn byjcj

Checked byjd

S0.1

Scale3/4" = 1'-0"

Shear Plate Connection Schedule

Length	# of bolts	End reaction	Min plate thickness
6"	2	8.2k	1/4"
9"	3	16.3k	1/4"
12"	4	26.1k	1/4"
15"	5	36.3k	1/4"
18"	6	46.3k	1/4"
21"	7	56.4k	1/4"

Reinforcing Steel Lap Splice & Development Length for Concrete Masonry

Bar Size	Bar in center of wall			Bar in each face of wall
	6" CMU	8" CMU	12" CMU	
#3	16"	16"	16"	16"
#4	21"	21"	21"	30"
#5	32"	26"	26"	46"
#6	61"	43"	40"	85"
#7	NA	60"	46"	115"
#8	NA	NA	61"	NA

Notes:

- Lengths are for vertical splices in walls.
- Bar length for center of wall are based on f'm of 1500 psi or greater.
- Bar length for face of wall are based on f'm of 2000 psi or greater.
- Refer to General Notes and details for masonry strength.

Components and Cladding Schedule a = 5.5'

Area(sf)	Zone 1,2,3 (+)(psf)	Zone 1 (-)(psf)	Zone 2,3 (-)(psf)	Zone 4,5 (+)(psf)	Zone 4 (-)(psf)	Zone 5 (-)(psf)
10	29.4	-32.1	-37.5	32.1	-34.8	-43.0
50	27.5	-28.3	-33.7	28.8	-31.5	-36.3
100	26.7	-26.7	-32.1	27.3	-30.0	-33.4



Frame Connection Schedule

Length	# of bolts	End reaction	Min angle thickness
5-1/2"	2	37.1k	5/16"
8-1/2"	3	55.3k	5/16"
11-1/2"	4	72.7k	5/16"
14-1/2"	5	88.7k	5/16"
17-1/2"	6	104.0k	5/16"

Length	Size of Weld A	End reaction	Min angle thickness
5-1/2"	3/16"	37.1k	5/16"
8-1/2"	3/16"	55.3k	5/16"
11-1/2"	3/16"	72.7k	5/16"
14-1/2"	3/16"	88.7k	5/16"
17-1/2"	3/16"	104.0k	5/16"

Length	Size of Weld B	End reaction	Min angle thickness
5-1/2"	1/4"	14.6k	5/16"
8-1/2"	1/4"	32.2k	5/16"
11-1/2"	1/4"	53.4k	5/16"
14-1/2"	1/4"	76.6k	5/16"
17-1/2"	1/4"	101.0k	5/16"

Depth of beam	Min length of angle	Depth of beam	Min Length of angle
W12	5-1/2"	W24	11-1/2"
W14	5-1/2"	W27	11-1/2"
W16	5-1/2"	W30	14-1/2"
W18	8-1/2"	W33	14-1/2"
W21	8-1/2"	W36	17-1/2"




Reinforcing Steel Lap Splice Lengths


Bar Size	Column Splices	Bm, Ftg & Wall Splices	
		Top Bars	Other Bars
# 3	12"	19"	15"
# 4	15"	25"	19"
# 5	19"	31"	24"
# 6	23"	37"	29"
# 7	26"	54"	42"
# 8	30"	62"	48"
# 9	34"	70"	54"
# 10	38"	79"	61"
# 11	42"	87"	67"

Notes:


- Top bars are any horizontal reinforcing steel that has another layer of steel more than 2" below the bars or reinforcing steel that has more than 12" of concrete below the bars.
- All horizontal reinforcing bars in walls may be detailed as "Other Bars".
- All corner bars may be detailed as "Other Bars".



Single Footing Step





Multiple Footing Step




CMU Lintel Elevation


Typical Anchor Bolt Detail Typical Base Plate




Typical Control Joint



Typical Construction Joint



Typical Masonry Wall Control Joint




Less than 4'-0" Less than 8'-0"


CMU Lintel Schedule

See sections on S5.1 for overhead door lintel


Typical Joint Reinforcing at Corner




Typical Beam, Wall or Footing Reinforcing at Corners



Typical Joint Reinforcing at Intersection



Typical Beam, Wall or Footing Reinforcing at Intersections



Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC. All Rights Reserved.

Typical Details

Project number	24028
Date	11/8/2024
Drawn by	jcj
Checked by	jd

S0.2

Scale 3/4" = 1'-0"

Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Foundation Plan


Project number	24028
Date	11/8/2024
Drawn by	jcj
Checked by	jd

S1.1

Scale As indicated



PIT FOUNDATION PLAN
1/8" = 1'-0"



OIL CHANGE FOUNDATION PLAN

1/8" = 1'-0"

Sheet Notes:

- See Sheet No S0 for typical details and general notes.
- Reference all elevations to finish floor elevation (+) 0'-0".
- Floor construction 3" concrete slab with 6x6 W2.9xW2.9 wwf over 2" x 20 ga. galvanized composite metal deck. Total slab thickness = 5". Provide 5/8" dia puddle welds on 36/4 pattern w/ (3) #12 TEK screw sidelap fasteners per span.
- All steel beam reactions shall be designed for 10 kips (ASD) unless noted otherwise.
- Refer to architectural for all dimensions, slopes, elevations, etc. not illustrated on this plan. Coordinate all final dimensions and elevations with architectural.

Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Roof Framing Plan


Project number	24028
Date	11/8/2024
Drawn by	jcj
Checked by	jd

S3.1

Scale As indicated




EQUIPMENT PLATFORM FRAMING PLAN
1/8" = 1'-0"



Roof Perimeter
Blocking Detail

See 9/S5.1



OIL CHANGE ROOF FRAMING PLAN

1/8" = 1'-0"

Sheet Notes:

- See Sheet No S0.x for typical details and general notes.
- Reference all elevations to finish floor elevation (+) 0'-0"
- Roof construction 5/8" plywood deck with H-clips. Attach with 8d nails @ 6" o.c..
- Roof slope = 8:12
- Refer to architectural drawings for all dimensions, slopes, elevations, etc... not illustrated on this plan. Coordinate all final dimensions and elevations with architectural.
- Truss loading: Top Chord Dead Load = 10 psf, Bottom Chord Dead Load = 10 psf, use Total dead load = 10psf for wind load calculations.
- Truss requirements: (note that all of these requirements must be included in the truss submittal prior to receiving approval)
 - Furnish design calculations sealed by a Professional Engineer licensed in the state in which the project occurs for all truss members.
 - Truss manufacturer shall specify and provide all truss to truss and truss bearing connections, and not contain mention of "by others" in relation to design.
 - Truss manufacturer shall be responsible for providing and illustrating all temporary and permanent bracing required.



11/8/2024

Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama












FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Sections and
Details

Project number	24028
Date	11/8/2024
Drawn by	jcj
Checked by	jd
S5.1	
Scale	3/4" = 1'-0"



Section 4
3/4" = 1'-0"

Section 3
3/4" = 1'-0"

Section 2
3/4" = 1'-0"

Section 1
3/4" = 1'-0"

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date



© 2024 Aho Architects, LLC.
All Rights Reserved.

Sections and
Details


Project number	24028
Date	11/8/2024
Drawn by	jcj
Checked by	jd

S5.2


Scale As indicated




Section 12
3/4" = 1'-0"




Section 4
3/4" = 1'-0"




Section 3
3/4" = 1'-0"




Section 8
3/4" = 1'-0"




Section 6
3/4" = 1'-0"



Section 2
3/4" = 1'-0"



Section 5
3/4" = 1'-0"



Section 1
3/4" = 1'-0"

12x20

DUCT SIZE, FIRST FIGURE IS SIDE SHOWN
INSIDE CLEAR DIMENSION UNLESS NOTED OTHERWISE

24x12

LOW PRESSURE, RECTANGULAR (GALVANIZED STEEL)

LOW PRESSURE, RECTANGULAR (ALUMINUM STEEL)

20"ø

ROUND (GALVANIZED STEEL)

20x10

MEDIUM PRESSURE, FLAT OVAL (GALVANIZED STEEL)

FLEXIBLE DUCT

R

DUCT RISE

D

DUCT DROP

EXISTING DUCTWORK TO REMAIN

DUCT TRANSITION

RECTANGULAR TO ROUND DUCT TRANSITION

TURNING VANES

FD

FIRE DAMPER AND SLEEVE, PROVIDE ACCESS DOOR

SD

SMOKE DAMPER AND SLEEVE, PROVIDE ACCESS DOOR

SDFD

COMBINATION FIRE/SMOKE DAMPER, PROVIDE ACCESS DOOR

MANUAL VOLUME DAMPER

STANDARD 45° BRANCH, SUPPLY OR RETURN, NO SPLITTER

STANDARD 45° BRANCH, SUPPLY OR RETURN, NO SPLITTER,
WITH MANUAL VOLUME DAMPER

CONICAL SPIN-IN FITTING WITH BUTTERFLY DAMPER

GRILLE OR REGISTER, CEILING

A

ACCESS DOOR

D

CONDENSATE DRAIN PIPING

AD

AUXILIARY CONDENSATE DRAIN PIPING

R

REFRIGERANT PIPING (2 LINES TOTAL)

90°

ELBOW, 90° (LONG RADIUS)

+

+

TEE

+

+

TEE, TURNED UP

+

+

TEE TURNED DOWN

+

+

ELBOW, TURNED DOWN

+

+

ELBOW, TURNED UP

Ⓣ

WALL MOUNTED THERMOSTAT

Ⓜ

WALL MOUNTED HUMIDISTAT

Ⓢ

WALL MOUNTED TEMPERATURE SENSOR

Ⓢ

WALL MOUNTED CARBON DIOXIDE SENSOR

Ⓢ

WALL MOUNTED DEVICE W/ COVER GAURD

SMOKE

SMOKE DETECTOR

TIE NEW INTO EXISTING

UC

UNDERCUT DOOR 3/4 INCHES

→

SUPPLY AIR FLOW

↔

RETURN OR EXHAUST AIR FLOW

LEGEND

AB, CL'G

ABV.

AC

A/C

AFF

AHU

AI

ALT.

AMP

AO

APPROX.

ARCH.

AVG

B

BTU

CFM

CH

CHWP

CLS

CT

CU

CWP

DEFL

DET

DI

DIA

Ø

DO

EDB

ELEC.

ELEV.

EWB

EWT

EXH

EXIST.

°F

GFF

GPM

FPM

FPS

FT

HD.

HP

HR

HT

HTR

HVAC

HWP

HX

HZ

ID

IN.

KW

KWH

MAX

MBH.

MECH.

MFR.

MIN

NO.

N/A

NC

O.D.

OA

⊖

ORIG.

PH

PIU

PRESS

RTN

RTU

SDC

SENS

SQ.

SPLY

TEMP

VAV

W

W/

W.P.D.

ABOVE CEILING

ABOVE

ALTERNATING CURRENT

AIR COMPRESSOR

ABOVE FINISHED FLOOR

AIR HANDLING UNIT

ANALOG INPUT

ALTERNATE

AMPERE

ANALOG OUTPUT

APPROXIMATELY

ARCHITECTURAL

AVERAGE

BOILER

BRITISH THERMAL UNIT

CUBIC FEET PER MINUTE

CHILLER

CHILLED WATER PUMP

CEILING

COOLING TOWER

CONDENSING UNIT

CONDENSER WATER PUMP

DEFLECTION

DETAIL

DIGITAL INPUT

DIAMETER

DIAMETER

DIGITAL OUTPUT

ENTERING DRY BULB

ELECTRICAL

ELEVATION

ENTERING WET BULB

ENTERING WATER TEMPERATURE

EXHAUST

EXISTING

DEGREES FAHRENHEIT

GAS FIRED FURNACE

GALLONS PER MINUTE

FEET PER MINUTE

FEET PER SECOND

FOOT OR FEET

HEAD

HORSE POWER

HOUR(S)

HEIGHT

HEATER

HEATING, VENTILATION AND AIR CONDITIONING

HOT WATER PUMP

HEAT EXCHANGER

FREQUENCY (HERTZ)

INSIDE DIAMETER

INCHES

KILOWATT

KILOWATT HOUR

MAXIMUM

1000 BTU PER HOUR

MECHANICAL

MANUFACTURER

MINIMUM

NUMBER

NOT APPLICABLE

NOISE CRITERIA

OUTSIDE DIAMETER

OUTSIDE AIR

OVAL DUCTWORK

ORIGINAL

PHASE

POWERED INDUCTION UNIT

PRESSURE

RETURN AIR

ROOFTOP AIR HANDLING UNIT

STAND ALONE DIGITAL CONTROLLER

SENSIBLE

SQUARE

SUPPLY

TEMPERATURE


VARIABLE AIR VOLUME

WATT

WITH

WATER PRESSURE DROP

ABBREVIATIONS



1 AIR DEVICE LEGEND
MEP## NO SCALE

NOTE: THIS LEGEND IS FOR REFERENCE ONLY.
ALL SYMBOLS WHICH APPEAR WITHIN THE
LEGEND MAY NOT APPLY TO THIS PROJECT.

AIR HANDLING UNIT SCHEDULE																					
EQUIPMENT NO.	MANUFACTURER/ MODEL NO.	CFM	OA CFM	E.S.P. (IN. W.C.)	FAN		COOLING CAPACITY				ELECTRIC HEAT			DISCONNECT	ELECTRICAL				MOUNTING	WEIGHT (LBS.)	REMARKS
					H.P.	DRIVE	EDB (°F)	EWB (°F)	LDB (°F)	LWB (°F)	TOTAL (KW) (208v)	TOTAL (KW) (240v)	STAGES		VOLTS/PH./HZ. 208/1/60		VOLTS/PH./HZ. 240/1/60				
															UNIT MCA	UNIT MOCP	UNIT MCA	UNIT MOCP			
AHU-1	TRANE TEM4A0B30	975	150	0.50	0.5	--	80	67	58.6	57.7	10.8	14.4	1	BY DIV. 26	73	80	83	90	HORIZONTAL	150	1), 2), 3)

REMARKS:
1) SUSPEND UNIT FROM STRUCTURE PER DETAIL.
2) PROVIDE UNIT WITH SINGLE POINT POWER CONNECTION.
3) PROVIDE WITH 1" THROWAWAY FILTERS.

OUTDOOR CONDENSING UNIT SCHEDULE												
EQUIPMENT NO.	MANUFACTURER/ MODEL NO.	SERVICE	COOLING CAPACITY		DISCONNECT	ELECTRICAL				SEER	WEIGHT (LBS.)	REMARKS
			NOMINAL (TONS)	AMBIENT TEMP. (F)		VOLTS/PH./HZ. 208/1/60		VOLTS/PH./HZ. 240/1/60				
						UNIT MCA	UNIT MOCP	UNIT MCA	UNIT MOCP			
CU-1	TRANE 4TTR4030	AHU-1	2.5	95	BY DIV. 26	17	25	17	25	15.5	175	1), 2)

REMARKS:
1) PROVIDE WITH LOW AMBIENT CONTROLS.
2) LOCATE UNIT ON HOUSEKEEPING PAD. ANCHOR UNIT TO PAD WITH EXPANSION BOLTS.

POWER VENTILATOR SCHEDULE														
EQUIPMENT NO.	MANUFACTURER/ MODEL NO.	CFM	E.S.P. (IN. W.C.)	RPM	MAX. SONES	ELECTRICAL				LOCATION	TYPE	DRIVE	WGT (LBS.)	REMARKS
						DISCONNECT	MOTOR STARTER	WATTS	MOTOR VOLTS/PH./HZ					
EF-1	COOK GC-146	70	0.35	849	1.5	BY DIV. 26	BY DIV. 23	32	115/1/60	CEILING	CENTRIFUGAL	DIRECT	15	1), 3), 5)
EF-2	COOK GC-146	70	0.35	849	1.5	BY DIV. 26	BY DIV. 23	32	115/1/60	CEILING	CENTRIFUGAL	DIRECT	15	1), 3), 5)
EF-3	COOK 180W10D	3000	0.25	1058	13.5	BY DIV. 26	BY DIV. 23	3/4 HP	115/1/60	WALL	CENTRIFUGAL	DIRECT	90	2), 3), 4)

REMARKS:
1) PROVIDE OCCUPANCY SENSOR FOR FAN OPERATION IN EACH RESTROOM.
2) FAN SHALL RUN CONTINUOUSLY DURING OCCUPIED HOURS. INTERLOCK WITH LOCAL SWITCH. COORDINATE WITH ELECTRICAL.
3) PROVIDE WITH FAN SPEED CONTROLLER.
4) PROVIDE WITH INLET GUARDS AND GRAVITY SHUTTER.
5) PROVIDE WITH BACKDRAFT DAMPER.

GAS RADIANT HEATER SCHEDULE								
EQUIPMENT NO.	MANUFACTURER/ MODEL NO.	HEATING CAPACITY (MBH)	AMPS	ELECTRICAL		WEIGHT (LBS)	MOUNTING HEIGHT	REMARKS
				DISCONNECT	VOLTS/PH./HZ.			
RH-1	RE-VERBER-RAY DR-50	50	0.1	BY DIV. 26	115/1/60	50	11' 9"	1), 2), 3), 4)
RH-2	RE-VERBER-RAY DR-50	50	0.1	BY DIV. 26	115/1/60	50	11' 9"	1), 2), 3), 4)

REMARKS:
1) MAINTAIN DISTANCES FROM COMBUSTIBLES PER MANUFACTURERS INSTALLATION DETAILS.
2) PROVIDE WITH 24V TRANSFORMER AND LOW VOLTAGE THERMOSTAT.
3) ANGLE UNITS AT 30 DEGREES FROM HORIZONTAL. SUSPEND UNITS FROM STRUCTURE WITH 3/8" THREADED RODS.
4) HEIGHT SHOWN MEASURED FROM BOTTOM OF HEATING RAY HEAD/TUBE.

OUTSIDE AIR CALCULATIONS																		
MECHANICAL CODE OUTSIDE AIR REQUIREMENT																		
		Supply	Area	Occupancy	Max Number of	Number of	O.A. Area	O.A. People	O.A. Area					MAX OA REQUIRED				
		Air (cfm)	(sq. ft)	Classification	Occupants/SF	Occupants	(cfm / sq. ft)	(cfm/person)	(cfm)	O.A. People	O.A. (cfm)	Zone	Corrected		Primary	Ventilation		
Served By	Space Name	Vpz (Max)	Az		(per 1000 SF)	Rp	Ra	Pz		(cfm)	Vbz	Ez	CFM	Vot	Zp	Ev		Remarks
AHU-1	1 Service Writing	575	296	Lobbies	--	1	0.06	5	18	5	23	0.80	28	28	0.05	1		
	4 Storage	85	73	Storage	--	15	0.12	0	9	0	9	0.80	11	11	0.13	1		
	5 Manager	115	56	Office	5	1	0.06	5	3	5	8	0.80	10	10	0.09	1		
	7 Break Room	100	65	Break Room	35	1	0.06	10	4	10	14	1.80	8	8	0.08	1		
															OA	Lowest Ev		
															57.57	1.00		

Pinnacle

ENGINEERING, INC.

Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262

AHO ARCHITECTS, LLC

www.ahoarch.com

ALABAMA
REGISTERED
No. 30374
PROFESSIONAL
ENGINEER

11/8/24

Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Mechanical
Legend,
Abbreviations and
Schedules


Project number24028
Date11/8/2024
Drawn byCA
Checked byJB

M0.01


Scale12" = 1'-0"

11/7/2024 4:32:41 PM

SECTION 15892 - LOW PRESSURE DUCTWORK			SECTION 15906 - TEMPERATURE CONTROLS			SECTION 15936 - REGISTERS, GRILLES AND DIFFUSERS		
A. GENERAL			A. GENERAL:			A. PRODUCT PERFORMANCE DATA SHALL BE TAKEN FROM TESTS CONDUCTED IN ACCORDANCE WITH ANSI/ASHRAE 70, AND ARI-880.		
1. DUCT SYSTEM SHALL BE FABRICATED WITH SHEET METAL THICKNESSES AND REINFORCED IN ACCORDANCE WITH SMACNA, AS SHOWN ON THE DRAWINGS AND AS DESCRIBED HEREIN. DUCTS 18 INCHES AND LARGER ON ANY SIDE SHALL BE STIFFENED BY BEADING ON NOT TO EXCEED 12 INCH CENTERS, UNLESS NOTED OTHERWISE THE MINIMUM PRESSURE/VELOCITY CLASSIFICATION SHALL BE 2 INCH W.G. PLUS OR MINUS, AT 2500 FT. PER MINUTE, DUCT SEAL CLASS "X". DUCT SIZES SHOWN ARE CLEAR INSIDE DIMENSIONS.			1. FURNISH AND INSTALL AN ELECTRIC SYSTEM OF AUTOMATIC TEMPERATURE CONTROL AS SPECIFIED HEREIN AND AS SHOWN ON THE CONTRACT DRAWINGS AS MANUFACTURED BY HONEYWELL, JOHNSON CONTROLS, INVENYS, OR APPROVED EQUAL.			B. THE NOMINAL OR DUCT CONNECTION SIZE OF GRILLES (NOT OVERALL DIMENSIONS) IS GIVEN ON PLANS. GRILLES AND REGISTERS INCLUDING VOLUME CONTROLLERS SHALL BE CONSTRUCTED OF THE SAME MATERIALS SPECIFIED FOR THE GRILLE. THE GRILLE FINISH SHALL BE WHITE UNLESS NOTED OTHERWISE.		
2. DUCTWORK HANGERS SHALL BE SUPPORTED BY FASTENERS ATTACHED TO STRUCTURAL STEEL. REPAIR FIRE PROOFING WHICH WAS REMOVED FOR DUCTWORK INSTALLATION. INSTALLATION TO BE DONE BY AN APPROVED QUALIFIED TRADESMAN.			2. WIRING, CONTRACT DRAWINGS CHANGES, CHANGES IN DESIGN, ADDED SUPERVISION, ETC., SHALL BE THE RESPONSIBILITY OF THE TEMPERATURE CONTROL SUBCONTRACTOR (TCSC).			C. REFER TO ARCHITECTURAL DRAWINGS FOR THE VARIOUS CEILING TYPES. REFER TO DRAWINGS OF REFLECTED CEILING PLANS FOR LOCATION OF CEILING DIFFUSERS AND GRILLES. MOUNTING FRAMES SHALL BE PROVIDED FOR ALL GRILLES AND REGISTERS MOUNTED IN DRYWALL.		
3. INSTALL IN THE DUCTWORK DEVICES FURNISHED BY THE TEMPERATURE CONTROLS SUB-CONTRACTOR. INSTALL SMOKE DETECTORS IN DUCTWORK FURNISHED BY THE DIVISION 16 CONTRACTOR.			3. ALL CONTROL DEVICES SHALL INCLUDE THE FOLLOWING: MANUFACTURER'S DATA SHEETS OF ALL PRODUCTS (ORIGINAL COPIES), COMPLETE DESCRIPTION OF OPERATION OF ALL CONTROL LOOPS, INCLUDING RECOMMENDED SETPOINTS AND RANGES OF ADJUSTMENT; FULLY LABELED ELEMENTARY DIAGRAM (ELECTRICAL LADDER DIAGRAM), AND LISTS OF ALL PROPOSED DEVICES AND EQUIPMENT.			D. SUPPLIER SHALL CHECK ALL AIR DISTRIBUTION AND RETURN AIR DEVICES FOR PROPER PERFORMANCE, NOISE AND ACCESSORIES. ANY DEVICE EXCEEDING NOISE LEVEL HEREIN SPECIFIED SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEERS.		
4. WATER AND OTHER PIPES SHALL NOT BE ALLOWED TO PASS THROUGH AIR RISERS OR DUCTS, UNLESS APPROVED BY THE ENGINEERS, AND WHEN THIS OCCURS, THE SIZE OF SAID DUCT OR RISER SHALL BE PROPORTIONATELY INCREASED. SANITARY WASTE AND VENT PIPING SHALL NOT PENETRATE ANY DUCTWORK.			B. MOTOR OPERATORS: MOTOR OPERATOR SHALL BE SPRING RETURN TYPE, WHICH RETURNS MOTOR ACTUATOR SHAFT TO ITS FULL NORMAL MECHANICAL TRAVEL UPON POWER FAILURE. DAMPER MOTOR DRIVE MECHANISM WILL INCLUDE HOLDING BRAKE TO KEEP THE RETURN SPRING FROM DRAWING THE ACTUATOR FROM DRIVING TOWARD ITS NORMAL POSITION UNLESS POWER IS INTERRUPTED. SUPPLY AND INSTALL ELECTRIC MOTOR OPERATORS FOR ALL DAMPERS. UNIT SHALL BE HONEYWELL MS8105A SERIES OR APPROVED EQUAL.			E. CONTRACTOR SHALL COORDINATE OPENINGS IN HARD CEILINGS, FURRED WALLS, MASONRY WALLS, AND FLOORS. MOUNT EACH DEVICE SECURELY TO AVOID RATTLING AND VIBRATION. DEVICES SHALL BE PARALLEL TO THE PLANE OF THE SURFACES THEY ARE MOUNTED.		
B. GALVANIZED STEEL DUCTWORK:			C. AUTOMATIC DAMPERS: ALL CONTROL DAMPERS SHALL BE STANDARD PRODUCTS OF DAMPER OR TEMPERATURE CONTROL MANUFACTURERS UNLESS NOTED OTHERWISE. LOCAL FABRICATION OF DAMPERS IS NOT ALLOWED. DAMPERS SHALL BE OPPOSED BLADE TYPE. FURNISH FOR INSTALLATION BY THE MECHANICAL CONTRACTOR ALL MOTOR OPERATED DAMPERS. DAMPERS SHALL BE RUSKIN MODEL CDS0. GREENHECK IN AN APPROVED EQUAL.			F. CEILING DIFFUSER TYPE A - TITUS MODEL TDC STEEL LOUVERED FACE DIFFUSER WITH 12 X 12 INCH MODULE AND 9 X 9 INCH UNIFORM BACKPAN. DIFFUSER SHALL INCLUDE ROUND NECK, REMOVABLE CORE OF FIXED DEFLECTION LOUVERS AND EQUALIZING GRID. DIFFUSER SHALL BE SUITABLE FOR SURFACE MOUNTING WITH AIR PATTERN AS SHOWN ON DRAWINGS.		
1. GALVANIZED STEEL DUCTWORK SHALL CONFORM TO ASTM A653 (G60). ALL LONGITUDINAL SEAMS SHALL BE GROOVED, DOUBLE OR PITTSBURGH TYPE.			D. THERMOSTATS:			G. RETURN/EXHAUST/GRILLES TYPE A - TITUS MODEL 350 RL STEEL GRILLE. GRILL SHALL INCLUDE ONE SET OF FIXED BLADES SET AT 35° DEFLECTION ON 3/4 INCH SPACING).		
C. DUCTWORK FITTINGS:			1. PROVIDE HVAC THERMOSTAT WITH THE FOLLOWING FEATURES: SEVEN DAY PROGRAMMING, TWO OCCUPIED/TWO UNOCCUPIED PERIODS PER DAY; AUTOMATIC HEAT/COOL CHANGEOVER WITH 2°F MINIMUM DEAD BAND, TWO STAGE HEATING, TWO STAGE COOLING, TOUCHSCREEN DISPLAY, AUXILIARY CONTACT, AND TEMPERATURE OVERRIDE. THERMOSTAT SHALL BE HONEYWELL VISIONPRO 8000 OR EQUAL.			H. RETURN/EXHAUST/GRILLES TYPE B - TITUS MODEL 50F ALUMINUM EGG CRATE GRILL. GRILLE SHALL INCLUDE 2 X 2 X 2 INCH ALUMINUM GRID.		
1. FOR RECTANGULAR DUCTWORK, VANES SHALL BE PROVIDED IN ELBOWS WITH 90 DEGREE THROATS AND THROAT RADII LESS THAN 1-1/2 TIMES DUCT WIDTH. VANES SHALL BE LOCATED IN ACCORDANCE WITH ASHRAE STANDARDS. DOUBLE-VANE AIRFOIL TYPE TURNING VANES SHALL BE PROVIDED FOR ALL SQUARE TURNS.			2. PROVIDE HEATER AND VENTILATION THERMOSTAT WITH THE FOLLOWING FEATURES: SINGLE STAGE CONTROL, ON/OFF/AUTO SWITCHING, AND ADJUSTABLE SETPOINT CONTROL.			I. RETURN/EXHAUST GRILLES TYPE C - TITUS MODEL 33R STEEL HEAVY DUTY BAR GRILLE. GRILLE SHALL INCLUDE ONE SET OF FIXED BLADES SET AT 38° DEFLECTION ON 2 INCH SPACING. BARS SHALL BE 14 GAUGE STEEL. BARS SHALL BE REINFORCED BY PERPENDICULAR STEEL BARS SPACED ON 6 INCH MAXIMUM CENTERS.		
D. HANGERS AND SUPPORTS:			E. TEMPERATURE CONTROL WIRING:			SECTION 15990 - TESTING, ADJUSTING AND BALANCING		
1. PROVIDE CONCRETE INSERTS OR STRUCTURAL STEEL FASTENERS APPROPRIATE FOR BUILDING MATERIALS. PROVIDE TRAPEZE AND RISER SUPPORTS AS REQUIRED. SUPPORT MATERIALS SHALL BE THE SAME AS DUCTWORK SUPPORTING.			1. ALL CONTROL WIRINGS AND CONDUIT REQUIRED TO COMPLETE THE TEMPERATURE CONTROL SYSTEM SHALL BE PROVIDED BY THE TEMPERATURE CONTROL SUB-CONTRACTOR. ALL WIRING SHALL CONFORM TO STANDARDS AND SPECIFICATIONS OUTLINED IN DIVISION 16. WIRE SIZE SHALL BE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS AND NATIONAL ELECTRIC CODE. MINIMUM CONDUIT SHALL BE 1/2 INCH DIAMETER. TCSC SHALL COORDINATE ALL CONTROL POWER REQUIREMENTS WITH ELECTRICAL CONTRACTOR PRIOR TO BID.			A. THE TEST AND BALANCE CONTRACTOR SHALL BE AN INDEPENDENT CONTRACTOR THAT REGULARLY PERFORMS AIR AND WATER SYSTEMS TESTING AND BALANCING. MINIMUM QUALIFICATIONS FOR ACCEPTANCE SHALL BE GENERAL MEMBERSHIP IN NEBB OR AABC, EXCEPT THAT AFFILIATION WITH MANUFACTURERS, INSTALLING, CONTRACTORS, OR ENGINEERING FIRMS MAY NOT PRECLUDE ACCEPTANCE.		
2. HANGER, STRAPS AND RODS SHALL WITH SMACNA'S "HVAC DUCT CONSTRUCTION STANDARDS METAL AND FLEXIBLE" STANDARDS.			2. ELECTRIC CONNECTIONS BETWEEN THE VARIOUS UNIT CONTROL CABINETS SHALL BE MADE BY THE TCSC. ALL WIRING MUST BE TAGGED ON BOTH ENDS WITH PANEL NUMBER AND TERMINAL NUMBER.			B. PERFORM TESTING AND BALANCING PROCEDURES ON EACH SYSTEM ACCORDING TO THE PROCEDURES CONTAINED IN ASHRAE APPLICATIONS HANDBOOK, AABC OR NEBB NATIONAL STANDARDS.		
3. DUCT ATTACHMENTS: SHEET METAL SCREWS, BLIND RIVETS OR SELF-TAPPING METAL SCREWS; COMPATIBLE WITH DUCT MATERIALS.			3. THE TCSC IS RESPONSIBLE FOR ALL REQUIRED PROCESS AND ELECTRICAL CONNECTIONS TO ALL EQUIPMENT, CONTROL DEVICES, AND FIELD INSTRUMENTS. TCSC SHALL FURNISH AND INSTALL ALL CONDUITS, RACEWAYS, ETC., REQUIRED. TCSC SHALL FURNISH AND INSTALL ALL CONTROL AND INTERLOCK WIRING. TCSC SHALL FURNISH AND INSTALL ALL REQUIRED AUXILIARY STARTER CONTACTS OR RELAYS, ETC., FOR A COMPLETE ELECTRICAL INTERLOCK AND CONTROL WIRING SYSTEM.			C. CUT INSULATION, DUCTS, PIPES, AND EQUIPMENT CABINETS FOR INSTALLATION OF TEST PROBES TO THE MINIMUM EXTENT NECESSARY TO ALLOW ADEQUATE PERFORMANCE OF PROCEDURES. AFTER TESTING AND BALANCING, CLOSE PROBE HOLES AND PATCH INSULATION WITH NEW MATERIALS IDENTICAL TO THOSE REMOVED. RESTORE VAPOR BARRIER AND FINISH ACCORDING TO THE INSULATION SPECIFICATIONS FOR THIS PROJECT.		
E. SEALANT MATERIAL:			F. INSTALLATION			D. MARK EQUIPMENT SETTINGS WITH PAINT OR OTHER SUITABLE, PERMANENT IDENTIFICATION MATERIAL, INCLUDING DAMPER-CONTROL POSITIONS, VALVE INDICATORS, FAN-SPEED-CONTROL LEVERS, AND SIMILAR CONTROLS AND DEVICES. TO SHOW FINAL SETTINGS.		
1. SEALANTS SHALL BE SOLVENT OR WATER BASED TYPE U.I., CLASSIFIED MEETING NFPA 90A CLASS 1 WITH ZERO FIRE AND SMOKE DEVELOPMENT RATING. SEALER SHALL BE UNITED SHEET METAL, UNITED DUCT SEALER, OR HARDCAST IRON GRIP NO. 801.			1. THE ENTIRE CONTROL SYSTEM, INCLUDING LOW VOLTAGE WIRING, WITH THE EXCEPTION OF DUCT MOUNTED AUTOMATIC DAMPERS AND SMOKE DETECTORS, SHALL BE INSTALLED BY THE TEMPERATURE CONTROL CONTRACTOR, WHO SHALL MAKE ALL TESTS AND ADJUSTMENTS; ALL CONTROLS SHALL BE FIELD-TESTED AND FIELD-CALIBRATED.			E. SET HVAC SYSTEM AIRFLOW AND WATER FLOW RATES WITHIN THE FOLLOWING TOLERANCES:		
TRANSVERSE SEAMS SHALL BE TAPED AND SEALED WITH TWO LAYERS OF UNITED SHEET METAL, UNI-CAST OR CAULKED WITH DUCT SEALER.			2. SET POINTS OF ALL CONTROLLING INSTRUMENTS ARE INDICATED AT A SPECIFIC POINT; HOWEVER, ALL SET POINTS SHALL BE ADJUSTABLE UP AND DOWN FROM THE POINT INDICATED.			1. SUPPLY, RETURN, AND EXHAUST FANS: PLUS 5 TO PLUS 10 PERCENT.		
F. FLEXIBLE CONNECTORS:			3. CONTRACTOR SHALL SUBMIT TENTATIVE LOCATIONS OF ALL CONTROL DEVICES AND COMPONENTS (INCLUDING TEMPERATURE SENSORS) TO THE ARCHITECT FOR WRITTEN APPROVAL PRIOR TO INSTALLATION. CONTRACTOR SHALL PAY PARTICULAR ATTENTION TO LOCATION OF CONTROL DEVICES AND COMPONENTS TO LOCATION OF CONTROL DEVICES AND COMPONENTS. EFFECTS OF DRAFTS, RADIANT HEAT, VIBRATION, ETC ARE TO BE CONSIDERED WHEN INSTALLING CONTROL DEVICES AND COMPONENTS.			2. AIR OUTLETS AND INLETS: 0 TO MINUS 10 PERCENT.		
1. INSTALL FLEXIBLE CONNECTORS AT ALL SUPPLY AND EXHAUST FANS AND OTHER AIR HANDLING UNITS WITH INLET AND OUTLET DUCT OR CASING CONNECTIONS. CONNECTORS SHALL NOT BE PAINTED. CONNECTORS SHALL NOT BE USED AS TRANSITION PIECES BETWEEN FAN AND DUCTWORK.			4. PRIOR TO ORDERING FACTORY ASSEMBLED EQUIPMENT WHICH CONTAINS INTEGRAL CONTROL DEVICES AND COMPONENTS, THE CONTRACTOR SHALL OBTAIN A WRITTEN STATEMENT FROM BOTH THE MANUFACTURER AND THE INSTALLING CONTRACTOR THAT THEY HAVE REVIEWED THE APPROPRIATE SUBMITTAL DATA AND ARE AWARE OF THE MAKE, MODEL, TYPE, SIZE, CHARACTERISTICS, ETC. OF THE FACTORY ASSEMBLED CONTROL DEVICES AND COMPONENTS WHICH THEY SHALL BE REQUIRED TO INTERFACE TO AND/OR CONTROL.			3. HEATING-WATER FLOW RATE: 0 TO MINUS 10 PERCENT.		
2. CONNECTORS SHALL BE NOT LESS THAN 4 INCHES LONG (IN CLEAR) AND PROPERLY ATTACHED TO DUCT AND FAN CONNECTION COLLAR BY 1 X 1/8 INCH DRAW BAND (FABRICATED OF THE SAME MATERIAL AS ADJACENT DUCTWORK) FIRMLY CLAMPED AROUND COLLARS IN SUCH A MANNER AS TO BE AIRTIGHT AND SECURED TO COLLARS WITH SHEET METAL SCREWS.			5. ALL CONTROL DEVICES (BOTH FIELD AND PANEL MOUNTED) SHALL BE LABELED TO INDICATE BOTH THEIR CONTROL SYSTEMS DESIGNATION, E.G., RTU-1 THERMOSTAT, UNLESS INDICATED OTHERWISE, ABBREVIATIONS AND ACRONYMS FOR ALL ID TAGS AND PANEL FACEPLATES SHALL BE APPROVED BY THE ENGINEER.			4. COOLING-WATER FLOW RATE: 0 TO MINUS 5 PERCENT.		
3. FLEXIBLE CONNECTORS SHALL BE U.I. LISTED, NEOPRENE COATED HEAVY GLASS FABRIC. FABRIC SHALL BE VENTGLAS, MANUFACTURED BY VENTFABRICS, INC.			6. ALL CONTROL DEVICES ARE TO BE MOUNTED IN ACCESSIBLE LOCATIONS. ALL DEVICES EXPOSED TO THE WEATHER SHALL BE HOUSED IN WEATHERPROOF ENCLOSURES.			F. WITHIN 90 DAYS OF COMPLETING TESTING, ADJUSTING, AND BALANCING, PERFORM ADDITIONAL TESTING AND BALANCING TO VERIFY THAT BALANCED CONDITIONS ARE BEING MAINTAINED THROUGHOUT AND TO CORRECT UNUSUAL CONDITIONS. IF INITIAL TESTING, ADJUSTING, AND BALANCING PROCEDURES WERE NOT PERFORMED DURING NEAR-PEAK SUMMER AND WINTER CONDITIONS, PERFORM ADDITIONAL INSPECTIONS, TESTING, AND ADJUSTING DURING NEAR-PEAK SUMMER AND WINTER CONDITIONS.		
FLEXIBLE DUCTS SHALL BE USED FOR STRAIGHT RUNS OF DUCT OR OFFSETS UP TO 45 DEGREES, BUT NOT EXCEEDING 48 INCHES IN LENGTH. THE USE OF FLEXIBLE DUCTS AS ELBOWS WITH MORE THAN A 45 DEGREE BEND WILL NOT BE PERMITTED.			7. AT THE COMPLETION OF THE JOB, TCSC SHALL CORRECT HIS DRAWINGS TO INCLUDE ANY CHANGES MADE DURING CONSTRUCTION. TCSC SHALL PROVIDE COLOR-CODED DRAWINGS INDICATED ALL TEMPERATURE ZONES AND EQUIPMENT (3 COPIES).			G. THE MECHANICAL CONTRACTOR'S RESPONSIBILITIES: FURNISH THE TEST AND BALANCE CONTRACTOR ONE COMPLETE SET OF ACCEPTED EQUIPMENT DATA AND ONE COMPLETE SET OF ACCEPTED MECHANICAL SHOP DRAWINGS. THE MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE FOR ADVISING THE TEST AND BALANCE CONTRACTOR OF ANY CHANGE(S) MADE TO THE SYSTEM(S) DURING THE CONSTRUCTION PROCESS. MECHANICAL CONTRACTOR SHALL PROVIDE DRAWINGS, SPECIFICATIONS, SHOP DRAWINGS, CONTROL DIAGRAMS, ETC; DETAILING THE CHANGE(S) TO THE TEST AND BALANCE CONTRACTOR. REPLACE AND/OR INSTALL PULLEYS, BELTS, DAMPERS AND TRIM PUMP IMPELLERS AS REQUIRED FOR THE CORRECT BALANCE AS DIRECTED BY THE TEST AND BALANCE CONTRACTOR. ALLOCATE TIME IN THE CONSTRUCTION SCHEDULE FOR TEST AND BALANCE PROCEDURE. ASSIST THE TEST AND BALANCE CONTRACTOR IN COORDINATING WORK WITH THE OTHER TRADES, AND PREPARE THE SYSTEM FOR TESTING AND BALANCING.		
FLEXIBLE DUCT SHALL BE UL LISTED AND LABELED AS CLASS 1, AIR DUCT CONNECTOR, IN ACCORDANCE WITH U.I. STANDARD 181 AND SHALL MEET THE REQUIREMENTS OF THE LATEST NFPA BULLETIN, NO. 90A AND NO. 90B FOR FLAME SPREAD AND SMOKE DEVELOPMENT RATING.			G. OPERATION TEST AND OWNER'S INSTRUCTION:					
3. FLEXIBLE DUCT SHALL BE RATED FOR A MAXIMUM PRESSURE OF 6 INCH POSITIVE AND 3/4 INCH NEGATIVE AND 4000 FPM MAXIMUM VELOCITY. AIR DUCT SHALL CONSIST OF: OPE LINER, COATED SPRING STEEL WIRE HELIX, FIBERGLASS INSULATING BLANKET, FIBERGLASS SCORIM AND REINFORCED ALUMINUM VAPOR BARRIER. THERMAL CONDUCTANCE SHALL BE .23 OR LESS.			1. AT COMPLETION, TCSC SHALL OPERATE THE SYSTEM FOR A PERIOD OF AT LEAST THREE DAYS OF EIGHT HOURS EACH ON THE NEW SYSTEMS TO DEMONSTRATE FULFILLMENT OF THE REQUIREMENTS OF THE CONTRACT. DURING THIS TIME, ALL ADJUSTMENTS SHALL BE MADE TO THE EQUIPMENT SO THAT IT IS IN FIRST-CLASS OPERATING CONDITION. THE ENTIRE SYSTEM IS TO BE LEFT IN OPERATING CONDITION ACCEPTABLE TO THE ENGINEER.					
DUCT SHALL BE FLEXMASTER TYPE 8M OR PRIOR APPROVED EQUAL.			2. UPON COMPLETION OF THE WORK AND ACCEPTANCE BY THE OWNER, TCSC SHALL PROVIDE ONE SCHEDULED FOUR-HOUR PERIOD OF FORMAL INSTRUCTION TO THE OWNER'S OPERATING PERSONNEL WHO HAVE RESPONSIBILITY FOR THE MECHANICAL SYSTEM.					
A. VOLUME DAMPERS:			H. SEQUENCE OF OPERATIONS:					
1. SINGLE BLADE DAMPERS SHALL BE CONSTRUCTED OF .22 GAUGE GALVANIZED STEEL (BLADE AND FRAME). SINGLE BLADE DAMPERS SHALL BE LIMITED TO A 12 INCH HIGH BLADE. BLADE EDGES SHALL BE CRIMPED OR REINFORCED. DAMPER LEVERS SHALL INDICATE POSITIVELY THE OPEN AND CLOSED POSITION. END BEARINGS SHALL BE MOLDED SYNTHETIC. DAMPERS SHALL BE RUSKIN MD25 OR APPROVED EQUAL (RUSKIN MDRS25 FOR ROUND DUCTS).			1. HVAC UNITS:					
MULTIBLADE DAMPERS SHALL BE CONSTRUCTED OF SHEET METAL THE SAME MATERIAL AS THE ADJACENT DUCTWORK. DAMPER FRAME SHALL BE NOT LESS THAN 16 GA. DAMPER BLADES NOT WIDER THAN 6 INCHES CRIMPED OR REINFORCED. DAMPER LEVERS SHALL INDICATE POSITIVELY THE OPEN AND CLOSED POSITION. END BEARINGS SHALL BE MOLDED SYNTHETIC. DAMPER SHALL BE RUSKIN MD35 OR APPROVED EQUAL.			1. NORMAL OPERATION:					
B. FIRE DAMPERS:			1. UNITS SHALL BE CONTROLLED BY SPACE THERMOSTAT. FAN SHALL OPERATE CONTINUOUSLY DURING OCCUPIED MODE AND INTERMITTENTLY DURING UNOCCUPIED MODE.					
1. FIRE DAMPERS SHALL BE UNDERWRITERS APPROVED AND LABELED (UL555). DAMPERS SHALL BE FABRICATED OF GALVANIZED STEEL AND SHALL BE OF SUCH A DESIGN AND LENGTH AS TO FUNCTION AS A WALL MOUNTING SLEEVE, WHICH SHALL BE A PART OF THE FIRE DAMPER. SLEEVES SHALL BE OF WELDED OR BOLTED CONSTRUCTION. CRIMPING OR TABS WILL NOT BE ACCEPTABLE SUBSTITUTES FOR WELDING OR BOLTING.			2. HEATING AND COOLING SHALL BE ENABLED BY THERMOSTAT.					
2. FIRE DAMPERS SHALL BE RUSKIN DDB23 SERIES FOR 1 1/2 HOUR RATING. FIRE DAMPERS SHALL BE RUSKIN DDB23 SERIES FOR 3 HOUR RATING. INSTALL STYLE A FIRE DAMPERS BEHIND DUCTED GRILLES AND REGISTERS IN RATED WALLS. INSTALL STYLE B OR C FIRE DAMPERS IN DUCTED OPENINGS IN RATED WALLS. AIR BALANCE AND PREFCO ARE APPROVED EQUAL.			3. COOLING SETPOINT SHALL BE 73°F (ADJUSTABLE).					
C. DAMPER HARDWARE:			4. HEATING SETPOINT SHALL BE 68°F (ADJUSTABLE).					
1. ALL HARDWARE SHALL BE SMACNA ACCEPTED. INSULATED DUCTWORK (CONCEALED) - VENTLOK 638 ELEVATED DIAL REGULATOR. INSULATED DUCTWORK (EXPOSED) - VENTLOK 644 - SELF LOCKING REGULATOR. UNINSULATED DUCTWORK - VENTLOK 555 OR 560 QUADRANTS.			5. OUTSIDE AIR DAMPER SHALL OPEN DURING OCCUPIED MODE AND CLOSE DURING UNOCCUPIED MODE. OUTSIDE AIR DAMPER SHALL BE NORMALLY CLOSED AND RETURN TO NORMAL POSITION UPON LOSS OF POWER.					
D. DUCT ACCESS DOORS:			2. EXHAUST FANS:					
1. ACCESS DOORS SHALL BE HINGED, CONSTRUCTED OF THE SAME MATERIAL AS THE DUCTWORK. DOOR EDGES SHALL BE SEALED WITH 3/4 INCH WIDE X 1/8 INCH THICK NEOPRENE SPONGE GASKETING. DOOR HARDWARE SHALL BE VENTLOK #100 LATCHES. ACCESS DOORS ON INSULATED DUCTWORK SHALL BE DOUBLE WALL CONSTRUCTION WITH 1 INCH OF RIGID 3 PCF FIBERGLASS INSULATION.			1. INTERLOCK EXHAUST FANS AS NOTED ON SCHEDULE.					
2. PROVIDE DUCT ACCESS DOORS AT ALL DUCT MOUNTED DEVICES REQUIRING ADJUSTMENT OR RESETTING. ACCESS DOORS SHALL BE APPROXIMATELY 18 INCHES HIGH BY 24 INCHES WIDE. IN SMALLER DUCTWORK, THE HEIGHT SHALL BE REDUCED TO BE 2 INCHES LESS THAN THAT OF THE DUCTWORK.			3. UNIT HEATERS:					
			1. HEATERS SHALL ENERGIZE AS REQUIRED TO MAINTAIN SPACE TEMPERATURE.					
			2. HEATING SETPOINT SHALL BE 60°F (ADJUSTABLE).					



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262




11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Mechanical Specifications	
Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB
M0.03	
Scale	12" = 1'-0"



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



www.ahoarch.com



11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Mechanical
Comcheck

Project number 24028
Date 11/8/2024
Drawn by CA
Checked by JB

M0.04

Scale 6" = 1'-0"

11/7/2024 4:32:42 PM

COMcheck Software Version COMcheckWeb
Mechanical Compliance Certificate

Project Information
Energy Code: 2015 IECC
Project Title: EDC - NORTHPORT, AL
Location: Northport, Alabama
Climate Zone: 3B
Project Type: New Construction
Designer/Engineer: Jeff Boyer, PE
Project Number: 24028
Report Date: January 2024

Additional Efficiency Packets(s)
Credits: 1.0 Required: 0.0 Provided

Mechanical Systems List

Quantity: System Type & Description

- 1 AHU-5 (Single Zone)
Capacity: 1.0 tons (Cooling/Heating, Electric, Capacity = 34.4 MBtu/h)
No natural gas efficiency requirement
Capacity: 1.0 tons (Cooling/Heating, Electric, Capacity = 34.4 MBtu/h)
Required Efficiency: > 0.50 EER (EER, Required Part Load Efficiency > 0.80)
Part Load Efficiency: > 0.80
Part Load Efficiency: > 0.80
Part Load Efficiency: > 0.80
- 2 AHU-1, 2 (Single Zone w/ Temperature Control)
Capacity: 1.0 tons (Cooling/Heating, Electric, Capacity = 34.4 MBtu/h)
No natural gas efficiency requirement
- 3 Water Heaters
Capacity: 1.0 tons (Cooling/Heating, Electric, Capacity = 34.4 MBtu/h)
No natural gas efficiency requirement

Mechanical Compliance Statement
Compliance Statement: The proposed mechanical design represented in this document is consistent with the building code, applicable standards, and other applicable requirements. The proposed mechanical system has been designed to meet the 2015 IECC requirements in COMcheck Version COMcheckWeb and to comply with any applicable mechanical requirements listed in the applicable Code(s).

Jeff Boyer, PE
Signature: [Signature]
Date: 11/8/2024

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: EDC - NORTHPORT, AL
Data Reference: Report Date: 11/07/24
Page: 5 of 11

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

COMcheck Software Version COMcheckWeb
Inspection Checklist

Requirements: 11.0.0, were addressed directly in the COMcheck software.
Test in the "Comments/Assumptions" column is provided by the user in the COMcheck Requirements column. For each requirement, the user certifies that a code requirement was met and that the code is documented, or that an exception is being claimed. Where compliance is itemized in a separate table, a reference to that table is provided.

Section: 6.4.0.0

Section: 6.4.0.1

Section: 6.4.0.2

Section: 6.4.0.3

Section: 6.4.0.4

Section: 6.4.0.5

Section: 6.4.0.6

Section: 6.4.0.7

Section: 6.4.0.8

Section: 6.4.0.9

Section: 6.4.0.10

Section: 6.4.0.11

Section: 6.4.0.12

Section: 6.4.0.13

Section: 6.4.0.14

Section: 6.4.0.15

Section: 6.4.0.16

Section: 6.4.0.17

Section: 6.4.0.18

Section: 6.4.0.19

Section: 6.4.0.20

Section: 6.4.0.21

Section: 6.4.0.22

Section: 6.4.0.23

Section: 6.4.0.24

Section: 6.4.0.25

Section: 6.4.0.26

Section: 6.4.0.27

Section: 6.4.0.28

Section: 6.4.0.29

Section: 6.4.0.30

Section: 6.4.0.31

Section: 6.4.0.32

Section: 6.4.0.33

Section: 6.4.0.34

Section: 6.4.0.35

Section: 6.4.0.36

Section: 6.4.0.37

Section: 6.4.0.38

Section: 6.4.0.39

Section: 6.4.0.40

Section: 6.4.0.41

Section: 6.4.0.42

Section: 6.4.0.43

Section: 6.4.0.44

Section: 6.4.0.45

Section: 6.4.0.46

Section: 6.4.0.47

Section: 6.4.0.48

Section: 6.4.0.49

Section: 6.4.0.50

Section: 6.4.0.51

Section: 6.4.0.52

Section: 6.4.0.53

Section: 6.4.0.54

Section: 6.4.0.55

Section: 6.4.0.56

Section: 6.4.0.57

Section: 6.4.0.58

Section: 6.4.0.59

Section: 6.4.0.60

Section: 6.4.0.61

Section: 6.4.0.62

Section: 6.4.0.63

Section: 6.4.0.64

Section: 6.4.0.65

Section: 6.4.0.66

Section: 6.4.0.67

Section: 6.4.0.68

Section: 6.4.0.69

Section: 6.4.0.70

Section: 6.4.0.71

Section: 6.4.0.72

Section: 6.4.0.73

Section: 6.4.0.74

Section: 6.4.0.75

Section: 6.4.0.76

Section: 6.4.0.77

Section: 6.4.0.78

Section: 6.4.0.79

Section: 6.4.0.80

Section: 6.4.0.81

Section: 6.4.0.82

Section: 6.4.0.83

Section: 6.4.0.84

Section: 6.4.0.85

Section: 6.4.0.86

Section: 6.4.0.87

Section: 6.4.0.88

Section: 6.4.0.89

Section: 6.4.0.90

Section: 6.4.0.91

Section: 6.4.0.92

Section: 6.4.0.93

Section: 6.4.0.94

Section: 6.4.0.95

Section: 6.4.0.96

Section: 6.4.0.97

Section: 6.4.0.98

Section: 6.4.0.99

Section: 6.4.0.100

Section: 6.4.0.101

Section: 6.4.0.102

Section: 6.4.0.103

Section: 6.4.0.104

Section: 6.4.0.105

Section: 6.4.0.106

Section: 6.4.0.107

Section: 6.4.0.108

Section: 6.4.0.109

Section: 6.4.0.110

Section: 6.4.0.111

Section: 6.4.0.112

Section: 6.4.0.113

Section: 6.4.0.114

Section: 6.4.0.115

Section: 6.4.0.116


Section: 6.4.0.117

Section: 6.4.0.118

Section: 6.4.0.119

Section: 6.4.0.120

Section: 6.4.0.121



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama


FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Mechanical Floor Plan


Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB
M1.01	
Scale	As indicated




MAIN FLOOR PLAN
MECHANICAL
1/4" = 1'-0"

GENERAL NOTES:


- VERIFY EXISTING CONDITIONS IN FIELD PRIOR TO BEGINNING WORK.
- SPACE ABOVE CEILING IS LIMITED. CAREFUL COORDINATION WITH LIGHTING, ELECTRICAL, PLUMBING, STRUCTURAL, AND ARCHITECTURAL WORK IS CRITICAL TO DUCTWORK INSTALLATION.
- PROVIDE NECESSARY OFFSETS IN PIPING, ELECTRICAL CONDUIT, AND DUCTWORK AS REQUIRED TO ACCOMMODATE NEW WORK. DRAWINGS ARE DIAGRAMMATIC AND DO NOT SHOW ALL DETAILS NOR CHANGES IN DUCTWORK ELEVATIONS NECESSARY FOR COMPLETE INSTALLATION.
- COORDINATE CEILING AIR DEVICE LOCATIONS WITH LIGHTING PLAN AND ARCHITECT'S REFLECTED CEILING PLAN.
- DUCTWORK SHALL BE RUN TIGHT TO STRUCTURE. AVOID CROSSING OVER LIGHTS AND OTHER DUCTS DUE TO TIGHT CLEARANCES.
- LOUVERS SHALL BE RUSKIN ELF6375D OR APPROVED EQUAL. PROVIDE UNIT WITH BIRDSCREEN AND MILL ALUMINUM FINISH. COORDINATE EXACT HEIGHT AND COLOR OF LOUVER WITH ARCHITECT PRIOR TO ORDERING.
- MOUNT TEMPERATURE CONTROLS 48" ABOVE FINISHED FLOOR. COORDINATE EXACT LOCATION WITH ARCHITECT.
- SPILL CONDENSATE FROM AHUS INTO NEAREST FLOOR DRAIN.
- PROVIDE ENGRAVED PLASTIC LABEL AT TERMINATION OF EACH AUXILIARY CONDENSATE DRAIN LINE READING AS FOLLOWS:
"AHU-### AUXILIARY DRAIN LINE."
"NOTIFY MAINTENANCE PERSONNEL WHEN WATER IS FLOWING"
- CONNECT CONDENSATE DRAIN PIPING TO AIR HANDLING UNITS IN ACCORDANCE WITH DETAILS.
- OUTSIDE AIR VENTILATION INTAKES FOR OIL CHANGE AND SERVICE AREAS WILL BE PROVIDED BY OPEN ROLL-UP DOORS. DOORS SHALL BE OPEN WHILE VENTILATION SYSTEM IS ENABLED.




PIT FLOOR PLAN
MECHANICAL
1/4" = 1'-0"



3 Section Through Pit Exhaust1
M1.02 1/4" = 1'-0"




4 Section 1
M1.02 1/4" = 1'-0"



6 AHU Section1
M1.02 1/4" = 1'-0"

DRAWING NOTES:
1 INSTALL DUCTWORK AND EQUIPMENT IN EQUIPMENT PLATFORM SPACE TO ALLOW FOR MAXIMUM USE OF FLOOR AREA. EQUIPMENT SHALL BE HUNG FROM STRUCTURE ABOVE AND DUCTS ROUTED DOWN VERTICALLY THROUGH FLOOR.



EQUIPMENT PLATFORM
MECHANICAL
1/4" = 1'-0"

- GENERAL NOTES:
- 1 VERIFY EXISTING CONDITIONS IN FIELD PRIOR TO BEGINNING WORK.
 - 2 SPACE ABOVE CEILING IS LIMITED. CAREFUL COORDINATION WITH LIGHTING, ELECTRICAL, PLUMBING, STRUCTURAL, AND ARCHITECTURAL WORK IS CRITICAL TO DUCTWORK INSTALLATION.
 - 3 PROVIDE NECESSARY OFFSETS IN PIPING, ELECTRICAL CONDUIT, AND DUCTWORK AS REQUIRED TO ACCOMMODATE NEW WORK. DRAWINGS ARE DIAGRAMMATIC AND DO NOT SHOW ALL DETAILS NOR CHANGES IN DUCTWORK ELEVATIONS NECESSARY FOR COMPLETE INSTALLATION.
 - 4 COORDINATE CEILING AIR DEVICE LOCATIONS WITH LIGHTING PLAN AND ARCHITECT'S REFLECTED CEILING PLAN.
 - 5 DUCTWORK SHALL BE RUN TIGHT TO STRUCTURE. AVOID CROSSING OVER LIGHTS AND OTHER DUCTS DUE TO TIGHT CLEARANCES.
 - 6 LOUVERS SHALL BE RUSKIN ELF6375D OR APPROVED EQUAL. PROVIDE UNIT WITH BIRDSCREEN AND MILL ALUMINUM FINISH. COORDINATE EXACT HEIGHT AND COLOR OF LOUVER WITH ARCHITECT PRIOR TO ORDERING.
 - 7 MOUNT TEMPERATURE CONTROLS 48" ABOVE FINISHED FLOOR. COORDINATE EXACT LOCATION WITH ARCHITECT.
 - 8 SPILL CONDENSATE FROM AHUS INTO NEAREST FLOOR DRAIN.
 - 9 PROVIDE ENGRAVED PLASTIC LABEL AT TERMINATION OF EACH AUXILIARY CONDENSATE DRAIN LINE READING AS FOLLOWS:
"AHU-### AUXILIARY DRAIN LINE."
"NOTIFY MAINTENANCE PERSONNEL WHEN WATER IS FLOWING"
 - 10 CONNECT CONDENSATE DRAIN PIPING TO AHU IN ACCORDANCE WITH DETAILS.

Pinnacle
ENGINEERING, INC.
Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262

AHO ARCHITECTS, LLC
www.ahoarch.com

ALABAMA
REGISTERED
No. 30374
PROFESSIONAL
11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL		
No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Partial Mechanical
Floor Plans - Pit
and Platform

Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB

M1.02

Scale	As indicated
-------	--------------



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Mechanical Details


Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB

M2.01


Scale 12" = 1'-0"




7 REFRIGERANT PIPING SUPPORT DETAIL
TYPICAL FOR PIPING SUSPENDED FROM STRUCTURE
NO SCALE




4 TYPICAL DIFFUSER RUN-OUT DETAIL
NO SCALE




1 SIDEWALL EXHAUST FAN DETAIL
NO SCALE




8 REFRIGERANT PIPING DETAIL
NO SCALE




5 TYPICAL RETURN AND EXHAUST RUN-OUT DETAIL
NO SCALE



2 CONDENSATE DRAIN TRAP DETAIL
NO SCALE




9 LOUVER DETAIL
NO SCALE




6 REFRIGERANT LINE - WALL PENETRATION DETAIL
NO SCALE

- NOTES:
1. SEAL OPENING WITH POLYURETHANE FOAM, EQUAL TO VERSI-FOAM TRIM OFF EXCESS FOAM.
 2. PROVIDE INTERMEDIATE SUPPORTS AS REQUIRED.
 3. OMIT ELASTOMERIC INSULATION ON LIQUID LINE.



3 FLEXIBLE DUCT SUPPORT DETAIL
NO SCALE

11/7/2024 4:32:44 PM



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



www.ahoarch.com



11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date




© 2024 Aho Architects, LLC.
All Rights Reserved.

















Mechanical Details








Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB

M2.02

Scale 12" = 1'-0"



PLUMBING LEGEND, SYMBOLS AND ABBREVIATIONS					
-----	DOMESTIC COLD WATER		BALL VALVE	ABV	ABOVE
----- (D) -----	EXISTING DOMESTIC COLD WATER TO BE REMOVED		VALVE IN VERTICAL	AFF	ABOVE FINISHED FLOOR
-----	EXISTING DOMESTIC COLD WATER TO REMAIN		CAP ON END OF PIPE	INV	INVERT
-----	DOMESTIC HOT WATER		CLEANOUT - FLOOR TYPE	BFF	BELOW FINISHED FLOOR
----- (D) -----	EXISTING DOMESTIC HOT WATER TO BE REMOVED		CLEANOUT - WALL TYPE	CW	COLD WATER
-----	EXISTING DOMESTIC HOT WATER TO REMAIN		P-TRAP	DN	DOWN
-----	DOMESTIC HOT WATER RETURN		PIPE TURNING DOWN	EX	EXISTING
----- (D) -----	EXISTING DOMESTIC HOT WATER RETURN TO BE REMOVED		PIPE TURNING UP	HW	HOT WATER
-----	EXISTING DOMESTIC HOT WATER RETURN TO REMAIN		TEE DOWN	WS	WASTE STACK
-----	SANITARY VENT		TEE UP	VS	VENT STACK
--- (D) --- (D) ---	EXISTING SANITARY VENT TO BE REMOVED		TIE NEW INTO EXISTING	AC	ABOVE CEILING
-----	EXISTING SANITARY VENT TO REMAIN	P-1	PLUMBING FIXTURE NUMBER	WHA	WATER HAMMER ARRESTOR
----- SD (D) -----	EXISTING STORM DRAINAGE TO BE REMOVED		RISER NUMBER	BFG	BELOW FINISHED GRADE
----- SD -----	EXISTING STORM DRAINAGE TO REMAIN		WATER HAMMER ARRESTOR	TMV	THERMOSTATIC MIXING VALVE
-----	SANITARY WASTE		PLUG TYPE CLEANOUT	TP	TRAP PRIMER
----- (D) -----	EXISTING SANITARY WASTE TO BE REMOVED		BALANCING VALVE	DS	DOWNSPOUT
-----	EXISTING SANITARY WASTE TO REMAIN		CHECK VALVE	UG	UNDER GROUND

	GATE VALVE
	REDUCED PRESSURE ZONE BFP
	THERMOSTATIC MIXING VALVE
	FLOOR SINK
	FLOOR DRAIN
	ROOF DRAIN/OVERFLOW DRAIN
	FOOD SERVICE EQUIPMENT

PLUMBING FIXTURE CONNECTION SCHEDULE						
Equipment No.	Description	Hot Water	Cold Water	Waste	Vent	Remarks
WC-1	WATER CLOSET - ADA		1/2"	4"	2"	PRESSURE ASSIST - TANK TYPE
EW-1	EMERGENCY EYEWASH	1/2"	1/2"	2"	2"	PROVIDE WITH MIXING VALVE
EW-C-1	ELECTRIC WATER COOLER		1/2"	2"	1 1/2"	WALL MOUNT, ADA BI-LEVEL WITH BOTTLE FILLER
LAV-1	WALL MOUNTED LAV - ADA	1/2"	1/2"	2"	2"	PROVIDE WITH TRAP WRAP AND MIXING VALVE EQUAL TO ZW1070
SK-1	SERVICE SINK	1/2"	1/2"	2"	2"	DRAIN TO OIL INTERCEPTOR
WH-1	WALL HYDRANT - FREEZE PROOF		1/2"			

ELECTRIC WATER HEATER SCHEDULE													
EQUIPMENT NO.	MANUFACTURER	MODEL	SERVICE	ENTERING WATER TEMP (F)	LEAVING WATER TEMP (F)	RECOVERY RATE (GPH)	STORAGE CAPACITY	TANK DIMENSIONS		ELECTRICAL		VOLTS/PH./HZ.	COMMENTS
								DIAMETER	HEIGHT	WATER HEATER WATTAGE	NUMBER OF ELEMENTS		
EW1H	A. O. Smith	ECS-30X	BATHROOMS/EYEWASH	60 °F	120 °F	21	30.0 gal	1' - 8"	3' - 3"	4500 W	1	240/1/60	

PUMP SCHEDULE												
MARK	MANUFACTURER	MODEL	SERVICE	PUMP TYPE	FLOW RATE	PUMP HEAD (FT)	RATED SPEED (RPM)	DISCONNECT	MOTOR STARTER	HP	VOLTAGE	COMMENTS
REC-1	TACO	0010-SFS	HW RETURN	In-Line	2 GPM	10	2800	BY ELEC	INTEGRAL	.01	120 V	1, 2

NOTES:
1. PROVIDE WITH AQUASTAT FOR OPERATION WITH ASHRAE 90.1.
2. PUMP SHALL BE STAINLESS STEEL BODY FOR DOMESTIC USE.

INTERCEPTOR SCHEDULE									
EQUIPMENT NO.	MANUFACTURER	MODEL	FLOW RATE - INT	LIQUID HOLD CAPACITY	INLET/OUTLET	VENT	LENGTH	WIDTH	DEPTH
OS-1	STRIEM	OS-25	20 GPM	21.0 gal	3"	2"	2' - 3"	1' - 11"	1' - 3"

NOTES:
1. PROVIDE WITH HEAVY DUTY LID AND EXTENSIONS TO MATCH GRADE.

WATER METER SIZING	
TOTAL LOAD (FIXTURE UNITS)	GPM
19	19




Pinnacle
ENGINEERING, INC.

Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



AHO ARCHITECTS, LLC

www.ahoarch.com



11/8/24

Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC. All Rights Reserved.

Plumbg Legend, Abbreviations, and Schedules

Project number24028


Date11/8/2024

Drawn byCA

Checked byJB

P0.01

Scale12" = 1'-0"



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Plumbing
Specifications

Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB

P0.02

Scale 12" = 1'-0"

SECTION 15011 - PLUMBING GENERAL

- A. PROVIDE EQUIPMENT, LABOR, MATERIAL, ETC., REQUIRED TO MAKE A COMPLETE WORKING INSTALLATION.
- B. INSTALL THE WORK IN ACCORDANCE WITH DRAWINGS, SPECIFICATIONS AND THE STANDARDS AND CODES (LATEST EDITION) THAT APPLY TO THIS WORK. IN THE EVENT OF A CONFLICT, INSTALL WORK IN ACCORDANCE WITH THE MOST STRINGENT CODE REQUIREMENTS DETERMINED BY THE ENGINEER.
- C. OBTAIN AND PAY FOR ALL PERMITS AND INSPECTIONS INCLUDING: BUILDING PERMITS, HEALTH DEPARTMENT PERMITS AND SEWER TAP PERMITS. DELIVER TO ENGINEER CERTIFICATES OF INSPECTION AND APPROVAL ISSUED BY AUTHORITY.
- D. ALL EQUIPMENT AND METHOD SHALL BE INSTALLED AND CONNECTED IN ACCORDANCE WITH THE BEST ENGINEERING PRACTICES AND IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.
- E. DISCONNECT, REMOVE AND RE-INSTALL PLUMBING SERVICES LOCATED ON OR CROSSING THROUGH CONTRACTOR LIMITS, ABOVE OR BELOW GRADE, OBSTRUCTING CONSTRUCTION OF PROJECT OR CONFLICTING WITH COMPLETED PROJECT OR ANY APPLICABLE CODES.
- F. PROVIDE CUTTING OF PAVEMENT, SIDEWALKS, DRIVEWAYS, ETC., EXCAVATING, TRENCHING, SHORING AND DE-WATERING. PROVIDE BACKFILL MATERIAL AND PERFORM BACKFILLING.
- G. RESTORE SITE TO ORIGINAL CONDITION OR NEW FINAL GRADES. PROVIDE PAVING, CONCRETE, SEED, OR SOD.
- H. DRAWINGS AND SPECIFICATIONS ARE COMPLEMENTARY. WORK CALLED FOR BY ONE IS BINDING AS IF CALLED FOR BY BOTH.
- I. DRAWINGS ARE DRAWN TO A SMALL SCALE AND ARE DIAGRAMMATIC ONLY. THE DRAWINGS INDICATE SIZE AND GENERAL ARRANGEMENT OF EQUIPMENT. DO NOT SCALE DRAWINGS FOR EXACT LOCATIONS. FIELD MEASUREMENTS TAKE PRECEDENCE.
- J. PROVIDE NECESSARY OFFSETS, ELBOWS AND FITTINGS AS REQUIRED TO AVOID CONFLICT WITH EQUIPMENT OF OTHER DIVISIONS AND TO OBTAIN PROPER HEADROOM AND CLEAR PASSAGEWAYS. THIS SHALL BE DONE AT NO ADDITIONAL COST TO THE OWNER.
- K. WORK UNDER THIS DIVISION SHALL BE FIRST CLASS WITH EMPHASIS ON NEATNESS AND WORKMANSHIP. INSTALL WORK USING COMPETENT MECHANICS, UNDER SUPERVISION OF FOREMAN, ALL DULY CERTIFIED BY LOCAL AUTHORITIES.
- L. INSTALLATION SUBJECT TO ENGINEER'S OBSERVATION, FINAL APPROVAL, AND ACCEPTANCE. ENGINEER MAY REJECT UNSUITABLE WORK.
- M. ALL MATERIALS SHALL BE NEW, ALL MATERIALS AND EQUIPMENT FOR WHICH A UL STANDARD, AN AGA APPROVAL, AN AWWA STANDARD, FM LISTING OR ASME REQUIREMENTS IS ESTABLISHED, SHALL BE SO APPROVED AND LABELED OR STAMPED.
- N. THE DRAWINGS ARE BASED ON THE USE OF PRODUCTS SPECIFIED AND LISTED FIRST. IF ANY REVISION IN PIPING, CONDUIT WORK, FOUNDATIONS, ANCHOR BOLTS, CONNECTIONS, ETC., IS REQUIRED BY OTHER NAMED PRODUCTS OR APPROVED SUBSTITUTIONS, IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO MAKE SUCH REVISIONS AT NO ADDITIONAL EXPENSE TO THE OWNER.
- O. SUBMIT SIX (6) ORIGINAL COPIES OF COMPLETE SHOP DRAWINGS FOR ALL MATERIALS AND EQUIPMENT FURNISHED UNDER DIVISION 15 OF SPECIFICATIONS TO ENGINEER FOR REVIEW. SHOP DRAWINGS SHALL BEAR THE STAMP OF APPROVAL OF THE CONTRACTOR AS EVIDENCE THAT THE DRAWINGS HAVE BEEN CHECKED BY HIM. DRAWINGS SUBMITTED WITHOUT THIS STAMP OF APPROVAL WILL NOT BE CONSIDERED AND WILL BE RETURNED FOR PROPER RESUBMISSION.
- P. REVIEW OF SHOP DRAWINGS DOES NOT RELIEVE CONTRACTOR OF RESPONSIBILITY FOR ERRORS AND OMISSIONS IN SHOP DRAWINGS. CONTRACTOR IS RESPONSIBLE FOR DIMENSIONS AND SIZES OF EQUIPMENT. INFORM ENGINEER IN WRITING OF EQUIPMENT DIFFERING FROM THAT SHOWN.
- Q. PROVIDE MAINTENANCE AND OPERATING MANUALS BOUND IN 8-1/2" X 11" HARDBACK, THREE-POST BINDERS. MANUALS SHALL CONTAIN WRITTEN INSTRUCTIONS FOR EACH SYSTEM, SHOP DRAWINGS, SCHEMATIC DRAWINGS, EQUIPMENT CATALOG CUTS, MANUFACTURER'S INSTRUCTIONS, MANUFACTURERS WARRANTIES, AND VALVE TAG LIST.
- R. PROVIDE AS-BUILT PRINTS AT THE COMPLETION OF JOB. KEEP ONE SET OF PRINTS ON JOB AND RECORD DAY TO DAY CHANGES TO CONTRACT DRAWINGS WITH RED PENCIL. INDICATE ACTUAL LOCATION OF PIPING, VALVES, AND EQUIPMENT. TURN OVER PRINTS TO ENGINEER AT FINAL OBSERVATION.
- S. FURNISH ENGINEER WRITTEN WARRANTY, STATING THAT IF WORKMANSHIP AND/OR MATERIALS EXECUTED UNDER THIS DIVISION IS PROVEN DEFECTIVE WITHIN ONE (1) YEAR AFTER FINAL ACCEPTANCE, SUCH DEFECTS AND OTHER WORK DAMAGED WILL BE REPAIRED AND/OR REPLACED.

SECTION 15051 - BASIC MATERIALS AND METHODS

- A. ACCESS PANELS:
- ACCESS PANELS SHALL HAVE WELDED STEEL FRAME, ONE PIECE DOORS, AND SELF LATCHING DOOR LOCKS. LOCKS SHALL BE SCREW DRIVERS OPERATED WITH CASE HARDENED STEEL CAM. PANELS SHALL BE MILCOR, GESCO, KARP OR EQUAL.
 - PROVIDE ACCESS PANELS IN WALLS AND CEILINGS AS NEEDED TO ALLOW ACCESS TO VALVES, EQUIPMENT, SHOCK ABSORBERS, TRAP PRIMERS, ETC. AND WHERE NOTED.
- B. FIRESTOPPING AND SOUNDSTOPPING:
- PENETRATIONS THROUGH FLOORS AND FIRE RESISTANT WALLS SHALL BE SEALED TO THE RATED FIRE RESISTANCE EQUAL TO THE WALL. INSTALLATION SHALL BE DONE BY A QUALIFIED INSTALLER, APPROVED BY THE MANUFACTURER.
 - PROVIDE SOUND PROOFING THROUGH NON-RATED WALLS.
- C. PIPING SEALS:
- PROVIDE MODULAR, RESILIENT SEALS AROUND PIPES PENETRATING ALL EXTERIOR WALLS, AND FLOORS BELOW GRADE. PIPING SEALS SHALL BE THUNDERLINE CORP. "LINK SEAL" LS SERIES.
- D. CUTTING AND PATCHING:
- CONTRACTOR SHALL BE RESPONSIBLE FOR CUTTING AND PATCHING. CUT WALLS, FLOORS, CEILINGS, PARTITIONS, ETC., REQUIRED FOR THE INSTALLATION OF THIS WORK IN A NEAT AND CAREFUL MANNER. CORE DRILL FOR PIPE SLEEVES AND OTHER OPENINGS THROUGH FLOORS AND WALLS. SAWCUT LARGER OPENINGS. CUTTING SHALL BE KEPT TO A MINIMUM.
 - REPLACE OR REPAIR DUCTWORK, CONDUIT, PIPING, ETC., THAT IS CUT. PATCH AROUND OPENING CUT BY THIS CONTRACTOR OR PROVIDED BY OTHERS FOR HIM. PATCHING SHALL BE DONE BY AN APPROVED QUALIFIED CONTRACTOR, BUT SHALL BE PAID FOR BY THIS CONTRACTOR. FINISHED PATCHING SHALL RETAIN FIRE AND SMOKE RATINGS OF THE ASSEMBLY AND SHALL MATCH SURROUNDING FINISH.
- E. ANCHORS:
- MOUNT ALL EQUIPMENT, BRACKETS, HANGERS, ANCHORS, ETC. TO SAFELY RESIST THE VIBRATION OR THRUST FORCES AND SUPPORT THE UNIT'S WEIGHT.
 - FLOOR MOUNTED ROTATING OR VIBRATING EQUIPMENT SHALL BE ANCHORED TO THE FLOOR USING GROUTED-IN-PLACE OR CAST-IN-PLACE ANCHOR BOLTS WITH THREE INCH HOOK AND SLEEVE. ANCHOR BOLTS SHALL BE OF THE SIZE RECOMMENDED BY THE MANUFACTURER.
 - FLOOR MOUNTED STATIC ITEMS, WALL AND CEILING MOUNTED EQUIPMENT BRACKET AND HANGERS SHALL BE INSTALLED USING DRILLED ANCHORS (OR CAST IN PLACE INSERTS). ANCHORS SHALL BE PHILLIPS DRILL COMPANY "RED HEAD" OR MULTI-SET II. SIZE ANCHORS (AND INSERTS) FOR FOUR TIMES THE APPLIED LOAD. BOLTS USED OUTDOORS OR IN A WET ENVIRONMENT SHALL BE HOT DIP GALVANIZED.
- A. PIPE IDENTIFICATION:
- IDENTIFICATION SHALL BE IN ACCORDANCE WITH ANSI-A13.1. PIPE MARKERS SHALL BE SETON'S WEATHER-CODE OR EQUAL.
 - PROVIDE PIPE MARKERS AND DIRECTIONAL ARROWS ON PIPES AT BOTH SIDES OF PARTITIONS AND FLOORS SLABS, AT BRANCH LINES, AT VALVES, AT INTERMEDIATE INTERVALS NOT IN EXCESS OF 20 FT. AND AT CONNECTIONS TO EQUIPMENT.
 - TAPE COLOR BAND IDENTIFYING MARKERS AND ARROWS ON EACH PIPE, BOTH INSULATED AND BARE PIPES. PIPE MARKERS AND ARROWS SHALL BE LOCATED WHERE READILY VISIBLE AND ON LOWER QUADRANTS OF OVERHEAD PIPES.
- B. VALVE TAG AND CHART:
- VALVE TAGS SHALL BE SETON M4508, BLACK FILLED LETTERS WITH BRASS JACK CHAIN. ONE VALVE NUMBER SHALL BE STAMPED ON EACH TAG. IDENTIFY EACH VALVE TAG FOR THE UTILITY IT SERVES, SUCH AS "CW" FOR COLD WATER, HW FOR HOT WATER, ETC. VALVE CHARTS SHALL BE SETON. ATTACH A NUMBERED VALVE TAG TO EACH VALVE.
 - PROVIDE A TYPE WRITTEN CHART IN FRAME UNDER GLASS COVER, GIVING THE FULL LIST OF ALL VALVES INSTALLED UNDER THIS CONTRACT. CHART SHALL LIST VALVE NUMBER, TYPE OF UTILITY, AND LOCATION. MOUNT CHART WHERE DIRECTED BY OWNER. PROVIDE ONE ADDITIONAL COPY TO OWNER.
- A. EQUIPMENT IDENTIFICATION:
- IDENTIFY EACH PIECE OF EQUIPMENT WITH A 1/8 INCH THICK ENGRAVED MELAMINE PLASTIC LAMINATE NAMEPLATE. LETTERS SHALL BE 1/2 INCH HIGH STANDARD STYLE. NAMES, ABBREVIATIONS, AND NUMBERING SHALL AGREE WITH THE CORRESPONDING EQUIPMENT DESIGNATIONS SHOWN ON THE DRAWINGS. USE BLACK LETTERS CUT IN A WHITE BACKGROUND FOR ALL EQUIPMENT ON STANDARD ELECTRICAL POWER.
 - FASTEN NAMEPLATES TO EQUIPMENT IN A CONSPICUOUS LOCATION USING SELF-TAPPING STAINLESS STEEL SCREWS, EXCEPT USE CONTACT EPOXY ADHESIVE WHERE SCREWS CANNOT OR SHOULD NOT PENETRATE SUBSTRATE.
- B. PIPE SLEEVES:
- PROVIDE PIPE SLEEVES WHERE PIPES PASS THROUGH FLOORS AND WALLS ABOVE OR BELOW CEILINGS. PROVIDE PIPE SLEEVES IN NEW WALLS AND FLOORS AS THE WORK PROGRESSES. PROVIDE SPLIT PIPE SLEEVES IN NEW WALLS BUILT UP AROUND EXISTING PIPES. TACK WELD SPLIT SLEEVES TOGETHER.
 - SIZE PIPE SLEEVES TO ALLOW CONTINUOUS INSULATION, BUT NOT LESS THAN TWO PIPE SIZES LARGER THAN PIPE. SLEEVES IN WALLS SHALL BE FLUSH WITH WALL. SLEEVES IN FLOORS SHALL EXTEND 3/4 INCHES ABOVE FLOOR AND BE FLUSH WITH STRUCTURE BELOW.
 - SLEEVES IN CONCRETE WALLS, FLOORS OR MASONRY SHALL BE SCH 40 STEEL PIPE, MACHINE CUT. SLEEVES IN GYPSUM BOARD OR PLASTER WALLS SHALL BE 14 GAUGE, ROLLED GALVANIZED SHEET METAL TACK WELDED ON THE LONGITUDINAL SEAM.
 - PROVIDE PLATES AROUND PIPES EXTENDING INTO EXPOSED AREAS WHERE THEY PASS THROUGH WALLS, FLOORS AND CEILINGS. SIZE PLATES TO COMPLETELY COVER PIPE SLEEVES. PLATES SHALL BE BEATON AND CADWELL, KEENEY OR GRINNELL, NICKEL PLATED STEEL, SPLIT PLATES WITH SET SCREW. CONCRETE FLOOR PLATE SHALL BE GRINNELL FIGURE 400.
- C. FLASHING:
- PROVIDE FLASHING AT PIPING AND DUCT PENETRATIONS THROUGH ROOF AND ROOF MOUNTED STRUCTURES FURNISHED UNDER THIS DIVISION. FLASH IN ACCORDANCE WITH ROOFING MANUFACTURER'S DETAILS. FLASHING MATERIALS SHALL BE IN ACCORDANCE WITH THE ROOFING MANUFACTURERS SYSTEM.
 - PROVIDE FLASHING AT PIPES PASSING THROUGH FLOORS WITH WATERPROOF MEMBRANE. FLASHING SHALL BE IN ACCORDANCE WITH WATERPROOFING MANUFACTURER'S DETAILS.

SECTION 15261 - PLUMBING INSULATION

- A. GENERAL:
- ALL INSULATION, JACKETING, AND ADHESIVE SHALL HAVE COMPOSITE SURFACE BURNING CHARACTERISTIC RATING AS TESTED BY ASTM E 84, UL 723, OR NFPA 255 NOT EXCEEDING A FLAME SPREAD OF 25 OR SMOKE DEVELOPED OF 50.
 - SUBMITTALS SHALL USE PAGES FROM MIDWEST INSULATION CONTRACTORS ASSOCIATION - "COMMERCIAL AND INDUSTRIAL INSULATION STANDARDS" FOR DEFINING HOW INSULATION MATERIALS WILL BE APPLIED.
 - ALL PIPE INSULATION SHALL BE CONTINUOUS THROUGH WALLS, CEILING OR FLOOR OPENINGS, OR SLEEVES; EXCEPT WHERE FIRESTOP OR FIRESEALING MATERIALS ARE REQUIRED.
 - INSULATE ITEMS MOUNTED IN PIPING WITH THE SAME THICKNESS OF INSULATION AS SPECIFIED FOR PIPING.
- B. REPAIR INSULATION DAMAGED BY WORK UNDER THIS CONTRACT TO MATCH EXISTING WORK OR REPLACE DAMAGED PORTION WITH INSULATION SPECIFIED FOR NEW WORK.
- C. DOMESTIC WATER PIPING:
- INSULATION SHALL BE 850 DEG. F. RATED AS MANUFACTURED BY OWENS CORNING, MANVILLE OR KNAUF. ROUTED OR MOLDED FITTING INSULATION SHALL BE HAMFAB.
 - INSULATION SHALL HAVE FACTORY-APPLIED, REINFORCED, FLAME RETARDANT, VAPOR BARRIER JACKET EQUAL TO OWENS-CORNING ASJ WITH SELF-SEALING LAP. BUTT JOINTS SHALL BE TAPED WITH FIELD-APPLIED ASJ TAPE 3 IN. WIDE.
 - INSULATION THICKNESSES SHALL BE IN ACCORDANCE WITH INTERNATIONAL ENERGY CONSERVATION CODE FOR PIPE SIZES NOTED ON PLAN.
 - ALL FITTINGS AND VALVES SHALL BE INSULATED WITH PREFORMED FIBER GLASS FITTINGS OR MITERED SECTIONS OF PIPE INSULATION. INSULATION SHALL BE OF EQUAL THICKNESS TO THE ADJACENT PIPE INSULATION.
 - METAL SLEEVES SHALL BE INSTALLED BETWEEN HANGERS OR SUPPORTS AND THE PIPING INSULATION. RIGID INSULATION INSERTS SHALL BE INSTALLED AS REQUIRED BETWEEN THE PIPE AND THE INSULATION SHIELDS. INSERTS SHALL BE OF EQUAL THICKNESS TO THE ADJACENT INSULATION AND SHALL BE VAPOR SEALED AS REQUIRED.
- D. ELASTOMERIC CLOSED CELL INSULATION:
- INSULATION SHALL BE RUBATEX OR ARMSTRONG. SECURE INSULATION WITH CONTACT ADHESIVE IN ACCORDANCE WITH MANUFACTURERS INSTRUCTIONS. EXPOSED OR EXTERIOR INSTALLATIONS SHALL BE PAINTED WITH TWO COATS OF WATER BASED ENAMEL.
 - PROVIDE 1 IN. THICK INSULATION ON DX REFRIGERANT PIPING, COOLING COIL, CONDENSE PIPEING, AND CAPS FOR ALL VALVE STEMS AND OPERATORS, GAUGE COCKS, THERMOMETER WELLS AND OTHER APURTRENANCES SUBJECT TO SWEATING.
- E. PIPING FINISHES:
- METAL JACKETING SHALL BE, SMOOTH, 0.16 IN. THICK, TYPE T 3003 ALUMINUM WITH LAMINATED MOISTURE BARRIER. JACKETING SHALL BE CHILDERS, ALUMINUM ROLL, JACKETING WITH POLYKRAFT MOISTURE BARRIER. COVER THE FOLLOWING INSULATED SYSTEMS WITH METAL JACKETING: PIPING INSTALLED OUTDOORS AND EXPOSED PIPING INDOORS WITHIN 8 FT. OF FINISHED FLOOR. METAL FITTING COVERS SHALL BE TWO PIECE ALUMINUM. COVERS SHALL BE ELL-JAC.
 - CONCEALED PIPING FINISH COVERING SHALL BE THE ALL SERVICE JACKET. FITTINGS SHALL BE COVERED BY WRAPPING THE FITTING WITH FIBER REINFORCED TAPE, WITH A 5 PERCENT OVERLAP. FITTING COVERS SHALL BE ONE PIECE 20 MIL PVC. COVERS SHALL BE CEEL-TITE 550 PVC-UVR BY CEEL-CO OR EQUALS.

SECTION 15410 - PLUMBING PIPING

- A. THE WORK REQUIRED UNDER THIS SECTION INCLUDES ALL WORK NECESSARY FOR A COMPLETE INSTALLATION OF SANITARY WASTE PIPING, STORM PIPING AND DOMESTIC WATER PIPING INSIDE THE BUILDING TO 5 FEET OUTSIDE THE BUILDING. SUBMIT SCHEDULE OF PIPE AND FITTINGS FOR EACH SERVICE.
- B. DOMESTIC WATER PIPING: WATER PIPING WITHIN THE SHALL BE COPPER TUBE, TYPE "L" HARD TEMPER, ASTM B-88. PIPING BELOW GROUND SHALL BE COPPER TUBE, TYPE "K" SOFT TEMPER, ASTM B-88. FITTINGS SHALL BE WROUGHT COPPER, SOLID TYPE, ASTM B-75, ANSI B16.22. SOLDER UNIONS SHALL BE WROT COPPER, WITH COPPER GROUND JOINT. ASTM B75, ANSI B16.22. D1-ELECTRIC, EPSO, 250 LB. WOG. SOLDER METAL SHALL CONFORM TO ASTM B32, LEAD-FREE.
- C. STORM, SANITARY WASTE, AND VENT PIPING: ABOVE GROUND: SCHEDULE 40 PVC-DWV ASTM D-2665 USING SOLVENT CEMENT. HORIZONTAL PIPING FOR FIXTURE ROUGH-INS MAY BE DWV COPPER, ASTM B-306. BELOW GROUND: SCHEDULE 40 PVC-DWV ASTM D-2665 USING SOLVENT CEMENT ASTM D-2564.
- D. STORM, SANITARY WASTE AND VENT FITTINGS: ABOVE GROUND: 1/NO HUB CAST IRON SOIL PIPE FITTINGS WITH COUPLING ASSEMBLY CISPI STANDARD 310.1 SCHEDULE 40 PVC-DWV, ASTM D-2855 USING SOLVENT CEMENT ASTM D-2564. BELOW GROUND: SCHEDULE 40 PVC-DWV, ASTM D-2855 USING SOLVENT CEMENT ASTM D-2564.
- E. BALL VALVES: VALVES SHALL BE NIBCO T-585-70, FULL PORT BALL TYPE WITH BRONZE BODY, CHROME PLATED BALL AND BRONZE THREADED ENDS, 600 PSI WOG OR NIBCO S-585-70 IN COPPER LINES. HAMMOND, CRANE, APOLLO, MILWAUKEE, OR APPROVED EQUAL.
- F. ALL PIPING SHALL BE ROUTED TO CONSERVE BUILDING SPACE, BE COORDINATED WITH ITEMS INSTALLED BY OTHER TRADES AND NOT INTERFERE WITH ACCESS TO OR OPERATION OF THE FACILITY.
- G. PROVIDE ROOF FLASHINGS FOR PIPE PENETRATIONS THROUGH ROOF, TO BE INSTALLED BY ROOFING CONTRACTOR.
- H. WATER PIPING WITHIN BUILDING SHALL BE SIZE INDICATED ON PLANS AND RISERS. IN THE EVENT NO SIZE IS SHOWN, PIPE SIZE OR SIZE REQUIRED BY THE PLUMBING CODE. PIPING SHALL BE SLOPED TOWARD A SYSTEM DRAIN AND TOWARD OUTLETS, TO PROVIDE FOR SYSTEM DRAIN-DOWN. IF INSTALLED NEAR EXTERIOR WALLS, PIPING SHALL BE LOCATED ON THE INTERIOR SIDE OF INSULATION. INSTALL PIPING TO PREVENT DIRECT CONTACT BETWEEN FERROUS AND NON-FERROUS MATERIALS. ALLOW FLEXIBILITY FOR EXPANSION IN PIPING.
- I. DOMESTIC WATER PIPING SYSTEM SHALL BE TESTED WITH POTABLE WATER AT A PRESSURE OF 125 PSIG OR 25 PSIG ABOVE DESIGN WORKING PRESSURE, WHICHEVER IS GREATER FOR 12 HOURS. TEST SHALL BE CONDUCTED WITH PLUMBING INSPECTOR UNLESS APPROVED OTHERWISE IN WRITING.
- J. WATER DISTRIBUTION PIPING SHALL BE DISINFECTED PRIOR TO OCCUPANCY OR SYSTEM START-UP WITH A CHLORINE SOLUTION 50 PPM. ALLOW SYSTEM TO STAND FOR SIX HOURS MINIMUM, THEN EXERCISE ALL VALVES TO ENSURE TREATMENT OF ALL BRANCHES AND COMPONENTS. SYSTEM SHALL BE FLUSHED WITH POTABLE WATER AFTER DISINFECTION AND PRIOR TO PLACEMENT INTO SERVICE.
- K. STORM, SANITARY WASTE AND VENT PIPING SHALL BE TESTED IN ACCORDANCE WITH WATER AND AIR TESTS AS SPECIFIED IN THE INTERNATIONAL PLUMBING CODE, IN ADDITION TO ANY TESTS REQUIRED BY THE LOCAL PLUMBING OFFICIAL. (10 FEET OF HEAD WITH NO APPARENT LEAKS. HOLD FOR 30 MINUTES MINIMUM). FLUSH ALL GRAVITY PIPING INCLUDING FLOOR DRAINS AND ROOF DRAINS PRIOR TO TURNING OVER TO THE OWNER.
- L. ALL PIPE SHALL BE CUT SQUARE. REAM PIPE AND TUBE ENDS AND REMOVE BURRS. CLEAN THE ENDS OF PIPES TO REMOVE OIL, GREASE AND OXIDES. PREPARE PIPING CONNECTIONS TO EQUIPMENT WITH FLANGES OR UNIONS.
- M. ALL SOLDERED PIPING AND EQUIPMENT CONNECTIONS SHALL BE PROPERLY PREPARED IN ACCORDANCE WITH GOOD PIPING PRACTICE. APPLY A THIN LAYER OF FLUX TO ONLY THE MALE TUBING. ROTATE INTO THE FITTING WITH ONE OR TWO REVOLUTIONS.
- N. DOMESTIC WATER PIPING: ROUTE PIPING IN ORDERLY MANNER, PLUMB AND PARALLEL TO BUILDING STRUCTURE, AND MAINTAIN GRADIENT. INSTALL PIPING TO ALLOW FOR EXPANSION AND CONTRACTION WITHOUT STRESSING PIPE, JOINTS, OR CONNECTED EQUIPMENT. PROVIDE CLEARANCE FOR INSTALLATION OF INSULATION AND ACCESS TO VALVES AND FITTINGS. PROVIDE ACCESS WHERE VALVES AND FITTINGS ARE NOT EXPOSED. INSTALL VALVES WITH STEMS UPRIGHT OR HORIZONTAL. PROVIDE DRAIN VALVES AT LOW POINTS IN SYSTEMS. TEST WATER PIPING BEFORE BEING INSULATED OR CONCEALED IN WALLS OR CEILING.
- O. STORM, SANITARY WASTE, AND VENT PIPING: HORIZONTAL SOIL, WASTE AND DRAINAGE LINES WITHIN BUILDING SHALL HAVE A MINIMUM UNIFORM SLOPE OF 1/8 INCH PER FOOT ON 3 INCH AND LARGER, AND 1/4 INCH PER FOOT ON LINES 2 INCH AND SMALLER. TURNS IN SANITARY, SOIL, AND DRAIN PIPING SHALL BE MADE USING 45 DEGREE ELBOWS, WYES, QUARTER, EIGHTH, SIXTEENTH BENDS, OR OTHER BENDS APPROVED BY THE PLUMBING CODE. DO NOT USE SANITARY TEES OR CROSSES EXCEPT WHERE DISCHARGING FROM HORIZONTAL TO VERTICAL. MAKE CHANGES IN PIPE SIZES WITH REDUCING FITTINGS AND RECESSED REDUCERS. DO NOT REDUCE LINE SIZE IN DIRECTION OF FLOW. PROVIDE CLEANOUTS IN ALL HORIZONTAL TURNS IN WASTE PIPING GREATER THAN 45 DEGREES. PROVIDE DEEP SEAL TRAPS ON ALL FLOOR DRAINS, AND TRAP PRIMERS/SEAL WHERE REQUIRED BY CODE OR AS INDICATED ON DRAWINGS. INDIRECT WASTE LINES DUMPING INTO FLOOR OR HUB DRAINS SHALL MAINTAIN A 2-INCH AIR GAP BETWEEN THE END OF THE WASTE LINE AND THE RIM OF THE FLOOR OR HUB DRAIN.

SECTION 15416 - GAS PIPING SYSTEMS

- A. PROVIDE COMPLETE INSTALLATION OF GAS PIPING FROM THE "POINT OF DELIVERY" UP TO AND INCLUDING CONNECTION TO ALL GAS-FIRED EQUIPMENT. CONNECT EQUIPMENT ITEMS FURNISHED UNDER OTHER SECTIONS OF SPECIFICATIONS. TEST IN ACCORDANCE WITH A.G.A., STANDARD GAS CODE, N.F.P.A. 54, AND APPLICABLE STATE AND LOCAL CODES.
- B. ROUTE GAS SERVICE ENTRANCE PIPING INTO BUILDING TO AVOID INTERFERENCE AND DAMAGE. PROVIDE MANUAL SHUTOFF VALVE, GAS COCK AND GAUGE. VALVES SHALL BE LABELED.
- C. PROVIDE ACCESS PANELS FOR VALVES AND OTHER ITEMS REQUIRING MAINTENANCE IN ENCLOSED SPACES. AVOID INSTALLING GAS APURTENANCES IN ENCLOSED SPACES WHERE POSSIBLE. INSTALL IN ENCLOSED SPACES ONLY AS ALLOWED BY APPLICABLE CODES.
- D. SUBMIT MANUFACTURER'S LITERATURE ON ALL MATERIALS AND EQUIPMENT INCLUDING: PIPE, PIPE COATINGS, ANODES, VALVES, FLEXIBLE CONNECTORS, FITTINGS, REGULATORS, RELIEF VALVES, GAUGES, GAS SERVICE.
- E. GAS SERVICE:
- COORDINATE INSTALLATION OF GAS SERVICE LINE WITH LOCAL GAS COMPANY. PAY ALL FEES.
 - PROVIDE 12 INCH ELEVATED METER MOUNTING PADS ON TOP OF A 4 INCH THICK CONCRETE PAD FOR SUPPORT OF GAS METER AND PIPING.
 - PROVIDE (TWO) 8 INCH DIAMETER PIPE BOLLARDS FOR GAS METER PROTECTION. BOLLARDS SHALL BE SIX FEET LONG (3 FEET BELOW GRADE), MOUNTED IN A 24 INCH DIAMETER HOLE, FILLED WITH 3,000 PSI CONCRETE.
- F. INTERIOR PIPING: CONNECT TO ENTERING LINE AND DISTRIBUTE GAS TO EQUIPMENT ITEMS REQUIRING GAS AND AS INDICATED. PERFORM WORK IN ACCORD WITH APPLICABLE A.G.A., N.F.P.A. 54, STATE AND LOCAL CODES. INSTALL GAS STOP VALVES AND DRIP LEGS AT EACH EQUIPMENT ITEM. PIPING SHALL BE ADEQUATELY DRAINED WITH A MINIMUM SLOPE OF 1/4 INCH PER 15 FEET AND DRIP LEGS (FULL SIZE OF PIPE) INSTALLED AT ADDITIONAL POINTS WHERE CONDENSATE MAY COLLECT. INSTALL PRESSURE REDUCING VALVES AS REQUIRED TO PROVIDE PRESSURE WITHIN EQUIPMENT MANUFACTURER'S REQUIREMENTS.
- G. EXTERIOR PIPING: EXTERIOR PIPING SHALL BE SCHEDULE 40 CARBON STEEL. PIPING 2 INCH AND SMALLER MAY USE THREADED FITTINGS. PIPING 2 1/2 INCH AND LARGER SHALL USE WELDED FITTINGS AND FLANGES.
- H. VALVES: EXTERIOR PIPING SHALL BE COATED WITH AN ALKYD ENAMEL PRIMER (MINIMUM DRY THICKNESS 3 MILS). EXTERIOR PIPING SHALL BE SUPPORTED ON GALVANIZED B-LINE CHANNELS AND STEEL CLAMPS.
- I. UNDERGROUND PIPING SHALL BE CARBON STEEL - A53/A106-WELDED OR POLYETHYLENE.
- UNDERGROUND STEEL PIPING SHALL HAVE AT LEAST 18 INCH OF PROPER BACKFILL COVER. UNDERGROUND PIPING SHALL BE PROTECTED FROM CORROSION. PROVIDE COATED PIPING AND FITTINGS. REPAIR SHALL MEET THE REG AT WELDS. INSTALL SACRIFICIAL ANODES ON STEEL PIPING INTERVALS NOT EXCEEDING 100 FT.
 - GAS LINES ROUTED UNDER A BUILDING SHALL BE STEEL AND SHALL BE ENCASED IN A SCH 40 OUTER CONDUIT (AT LEAST 3 PIPE SIZES LARGER THAN THE GAS LINE). CONDUIT SHALL BE SEAL WELDED TO THE GAS PIPE INSIDE THE BUILDING. CONDUIT SHALL BE VENTED TO OUTDOORS. CONDUIT SHALL BE PROTECTED FROM CORROSION SIMILARLY TO UNDERGROUND PIPING.
- J. PIPE/TUBING:
- STEEL PIPE: ASTM A53 GRADE A OR B, TYPE F, ERW OR SEAMLESS. SCHEDULE 40.
 - ASTM A106 SEAMLESS, SCHEDULE 40.
 - TUBING (STEEL) ASTM A539.
 - PLASTIC PIPE ASTM D2513 POLYETHYLENE. DRISCO PIPE 6500 OR PRIOR APPROVED EQUAL.
- K. FITTINGS:
- WELDED (STEEL): WELDING FITTINGS SHALL BE CARBON STEEL BUTT WELDING TYPE CONFORMING TO ASTM-234. ELBOWS SHALL BE LONG RADIUS TYPE. WELDING TEES SHALL BE USED ON BRANCH CONNECTIONS EQUAL TO OR GREATER THAN 2 THE DIAMETER OF THE MAIN RUN. FITTINGS SHALL BE LADISH, TUBE-TURN OR WELDBRAND. CARBON STEEL REINFORCED BRANCH, WELDING FITTINGS UP TO 3 INCHES, BUT NOT GREATER THAN 2 THE DIAMETER OF THE MAIN RUN MAY BE USED. FITTINGS SHALL BE BONNEY FORGE OR PHOENIX FORGING.
 - THREADED (MALLEABLE IRON): SCREWED FITTINGS SHALL BE MALLEABLE IRON ASTM A-197 CLASS 150 CONFORMING TO AISI B16.3. DIMENSIONS CONFORMING TO FEDERAL SPEC WW-P-521. FITTINGS SHALL BE GRINNELL, FLAGG OR STOCKHAM.
 - HEAT FUSION/COMPRESSION (POLYETHYLENE): SOCKET TYPE FUSION SHALL MEET THE REQUIREMENTS OF ASTM 2683. FITTINGS SHALL BE LISTED AND MARKED ASTM D2513. BUTT TYPE FUSION FITTING SHALL MEET THE REQUIREMENTS OF ASTM D3261.
- L. UNIONS (DIELECTRIC): CLASS 250 MALLEABLE, SCREWED ASTM A-197.
- M. VALVES:
- 1 INCH AND SMALLER: BALL VALVE - CLASS 125 BRASS FULL PART, 2 PIECE BODY, CHROME PLATED BALL, BLOWOUT PROOF STEAM, TFE SEATS.
 - 2 INCHES AND SMALLER: PLUG COCK - CLASS 125 CAST IRON, SCREWED, FULL PORT AGA LISTED, ANSI B16.33 HOMESTEAD FIGURE 601.
 - 2 1/2 INCHES AND LARGER: PLUG VALVE - CLASS 125 FLANGED CAST IRON ASTM A126 CONFORMING TO ANSI B16.1.
- N. PIPE COATING: X-TRU COAT OR PRIOR APPROVED EQUAL INCLUDING JOINTS AND FITTINGS.
- O. PRESSURE REGULATORS: CAST IRON OR ALUMINUM BODY AND SPRING CASE WITH STAINLESS STEEL VALVE STEAM, SEAT RING AND VALVE PLUG, PLATED STEEL SPRINGS, NEOPRENE DIAPHRAGM AND GASKETS AND TFE DISC. REGULATING VALVES SHALL BE SIZED FOR THE FLOW INDICATED AND FOR INLET AND OUTLET PRESSURES INDICATED. OUTLET PRESSURE SHALL BE MAINTAINED UNDER THE DESIGN FLOW CONDITION AND AT NO FLOW. REGULATING VALVES TWO PSI AND BELOW SHALL HAVE LEAK LIMITING DEVICES. REGULATING VALVES OVER TWO PSI SHALL BE VENTED FULL SIZE TO OUTSIDE OF THE BUILDING. OTHER REGULATING VALVES REQUIRING ACCESS TO THE ATMOSPHERE SHALL BE EQUIPPED WITH VENT PIPING LEADING TO OUTSIDE. PROVIDE A PRESSURE RELIEF VALVE IF THE REGULATOR CONNECTION SIZE EXCEEDS TWO-INCHES. REGULATING VALVES SHALL BE FISHER, MAXITROL OR PRIOR APPROVED EQUAL MEETING ANSI Z21.18.
- P. PRESSURE GAGE: FOR MEDIUM PRESSURE GAS: 0-5 PSI RANGE. FOR LOW PRESSURE GAS: 0-30 INCH W.C. RANGE. USE LOW PRESSURE TYPE 2-1/2 INCH DIAL PRESSURE GAGE WITH APPROPRIATE RANGE, OGI MODEL CO 34, TREXICE, WEKSLER OR APPROVED EQUAL.

SECTION 15430 - PLUMBING SPECIALTIES


- A. THIS SPECIFICATION DESCRIBES THE REQUIREMENTS FOR LABOR AND MATERIALS REQUIRED FOR THE INSTALLATION OF PLUMBING SPECIALTIES INCLUDED AS PART OF THE BUILDING PLUMBING SYSTEM. MANUFACTURER'S LITERATURE INDICATING MODEL NUMBERS AND OPTIONS SHALL BE SUBMITTED FOR ALL FIXTURES AND EQUIPMENT. FORMAT SHALL INCLUDE A SCHEDULE OF THE SPECIALTIES SUBMITTED AND INCLUDE IDENTIFICATION NUMBER OF EACH ITEM, SUCH AS "FD-1 FLOOR DRAIN, A LIST OF EACH COMPONENT, ACCESSORY, AND OPTION OF THE ITEM BEING SUBMITTED. THIS SCHEDULE MUST BE INCLUDED IN THE FRONT OF THE SUBMITTAL PAGE.
- C. CLEANOUTS SHALL CONSIST OF A COATED CAST IRON BODY WITH THREADED TOP WITH SPIGOT OR NO-HUB CONNECTION AND GASKETED BRONZE CLOSURE PLUG WITH COUNTERSUNK SLOT. HEAD SHALL BE ADJUSTABLE IN HEIGHT; PROVIDE NON-SKID COVERS FOR FLOOR CLEANOUTS. PROVIDE THREAD SHIELD TO PROTECT ADJUSTMENT THREADS FROM CONCRETE AS REQUIRED. CLEANOUTS SHALL BE INSTALLED IN HORIZONTAL RUNS AT SPACING OF NO MORE THAN 75 FEET. INSTALL CLEANOUTS AT THE BASE OF EVERY SOIL AND WASTE STACK, AND AT EACH 90 DEGREE CHANGE IN DIRECTION. INSTALL CLEANOUTS WHICH ARE NOT EASILY ACCESSIBLE UP THROUGH FLOOR OR WALL AND PROVIDE APPLICABLE COVERS. INSTALL CLEANOUTS TO ALLOW AT LEAST 18" FOR RODDING.
- D. WATER HAMMER ARRESTORS SHALL BE CONSTRUCTED OF A STAINLESS STEEL OR COPPER SHELL, STAINLESS STEEL OR ELASTOMER BELLOWS, WITH PRECHARGE OF AIR, NITROGEN, OR ARGON. ARRESTORS SHALL CONFORM TO ASSE STD. 1010, AND SHALL BE ZURN "SHOKTROL", JOSAM "ABSORBOTRON", WADE "SHOKSTOP", OR PRECISION PLUMBING PRODUCTS "SHOCK ARRESTOR". UNIT SHALL BE SIZED IN ACCORDANCE WITH TO PSI STANDARDS. WATER HAMMER ARRESTORS SHALL BE SIZED TO ACTUAL PIPE SIZE AND INSTALLED AS NEAR THE SHOCK SOURCE AS PRACTICAL. INSTALL TO ALLOW UNOBSTRUCTED PATH FROM SHOCK SOURCE TO ARRESTOR.
- E. BALANCING VALVES (DOMESTIC HOT WATER RETURN): VALVES SHALL BE BELL AND GOSSETT CB SERIES CIRCUIT SETTER, PRESETTABLE BALANCE VALVE, VARIABLE ORIFICE FLOW METER AND POSITIVE SHUT-OFF SERVICE VALVE. EQUIPMENT WITH CAPPED READOUT VALVES FITTED WITH INTERNAL CHECK VALVES, 1/4 INCH NPT TAPPED AND PLUGGED DRAIN PORT. BRONZE BODY/BRASS BALL CONSTRUCTION WITH GLASS AND CARBON FILLED BALL SEAT RINGS, SOLDER CONNECTIONS. VALVES TO HAVE DIFFERENTIAL PRESSURE READ-OUT PORTS ACROSS VALVE SEAT AREA. FURNISH WITH PREFORMED INSULATION TO PERMIT ACCESS FOR BALANCE AND READ-OUT. TACO IS AN APPROVED EQUAL.
- F. PRESSURE REDUCING VALVES: VALVES SHALL BE EQUAL TO WATTS SERIES U6B-GG BRONZE BODY SINGLE SEATED WITH COMPOSITION DIAPHRAGM AND STAINLESS STEEL SPRING, DIRECT ACTING WITH STRAINER ON INLET SIDE, INTEGRAL BY-PASS CHECK VALVE, GAUGE, AND THREADED ENDS. INSTALL IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
- G. TRAP GUARD SEALS: PROVIDE AN ELASTOMERIC, NORMALLY CLOSED TRAP GUARD DEVICE TO PREVENT EVAPORATION OF THE TRAP SEAL AND TO PROTECT AGAINST SEWER GASES FROM BACKING UP INTO HABITABLE AREAS. DEVICE SHALL OPEN WITH FLUID AND ALLOWS LIQUID DRAINAGE TO FLOW THROUGH INTO THE BUILDING DRAIN. TRAP SEAL SHALL BE TRAP GUARD BY PRO-VENT SYSTEMS OR APPROVED EQUAL.
- H. FLOOR DRAINS (FD-1): DRAIN SHALL INCLUDE COATED CAST IRON BODY WITH BOTTOM OUTLET, 1/2" TRAP PRIMER CONNECTION, COMBINATION INVERTIBLE MEMBRANE CLAMP AND ADJUSTABLE COLLAR WITH TYPE "B" ROUND POLISHED NICKEL-BRONZE LIGHT DUTY STRAINER TOP WITH SQUARE HEEL-PROOF OPENINGS AND SECURED GRATE. DRAIN SHALL BE ZURN Z-45-P-NH OR EQUAL BY JAY R. SMITH, WADE, OR JOSAM. PROVIDE 3 FT. SQ. 6 MIL BUTYL MEMBRANE, AT EACH FLOOR DRAIN. CLAMP MEMBRANE. MEMBRANE SHALL BE RECESSED IN THE FLOOR SLAB WITH TOPPING POURED OVER IT. DRAINS INSTALLED IN ELEVATED BUILDING FLOORS SHALL BE SEALED IN SUCH A MANNER AS TO PREVENT LEAKAGE OF WATER AROUND TRAP AND BODY TO CEILING BELOW.
- I. FLOOR DRAIN (FD-2): DRAIN SHALL INCLUDE SUR-SET BUCKET, 9" DIAMETER MEDIUM DUTY CAST IRON GRATE, COATED CAST IRON BODY, 1/2" TRAP PRIMER CONNECTION, BOTTOM OUTLET, SEEPAGE PAN, AND COMBINATION MEMBRANE CLAMP. DRAIN SHALL BE ZURN Z-55-P-NH OR EQUAL BY JAY R. SMITH, WADE, OR JOSAM. PROVIDE 3 FT. SQ. 6 MIL BUTYL MEMBRANE, AT EACH FLOOR DRAIN. CLAMP MEMBRANE. MEMBRANE SHALL BE RECESSED IN THE FLOOR SLAB WITH TOPPING POURED OVER IT. DRAINS INSTALLED IN ELEVATED BUILDING FLOORS SHALL BE SEALED IN SUCH A MANNER AS TO PREVENT LEAKAGE OF WATER AROUND TRAP AND BODY TO CEILING BELOW.
- J. HUB DRAIN (HD): DRAIN SHALL INCLUDE CAST IRON DEEP SEAL, 1" TRAP WITH INDIRECT WASTE FUNNEL INLET AND SIDE OUTLET THREADED AND WITH 1/2 INCH THREADED FLUSH CONNECTION. DRAIN SHALL BE JOSAM 8821-051 OR EQUAL BY ZURN, JAY R. SMITH, OR WADE.
- K. REDUCED PRESSURE ZONE BACKFLOW PREVENTER (ASSE 1015): BACKFLOW PREVENTER SHALL INCLUDE NPT BODY CONNECTIONS, QUARTER TURN, FULL PORT, RESILIENT SEATED BRONZE BALL VALVE, AND STRAINER. UNIT SHALL BE WATTS SERIES 909 QT OR EQUAL BY WILKINS, OR CONBRACO. BACKFLOW PREVENTERS SHALL BE INSTALLED IN ACCORDANCE WITH PER MANUFACTURER'S INSTRUCTIONS. AFTER INSTALLATION, BUT BEFORE SYSTEM IS PUT INTO SERVICE, TEST BACKFLOW PREVENTER FOR FUNCTIONALITY WITH TEST KIT AS RECOMMENDED BY MANUFACTURER. PIPE DISCHARGE FROM BACKFLOW PREVENTER VENT WITH CONNECTION-SIZE COPPER TUBING TO NEAREST FLOOR DRAIN. ENSURE AIR GAP IS PROVIDED IN RELIEF LINE EITHER BY AIR GAP FITTING OR ELEVATED DISCHARGE ABOVE DRAINS. BACKFLOW PREVENTER PIPING SHALL BE INSTALLED WITH UNIONS FOR REMOVAL.
- L. WALL HYDRANTS (WH-1): WALL HYDRANTS SHALL BE NICKEL BRONZE PLATED, INTEGRAL VACUUM BREAKER, 3/4 INCH HOSE THREAD, KEY OPERATOR, NON-FREEZE TYPE, HOUSED IN A RECESSED STAINLESS STEEL BOX WITH HINGED LOCKING COVER. HYDRANT SHALL BE JAY R. SMITH 5503 QT OR EQUAL BY WADE, JOSAM OR ZURN. INSTALL WALL HYDRANTS AS INDICATED ON DRAWINGS, MINIMUM HEIGHT 18" A.F.F. UNLESS OTHERWISE INDICATED.
- M. HOSE BIBB (HB-1): CHROME PLATED, 1/2 INCH HOSE THREAD OUTLET, LOCK SHIELD CAP WITH INTEGRAL VACUUM BREAKER. CHICAGO FAUCET NO. 932 OR T&S BRASS.
- N. THERMOSTATIC MIXING VALVES: MIXING VALVE SHALL BE THERMOSTATIC TYPE WITH LIQUID FILLED MOTOR AND LEAD-FREE BRONZE BODY CONSTRUCTION WITH REPLACEABLE CORROSION RESISTANT COMPONENTS. VALVE CONSTRUCTION SHALL BE SLIDING PISTON CONTROL MECHANISM. PISTON AND LINER SHALL BE OF STAINLESS STEEL MATERIAL. VALVES SHALL BE EQUIPPED WITH REMOVABLE UNION END STOP AND CHECK INLETS WITH STAINLESS STEEL STRAINERS. VALVE SHALL PROVIDE PROTECTION FROM HOT AND COLD SUPPLY LINE FAILURE AND THERMOSTAT FAILURE. PROVIDE WITH DIAL THERMOMETER AND SHUT OFF VALVE ON TEMPERED WATER OUTLET. MIXING VALVE SHALL BE LAWLOR 800 SERIES OR EQUAL BY HOLBY, SYMMONS, LEONARD, OR WATTS. INSTALL IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
- O. OIL SEPARATOR: MIFAB® SERIES MI-O-PL HDPE INJECTION MOLDED OIL INTERCEPTOR WITH FLOW RATING OF 20 GPM AND OIL STORAGE HOLDING CAPACITY OF 20 GALLONS. UNIT SHALL INCLUDE: SEDIMENT BUCKET (1 1/4" DIAMETER HOLES) WITH PERFORATED BAFFLE (3/8" X 1 1/4" SLOTS) NEAR INLET, DEEP SEAL TRAP COVERED BY LID, SEWER GAS STOPPER, SECURING LATCHES, STAINLESS STEEL CALIBRATED ORIFICE PLATE, INTERNAL AIR RELIEF BY-PASS, ADJUSTABLE AUTOMATIC DRAIN-OFF ASSEMBLY, DOUBLE VENT CONNECTION ON EACH SIDE, AND HDPE INJECTION MOLDED, NON SKID, RECTANGULAR GASKETED LIDS). PROVIDE WITH EXTENSIONS FOR LIDS AS REQUIRED TO MEET SLAB LEVEL.

SECTION 15440 - PLUMBING FIXTURES


- A. THIS SPECIFICATION DESCRIBES THE REQUIREMENTS FOR PLUMBING FIXTURES AND THEIR INSTALLATION. SUBMITTALS SHALL INCLUDE MANUFACTURER'S DATA SHEETS AND DIMENSIONAL INFORMATION ON ALL FIXTURES AND ACCESSORIES. FORMAT SHALL INCLUDE A SCHEDULE OF THE FIXTURES SUBMITTED AND INCLUDE IDENTIFICATION NUMBER OF EACH ITEM, SUCH AS "P-1 WATER CLOSET", AND LIST OF EACH COMPONENT AND ACCESSORY OF THE FIXTURE, INCLUDING MANUFACTURER'S MODEL NUMBER. THIS SCHEDULE MUST BE INCLUDED IN THE FRONT OF THE SUBMITTAL BOOKLET.
- C. VITREOUS WARE SHALL BE WHITE, REGULAR SECTION, OF WEIGHT REQUIRED, FREE FROM CRACKS, FLAWS, BUSTERS, CRAZES OR OTHER DEFECTS. PROVIDE WITH MOUNTING BRACKETS FOR WALL MOUNTED FIXTURES UNLESS FLOOR CARRIERS ARE INDICATED.
- D. STAINLESS STEEL SHALL HAVE MACHINE GROUND FINISH. DECKS AND SINK COMPARTMENT SIDES SHALL BE BUFFED. EXPOSED SURFACES SHALL HAVE NO. 4 SATIN FINISH. INTERIOR SURFACES SHALL BE DEADENED. EXPOSED METAL PARTS SHALL BE CHROMIUM PLATED AND PROTECTED DURING CONSTRUCTION BY A COAT OF GREASE.
- E. WATER CLOSET AND URINAL CARRIERS SHALL HAVE TAPERED THREAD FACE PLATE, PLASTIC COUPLING WITH TEST CAP, AND NEOPRENE RUBBER GASKET. LAVATORY, SINK AND URINAL CARRIERS SHALL HAVE RECTANGULAR STRUCTURAL STEEL UPRIGHTS. CARRIERS SHALL HAVE NECESSARY ACCESSORIES FOR PROPER INSTALLATION. CARRIERS SHALL BE ACCORDING TO ANSI A112.6.1M.
- F. WATER CLOSETS AND URINALS SHALL HAVE BOLT CAPS.
- G. SEATS SHALL BE WHITE, SOLID PLASTIC, WITH INTERNAL CHECK AND MOLDED STAINLESS STEEL HINGE WITHOUT VISIBLE METAL PARTS, EXCEPT AS HEREINAFTER SPECIFIED.
- H. CHROMIUM PLATED TRAPS SHALL BE BRASS WITH CHROMIUM PLATED NIPPLE TO WALL AND ESCUTCHEON.
- I. FITTINGS AND ACCESSORIES SPECIFIED DESIGNATE TYPE ONLY; PROVIDE MODIFICATIONS TO MAKE FITTINGS WORK PROPERLY WITH FIXTURE AND PIPING. PROVIDE NECESSARY TAILPIECE AND SHANKS.
- J. INSTALL EYEWASH STATION WITHIN 10 FEET OF HAZARD AREA, COMPLETELY UNOBSTRUCTED FROM VIEW OR ACCESS, ANCHOR TO FLOOR IN ACCORDANCE WITH MANUFACTURER'S REQUIREMENTS. PROVIDE AND INSTALL STRAINER AT DOMESTIC WATER INLET TO STATION. PROVIDE AND INSTALL ON WALL ABOVE STATION, A PLASTIC ENGRAVED SIGN READING "EMERGENCY USE ONLY", WHITE LETTERS ON RED BACKGROUND. PROVIDE MINIMUM 5 GALLON CONTAINER AND PROVIDE TIMED FLOW TEST FOR ALL EYEWASHES AND EMERGENCY SHOWERS. SUBMIT REPORT TO ARCHITECT OR ENGINEER PRIOR TO FINAL INSPECTION.
- K. FIXTURES
- WC-1 WATER CLOSET (17-1/2" HIGH, FLOOR MOUNT, TANK TYPE):
1. KOHLER K-3658 VITREOUS CHINA, 1.28 GALLON FLUSH; PRESSURE ASSISTED CLOSE COUPLED TANK WITH ELONGATED BOWL.
 2. KOHLER K-7637 3/8" POLISHED CHROME ANGLE SUPPLY WITH STOP.
 3. BENEKE 627SS ELONGATED SELF-SUSTAINING WITH CHECK HINGES, OPEN FRONT, HEAVY DUTY SOLID PLASTIC SEAT.
- LAV-1 LAVATORY (ADA COMPLIANT, WALL HUNG):
1. KOHLER K-2005 WALL MOUNTED LAVATORY, VITREOUS CHINA, WITH OVER FLOW AND 4" FAUCET CENTERS, DRILLED FOR CONCEALED ARM CARRIER.
 2. ZURN Z-7443-VP SINGLE CONTROL FAUCET, LEVER HANDLE, 4" CENTER MOUNT, 1-1/4" GRID STRAINER.
 3. MCGUIRE 170 1/2" X 3/8" SWEAT LAVATORY SUPPLIES WITH WHEEL HANDLE STOPS.
 4. MCGUIRE 8902, 1-1/4 INCH X 1-1/2 INCH P-TRAP WITH ESCUTCHEON; ZURN GH, 1-1/4" OFFSET HANDICAP GRID DRAIN.
 5. TRAP AND SUPPLIES COVERED WITH TRAP WRAP EQUAL TO BROCHAR INDUSTRIES.
 6. ZURN Z-1231 LAVATORY CONCEALED ARM CARRIER.
- EW-1 EYE/FACE WASH (PEDESTAL MOUNT):
1. STAINLESS STEEL BOWL WITH TWIN EYEWASH HEADS WITH FLIP TOP COVERS, CHROME PLATED WATER EYEWASH ASSEMBLY.
 2. INCLUDE UNIVERSAL EMERGENCY SIGN CONFORMING TO ANSI Z53.1.
 3. INCLUDE MIXING VALVE/TEMPERED WATER BLENDING SYSTEM.
 4. EQUAL TO GUARDIAN G1825. CONFORM TO ANSI Z358.1.
- SK-1 LAUNDRY TUB (SINGLE COMPARTMENT):
1. FIAT MODEL NO. FL-1 SINGLE MOLDED STONE LAUNDRY TUB WITH FREE DRAINING SOAP TRAY ON BACK LEDGE. INCLUDE FOUR WHITE BAKED ENAMEL ANGLE LEGS THAT SLIP INTO MOLDED SOCKETS. SELF-LEVELING LEGS WITH FLOOR ANCHORS.
 2. FIAT MODEL A-1 BRASS FAUCET WITH SWING SPOUT.
 3. MCGUIRE 170 1/2" X 3/8" SWEAT LAVATORY SUPPLIES WITH WHEEL HANDLE STOPS.
 4. MCGUIRE #150 TRAY PLUG WITH RUBBER STOPPER (1-1/2").
 5. MCGUIRE #8912 1-1/2" X 1-1/2", 17 GAUGE BRASS P-TRAP.
- EW-1 WATER COOLER (WALL MOUNT, BOTTLE FILLING STATION, ADA):
1. ELKAY LZSTL6WSVRSK. HANDS FREE, ADA COMPLIANT DUAL STATION WITH BOTTLE FILLING STATION.
 2. MCGUIRE 8902 P-TRAP WITH ESCUTCHEON.
 3. MCGUIRE 170 STOP AND SUPPLY.
- L. ACCEPTABLE MANUFACTURERS: FIXTURES, VITREOUS CHINA - AMERICAN STANDARD, CRANE, ELJER, KOHLER. FIXTURES, STAINLESS STEEL - JUST, ELKAY. FLUSH VALVES - SLOAN, DELANEY. ZURN. TOILET SEATS - OLSONITE, SPERZEL, CHURCH, BENEKE, BEMIS. FAUCETS - T&S BRASS, SPEAKMAN, CHICAGO, SYMMONS, ELJER. TERRAZZO - FIAT, OUTLER, FLORESTONE, STERN-WILLIAMS. TRIM, CHROMED BRASS - MCGUIRE, SANITARY DASH, BRIDGEPORT. SHOWER MIXING VALVES - POWERS, LEONARD, LAWLOR, SYMMONS, SPEAKMAN, ZURN. SHOWER HEADS - SYMMONS, SPEAKMAN, ZURN. ELECTRIC WATER COOLERS - ELKAY, HALSEY TAYLOR, SUNROC, OASIS, HAWS. USE ONLY WATER COOLERS WHICH DO NOT USE CFC'S FOR REFRIGERATION. SCRUB SINKS - ELJER, AMERICAN STANDARD, KOHLER, CRANE CARRIERS - J. R. SMITH, JOSAM, ZURN, WADE. EMERGENCY EQUIPMENT - GUARDIAN, HAWS, WESTERN, SPEAKMAN.
- M. INSTALL PLUMBING FIXTURE LEVEL AND PLUMB, IN ACCORDANCE WITH FIXTURE MANUFACTURERS PUBLISHED LITERATURE, ROUGH-IN DRAWINGS, CODES REGULATIONS, AND REFERENCE STANDARDS. FASTEN PLUMBING FIXTURES SECURELY TO SUPPORTS OR BUILDING STRUCTURE. RIGIDLY SUPPORT WATER SUPPLIES BEHIND OR WITHIN WALL CONSTRUCTION. PROVIDE STOP VALVE IN THE WATER SUPPLY TO EACH FIXTURE IN AN ACCESSIBLE LOCATION. CONNECT WALLS HUNG URINALS TO WASTE PIPING WITH RED BRASS NIPPLES. CONNECT FIXTURES TO WATER SUPPLY WITH COPPER OR BRASS (NO STEEL). EACH FIXTURE, FLOOR DRAIN AND PIECE OF EQUIPMENT REQUIRING CONNECTION TO DRAINAGE SYSTEM TO HAVE SEPARATE TRAPS INSTALLED AS CLOSE TO FIXTURE AS POSSIBLE. PROVIDE IRON OR STEEL BACKING FOR ALL WALL MOUNTED FIXTURES (OR WOOD BACKING ONLY IF BUILDING STRUCTURE IS WOOD). PROVIDE ESCUTCHEONS AT EACH WALL, FLOOR AND CEILING. PENETRATION IN EXPOSED FINISHED LOCATIONS AND WITHIN CABINETS AND MILLWORK. APPLY SCP3154 PRIMER AND GENERAL ELECTRIC CO.'S NO. 1702 SILICONE SANITARY SEALANT AROUND PLUMBING FIXTURES TO CONCEAL VOIDS AT WALL AND CONTACT POINTS OF FIXTURE AFTER WALLS HAVE BEEN PAINTED. APPLY SCP3154 PRIMER AND GENERAL ELECTRIC CO.'S SILPRUF SEALANT ON PLAIN CONCRETE WALLS.

SECTION 15450 - PLUMBING EQUIPMENT

- A. ELECTRIC WATER HEATERS:
1. WATER HEATER SHALL COMPLY WITH UL 1453.
 2. STORAGE TANK CONSTRUCTION: ASME-CODE STEEL WITH 150 PSIG WORKING-PRESSURE RATING. STEEL JACKET WITH ENAMELED FINISH.
 3. TAPPINGS: FACTORY FABRICATED OF MATERIALS COMPATIBLE WITH TANK FOR PIPING CONNECTIONS, RELIEF VALVE, PRESSURE GAGE, THERMOMETER, DRAIN, ANODE RODS, AND CONTROLS AS REQUIRED. ATTACH TAPPINGS TO TANK SHELL BEFORE TESTING AND LABELING. TAPPINGS SHALL HAVE THREADED ENDS ACCORDING TO ASME B1.20.1. PIPE THREADS INTERIOR FINISH: MATERIALS AND THICKNESSES COMPLYING WITH NSF 61, BARRIER MATERIALS FOR POTABLE-WATER TANK LININGS. EXTEND FINISH INTO AND THROUGH TANK FITTINGS AND OUTLETS.
 4. INSULATION: COMPLY WITH ASHRAE 90.1. SURROUND ENTIRE STORAGE TANK EXCEPT CONNECTIONS AND CONTROLS.
 5. HEATING ELEMENTS: ELECTRIC, SCREW-IN OR BOLT-ON, IMMERSION TYPE. STAGING AS NOTED IN SCHEDULE.
 6. TEMPERATURE CONTROL: ADJUSTABLE IMMERSION THERMOSTAT.
 7. SAFETY CONTROLS: AUTOMATIC, HIGH-TEMPERATURE-LIMIT AND LOW-WATER CUTOFF DEVICES OR SYSTEMS.
 8. DRAIN VALVE: ASSE 1005 CORROSION-RESISTANT METAL, FACTORY INSTALLED.
 9. ANODE RODS: FACTORY INSTALLED, MAGNESIUM.
 10. DIP TUBE: FACTORY INSTALLED. NOT REQUIRED IF COLD-WATER INLET IS NEAR BOTTOM OF STORAGE TANK.
 11. SPECIAL REQUIREMENT: NSF 5 CONSTRUCTION.
 12. ACCEPTABLE MANUFACTURERS ARE LOCHINVAR, A. O. SMITH, OR PRIOR APPROVAL EQUAL.
- B. THERMAL EXPANSION TANK (DOMESTIC WATER):
1. PRE-CHARGED HYDRO-PNEUMATIC STEEL EXPANSION TANK, CONSTRUCTED IN ACCORDANCE WITH SECTION VIII OF ASME BOILER AND PRESSURE CODE, WITH ALL WELDS CONFORMING TO ASME SECTION IX. TANK MUST BE STAMPED WITH A MAXIMUM WORKING PRESSURE OF 125 PSI, AND A MAXIMUM WORKING TEMPERATURE OF 200 DEGREES F. ALL INTERNAL WETTED PARTS MUST COMPLY WITH FDA REGULATIONS AND APPROVALS. AN INTERNAL BUTYL DIAPHRAGM WILL BE USED TO ISOLATE AIR FROM WATER. AMTROL OR APPROVED EQUAL AST SERIES.



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



Express Oil Change & Tire Engineers

Left Hand Oil Change Building


Northport, Alabama

FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Plumbing Specifications


Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB
P0.03	
Scale	12" = 1'-0"



MAIN FLOOR PLAN
PLUMBING - GRAVITY
1/4" = 1'-0"

GENERAL NOTES:

- SPACE ABOVE CEILING IS LIMITED. CAREFUL COORDINATION WITH LIGHTING, ELECTRICAL, MECHANICAL, FIRE PROTECTION, STRUCTURAL AND ARCHITECTURAL WORK IS CRITICAL FOR COMPLETE PIPING INSTALLATION. CONTRACTOR SHALL PROVIDE NECESSARY OFFSETS IN NEW AND EXISTING PIPING AND ELECTRICAL CONDUIT AS REQUIRED TO ACCOMMODATE NEW WORK. CONTRACTOR SHALL ALLOW FOR ANY CONFLICTS ENCOUNTERED.
- PIPING LAYOUTS ARE DIAGRAMMATIC AND DO NOT SHOW ALL ELEMENTS OF CONSTRUCTION. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CHANGES ON DIRECTION, ELEVATION AND MINOR OFFSETS NECESSARY FOR COMPLETE INSTALLATION OF ELEMENTS SHOWN.
- ALL WASTE PIPING SHOWN IS BELOW FINISHED FLOOR UNLESS OTHERWISE NOTED. ALL VENT PIPING SHOWN IS ABOVE CEILING UNLESS OTHERWISE NOTED.
- REFER TO ARCHITECTURAL REFLECTED CEILING PLANS FOR LOCATIONS OF ALL CEILING MOUNTED DEVICES. REFER TO ARCHITECTURAL FLOOR PLANS FOR ALL DIMENSIONS.
- COORDINATE ACCESS DOOR LOCATIONS WITH GENERAL CONTRACTOR AND ARCHITECT.



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



www.ahoarch.com



11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Plumbing Floor
Plan Gravity

Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB

P1.01


Scale As indicated



MAIN FLOOR PLAN
PLUMBING - PRESSURE
1/4" = 1'-0"

GENERAL NOTES:

- SPACE ABOVE CEILING IS LIMITED. CAREFUL COORDINATION WITH LIGHTING, ELECTRICAL, MECHANICAL, FIRE PROTECTION, STRUCTURAL AND ARCHITECTURAL WORK IS CRITICAL FOR COMPLETE PIPING INSTALLATION. CONTRACTOR SHALL PROVIDE NECESSARY OFFSETS IN NEW AND EXISTING PIPING AND ELECTRICAL CONDUIT AS REQUIRED TO ACCOMMODATE NEW WORK. CONTRACTOR SHALL ALLOW FOR ANY CONFLICTS ENCOUNTERED.
- PIPING LAYOUTS ARE DIAGRAMMATIC AND DO NOT SHOW ALL ELEMENTS OF CONSTRUCTION. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CHANGES ON DIRECTION, ELEVATION AND MINOR OFFSETS NECESSARY FOR COMPLETE INSTALLATION OF ELEMENTS SHOWN.
- ALL PRESSURE PIPING SHOWN IS ABOVE THE CEILING UNLESS OTHERWISE NOTED.
- REFER TO ARCHITECTURAL REFLECTED CEILING PLANS FOR LOCATIONS OF ALL CEILING MOUNTED DEVICES. REFER TO ARCHITECTURAL FLOOR PLANS FOR ALL DIMENSIONS.
- COORDINATE ACCESS DOOR LOCATIONS WITH GENERAL CONTRACTOR AND ARCHITECT.
- EXPOSED DOMESTIC WATER PIPING SHALL BE TYPE K COPPER. PIPING WITHIN WALLS AND CEILINGS SHALL BE PERMITTED TO BE PEX.
- ALL ABOVE GROUND COMPRESSED AIR PIPING SHALL BE BLACK STEEL.
- PRESSURE REGULATORS FOR GAS PIPING SHALL BE EQUAL TO MAXITROL 325 SERIES.



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Plumbing Floor
Plan Pressure


Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB

P1.02

Scale As indicated



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



www.ahoarch.com



11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Partial Plumbing
Floor Plans - Pit
and Platform

Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB

P1.03


Scale As indicated




PIT FLOOR PLAN PLUMBING
1/4" = 1'-0"
NORTH

GENERAL NOTES:

- SPACE ABOVE CEILING IS LIMITED. CAREFUL COORDINATION WITH LIGHTING, ELECTRICAL, MECHANICAL, FIRE PROTECTION, STRUCTURAL AND ARCHITECTURAL WORK IS CRITICAL FOR COMPLETE PIPING INSTALLATION. CONTRACTOR SHALL PROVIDE NECESSARY OFFSETS IN NEW AND EXISTING PIPING AND ELECTRICAL CONDUIT AS REQUIRED TO ACCOMMODATE NEW WORK. CONTRACTOR SHALL ALLOW FOR ANY CONFLICTS ENCOUNTERED.
- PIPING LAYOUTS ARE DIAGRAMMATIC AND DO NOT SHOW ALL ELEMENTS OF CONSTRUCTION. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CHANGES ON DIRECTION, ELEVATION AND MINOR OFFSETS NECESSARY FOR COMPLETE INSTALLATION OF ELEMENTS SHOWN.
- ALL PRESSURE PIPING SHOWN IS ABOVE THE CEILING UNLESS OTHERWISE NOTED. ALL TRAP PRIMER LINES AND HOT WATER RETURN LINES SHALL BE 1/2" UNLESS OTHERWISE NOTED.
- REFER TO ARCHITECTURAL REFLECTED CEILING PLANS FOR LOCATIONS OF ALL CEILING MOUNTED DEVICES. REFER TO ARCHITECTURAL FLOOR PLANS FOR ALL DIMENSIONS.
- COORDINATE ACCESS DOOR LOCATIONS WITH GENERAL CONTRACTOR AND ARCHITECT.




EQUIPMENT PLATFORM -
PLUMBING
1/4" = 1'-0"
NORTH



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



www.ahoarch.com



11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama


FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Gravity Riser

Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB
P2.01	
Scale	




1 Gravity Riser
P2.01



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



www.ahoarch.com



11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Pressure Riser


Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB

P2.02


Scale




2 Pressure Riser
P2.02




5 DOMESTIC WATER ENTRANCE DETAIL
NO SCALE




6 OIL SEPERATOR DETAIL
1/2" = 1'-0"




3 TYPICAL LAVATORY MIXING VALVE
SCALE: NONE




4 WALL CLEANOUT
NO SCALE



1 TYPICAL GAS CONNECTION
NO SCALE



2 ELECTRIC WATER HEATER (FLOOR MOUNTED)
NO SCALE



7 RADIANT HEATER GAS CONNECTION DETAIL
NO SCALE



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



www.ahoarch.com



11/8/24

Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Plumbing Details

Project number	24028
Date	11/8/2024
Drawn by	CA
Checked by	JB

P2.03

Scale As indicated

11/7/2024 4:32:49 PM

LIGHTING FIXTURE SCHEDULE

TYPE	MANUFACTURER	CATALOG NUMBER	LAMPS			MTG. TYPE	MTG. HT.	REC. DEPTH	DESCRIPTION
			QUANTITY	WATTS	TYPE				
L1P	MAXLITE	(2)VT-4850U-40, VT-CONKIT, VT-ENDBRKT, (2)MLCHKLSV15	4	100	LED	P	15'5" AFF	-	CONTINUOUS RUN OF (2) 4' LONG LINEAR LED FIXTURES WITH ALUMINUM VAPOR TIGHT HOUSING, 7600 LUMEN OUTPUT, 4000K COLOR TEMPERATURE. PROVIDE ALL REQUIRED ACCESSORIES FOR SUSPENDED MOUNTING. NOTE 1
	APPROVED EQUAL								
L2	MAXLITE	VT-4850U-40	13	50	LED	S	C	-	4' LINEAR LED FIXTURE, SURFACE MOUNTED WITH ALUMINUM VAPOR TIGHT HOUSING, 5700 LUMEN OUTPUT, 4000K COLOR TEMPERATURE. PROVIDE ALL REQUIRED ACCESSORIES FOR SURFACE MOUNTING. SEE LIGHTING PLANS FOR LOCATIONS AND QUANTITIES. NOTE 1
	APPROVED EQUAL								
L2P	MAXLITE	VT-4850U-40 MLCHKLSV15	8	50	LED	P	15'5" AFF	-	4' LINEAR LED FIXTURE, PENDANT MOUNTED WITH ALUMINUM VAPOR TIGHT HOUSING, 5700 LUMEN OUTPUT, 4000K COLOR TEMPERATURE. PROVIDE ALL REQUIRED ACCESSORIES FOR SUSPENDED MOUNTING. SEE LIGHTING PLANS FOR LOCATIONS AND QUANTITIES. NOTE 1
	APPROVED EQUAL								
L3	MAXLITE	LSU4U3540	16	35	LED	S	C	-	4' SURFACE MOUNTED LED WRAPAROUND FIXTURE WITH CURVED PRISMATIC LENS, STEEL HOUSING, 4000K COLOR TEMPERATURE, 4253 LUMEN OUTPUT.
	APPROVED EQUAL								
L3E	MAXLITE	LSU4U3540EM	7	35	LED	S	C	-	4' SURFACE MOUNTED LED WRAPAROUND FIXTURE WITH CURVED PRISMATIC LENS, STEEL HOUSING, 4000K COLOR TEMPERATURE, 4253 LUMEN OUTPUT, AND EMERGENCY BATTERY PACK.
	APPROVED EQUAL								
L4	MAXLITE	M40U4W-CSBWCR MYCL40-55W	4	38	LED	W	12' AFF	-	FIXED WALL MOUNTED LED FIXTURE WITH BLACK FINISH, DIE-CAST ALUMINUM HOUSING, SELECTABLE COLOR TEMPERATURE, 3512 LUMEN OUTPUT, WIDE DISTRIBUTION. UL LISTED FOR WET LOCATION. NOTE 4.
	APPROVED EQUAL								
L4E	MAXLITE	M40U4W-CSBWCREO MYCL40-55W	2	38	LED	W	12' AFF	-	FIXED WALL MOUNTED LED FIXTURE WITH BLACK FINISH, DIE-CAST ALUMINUM HOUSING, SELECTABLE COLOR TEMPERATURE, 3512 LUMEN OUTPUT, WIDE DISTRIBUTION, ELECTRONIC DRIVER, AND EMERGENCY BATTERY PACK. UL LISTED FOR WET LOCATION. NOTE 4.
	APPROVED EQUAL								
L5	PROVIDED BY GENERAL CONTRACTOR		FURNISHED WITH UNIT			R	C	-	RECESSED LED DOWNLIGHT WITH 4000K COLOR TEMPERATURE, 3000 LUMEN OUTPUT, AND EMERGENCY BATTERY PACK. UL LISTED FOR WET LOCATION. FIXTURES ARE PROVIDED BY GENERAL CONTRACTOR AS PART OF THE METAL AWNING SYSTEM.
	PROVIDED BY GENERAL CONTRACTOR								
	PROVIDED BY GENERAL CONTRACTOR								
S1	PROVIDED BY SIGN MANUFACTURER		FURNISHED WITH UNIT			W	NOTE 3	-	WALL MOUNTED LED SIGN LIGHTING FIXTURE. NOTE 2.
	PROVIDED BY SIGN MANUFACTURER								
	PROVIDED BY SIGN MANUFACTURER								
S2	PROVIDED BY SIGN MANUFACTURER		FURNISHED WITH UNIT			W	NOTE 3	-	WALL MOUNTED LED LIGHT FIXTURE. NOTE 2.
	PROVIDED BY SIGN MANUFACTURER								
	PROVIDED BY SIGN MANUFACTURER								
S3	PROVIDED BY SIGN MANUFACTURER		FURNISHED WITH UNIT			W	NOTE 3	-	LED LIGHT BAR. NOTE 2.
	PROVIDED BY SIGN MANUFACTURER								
	PROVIDED BY SIGN MANUFACTURER								
W1	MAXLITE	LSV2U20WCSCR	1	30	LED	W	8' AFF	-	2' LONG LINEAR LED SURFACE MOUNTED FIXTURE WITH ALUMINUM VAPOR TIGHT HOUSING, SELECTABLE WATTAGE, 4000 LUMEN OUTPUT, 4000K SELECTABLE COLOR TEMPERATURE, UNIVERSAL VOLTAGE, MOTION SENSOR AND EMERGENCY BATTERY PACK.
	APPROVED EQUAL								
BL	LITHONIA	ELM6L	FURNISHED WITH UNIT			W	9' AFF	-	WALL MOUNTED TWO HEAD LED EMERGENCY FIXTURE WITH WHITE THERMOPLASTIC HOUSING, 1100 LUMEN OUTPUT, SELF DIAGNOSTICS, AND EMERGENCY BATTERY PACK.
	APPROVED EQUAL								
XL	MAXLITE	EX-GW	FURNISHED WITH UNIT			W	AD	-	WHITE THERMOPLASTIC LED EXIT SIGN WITH SINGLE FACE, GREEN LETTERS, UNIVERSAL MOUNTING, SELF DIAGNOSTICS, AND EMERGENCY BATTERY PACK.
	APPROVED EQUAL								

ABBREVIATIONS: LI-LAY-IN C-CEILING LG-LENS GASKETING GMF-INTERNAL SLOW BLOW FUSE FL-FLUORESCENT MH-METAL HALIDE HO-HIGH OUTPUT
AFF-ABOVE FINISH FLOOR P-PENDENT FC-FROM CEILING R-RECESSED AM-ABOVE MIRROR W-WALL AD-ABOVE DOOR
S-SURFACE DTT-DOUBLE TWIN TUBE FLUORESCENT CA-CANOPY TC-TOP OF METAL CANOPY AW-ABOVE WINDOW VA-VERIFY WITH ARCHITECT

LIGHTING FIXTURE SCHEDULE GENERAL NOTES:

- FIXTURE OUTLET BOX LOCATIONS SHOWN ON THE DRAWINGS ARE DIAGRAMMATIC AND APPROXIMATE IN LOCATION. EXACT POSITION OF THE OUTLET BOX SHALL DEPEND ON THE FIXTURE AND THE MOUNTING DETAIL.
- MOUNTING AND SUPPORT DETAILS FOR LIGHTING FIXTURES SHALL BE SUBMITTED TO AND APPROVED BY THE ENGINEER BEFORE THE FIXTURES ARE INSTALLED. NO COMBUSTIBLE MATERIALS SHALL BE USED.
- WET LOCATION FIXTURES SHALL BE MOUNTED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATION SO AS TO ENSURE THE PREVENTION OF MOISTURE FROM ENTERING THE FIXTURE. IN ADDITION, EACH CONDUIT ENTRY WILL BE SEALED BY USE OF AN APPROVED SWEDGE FITTING WITH A NEOPRENE SEAL, AS MANUFACTURED BY JOHN REMKE COMPANY OR APPROVED EQUAL.
- OUTLET BOXES SERVING WET LOCATION FIXTURE SHALL BE CODE SIZE, WITH A WATERTIGHT SOLID CAST TOP. CONDUIT ENTRIES SHALL BE THREADED.
- FIXTURE MOUNTING HEIGHTS IN SCHEDULE ARE TYPICAL UNLESS NOTED OTHERWISE ON DRAWINGS.
- FOR LIGHTING PACKAGE PRICING, CONTACT THE FOLLOWING:

MIKE MCMAKEN
REXEL ENERGY SOLUTIONS
(M) 906-235-2979
MIKE.MCMAKEN@REXELENERGY.COM


STEPHEN MITCHELL
MAXLITE
(M) 908-256-3115
SMITCHELL@MAXLITE.COM

LIGHTING FIXTURE SCHEDULE NOTES:

- SEE MOUNTING DETAIL ON THIS SHEET FOR MORE INFORMATION.
- INSTALLED BY SIGN COMPANY.
- VERIFY MOUNTING HEIGHT WITH SIGN COMPANY BEFORE ROUGHING IN.
- FIXTURE SHALL BE MOUNTED SO THAT THE TOP OF THE FIXTURE IS AT 12' AFF TO ALIGN WITH BANDING ON EXTERIOR OF BUILDING.

GENERAL NOTES:

- VERIFY ALL DOOR SWINGS WITH ARCHITECTURAL BEFORE ROUGHING IN LIGHT SWITCHES TO ENSURE PROPER SWITCH LOCATION. VERIFY ALL CASEWORK DETAILS TO ENSURE THAT ALL OUTLETS ABOVE CASEWORK ARE AT THE PROPER HEIGHT.
- SERVICE TO THE BUILDING SHALL BE 120/240 VOLTS, 1PHASE, 3WIRE. CONTRACTOR SHALL VERIFY AVAILABLE VOLTAGE WITH UTILITY COMPANY PRIOR TO BID.
- ALL CONDUIT SHALL BE RUN CONCEALED UNLESS SPECIFICALLY SHOWN EXPOSED, OR INSTALLED IN EXPOSED CEILING.
- THE CONTRACTOR SHALL CHECK ALL LIGHTING FIXTURES FOR EXACT TYPE MOUNTING AND SPACE REQUIRED BEFORE ROUGHING IN.
- THE CONTRACTOR SHALL WORK CLOSELY WITH THE GENERAL CONTRACTOR AND VERIFY EXACT TYPE OF EQUIPMENT TO BE INSTALLED AND THE DIMENSIONS WHICH MAY AFFECT THE EXACT PLACEMENT OF ELECTRICAL WORK.
- VERIFY THE EXACT LOCATION OF ALL MOTORS AND EQUIPMENT BEFORE ROUGHING IN. LIKEWISE APPRAISE ALL TRADES OF THE LOCATIONS OF ELECTRICAL WORK THAT AFFECTS WALL THICKNESS, PLUMBING, MECHANICAL, ETC.
- ALL CONDUIT STUBBED OUT FOR FUTURE SHALL BE CAPPED AND HAVE LOCATION MARKED WITH A 2" SQUARE, PAINTED RED, WITH CONDUIT NAME AND SIZE SHOWN IN WHITE.
- ALL BRANCH CIRCUITS AND FEEDERS SHALL HAVE AN INSULATED GROUND WIRE PULLED IN THE CONDUIT WITH CURRENT CONDUCTOR UNLESS SPECIFICALLY NOTED OTHERWISE ON THE PLANS. THE GROUNDING CONDUCTOR SHALL BE SIZED ACCORDING TO TABLE 250-122 OF THE LATEST EDITION OF THE NATIONAL ELECTRICAL CODE UNLESS INDICATED TO BE LARGER IN THE SPECIFICATIONS OR PLANS.
- DO ALL WORK IN COMPLIANCE WITH ALL APPLICABLE CODES, LAWS AND ORDINANCES, THE NATIONAL ELECTRICAL CODE (HEREINAFTER REFERRED TO AS "CODE" OR "NEC"), THE AMERICANS WITH DISABILITIES ACT, AND THE REGULATIONS OF THE LOCAL AUTHORITIES HAVING JURISDICTION AND, WHERE APPLICABLE, UTILITY COMPANIES. OBTAIN AND PAY FOR ANY AND ALL REQUIRED PERMITS, INSPECTIONS, CERTIFICATES OF INSPECTIONS AND APPROVAL, AND THE LIKE, AND DELIVER SUCH CERTIFICATES TO THE OWNER.
- THE MAIN SERVICE SHALL HAVE THE GROUNDED CONDUCTOR (NEUTRAL) GROUNDED TO THE GROUNDING ELECTRODE SYSTEM AT THE SUPPLY SIDE OF THE SERVICE DISCONNECTING MEANS BY A GROUNDING ELECTRODE CONDUCTOR NOT SMALLER THAN THAT SHOWN IN TABLE 250-66 OF THE NEC. THE GROUNDED CONDUCTOR (NEUTRAL), THE GROUNDING ELECTRODE CONDUCTOR, AND THE EQUIPMENT GROUNDING CONDUCTOR CONNECTIONS SHALL BE MADE INSIDE THE SERVICE ENTRANCE EQUIPMENT.
- ALL CONDUCTORS SHALL BE COPPER, EXCEPT WHERE SHOWN ON DRAWINGS TO BE ALUMINUM.
- MINIMUM CONDUCTOR SIZE SHALL BE #12.
- ALL CONDUIT INSTALLED INDOORS SHALL BE EMT, OTHERWISE SHALL BE IMC.
- SWITCH AND RECEPTACLE COVER PLATES SHALL BE STAINLESS STEEL.
- ALL DEVICES SHALL BE GRAY.
- ALL FUSES SHALL BE DUAL ELEMENT, TIME DELAY, RATED 100,000 AIC.
- ALL DISCONNECT SWITCHES SHALL BE HEAVY DUTY TYPE.
- ALL CONDUCTORS SHALL BE DUAL RATED THHN/THWN TYPE INSULATION.
- GUTTERS (WIREWAYS) SHALL BE SIZED AS SHOWN OR AS REQUIRED BY CODE. ALL GUTTERS SHALL HAVE HINGED COVERS WITH APPROVED FASTENING DEVICES & SHALL BE A STANDARD MANUFACTURED ITEM WITH U.L. LABEL. GUTTERS FROM AC DUCT MATERIAL ARE NOT ACCEPTABLE. GUTTERS SHALL BE AS MANUFACTURED BY HOFFMAN, SQUARE "D", B & C OR APPROVED EQUAL. GUTTER TAPS SHALL BE ILSCO TYPE GTA OF PTA WITH GTC OR PTC INSULATING COVERS.
- IT SHALL BE THE RESPONSIBILITY OF THIS CONTRACTOR, PRIOR TO BID, TO REAFFIRM WITH THE UTILITY COMPANIES INVOLVED, THAT THE LOCATION, ARRANGEMENT (AND THE POWER COMPANY: VOLTAGE, PHASE & METERING REQUIRED) AND CONNECTIONS AT THE UTILITY SERVICE ARE IN ACCORDANCE WITH THEIR REGULATIONS & REQUIREMENTS. IF THEIR REQUIREMENTS ARE AT A VARIANCE WITH THESE DRAWINGS & SPECIFICATIONS, THE CONTRACT PRICE SHALL INCLUDE ANY ADDITIONAL COST NECESSARY TO MEET THOSE REQUIREMENTS WITHOUT EXTRA COST TO THE OWNER AFTER A CONTRACT HAS BEEN ENTERED INTO.
- ON MANY PROJECTS, THE UTILITY COMPANY MAY LEVY CHARGES DUE TO LOCATION, SIZE OR TYPE OF SERVICE INVOLVED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THESE CHARGES, UNLESS SUCH CHARGES ARE NOT AVAILABLE PRIOR TO BID & CONTRACTOR SO DOCUMENTS AT BID OPENING. SHOULD THE THE COST NOT BE AVAILABLE, PRIOR TO BID, THE CONTRACTOR SHALL SUBMIT A LETTER SO STATING WITH HIS BID.
- ARRANGE WITH UTILITY COMPANIES FOR SUCH SERVICE AS SHOWN OR HEREIN SPECIFIED & INSTALLATION OF METER WHERE SHOWN. FURNISH WITH SHOP DRAWINGS, A SIGNED DOCUMENT FROM UTILITY COMPANIES DESCRIBING THE LOCATION & TYPE OF SERVICES TO BE FURNISHED AND ANY REQUIREMENTS THEY MAY HAVE. THIS DOCUMENT SHALL BE SIGNED FOR EACH UTILITY COMPANY BY A PERSON RESPONSIBLE FOR GRANTING SUCH SERVICES.
- PAY ALL CHARGES (IF ANY) IN CONNECTION THEREWITH, INCLUDING PERMANENT METER DEPOSIT. METER DEPOSIT WILL BE REFUNDED TO THE CONTRACTOR AT TIME OF OWNER'S ACCEPTANCE.



DETAIL
FIXTURE "L1" & "L2" MOUNTING
NOT TO SCALE

GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWMAAE@GW-ENG.COM | 205.413.4112
THWGNBOTHAM@GW-ENG.COM | 205.317.3969



Express Oil Change & Tire Engineers

Left Hand Oil Change Building








Northport, Alabama





FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.













General Notes & Fixture Schedules	
Project number	24028
Date	11/8/2024
Drawn by	TH
Checked by	GW
E100	
Scale	NO SCALE

GRAPHICAL ELECTRICAL SYMBOLS

BRANCH CIRCUIT SYMBOLS		
	BRANCH CIRCUIT	HOMERUN TO 20A, 1POLE CIRCUIT BREAKER IN PANELBOARD OR DEVICE NOTED. WIRE SIZE IS 2#12&1#12GRD-3/4"C.
	BRANCH CIRCUIT	CONCEALED IN CEILING OR WALL.
	BRANCH CIRCUIT	CONCEALED IN FLOOR.
	BRANCH CIRCUIT	EXISTING CONDUIT BARS DENOTE NEW CONDUCTORS.
	BRANCH CIRCUIT	EXPOSED.
	BRANCH CIRCUIT	RISER UP.
	BRANCH CIRCUIT	RISER DOWN.

BRANCH CIRCUIT NOTES		
	BRANCH CIRCUIT	3#12&1#12GRD-3/4"C
	BRANCH CIRCUIT	4#12&1#12GRD-3/4"C
	BRANCH CIRCUIT	2#10&1#10GRD-3/4"C
	BRANCH CIRCUIT	3#10&1#10GRD-3/4"C






SIZE CONDUIT PER MC FOR GREATER NUMBER OF CONDUCTORS OR AS NOTED. THE NUMBER IN THE CIRCUIT INDICATES AWG WIRE SIZE AND THE HASHMARKS INDICATE THE NUMBER OF WIRES REQUIRED. EQUIPMENT GROUND CONDUCTOR SHALL BE SIZED IN ACCORDANCE WITH NEC TABLE 250-122. THE NUMBER OF HASH MARKS DO NOT INCLUDE EQUIPMENT GROUNDING CONDUCTOR.








GENERAL SYMBOLS	
	JUNCTION BOX.
	WALL MOUNTED JUNCTION BOX.
	WALL MOUNTED JUNCTION BOX WITH FLEXIBLE CONNECTION TO EQUIPMENT.
	TWO GANG BOX WITH 3/4" C. STUB UP ABOVE ACCESSIBLE CEILING WITH COAXIAL CABLE AND TV JACKS. HOMERUN COAXIAL CABLE TO TBB.
	MANUAL MOTOR STARTER WITH THERMAL PROTECTION.
	SAFETY SWITCH, NON-FUSED.
	SAFETY SWITCH, FUSED.
	CIRCUIT BREAKER MOUNTED IN NEMA 1 ENCLOSURE UNLESS NOTED OTHERWISE
	LIGHTING PANEL AND/OR RECEPTACLE PANEL.
	POWER PANEL.
	TRANSFORMER.
	GROUND.

GENERAL ABBREVIATIONS	
H	MOUNTING HEIGHT ABOVE FINISHED FLOOR.
AF	ABOVE FINISHED FLOOR.
WP	WEATHER PROOF - NEMA 3R
RT	RAIN TIGHT - NEMA 4.
EP	EXPLOSION PROOF.
TP	TAMPER PROOF.
A	MOUNT ABOVE COUNTER.
BC	MOUNT BELOW COUNTER.
F	FLUSH MOUNTED.
SLD	SEE SINGLE LINE DIAGRAM.
GFI	GROUND FAULT INTERRUPTING.
C	CONDUIT.
EC	EMPTY CONDUIT
GC	FLEXIBLE CONDUIT.
SFC	SEALTITE FLEXIBLE CONDUIT.
EMT	ELECTRICAL METALLIC TUBING.
IMT	INTERMEDIATE METALLIC CONDUIT.
RG	RIGID CONDUIT.
PVC	NONMETALLIC RIGID CONDUIT.
EX	EXISTING.
XR	EXISTING TO BE REMOVED
RL	EXISTING TO BE REMOVED AND RELOCATED.
RQ	EXISTING TO BE REMOVED. EXTEND CIRCUIT CONDUCTORS AS REQUIRED AND INSTALL FINISHED BLANK COVER.
RR	EXISTING TO BE REMOVED AND REPLACED WITH NEW.
RL'D	RELOCATED POSITION.
EM	EMERGENCY BATTERY PACK



LIGHTING FIXTURE & CONTROL SYMBOLS		
	CEILING OUTLET	FIXTURE TYPE "A" CIRCUIT #1.
	CEILING OUTLET	EXISTING.
	CEILING OUTLET	FLUORESCENT FIXTURE, SINGLE OR CONTINUOUS, LENGTHS AS SHOWN.
	CEILING OUTLET	FLUORESCENT STRIP.
	WALL OUTLET	BRACKET TYPE FIXTURE.
	WALL OUTLET	FLUORESCENT BRACKET TYPE FIXTURE.
	WALL OUTLET	A.C. TYPE, SINGLE POLE, 20A, 125/277V.
	WALL OUTLET	A.C. TYPE, THREE WAY, 20A, 125/277V.
	WALL OUTLET	A.C. TYPE, FOUR WAY, 20A, 125/277V.
	WALL OUTLET	180° DUAL TECH SENSOR LIGHTING MOTION DETECTOR, WALL MOUNTED. WATT STOPPER #DW-100.
	CEILING OUTLET	LIGHTING MOTION DETECTOR POWER PACK. INSTALL ABOVE ACCESSIBLE CEILING.
	SWITCH OUTLET	0-10V DIMMER UNLESS OTHERWISE NOTED.
	CEILING OUTLET	LIGHTING MOTION DETECTOR, CEILING MOUNTED.

SWITCH OUTLET NOTES	
"a" "b" ETC.	FIXTURE CORRESPONDS TO A SWITCH DENOTED WITH THE SAME LOWER CASE LETTER.

EXIT LIGHT SYMBOLS	
	WALL OR CEILING MOUNTED, SINGLE FACE, NO ARROW.
	CEILING MOUNTED, DOUBLE FACE, LEFT OR RIGHT ARROWS.
	WALL OR CEILING MOUNTED, SINGLE FACE, LEFT OR RIGHT ARROW.
	WALL OR CEILING MOUNTED, SINGLE FACE, LEFT AND RIGHT ARROWS.
	CEILING MOUNTED, DOUBLE FACE, LEFT AND RIGHT ARROWS.


RECEPTACLE OUTLET SYMBOLS		
	WALL OUTLET	DUPLEX RECEPTACLE, 20A, 125V, 3WIRE, NEMA 5-20R.
	WALL OUTLET	DOUBLE DUPLEX RECEPTACLE, 20A, 125V, 3WIRE, NEMA 5-20R, SINGLE PLATE.
	WALL OUTLET	DUPLEX RECEPTACLE, 20A, 125V, NEMA 5-20R, GFCI, WEATHER-RESISTANT, WITH EXTRA DUTY IN-USE WEATHERPROOF COVER.
	WALL OUTLET	SINGLE RECEPTACLE, 20A, 250V, 3WIRE, NEMA 6-20R.
	WALL OUTLET	SINGLE RECEPTACLE, 20A, 250V, 3WIRE, NEMA L6-20R.
	FLOOR OUTLET	FLUSH MOUNTED IN-GRADE WITH DOUBLE DUPLEX RECEPTACLE, 20A, 125V, 3WIRE, NEMA 5-20R, FOUR SPACES FOR KEYSTONE CONNECTORS, AND BRUSHED BRASS COVER.
	CEILING OUTLET	DUPLEX RECEPTACLE, 20A, 125V, 3WIRE, NEMA 5-20R.

RECEPTACLE OUTLET NOTES	
"G"	GROUND FAULT INTERRUPTER.
"GA"	GROUND FAULT INTERRUPTER, MOUNTED ABOVE COUNTER.
"A"	MOUNTED ABOVE COUNTER.
"BC"	MOUNTED BELOW COUNTER.
"DF"	FOR DRINKING FOUNTAIN.

VOICE/DATA OUTLET & CONDUIT SYMBOLS		
	VOICE/DATA OUTLET	WALL MOUNTED, WITH 3/4" CONDUIT HOMERUN TO NEAREST TELEPHONE CABINET OR BACKBOARD UNLESS NOTED OTHERWISE.
	VOICE/DATA OUTLET	TELEPHONE BACKBOARD – 3/4" PLYWOOD PAINTED WITH TWO COATS OF FIRE RETARDANT PAINT, 48"x96" HIGH, UNLESS SHOWN OTHERWISE.
VOICE/DATA OUTLET NOTES		
"A"	MOUNTED ABOVE COUNTER.	
"BC"	MOUNTED BELOW COUNTER.	

NOTES:

1. INDICATED MOUNTING HEIGHTS ARE FROM FINISHED FLOOR TO CENTERLINE OF OUTLET BOX, UNLESS OTHERWISE NOTED.
2. REFER TO ARCHITECTURAL DETAILS FOR ADDITIONAL REQUIREMENTS.
3. INSTALL OUTLETS THAT ARE IN CLOSE PROXIMITY ON THE SAME CENTERLINE.
4. MOUNTING HEIGHTS SHOWN HERE ARE TYPICAL UNLESS NOTED OTHERWISE ON DRAWINGS.



DETAIL
TYPICAL MOUNTING
HEIGHTS
NOT TO SCALE



AHO ARCHITECTS, LLC

www.ahoarch.com



Express Oil Change & Tire Engineers
Left Hand Oil Change Building

Northport, Alabama

FINAL

[illegible]

© 2024 Aho Architects, LLC.
All Rights Reserved.

Symbol Legends and Details

Project number	24028
Date	11/8/2024

Drawn by	TH
Checked by	GW

E101




Scale	NO SCALE
-------	----------

GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35172
 GWAMAE@GW-ENG.COM | 205.413.4112
 THIGGINBOTHAM@GW-ENG.COM | 205.317.3969

NOTES:


- 48"x48" FREE STANDING TELEPHONE BACKBOARD. PROVIDE ACCESS AS REQUIRED BY CLEAR COM.
- CONDUIT ELBOWS SHALL BE SWEEPING WITH NO HARD ANGLES.




DETAIL
ARC FLASH HAZARD WARNING LABEL
NOT TO SCALE

GENERAL NOTES:

- COORDINATE SECONDARY SERVICE REQUIREMENTS WITH POWER COMPANY BEFORE BID. PROVIDE PER POWER COMPANY REQUIREMENTS.
- EQUIPMENT WITH ALUMINUM FEEDERS SHALL BE PROVIDED WITH DUAL RATED TERMINALS.
- SERVICE ENTRANCE RATED DISCONNECT SWITCH, NEMA 3R ENCLOSURE.
- COORDINATE METERING WITH POWER COMPANY BEFORE ROUGHING IN.
- SERVICE DISCONNECTS SHALL BE MOUNTED SUCH THAT CENTER OF OPERATING HANDLE SHALL NOT BE LESS THAN 4' AND NOT MORE THAN 6'-7" ABOVE GRADE.
- PROVIDE ENGRAVED LABEL INDICATING MAXIMUM AVAILABLE FAULT CURRENT AND DATE OF CALCULATION. SEE DETAIL ON SHEET OC-E103.
- PROVIDE LABEL INDICATING LOCATION OF SERVICE DISCONNECT "FED FROM SERVICE DISCONNECT # 1, LOCATED AT EXTERIOR OF OIL CHANGE BUILDING."
- PROVIDE LABEL INDICATING LOCATION OF SERVICE DISCONNECT "FED FROM SERVICE DISCONNECT #2, LOCATED AT EXTERIOR OF OIL CHANGE BUILDING."
- PROVIDE LABEL "SERVICE DISCONNECT SWITCH #1 FOR OIL CHANGE BUILDING."
- PROVIDE LABEL "SERVICE DISCONNECT SWITCH #2 FOR SERVICE BUILDING."
- GROUND TO EQUIPMENT GROUND BUS BAR ONLY. DO NOT GROUND NEUTRAL.




PANEL LOAD SUMMARY													
Panel: PP													
Equipment	LIGHT & CONT.	RCPT	O/M	CB SIZE	CIRCUIT #	PHASE A	PHASE B	CIRCUIT #	CB SIZE	LIGHT & CONT.	RCPT	O/M	Equipment
WAITING/WRITING ETC. LTG.	480			20/1	1	1204		2	20/1	724			OIL CHANGE LIGHTING
	540			20/1	3		840	4	20/1	300			SIGN LIGHTING
EQUIPMENT PLATFORM LTG.	320			20/1	5	445		6	20/1	125			EXTERIOR LIGHTING
WAITING ROOM RECEP.		200		20/1	7		400	8	20/1		200		PIT SUMP PUMP RECEP.
WAITING ROOM RECEP.		400		20/1	9	800		10	20/1		400		DRINKING FOUNTAIN
SERVICE WRITING RECEP.		600		20/1	11		1200	12	20/1		600		PIT RECEPTACLE
TOILET RECEPTACLE		600		20/1	13	800		14	20/1		200		PIT TABLE RECEPTACLE
OUTDOOR RECEPTACLE		800		20/1	15		4150	16				3360	AIR COMPRESSOR
BREAK ROOM RECEPTACLE		400		20/1	17	3760		18	60/2			3360	
BREAK ROOM RECEPTACLE		200		20/1	19		400	20	20/1		200		TBB-OC RECEPTACLECONTACTORS
BREAK ROOM FRIDGE		200		20/1	21	1856		22	20/1	1656			EF-3
MANAGER RECEPTACLE		800		20/1	23		900	24	20/1			100	RH-1 & RH-2
OIL CHANGE RECEPTACLE		600		20/1	25	650		26	20/1		50		REC-1
TOILET RECEPTACLE		600		20/1	27		800	28	20/1		200		LOT BELL
FUTURE EV CHARGER				50/2	29	200		30	20/1		200		MONUMENT SIGN
					31		1680	32				1680	
OIL CHANGE RECEPTACLE		400		20/1	33	2080		34	25/2			1680	CU-1
OIL CHANGE DESK RECEP.		200		20/1	35		7400	36			7200		AHJ-1
OIL CHANGE DESK RECEP.		200		20/1	37	7400		38			7200		
OIL CHANGE DESK RECEP.		200		20/1	39		2450	40			2250		
OIL CHANGE DESK RECEP.		200		20/1	39		2450	40	25/2			2250	EW-1
OIL CHANGE RECEPTACLE		600		20/1	41	2850		42				2250	
Sub-Total	1340	7000	0			22045	20230			2805	2050	29080	Sub-Total
TOTAL CONNECTED LOAD PER PHASE				DEMAND LOAD (VA)				WIRE SIZE CALCULATIONS				ENCLOSURE	
												NEMA 1	
LOAD TYPE	Phase A	Phase B		DEMAND FACTOR	Phase A	Phase B	LARGEST PHASE DEMAND	22.87	KVA	MOUNTING		SURFACE	
							NO. OF PHASES	2.00		MAIN TYPE		MB	
LIGHTING & CONTINUOUS LOADS	3305.00	840.00		1.25	4131.25	1050.00	DEMAND LOAD	45.74	KVA	SIZE		225A	
RECEPTACLES	4250.00	4800.00		*	4250.00	4800.00				FEED THRU		NO	
MOTORS/OTHER	14490.00	14590.00		1.00	14490.00	14590.00	TOTAL DEMAND LOAD	45.74	KVA	FEED		BOTTOM	
TOTAL	22045.00	20230.00			22871.25	20440.00	SUPPLY VOLTAGE	240.00	V	BUS RATING		225A	
												SERVICE RATED	
												NO	
												MIN FULL EQUIP KVA RATING	
												22	
												TYPE	
												LOAD CENTER	
												MANUFACTURER	
												OTHER	





GROUNDING SYSTEM DETAIL
NOT TO SCALE

GROUNDING SYSTEM DETAIL – KEY NOTES


- ① BARE GROUNDING ELCTRODE CONDUCTOR, SEE SLD.
- ② 3/4"x10'-0" CLAD STEEL GROUND ROD, DRIVEN 24" BELOW GRADE, MINIMUM.
- ③ BARE GROUNDING ELECTRODE CONDUCTOR IN 2"PVC-40, SEE SLD.
- ④ EXOTHERMIC WELD CONNECTOR:
TWO CABLES TO GROUND ROD, CADWELD #GT OR #GY
CABLE TO CABLE TEE, CADWELD #TA
ONE CABLE TO GROUND ROD, CADWELD #GR
- ⑤ CAST BRONZE, UL LISTED GROUND CLAMP, O-Z/GEDNEY TYPE-G.
- ⑥ BONDING JUMPER, SIZED BY EQUIPMENT MANUFACTURER PER NEC 250-66.
- ⑦ BONDING JUMPER TO GROUNDING BUSHING. AND BONDING JUMPERS FROM CONDUIT TO CONDUIT. ALL CONDUIT CONNECTED TO THE SERVICE ENTRANCE ENCLOSURE SHALL BE BONDED, SIZED PER NEC 250.
- ⑧ MAIN BONDING JUMPER, SIZED BY MANUFACTURER PER 250-66.
- ⑨ BONDING JUMPER.
- ⑩ 6 CONDUCTOR GROUND BUS, COPPER OR ALUMINUM RATED, ILSCO #PDE.




ELEVATION
LIFT POWER DETAIL
NOT TO SCALE




DETAIL
WIRING DESIGNATION
NOT TO SCALE





DETAIL
RECEPTACLE INSTALLATION
NOT TO SCALE




DETAIL
AVAILABLE FAULT CURRENT NAMEPLATE
NOT TO SCALE



DETAIL
120/240V PANELBOARD INSTALLATION
& NAMEPLATE DETAIL
NOT TO SCALE



DETAIL
ELECTRICAL NAMEPLATE
NOT TO SCALE



LIFT LIMIT SWITCH
WIRING DETAIL
NOT TO SCALE



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Details


Project number	24028
Date	11/8/2024
Drawn by	TH
Checked by	GW

E103

Scale NO SCALE

GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWMAE@GW-ENG.COM | 205.413.4112
TH@GNBOTHAM@GW-ENG.COM | 205.317.3869



- NOTES:**
1. VERIFY EXACT LOCATION OF STUB UP BEFORE ROUGH IN.
 2. HOMERUN TO PANELBOARD PP THROUGH LIGHTING CONTACTOR C-2.
 3. LOCATION OF MONUMENT SIGN SHOWN HERE IS FOR REFERENCE ONLY. VERIFY EXACT LOCATION OF MONUMENT SIGN WITH CIVIL PRIOR TO ROUGH IN.
 4. PROVIDE 1-1" EMPTY CONDUIT. HOMERUN TO PANEL PP FOR FUTURE EV CHARGING STATION. VERIFY EXACT LOCATION OF STUB UP WITH ARCHITECT AND CIVIL PRIOR TO INSTALLATION.

1 Site Plan - Electrical
1" = 20'-0"



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Site Plan - Electrical

Project number	24028
Date	11/8/2024
Drawn by	TH
Checked by	GW
E104	
Scale	1" = 20'-0"

GW ENGINEERING, LLC
4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
TH@GNBOTHAM@GW-ENG.COM | 205.317.3869

GENERAL NOTES:

- CONNECT ALL "BL", "XL" AND EMERGENCY BATTERY PACKS IN FUTURES MARKED "EM" TO UNSWITCHED HOT LEG OF CIRCUIT.
- ENSURE LIGHT FIXTURES L1 AND L2 DO NOT CONFLICT WITH OVERHEAD DOORS.
- FOR THE LIGHTING PACKAGE PRICING, CONTACT THE FOLLOWING:


MIKE MCMAKER
REXEL ENERGY SOLUTIONS
(M) 906-235-2979
MIKE.MCMAKEN@REXELENERGY.COM

STEPHEN MITCHELL
MAXLITE
(M) 908-256-3115
SMITCHELL@MAXLITE.COM

- ALL CONDUIT CROSSING OVERHEAD DOORS SHALL BE MOUNTED AS TIGHT TO THE STRUCTURE AS POSSIBLE TO AVOID CONFLICT WITH THE OVERHEAD DOOR TRACK.
- OIL CHANGE BUILDING IS A MINOR REPAIR GARAGE AND IS UNCLASSIFIED. SEE MECHANICAL DRAWINGS FOR PROVIDED VENTILATION.
- FOR LIGHTING, QUICK CONNECT CABLES SHALL NOT BE INSTALLED ABOVE CEILING. SURFACT MOUNT QUICK CONNECT CABLES BELOW CEILING.

NOTES:

- CONNECT TO PIT LIGHTING. SEE SHEET E201 FOR CONTINUATION.
- CONNECT TO EQUIPMENT PLATFORM LIGHTING. SEE SHEET E201 FOR CONTINUATION.
- HOMERUN TO 20A 1POLE CIRCUIT BREAKER IN PANELBOARD PP THROUGH LIGHTING CONTACTOR C-1. SEE DETAIL ON SHEET E102.
- HOMERUN TO 20A 1POLE CIRCUIT BREAKER IN PANELBOARD PP THROUGH LIGHTING CONTACTOR C-2. SEE DETAIL ON SHEET E102.
- JUNCTION BOX FOR SIGN COMPANY PROVIDED FIXTURE SHALL BE MOUNTED FLUSH WITH EXTERIOR FACE OF WALL AT 60" ABOVE GRADE ON CENTER.
- JUNCTION BOX SIGN COMPANY PROVIDED FIXTURE SHALL BE MOUNTED ON EXTERIOR FACE OF WALL AT 17' AFF. COORDINATE EXACT LOCATION WITH SIGN LIGHTING INSTALLER BEFORE ROUGHING IN.
- COORDINATE EXACT LOCATION OF L2 LIGHT FIXTURES PRIOR TO INSTALLATION. FIXTURE SHALL NOT BE MOUNTED ABOVE RADIANT HEATER. ENSURE FIXTURES DO NOT CONFLICT WITH OVERHEAD DOOR TRACK.
- JUNCTION BOX FOR SIGN COMPANY PROVIDED FIXTURE SHALL BE ACCESSIBLE FROM EXTERIOR FACE OF WALL AND SHAL BY COORDINATED WITH SIGN LIGHTING INSTALLER BEFORE ROUGH IN.



① Main Level - Lighting
1/4" = 1'-0"

PLAN
NORTH

GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THGONBOTHAM@GW-ENG.COM | 205.317.3969



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.


Main Level Floor
Plan - Lighting

Project number	24028
Date	11/8/2024
Drawn by	TH
Checked by	GW

E200

Scale 1/4" = 1'-0"

11/8/2024 12:54:44 PM



3 Equipment Platform - Lighting
1/4" = 1'-0"

GENERAL NOTES:


- CONNECT ALL "BL" "XL" AND EMERGENCY BATTERY PACKS IN FUXTURES MARKED EM TO UNSWITCHED HOT LEG OF CIRCUIT.
- FOR THE LIGHTING PACKAGE PRICING, CONTACT THE FOLLOWING:

MIKE MCMAKER
REXEL ENERGY SOLUTIONS
(M) 906-235-2979
MIKE.MCMAKEN@REXELENERGY.COM

STEPHEN MITCHELL
MAXLITE
(M) 908-256-3115
SMITCHELL@MAXLITE.COM
- OIL CHANGE BUILDING IS A MINOR REPAIR GARAGE AND IS UNCLASSIFIED. SEE MECHANICAL DRAWINGS FOR PROVIDED VENTILATION.
- ADJUST LIGHT FIXTURES AS NEEDED TO AVOID CONFLICT WITH STRUCTURAL STEEL.

NOTES:

- CONNECT TO LIGHT SWITCH ON FIRST FLOOR. SEE SHEET E200 FOR CONTINUATION.
- HOMERUN TO 20A 1POLE CIRCUIT BREAKER IN PANELBOARD PP THROUGH LIGHTING CONTACTOR C-1. SEE DETAIL ON SHEET E102.



1 Pit Level - Lighting
1/4" = 1'-0"



GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THIGONBOTHAM@GW-ENG.COM | 205.317.3969



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Pit Level &
Equipment
Platform Floor Plan
- Lighting

Project number	24028
Date	11/8/2024
Drawn by	TH
Checked by	GW

E201

Scale 1/4" = 1'-0"

GENERAL NOTES:

- CONTRACTOR SHALL VERIFY/ COORDINATE LOCATION OF ALL POWER & DATA OUTLETS FOR EQUIPMENT. OBTAIN OWNER'S APPROVAL BEFORE ROUGH IN. NO EXCEPTIONS. NO ADDITIONAL COMPENSATION SHALL BE AWARDED FOR ANY ADDITIONAL WORK REQUIRED TO RELOCATE OUTLETS DUE TO CONTRACTOR'S FAILURE TO COORDINATE WITH OWNER.
- ALL HORIZONTAL CONDUIT RUNS SHALL BE A MINIMUM OF 8' ABOVE FINISHED FLOOR EXCEPT FOR DROPS. ENSURE CONDUIT DOES NOT CONFLICT WITH OVERHEAD DOOR.
- OIL CHANGE BUILDING IS A MINOR REPAIR GARAGE AND IS UNCLASSIFIED. SEE MECHANICAL DRAWINGS FOR PROVIDED VENTILATION.
- EXPRESS OIL CHANGE HAS OBTAINED EQUIPMENT AVAILABILITY AND SPECIAL VOLUME PRICING ON POWER EQUIPMENT AND LIGHTING CONTROL PACKAGES FROM REXEL. SEE CONTACTS BELOW FOR PRICING AND INFORMATION:


JEFFREY PARKER
REXEL
(M) 508-916-758
JEFFREY.PARKER@REXELUSA.COM

COLIN BLACK
REXEL
COLIN.BLACK@REXELUSA.COM

MIKE MCMAKEN
REXEL ENERGY SOLUTIONS
(M) 906-235-2979
MIKE.MCMAKEN@REXELENERGY.COM
- ALL CONDUIT CROSSING OVERHEAD DOORS SHALL BE MOUNTED AS TIGHT TO THE STRUCTURE AS POSSIBLE TO AVOID CONFLICT WITH THE OVERHEAD DOOR TRACK.

NOTES:

- 3/4" CONDUIT STUBBED UP 18" INTO WORK PEDESTAL BASE POST. PROVIDE FLEXIBLE CONDUIT INTO WORK PEDESTAL CABINET. COORDINATE OUTLET REQUIREMENTS PRIOR TO ROUGH-IN.
- HOMERUN 3/4"EC TO TELEPHONE BACKBOARD ON EQUIPMENT PLATFORM.
- CONDUIT FOR WORK PEDESTALS IN OIL CHANGE AREA SHALL BE MOUNTED/ROUTED ON THE CEILING OF THE PIT IN LIEU OF IN THE SLAB.
- ELECTRICAL CONTRACTOR SHALL FURNISH AND INSTALL ZOELLER-Z CONTROL APAK INDOOR ALARM WITH MECHANICAL FLOAT, MODEL # 10-4014. SEE MANUFACTURER INSTALLATION INSTRUCTIONS PRIOR TO ROUGH IN. PROVIDE BATTERIES.



① Main Level - Power & Voice/Data
1/4" = 1'-0"



GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THGONBOTHAM@GW-ENG.COM | 205.317.3969



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.


Main Level Floor
Plan - Power &
Voice/Data

Project number	24028
Date	11/8/2024
Drawn by	TH
Checked by	GW

E300

Scale 1/4" = 1'-0"

11/8/2024 12:55:10 PM



② Equipment Platform - Power & Voice/Data
1/4" = 1'-0"

GENERAL NOTES:

- OIL CHANGE BUILDING IS A MINOR REPAIR GARAGE AND IS UNCLASSIFIED. SEE MECHANICAL DRAWINGS FOR PROVIDED VENTILATION.
- EXPRESS OIL CHANGE HAS OBTAINED EQUIPMENT AVAILABILITY AND SPECIAL VOLUME PRICING ON POWER EQUIPMENT AND LIGHTING CONTROL PACKAGES FROM REXEL. SEE CONTACTS BELOW FOR PRICING AND INFORMATION:


JEFFREY PARKER
REXEL
(M) 508-916-758
JEFFREY.PARKER@REXELUSA.COM

COLIN BLACK
REXEL
COLIN.BLACK@REXELUSA.COM

MIKE MCMAKEN
REXEL ENERGY SOLUTIONS
(M) 906-235-2979
MIKE.MCMAKEN@REXELENERGY.COM

NOTES:

- SEE AUXILIARY SINGLE LINE DIAGRAM ON SHEET E102 FOR MORE INFORMATION ON TELEPHONE BACKBOARD. COORDINATE LOCATOIN WITH DUCTWORK
- 2"EC HOMERUN TO TELEPHONE BACKBOARD ON EQUIPMENT PLATFORM.
- MOUNT RECPTACLES ONTO STRUCTURAL COLUMN.



① Pit Level - Power & Voice/Data
1/4" = 1'-0"



GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THIGGINBOTHAM@GW-ENG.COM | 205.317.3969



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Pit Level &
Equipment
Platform - Power &
Voice/Data

Project number	24028
Date	11/8/2024
Drawn by	TH
Checked by	GW

E301


Scale 1/4" = 1'-0"

GENERAL NOTES:

1. OIL CHANGE BUILDING IS A MINOR REPAIR GARAGE AND IS UNCLASSIFIED. SEE MECHANICAL DRAWINGS FOR PROVIDED VENTILATION.

NOTES:

1. HOMERUN TO 20A 1POLE CIRCUIT BREAKER IN PANELBOARD PP THROUGH LIGHTING CONTACTOR C-1. SEE DETAIL ON SHEET E102 FOR MORE INFORMATION.
2. CONNECT TO LIGHTING CIRCUIT AND CONTROLS IN THIS AREA.



① Main Level - Electrical Connection to Mechanical
1/4" = 1'-0"



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Main Level Floor
Plan - Electrical
Connection to
Mechanical


Project number	24028
Date	11/8/2024
Drawn by	TH
Checked by	GW

E400

Scale 1/4" = 1'-0"

GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THGONBOTHAM@GW-ENG.COM | 205.317.3969



- GENERAL NOTES:
- OIL CHANGE BUILDING IS A MINOR REPAIR GARAGE AND IS UNCLASSIFIED. SEE MECHANICAL DRAWINGS FOR PROVIDED VENTILATION.

① Equipment Platform - Electrical Connection to Mechanical
1/4" = 1'-0"



Express Oil Change & Tire Engineers
Left Hand Oil Change Building
Northport, Alabama

FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Equipment Platform Floor Plan - Elec. Conn. To Mechanical	
Project number	24028
Date	11/8/2024
Drawn by	TH
Checked by	GW
E401	
Scale	1/4" = 1'-0"



Express Oil Change & Tire Engineers

Left Hand Oil Change Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

COMcheck

Project number	24028
Date	11/8/2024
Drawn by	TH
Checked by	GW
E600	
Scale	NO SCALE

GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THIGGINBOTHAM@GW-ENG.COM | 205.317.3969

COMcheck Software Version 4.1.5.5

Interior Lighting Compliance Certificate

Project Information

Energy Code: 2015 IECC
Project Title: Express Oil Change & Tire Engineers - Oil Change Building
Project Type: New Construction

Construction Site: Northport, AL
Owner/Agent: Express Oil Change & Tire Engineers
Designer/Contractor: Taylor Higginbotham
GW Engineering
Trussville, AL 35173
205-317-3969
thigginbotham@gw-eng.com

Additional Efficiency Package(s)

Credits: 1.0 Required 1.0 Proposed
Reduced Lighting Power: 1.0 credit

Allowed Interior Lighting Power

A Area Category	B Floor Area (ft²)	C Allowed Watts / ft²	D Allowed Watts (B X C)
1-Oil Change Bldg. (Automotive Facility)	4063	0.72	2940
Total Allowed Watts =			2940

Proposed Interior Lighting Power

A Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast	B Lamps/ Fixture	C # of Fixtures	D Fixture Watt.	E (C X D)
1-Oil Change Bldg. (Automotive Facility)				
LED 7' L1: Other	1	4	100	400
LED 6' L2: Other	1	21	50	1050
LED 8' L3/L5: Other	1	23	35	805
Total Proposed Watts =				2255

Interior Lighting PASSES: Design 23% better than code

Interior Lighting Compliance Statement

Compliance Statement: The proposed interior lighting design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed interior lighting systems have been designed to meet the 2015 IECC requirements in COMcheck Version 4.1.5.5 and to comply with any applicable mandatory requirements listed in the Inspection Checklist.

Taylor Higginbotham
Name - Title
Signature: Taylor Higginbotham
Date: 11/08/2024

Project Title: Express Oil Change & Tire Engineers - Oil Change Building
Report date: 11/08/24
Data filename: C:\Users\Taylor Higginbotham\Documents\GW Engineering\2024 - AHO - EDC Guntersville, AL\Project Files\08 - Lighting Calculations & Cutsheets\OC Bldg\Comcheck - EDC Guntersville, AL - OC Bldg.cck
Page 1 of 7

COMcheck Software Version 4.1.5.5

Exterior Lighting Compliance Certificate

Project Information

Energy Code: 2015 IECC
Project Title: Express Oil Change & Tire Engineers - Oil Change Building
Project Type: New Construction
Exterior Lighting Zone: 2 (Residential mixed use area (LZ2))

Construction Site: Northport, AL
Owner/Agent: Express Oil Change & Tire Engineers
Designer/Contractor: Taylor Higginbotham
GW Engineering
Trussville, AL 35173
205-317-3969
thigginbotham@gw-eng.com

Allowed Exterior Lighting Power

A Area/Surface Category	B Quantity	C Allowed Watts / Unit	D Tradable Wattage	E Allowed Watts (B X C)
Entry canopy	110 ft2	0.25	Yes	28
Illuminated area of facade wall or surface	648 ft2	0.1	No	65
Total Tradable Watts (a) =				28
Total Allowed Watts =				92
Total Allowed Supplemental Watts (b) =				600

(a) Wattage tradeoffs are only allowed between tradable areas/surfaces.
(b) A supplemental allowance equal to 600 watts may be applied toward compliance of both non-tradable and tradable areas/surfaces.

Proposed Exterior Lighting Power

A Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast	B Lamp/ Fixture	C # of Fixtures	D Fixture Watt.	E (C X D)
Entry canopy (110 ft2): Tradable Wattage				
LED 1' L5: Other	1	2	25	50
Illuminated area of facade wall or surface (648 ft2): Non-tradable Wattage				
LED 2' L4/L6: Other	1	6	35	210
Total Tradable Proposed Watts =				50

Exterior Lighting PASSES: Design 90% better than code

Exterior Lighting Compliance Statement

Compliance Statement: The proposed exterior lighting design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed exterior lighting systems have been designed to meet the 2015 IECC requirements in COMcheck Version 4.1.5.5 and to comply with any applicable mandatory requirements listed in the Inspection Checklist.

Taylor Higginbotham
Name - Title
Signature: Taylor Higginbotham
Date: 11/08/2024

Project Title: Express Oil Change & Tire Engineers - Oil Change Building
Report date: 11/08/24
Data filename: C:\Users\Taylor Higginbotham\Documents\GW Engineering\2024 - AHO - EDC Guntersville, AL\Project Files\08 - Lighting Calculations & Cutsheets\OC Bldg\Comcheck - EDC Guntersville, AL - OC Bldg.cck
Page 2 of 7




Northport, Alabama

[illegible]

OC-E700

Scale 1" = 20'-0"

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THIGGINBOTHAM@GW-ENG.COM | 205.317.3969



② Light Fixture Cutsheets
N.T.S.

Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
Calc Zone #1	+	1.3 fc	8.2 fc	0.0 fc	N/A	N/A
Calc Zone #2	+	0.3 fc	0.8 fc	0.0 fc	N/A	N/A

EXPRESS OIL CHANGE & TIRE ENGINEERS

SERVICE BUILDING

HWY 43 LURLEEN B WALLACE & 27th STREET
NORTHPORT, AL 35476

ATTENTION AUTHORITY HAVING JURISDICTION

Notice is hereby given that Aho Architects, LLC, the Architect of Record on the above referenced project, will be providing construction administration services on a limited basis, supplemented by a third-party independent engineering consulting service as described below.

This project has been designed by the Architect and Engineers ("Design Team") for its specific location, or adapted from prototypical designs, to comply with the following codes, ordinances, and similar requirements adopted by the Authority Having Jurisdiction ("AHJ"):

- See codes listed on Sheet LS100.

During the Construction Administration Phase of the Project:

- General: The Design Team will respond to inquiries or requests from the Owner or Contractor, specifically related to documents prepared by the Design Team. As is standard in Construction Law and Professional Service Agreements, the Design Team shall not have control over, charge of, or responsibility for the construction means, methods, techniques, sequences or procedures, or for safety precautions and programs in connection with the Project(s), nor shall the Architect be responsible for the Owner's or Contractor's failure to perform the work in accordance with the requirements of the Permit Set Documents. The Architect shall be responsible for the Architect's negligent acts or omissions, but shall not have control over or charge of, and shall not be responsible for, acts or omissions of the Owner, Contractor, or of any other persons or entities performing portions of the work.
- Experienced Contractor: The Owner will use experienced and licensed Contractors familiar with the construction of Projects of this type and in similar locations, and experienced with the applicable building codes, selection of materials and systems, and methods of installation and construction; and able to implement the Permit Set Documents through completion of the Project(s).
- Submittals: The Design Team's Basic Construction Administration Services include review of critical submittals (e.g. shop drawings) by engineering disciplines (Structural). The Design Team shall also review, approve or take other appropriate action on any submittal for which the AHJ requires approval by the Architect/Engineer, as Additional Services.
- Site Visits: The Architect and Design Engineers typically will not be making any site visits unless specifically required to do so.
 - The Owner has been advised and acknowledges that some States and AHJs require the Architect to perform at least some site visits or provide a notice such as this statement.
 - In consideration of this, the Owner will provide site visits, observation, testing, and related work by a third party independent engineering consulting service:
 - The Owner has an agreement with Terracon, a provider of geotechnical, environmental, construction materials and facilities engineering
 - Experienced Professional Engineers or field technicians under the responsible control of a Professional Engineer will perform site observation, construction materials testing, and required Special Inspections (per IBC Chapter 17; see Schedule of Special Inspections on structural drawings provided) including review of construction for conformance with the permit drawings, supplemental drawings, shop drawings/submittals, and similar relevant documents. Written reports shall be provided, with the Design Team included on the distribution list and involved in resolving any deficiencies noted or other items requiring the Design Team's input.
 - If the above provisions are not acceptable to the AHJ and the AHJ gives notice requiring the Architect to make site visit(s), the Owner has agreed to authorize the Architect's Additional Services and Reimbursable Expenses to comply with the AHJ's requirements.

If you have any questions, or if there is anything else we can do for you, please do not hesitate to contact April Cain, the project manager or Tim Aho, Architect at the address/phone listed below, or by email at [HYPERLINK "mailto:acain@ahoarch.com"](mailto:acain@ahoarch.com) acain@ahoarch.com or [HYPERLINK "mailto:taho@ahoarch.com"](mailto:taho@ahoarch.com) taho@ahoarch.com. Thank you very much, and we appreciate the opportunity to be involved in this project in your jurisdiction.



*Image above is generic. See Civil for actual site conditions

ARCHITECT

AHO ARCHITECTS, LLC
1855 DATA DRIVE, SUITE 150
HOOVER, ALABAMA 35244
205-983-6000

CIVIL ENGINEER

INSITE ENGINEERING, LLC
5800 FELDSPAR WAY
HOOVER, AL 35244
205-733-9696

STRUCTURAL ENGINEER

BARNETT-JONES-WILSON, LLC
125 18TH STREET NORTH
PELL CITY, ALABAMA 35125
205-884-5334


MECHANICAL / PLUMBING ENGINEER

PINNACLE ENGINEERING, INC.
2031 SHADY CREST DRIVE
HOOVER, ALABAMA 35216
205-733-6912

ELECTRICAL ENGINEER

GW ENGINEERING, LLC
4120 OVERLOOK CIRCLE
TRUSSVILLE, ALABAMA 35173
205-413-4112

FINAL



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Title Sheet

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A
T100	
Scale	12" = 1'-0"

GENERAL PROJECT NOTES

1. These documents are considered accurate and true to the best knowledge of the Architect at this time, but do not necessarily represent, nor are they intended to represent, actual existing conditions, dimensions, and tolerances. Contractor shall field-verify existing conditions including, but not limited to materials, construction, elevations, and dimensions prior to bidding and undertaking the work. Items of concern shall be brought to the attention of the Architect. Submittal of a proposal (bid) by a Contractor and their Subcontractors shall constitute an acknowledgement and confirmation of having complied with these requirements.
2. All work shall comply with all applicable local, state, and national codes, rules, ordinances and regulations and authorities having jurisdiction.
3. The Contractor shall comply with all applicable provisions of the specifications, including, but not limited to all general conditions, supplementary general conditions, special conditions, and material and construction provisions, which apply to materials or construction methods required by this project.
4. Where warranties are concerned, Contractor shall follow manufacturer’s standards and recommendations unless specifically directed otherwise. Any conditions which might negatively affect the warranty shall be brought to the attention of the Architect in advance.
5. The Owner and Contractor shall promptly report to the Architect any defects, suspected defects, or discrepancies in the Architect 's work or services of which the Owner or Contractor may become aware, so that the Architect may take measures to minimize the consequences of such a defect. Failure to notify the Architect shall relieve the Architect of costs of remedying the defects above the sum such remedy would have cost had prompt notification been given.
6. Neither the professional activities of the Architect, nor the presence of the Architect or its employees and consultants at a construction site shall relieve the Contractor or others of their obligations, duties, and responsibilities including, but not limited to: construction means and methods, sequence, techniques, or procedures necessary for performing, superintending, or coordinating all portions of the work in accordance with the contract documents and any health and safety precautions required by agencies having jurisdictional authority over the project. The Architect and its personnel have no authority to exercise control over any Contractor or other entity or their employees in connection with their means, methods, or safety precautions. The Contractor is solely responsible for jobsite safety. The Owner, Architect, and their Consultants shall be indemnified and shall be made additional insureds under the Contractor’s general liability insurance policy.
7. All work, unless specifically indicated otherwise, shall be the responsibility of the General Contractor and shall be performed by the tradesmen skilled in the required field.
8. “Provide” shall mean to furnish and install, complete and ready for intended use.
9. Provide pressure treated wood where in contact with concrete or masonry.
10. The Contractor shall be responsible for all cutting, fitting, and patching that may be required to complete the work.
11. Dimensions of existing construction and repetitive dimensions are sometimes omitted. Detailed dimensions not indicated may be found on large-scale drawings of the same areas. Drawings are intended to reflect the existing conditions as closely as possible, however, the Contractor shall field verify and accept all existing conditions and dimensions. Notify Architect of any discrepancies affecting the work.
12. Provide all temporary services required to facilitate the work indicated, including but not limited to the following: power, lighting, heat, and water.
13. The Contractor(s) shall provide all barriers, shoring, warning lights, etc. as required to conduct the work and maintain the site in a safe condition consistent with good construction practices and with all applicable rules and regulations.
14. All exist. utility services including domestic water, sanitary sewer, electricity, fuel oil and/or gas shall be disconnected and made safe prior to any demolition work. Any work which might require interruption of utility services to Owner or other tenants, shall be approved and coordinated beforehand with the Owner.
15. It is the intent of the bid and construction documents to indicate complete and fully operational systems (i.e. structural, HVAC, plumbing, electrical, roofing, etc.). The Contractor shall provide operational systems and testing which comply with applicable codes, regulations, and requirements of authorities having jurisdiction.
16. Any work or utility outages which might disrupt the operations of the Owner or others shall be approved and coordinated in advance with the Owner and the Architect. The Contractor shall give the Owner and Architect at least three days advance notice prior to undertaking work which might cause disruption. Activities which produce utility outages, excessive noise, dust and other disruption shall be coordinated with the Owner and Architect. Some of these activities may need to occur at “off hours” to minimize disruption of the Owner’s operations.
17. All wood blocking, trim, decking, etc. shall be decay-resistant treated, or as specified.
18. To prepare substrate for all wall mounted items, wall fixture, toilet accessories, etc. - fill all voids in the CMU surface to provide a sound base (provide blocking in stud walls) for all new wall mounted items, fixtures, etc. Install per manufacturer’s specifications and recommendations.
19. Do not paint any caulking or sealants which are subject to movement. Control joints shall be caulked after paint and special coating applications. Provide caulking or sealants in colors which match adjacent finished surface as approved by the Architect.
20. Bidders shall be responsible for obtaining a copy of the Geotech Report from the Owner.
21. The project may include some items that are delegated design. Bidders shall ensure these items are covered in their base bid.
22. All questions that affect cost, time, etc. shall be presented in the form of RFI’s to the Architect prior to bid.

GENERAL ACCESSIBILITY NOTES

1. All door hardware shall be accessible type per section 404 of the 2017 ICC A117.1 / 2010 ADA Standards.
2. All walking surfaces shall have a maximum slope of 1:20 per section 405 of the 2017 ICC A117.1 / 2010 ADA Standards
3. All floor or ground surfaces shall be stable, firm, and slip resistant per section 302 of the 2017 ICC A117.1 / 2010 ADA Standards
4. Changes in level of 1/4" high maximum shall be permitted to be vertical per section 303 of the 2017 ICC A117.1 / 2010 ADA Standards
5. Provide maneuvering clearances at manual swinging doors per section 404 of the 2017 ICC A117.1 / 2010 ADA Standards
6. ADA mounting heights, dimensions, tolerances, etc. shall apply to all construction and the location of all fixtures, etc. unless specifically noted otherwise.

GENERAL INTERIOR NOTES

1. Quantities (area, perimeter, etc.) shown on finish schedule are approximate and are provided as a convenience to the Contractor. Actual quantities may vary and it is the responsibility of the Contractor to field verify.
2. Anything specified with a directional pattern (e.g. brushed aluminum, wood grain laminate, etc.) the pattern shall go in the same direction as directed by Architect.
3. The Contractor shall provide all necessary blocking in walls for support of all equipment, shelving, accessories, grab bars, and other required elements.
4. Provide pressure treated wood where in contact with concrete or masonry.
5. Ease all edges on casework to prevent sharp corners.
6. Paint all HVAC wall grilles to match adjacent surface color unless otherwise noted or instructed by the Architect.
7. Use moisture resistant gypsum board at all walls subject to moisture unless wall will be subject to standing water or frequent wetting in which case you shall use cementitious backer.
8. Provide thresholds where required. All shall be ADA compliant.
9. All gypsum board to have a level 4 finish unless otherwise indicated.


BIDDING INQUIRES

Company:
Contact:
E-Mail:
Phone:

Express Oil Change
Chris Plummer
chris.plummer@expressoil.com
205-945-1771

Note:

Sub-contractors to call bidding General Contractor for questions



Sheet Index

Sheet Number	Sheet Name
T100	Title Sheet
G100	General Information
G200	Architectural Specifications
G201	Architectural Specifications
G202	Architectural Specifications
G300	EOC Standards - Exterior
G301	EOC Standards - Interior
LS100	Life Safety / Code Summary
LS101	Life Safety / Code Summary
LS102	Life Safety Plan - Main
AS100	Architectural Site Plan
A100	Floor Plan - Main
A101	Enlarged Plans & Site Details
A104	Reflected Ceiling Plan - Main
A108	Roof Plan
A200	Exterior Elevation - Front (South)
A201	Exterior Elevation - Rear (North)
A202	Exterior Elevation - Right (East)
A203	Exterior Elevation - Left (West)
A300	Building Sections
A301	Building Sections
A400	Wall Types
A600	Interior Elevations
A601	Interior Elevations
A605	Interior Dimensional Info.
A610	Floor Finishes - Main
A620	Schedules
A621	Finish Schedules & Head, Jamb, and Sill Details
R100	3D Views
S0.1	General Notes & Schedule of Special Inspections
S0.2	Typical Details
S1.1	Foundation and Roof Framing Plan
S5.1	Sections and Details
M0.01	Mechanical Legend, Schedules and Details
M0.02	Mechanical Specifications
M0.03	Mechanical Specifications
M0.04	Mechanical ComCheck
M1.01	Mechanical Floor Plan
P0.01	Plumbing Legend, Abbreviations, and Schedules
P0.02	Plumbing Specifications
P0.03	Plumbing Specifications
P1.01	Plumbing Floor Plans
P2.01	Plumbing Risers
P3.01	Plumbing Details
E100	General Notes and Fixture Schedules
E101	Symbol Legends and Details
E102	Single Line Diagram and Panelboard Schedules
E103	Details
E104	Site Plan - Electrical
E200	Floor Plan - Lighting
E300	Floor Plan - Power & Voice/Data
E400	Floor Plan - Elec. Conn. to Mech.
E500	Specifications
E600	ComCheck



Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

General Information

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

G100

Scale 12" = 1'-0"

<div><div>DIVISION 08 - OPENINGS</div><div>081113- Hollow Metal Doors and Frames (Standard)</div><div>Manufacturers:</div><div>Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>CECO Door Products</u>, or a comparable product by one of the following:</div><div><div>1. Curries Company</div><div>2. Steelcraft</div><div>3. Or Approved equal</div></div><div>Products:</div><div>Materials</div><div><div>A. Cold-Rolled Steel Sheet: ASTM A 1008/A 1008M, Commercial Steel (CS), Type B; suitable for exposed applications.</div><div>B. Metallic-Coated Steel Sheet: ASTM A 653/A 653M, Commercial Steel (CS), Type B; with minimum G60 (Z180) or A60 (ZF180) metallic coating.</div><div>C. Frame Anchors: ASTM A 653/A 653M, Commercial Steel (CS), Commercial Steel (CS), Type B; with minimum G60 (Z180) or A60 (ZF180) metallic coating.</div></div><div>Hollow Metal Doors</div><div><div>A. General: Provide 1-3/4 inch doors of design indicated, not less than thickness indicated; fabricated with smooth surfaces, without visible joints or seams on exposed faces unless otherwise indicated. Comply with ANSI/SDI A250.8 and ANSI/NAAMM HMMMA 867.</div><div>B. Exterior Doors: Face sheets fabricated of commercial quality hot-dipped zinc coated steel that complies with ASTM A 653/A 653M, Coating Designation A60. Provide doors complying with requirements indicated below by referencing ANSI/SDI A250.8 for level and model and ANSI/SDI A250.4 for physical performance level.</div><div><div>1. Design: Flush panel.</div><div>2. Level/Model: Level 2 and Physical Performance Level B (Heavy Duty), Minimum 18 gauge (0.042-inch - 1.0-mm) thick steel, Model 2.</div><div>3. Top and Bottom Edges: Reinforce tops and bottoms of doors with a continuous steel channel not less than 16 gauge, extending the full width of the door and welded to the face sheet. Doors with an inverted top channel to include a steel closure channel, screw attached, with the web of the channel flush with the face sheets of the door. Plastic or composite channel fillers are not acceptable.</div><div>4. Hinge Reinforcement: Minimum 7 gauge (3/16") plate 1-1/4" x 9" or minimum 14 gauge continuous channel with pierced holes, drilled and tapped.</div><div>5. Hardware Reinforcements: Fabricate according to ANSI/SDI A250.6 with reinforcing plates from same material as door face sheets.</div></div><div>D. Interior Doors: Face sheets fabricated of commercial quality cold rolled steel that complies with ASTM A 1008/A 1008M. Provide doors complying with requirements indicated below by referencing ANSI/SDI A250.8 for level and model and ANSI/SDI A250.4 for physical performance level:</div><div><div>1. Design: Flush panel.</div><div>a. Fire Door Core: As required to provide fire-protection and temperature-rise ratings indicated.</div><div>2. Level/Model: Level 2 and Physical Performance Level B (Heavy Duty), Minimum 18 gauge (0.042-inch - 1.0-mm) thick steel, Model 2.</div><div>3. Top and Bottom Edges: Reinforce tops and bottoms of doors with a continuous steel channel not less than 16 gauge, extending the full width of the door and welded to the face sheet.</div><div>4. Hinge Reinforcement: Minimum 7 gauge (3/16") plate 1-1/4" x 9" or minimum 14 gauge continuous channel with pierced holes, drilled and tapped.</div><div>5. Hardware Reinforcements: Fabricate according to ANSI/SDI A250.6 with reinforcing plates from same material as door face sheets.</div></div><div>F. Manufacturers Basis of Design:</div><div>1. CECO Door Products (C) Honeycomb Core - Regent Series.</div><div>Hollow Metal Frames</div><div><div>A. General: Comply with ANSI/SDI A250.8 and with details indicated for type and profile.</div><div>B. Exterior Frames: Fabricated of hot-dipped zinc coated steel that complies with ASTM A 653/A 653M, Coating Designation A60.</div><div><div>1. Fabricate frames with mitered or coped corners. Profile as indicated on drawings.</div><div>2. Manufacturers Basis of Design:</div><div>a. CECO Door Products (C) – SQSeries.</div><div>b. Curries Company (CU) – M Series.</div></div><div>C. Interior Frames: Fabricated from cold-rolled steel sheet that complies with ASTM A 1008/A 1008M.</div><div><div>1. Fabricate frames with mitered or coped corners. Profile as indicated on drawings.</div><div>2. Manufacturers Basis of Design:</div><div>a. CECO Door Products (C) - SQ Series.</div><div>b. Curries Company (CU) - M Series.</div></div><div>D. Fire rated frames: Fabricate frames in accordance with NFPA 80, listed and labeled by a qualified testing agency, for fire-protection ratings indicated.</div><div>E. Hardware Reinforcement: Fabricate according to ANSI/SDI A250.6 Table 4 with reinforcement plates from same material as frames.</div><div>Frame Anchors</div><div><div>A. Jamb Anchors:</div><div>1. Masonry Type: Adjustable strap-and-stirrup or T-shaped anchors to suit frame size, formed from A60 metallic coated material, not less than 0.042 inch thick, with corrugated or perforated straps not less than 2 inches wide by 10 inches long; or wire anchors not less than 0.177 inch thick.</div><div>2. Stud Wall Type: Designed to engage stud and not less than 0.042 inch thick.</div><div>3. Compression Type for Drywall Slip-on (Knock-Down) Frames: Adjustable compression anchors.</div><div>4. Windstorm Opening Anchors: Types as tested and required for indicated wall types to meet specified wind load design criteria.</div></div><div>B. Floor Anchors: Floor anchors to be provided at each jamb, formed from A60 metallic coated material, not less than 0.042 inches thick.</div><div>C. Mortar Guards: Formed from same material as frames, not less than 0.016 inches thick.</div><div>Installation:</div><div>Install hollow metal doors and frames according to manufacturers' written instructions.</div><div>Warranty:</div><div>Provide manufacturers' standard product warranty.</div></div></div></div>	<div><div>083613- Sectional Doors (Standard and Hurricane Non-Impact):</div><div>Manufacturers:</div><div>Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Raynor Garage Doors</u>, or a comparable product by an approved manufacturer.</div><div>Please note: Overhead Door Company is <u>not</u> an approved manufacturer.</div><div>Products:</div><div>Notes:</div><div><div>1.) All glazing to have proper labels as required by local AHJ and building codes.</div><div>2.) All glazing shall be reviewed and approved by the local distributor to meet the requirements for the region in which the glazing is being installed. Any issues with items specified shall be brought to the attention of the Architect prior to bid.</div></div><div>1.1 MANUFACTURERS</div><div>A. Acceptable Manufacturer: Raynor, which is located at: 1101 East River Rd. P. O. Box 448; Dixon, IL 61021-0448; Toll Free Tel: 800-4-RAYNOR; Tel: 815-288-1431; Fax: 888-598-4790; request info (architectsupport@raynor.com); Web:http://www.raynor.com</div><div>B. Requests for substitutions will be considered in accordance with provisions of Section 01 60 00 - Product Requirements.</div><div>1.2 SECTIONAL RIBBED PAN DOOR (Standard Windload)</div><div>A. SteelForm as manufactured by Raynor Garage Doors:</div><div>1. Doors:</div><div>a. Operation:</div><div>1) Provide doors designed for manual operation.</div><div>b. Jamb Construction:</div><div>1) Steel jambs with self-tapping fasteners.</div><div>c. Structural Performance Requirements:</div><div>1) Wind Loads: See Structural.</div><div>2. Sections:</div><div>a. SteelForm S24C (Basic):</div><div>1) Section end stiles and center stiles to be a minimum 16 gauge galvanized steel. End stiles and center stiles to be riveted to outside face with stainless steel rivets and resistance welded to interior rail.</div><div>2) Material: Steel pan construction, 2 inches thick, roll formed from 24 gauge embossed thickness, commercial quality, hot-dipped galvanized (G40) steel complying with ASTM A 653. Exterior of door to have two deep ribs, four pencil grooves, and roll-formed tongue-and-groove joints for weathertight closure.</div><div>3) Finish: Exterior skin to have two coats of paint, one primer coat and one finish coat.</div><div>a) Color: See Finish Schedule.</div><div>b. Seals: Bottom of door to have flexible U-shaped vinyl seal retained in aluminum rail. Optional blade seal on top section to prevent airflow above header</div><div>c. Trussing: Doors designed to withstand specified windload. Deflection of door in horizontal position to be maximum of 1/120th of door width.</div><div>3. Windows: Locations to comply with door elevation drawings.</div><div>a. Full-view windows consisting of aluminum stile and rail construction and (where applicable) color matched to door exterior with powdercoat paint in specified door sections. - See door elevation sheet.</div><div>b. Non-Impact Rated Glazing: 1/4 inch Clear Tempered Glass consisting of one pane of 1/4 inch non-insulated glass.</div><div>c. Mounting: Sections mounted in door opening using:</div><div>a. Lap Jamb Angle Mounting: section overlap door jambs by 1 inch on each side of door opening.</div><div>5. Track:</div><div>a. Material: Hot-dipped galvanized steel (ASTM A 653), fully adjustable for adequate sealing of door to jamb or weatherseal.</div><div>b. Track Size: 2 inches.</div><div>1) Jamb Type: Steel.</div><div>a) Mounting: QuikClip. Clip-Angle brackets pre-assembled to continuous angle from floor to door header and continuous angle from door header to door shaft. Angle Size: 2-5/16 x 1-1/4 x 3/32 inches.</div><div>6. Counterbalance:</div><div>a. Counterbalance System: Provided with aircraft-type, galvanized steel lifting cables with minimum safety factor of 5. Torsion Springs consisting of heavy-duty oil-tempered wire torsion springs on a continuous ball-bearing cross-header shaft.</div><div>1) Spring Cycle Requirements: High cycle: 50,000 cycles.</div><div>7. Hardware:</div><div>a. Hinges and Brackets: Fabricated from galvanized steel.</div><div>b. Perimeter Seal: Provide complete weather stripping system to reduce air infiltration. Weather stripping shall be replaceable.</div><div>1) For angle mounted doors provide angle clip-on seal.</div><div>c. Furnish door system with locks: Two interior slide locks with dead bolt provided with hole to receive padlock provided by Owner.</div><div>d. Provide leaf spring bumpers.</div><div>8. SteelForm Limited Warranty: Raynor warrants the door sections against defects in material and workmanship, and deterioration due to rust-through for ten years from date of delivery to the original purchaser. Window components are warranted against defects in material and workmanship for one year from date of delivery to the original purchaser. Raynor warrants all hardware and spring components against defects in material and workmanship for one year (or cycle life of the springs) from date of delivery to the original purchaser. Additional Limited Warranty requirements in accordance with manufacturer's full standard limited warranty documentation.</div><div>9. Configuration Type: Vertical Lift Clearance. Track must provide 35" available headroom, which will maintain 14'-0" minimum clearance from finish floor to underside of lift equipment.</div><div>10. Follow manufacturer's instructions for installation. Support tracks are to be adequately reinforced with continuous angle attached to structure.</div><div>PART 2 EXECUTION</div><div>2.1 EXAMINATION</div><div>A. Do not begin installation until substrates have been properly prepared. Verify that site conditions are acceptable for installation of doors, operators, controls and accessories. Ensure that openings are square, flush and plumb.</div><div>B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.</div><div>2.2 PREPARATION</div><div>A. Clean surfaces thoroughly prior to installation.</div><div>B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.</div><div>2.3 INSTALLATION</div><div>A. General: Install door, track and operating equipment complete with all necessary accessories and hardware according to shop drawings, manufacturer's instructions.</div><div>B. Lubricate bearings and sliding parts, and adjust doors for proper operation, balance, clearance and similar requirements.</div><div>2.4 PROTECTION</div><div>A. Clean installed products in accordance with manufacturer's instructions prior to Owner's acceptance. Remove and legally dispose of construction debris from project site.</div><div>B. Remove temporary coverings and protection of adjacent work areas. Repair or replace installed products damaged prior to or during installation.</div><div>C. Lubricate bearings and sliding parts, assure weather tight fit around door perimeter and adjust doors for proper operation, balance, clearance and similar requirements. Protect installed products until completion of project.</div><div>D. Touch-up, repair or replace damaged products before Substantial Completion.</div><div>Installation:</div><div>Install sectional doors according to manufacturers' written instructions.</div><div>Warranty:</div><div>Provide manufacturers' standard product warranty.</div></div>	<div><div>084113- Aluminum-Framed Entrances and Storefronts (Standard & Hurricane Non-Impact)</div><div>Manufacturers:</div><div>Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>YKK AP America Inc.</u>, or a comparable product by one of the following:</div><div><div>1. Kawneer</div><div>2. Or Approved equal</div></div><div>Products:</div><div>A. Exterior Storefront System</div><div><div>1. YES 45 TU</div><div>2. Center set</div><div>3. Thermal Barrier: Provide continuous thermal barrier by means of a poured and debrided pocket consisting of a two part, chemically curing high density polyurethane which is bonded to the aluminum by YKK ThermoBond Plus.</div><div>4. Materials: Anodized Aluminum; 0.050" minimum thickness.</div><div>5. Accessories: As recommended by the manufacturer.</div><div>6. Components: Manufacturer's standard extruded aluminum mullions, entrance doors, framing, and indicated shapes, perimeter anchor fillers and steel reinforcing as required.</div><div>7. Glazing Stops: Manufacturer's standard glazing stops with EPDM glazing gaskets to prevent water infiltration at the exterior and Dow Corning 995 Structural Silicone Sealant with fixed stops at the interior. Color to match storefront.</div><div>8. Finish: See finish schedule.</div><div>9. Wind Load: See Structural for design pressures.</div><div>10. Door: 35D - Medium Stile</div><div>a. Material: 0.050" aluminum min. thickness</div><div>b. Finish: See finish schedule.</div><div>c. Hardware: See Division 8 Door Hardware</div><div>d. Accessories: Manufacturer's standard</div><div>e. Glass: See Division 8 Glazing</div><div>f. Glazing Stops: Manufacturer's standard</div><div>g. Weather-stripping: Manufacturer's standard</div></div><div>B. Storefront Glazing</div><div><div>1. Glazing: Comply with Division 08 "Glazing"</div><div>2. Glazing Gaskets: Manufacturer's standard sealed-corner pressure-glazing system of resilient elastomeric glazing gaskets, setting blocks, and shims or spacers.</div><div>3. Glazing Sealants: As recommended by the manufacturer.</div></div><div>Installation:</div><div>Install aluminum-framed entrances and storefronts according to manufacturers' written instructions.</div><div>Warranty:</div><div>Provide manufacturers' standard product warranty.</div></div>	<div><div>088000- Glazing (IGU) Standard and Hurricane Non-Impact</div><div>Manufacturers:</div><div>Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Vitro</u>, or a comparable product by one of the following:</div><div><div>1. Guardian Industries Corp.</div><div>2. Or Approved equal</div></div><div>Products:</div><div>Notes:</div><div><div>1.) All glazing to have proper labels as required by local AHJ and building codes.</div><div>2.) All glazing shall be reviewed and approved by the local distributor to meet the requirements for the region in which the glazing is being installed. Any issues with items specified shall be brought to the attention of the Architect prior to bid.</div></div><div>A. GL-1 Insulated Glass Unit</div><div>Double Glazed Clear Solar Control Insulating Glass Unit Solarban® 90 on Clear 6mm (2) Air 1/2" (12.7mm) Clear 6mm</div><div><div>1. Conformance: ASTM E 2190</div><div>2. Outdoor Lite: Clear float glass as manufactured by Vitro Architectural Glass</div><div>a. Conformance: ASTM C 1036, Type 1, Class 1, Quality q3.</div><div>b. Glass Thickness: 6mm (1/4")</div><div>c. Magnetic Sputter Vacuum Deposition Coating (MSVD): ASTM C 1376.</div><div>d. Coating: Solarban® 90 on Surface # 2</div><div>e. Heat-Treatment: Tempered; ASTM C 1048, Kind FT; Safety Glazing meets ANSI Z97.1 and CPSC 16CFR-1201</div><div>3. Interspace Content: Air 1/2" (12.7mm)</div><div>4. Indoor Lite: Clear float glass as manufactured by Vitro Architectural Glass</div><div>a. Conformance: ASTM C 1036, Type 1, Class 1, Quality q3.</div><div>b. Heat-Treatment: Tempered; ASTM C 1048, Kind FT; Safety Glazing meets ANSI Z97.1 and CPSC 16CFR-1201</div><div>c. Glass Thickness: 6mm (1/4")</div><div>5. Performance Requirements:</div><div>a. Visible Light Transmittance: 51 percent minimum.</div><div>b. Winter Nighttime U-Factor: 0.29 (Btu/hr*ft**F) maximum.</div><div>c. Summer daytime U-Factor: 0.27 (Btu/hr*ft**F) maximum.</div><div>d. Shading Coefficient: 0.27 maximum.</div><div>e. Solar Heat Gain Coefficient: 0.23 maximum.</div><div>f. Outdoor Visible Light Reflectance: 12 percent maximum.</div></div><div>B. Glazing Installation</div><div>1. Install per manufacturers' standard written instructions.</div><div>C. Glazing warranty</div><div>1. Provide manufacturers' standard product warranty.</div></div> <div><div>DIVISION 9 - FINISHES</div><div>092900- Gypsum Board</div><div>Manufacturers:</div><div>Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Lafarge</u>, unless otherwise indicated, or a comparable product by one of the following:</div><div><div>1. Georgia-Pacific</div><div>2. USG</div><div>3. National Gypsum</div></div><div>Products:</div><div>A. Moisture and Mold-Resistant Type: Mold Defense</div><div><div>1. Thickness: 1/2 inch</div><div>2. Long Edges: Tapered</div><div>3. Finish: Level 4 in areas exposed to view. Level 1 in concealed areas.</div></div><div>B. Water-resistant Type: Watercheck (@ Toilet Rooms and behind plumbing fixtures)</div><div><div>1. Thickness: 1/2 inch</div><div>2. Long Edges: Tapered</div><div>3. Finish: Level 4</div><div>4. Cuts: All cuts in board shall be covered with special waterproofing sealant as recommended by the manufacturer.</div></div><div>C. Type X: Firecheck (As Required)</div><div><div>1. Thickness: 5/8"</div><div>2. Long Edges: Tapered</div><div>3. Finish: Level 4</div><div>4. All penetrations and joints to be sealed with fire caulk as recommended by the manufacturer.</div></div><div>Installation:</div><div>Install gypsum board and accessories according to manufacturers' written instructions.</div><div>Warranty:</div><div>Provide manufacturers' standard product warranty.</div></div> <div><div>096513- Resilient Base and Accessories</div><div>Manufacturers:</div><div>Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by <u>Roppe</u>, or a comparable product by one of the following:</div><div><div>1. Johnsonite, a Tarkett Company</div><div>2. Armstrong World Industries</div><div>3. Or Approved equal</div></div><div>Products:</div><div>A. Rubber Base: Pinnacle Rubber by Roppe</div><div><div>1. Height: 4"</div><div>2. Length: Coils in manufacturer's standard length</div><div>3. Outside Corners: Job formed</div><div>4. Inside Corners: Job formed</div><div>5. Color as indicated on finish schedule.</div></div><div>B. Adhesives: As recommended by the manufacturer</div><div>Installation:</div><div>Install resilient base according to manufacturers' written instructions.</div><div>Warranty:</div><div>Provide manufacturers' standard product warranty.</div></div>

AHO ARCHITECTS, LLC

www.ahoarch.com

STATE OF ALABAMA

TIMOTHY ARNOLD AHO

5099

BIRMINGHAM, ALABAMA

REGISTERED ARCHITECT

Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.


All Rights Reserved.

Architectural Specifications


Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

G201

Scale12" = 1'-0"



www.ahoarch.com



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Architectural
Specifications

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

G201

Scale 12" = 1'-0"

099113- Exterior Painting

Manufacturer:

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Sherwin-Williams.

Products:

A. Masonry: Pro Industrial Urethane Alkyd Enamel Gloss, B54-150 Series

B. Steel: Pro Industrial Urethane Alkyd Enamel Gloss, B54-150 Series

C. Wood: Pro Industrial Urethane Alkyd Enamel Gloss, B54-150 Series

D. Aluminum: Pro Industrial Urethane Alkyd Enamel Gloss, B54-150 Series

Note: Use 1 coat primer as recommended by manufacturer and 2 finish coats unless otherwise recommended by the manufacturer.

Installation:

Install exterior paint according to manufacturers' written instructions.

Warranty:

Provide manufacturers' standard product warranty.

099123- Interior Painting

Manufacturer:

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Sherwin-Williams.

Products:

A. Masonry: Pro Industrial Pre-Catalyzed Water Based Epoxy Semi-Gloss, K46W151 Series

B. Steel: Pro Industrial Urethane Alkyd Enamel Gloss, B54-150 Series

C. Wood: Pro Industrial Urethane Alkyd Enamel Gloss, B54-150 Series

D. Not Used.

E. Gypsum Board in Bay Area: ProMar 200 Zero VOC Interior Latex Egshel, B20W2600 Series. Use extreme bond primer at vinyl graphics.

F. Gypsum Board Ceilings: ProMar 200 Zero VOC Interior Latex Flat, B30W2650 Series

G. Sealed Concrete Floors: ArmorSeal Rextthane I Floor Coating + Shark Grip (1000 HS primer)

Note: Use 1 coat primer as recommended by manufacturer and 2 finish coats unless otherwise recommended by the manufacturer.

Installation:

Install interior paint according to manufacturers' written instructions.

Warranty:

Provide manufacturers' standard product warranty.

DIVISION 10 - SPECIALTIES

101419- Dimensional Letter Signage - By others.

101423.13 Room-Identification Signage

See drawing on A601.

102600 - Wall and Door Protection

Manufacturer:

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by InPro Corporation.

Products:

A. Stainless Steel Flush Mount Corner Guards

B. Corner Radius: 1/8"

C. Height: 4'-0"

D. Width: 1' 1/2"

E. Materials: Stainless Steel: Type 430, 16 gauge

F. Attachment: Pre-drilled beveled holes and Phillips head screws.

G. Finish: Stainless Steel No. 4 satin finish.

H. Location: As indicated on drawings.

J. Installation: Install per manufacturer's standard written instructions.

K. Warranty: Provide manufacturers' standard product warranty.

102800- Toilet, Bath, and Laundry Accessories

The following list of accessories is essentially complete; however, the Contractor shall examine the drawings carefully and shall supply such items not specifically called for to provide a complete installation.

Manufacturers:

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Bradley Corporation or a comparable product by one of the following:

1. Bobrick Washroom Equipment, Inc.

2. American Specialties, Inc.

3. Or Approved Equal

Products:

A. Robe Hook: Bradley Model 915.

B. Grab Bars: Bradley Model 812-001-42, Model 812-001-36, and Model 812-001-24

C. Toilet Tissue Dispenser: Bradley Model 5425 **(By Others)**

D. Mirror: Bradley Model 780-2436

E. Soap Dispenser: Bradley Model 6563 **(By Others)**

F. Paper Towel Dispenser: Bradley Model 2494 **(By Others)**

G. Under Lavatory Guard: Truebro Lav Guard 2 by IPS Corporation

Installation:

1. Install accessories according to manufacturers' written instructions, using fasteners appropriate to substrate indicated and recommended by unit manufacturer. Install units level, plumb, and firmly anchored in locations and heights indicated.

2. Install grab bars to withstand a downward load of at least 250 lbf, when tested according to ASTM F 446.

Warranty:

Provide manufacturers' standard product warranty.

104413- Fire Department Lock Box

Manufacturers:

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Knox, or a comparable product by one of the following:

1. Kidde

2. Or Approved Equal

Products:

A. Lock Box: 3200 Series Hinged Door Surface Mount

i. Color: As indicated on Finish Schedule

Installation:

1. Install fire department lock box in location and height as required by the authorities having jurisdiction.

2. Install per manufacturer's written installation instructions.

Warranty:

Provide manufacturers' standard product warranty.

104416- Fire Extinguishers

Manufacturers:

Basis-of-Design Product: Subject to compliance with requirements, provide products indicated below by Amerex Corporation, or a comparable product by one of the following:

1. Larsens Manufacturing Company

2. J.L. Industries

3. Or Approved Equal

Products:

A. ABC Dry Chemical Extinguisher: Amerex Model B456

B. Wall Bracket: Amerex Model 0546 Wall

C. UL and ULC Rating: 4A-80BC

Installation:

1. Install fire extinguishers in locations and heights indicated and in compliance with requirements of authorities having jurisdiction.

2. Install fire extinguishers and brackets according to manufacturers' written instructions.

Warranty:

Provide manufacturers' standard product warranty.

DIVISION 31- EARTHWORK

313116- Termite Control

Provide EPA Registered termiticide acceptable to authorities having jurisdiction, in an aqueous solution formulated to prevent termite infestation.

AHO ARCHITECTS, LLC

www.ahoarch.com

STATE OF ALABAMA

TIMOTHY ARNOLD AHO

5099

BIRMINGHAM, ALABAMA

REGISTERED ARCHITECT

Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Architectural Specifications

Project number24028

Date11/08/2024

Drawn byARC

Checked byN/A

G202

Scale12" = 1'-0"

11/21/2024 9:46:36 AM

EXPRESS OIL CHANGE & TIRE ENGINEER STANDARDS - EXTERIOR

EXTERIOR

RED BRICK

On newer prototype buildings, the red brick is left unpainted. The Blue Blood stripe extends all the way up to the flashing on the roof down to the top of the bay doors and all the way around the buildings). On Peak buildings, the peak is painted summit gray.

The Bay Doors are painted a bright white. The bollards that protect the bay doors are painted Safety Red. Downspouts and gutters to be painted Blue Blood.

If the building does not have a Peak, you must use the GRAY BRICK color scheme.

Must have a Gray, Black, or Blue Roof



3

PAINTED GRAY BRICK

Painted buildings include all of the same specs as the RED BRICK buildings except the red brick is painted Summit Gray. Downspouts are painted to match the background of the building.

If the building does not have a Peak, the blue stripe will go all the way around the building.

Must have a Gray, Black, or Blue Roof



4

CHANNEL LETTERS

White channel letters with 3" depth. Channel letter spacing is dictated by space and also may change due to the local sign regulations. In most cases, these letters are treated as directional signage. In most cases, sizes vary from 18" to 24".

FONT

Interstate Bold Condensed - Slit tracking


LETTERING FOR FRONT BUILDING
10 MINUTE OIL CHANGE
FULL SERVICE AUTO CARE
TIRE CENTER

LETTERING FOR BACK BUILDINGS
TIRES ALIGNMENT ROTATE & BALANCE
DIAGNOSTICS A/C BRAKES

8

Letters by Others

Note: Items shown on this page are EOC standards. See Finish Schedule for actual materials to be used on this project.



www.ahoarch.com



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

EOC Standards -
Exterior

Project number 24028
Date 11/08/2024
Drawn by ARC
Checked by N/A

G300

Scale

EXPRESS OIL CHANGE & TIRE ENGINEERS STANDARDS - INTERIOR

INTERIOR

INTERIOR PAINT
Adding lockwood blue walls to the interior creates a bold look that is consistent with EOC&TE branding. The vinyl graphics add an extra communication element.

13

IN-BAY MEDIA (OPTIONAL)
In-Bay Media integrates all EOC&TE services to the customer with powerful animated, custom messages. The video is currently over 7 minutes long, allowing some messages to be viewed more than once.

14

In Bay Media by Others

VINYL SCHEDULE

The vinyl is fully customizable as far as size and layout. Each location is different. It is best to send the vendor clear measurements of the lobby wall and of the bay walls so they can size appropriately. Please be aware of piping or shelving, or anything else that may be in the way. PLEASE ALLOW 1 WEEK FOR PAINT TO CURE BEFORE APPLYING VINYL.

Bay Area - Avery 700 Medium Gray and Rubber Duckie
Lobby Word Wall - Oracal 631 Gray 071

23

Wall Graphics by Others


PAINT SCHEDULE

BAY AREA

25

See Finish Schedule for Paint Selections

- CONSTRUCTION AND MATERIAL NOTES:**
- 1.) Cabinets - Plastic Laminate at Exposed Surfaces & Gray/Black Melamine Semi-Exposed Surfaces with 3MM PVC Edgebanding
 - 2.) Doors and Drawers - Plastic Laminate on 3/4" Gray/Black Melamine 3MM PVC Edgebanding
 - 3.) CounterTops - Plastic Laminate on 1 1/2" Plywood with 3MM PVC Edgebanding
 - 4.) Adjustable Shelf Supports - Standard Euro Style 5MM Pin System.
 - 5.) Hinges - European 120 Degree Concealed / Supports - 90 Degree Angle Brackets
 - 6.) Legs - 1" -2" Concealed Adjustable / Legs - 5" to 6" Aluminum or Chrome Adjustable
 - 7.) Finger Pulls - Hafele #126-27-036-005
 - 8.) Counter Tops - Wilsonart 4830K-18 Satin Stainless
 - 9.) Cabinets - Wilsonart 4880-38 Carbon Mesh



www.ahoarch.com

Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

EOC Standards - Interior

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

G301

Scale	As indicated
-------	--------------

11/21/2024 9:46:38 AM

1 General Information

PROJECT INFORMATION

Name of Project:

Two Building Design- Five Bay Service Building with Rear Tire Storage

Client:

Express Oil Change & Tire Engineers

Location:

Northport, AL

Authority Having Jurisdiction (AHJ):

City: Northport

County:

N/A

State:

N/A

Square Footage / Stories / Height:

Main Level G.S.F. = 3,293

Total G.S.F. = 3,293

Stories = 1

Height = 30'- 11 5/8"

PROJECT TYPE

☒ New Construction

☐ Addition

☐ Other

☐ Alteration

☐ Change of Occupancy

BUILDING USE

☒ Single Use

☐ Mixed Use (Separated)

☐ Mixed Use (Non-Separated)

☒ Description: Automotive repair garage used for general service on automobiles.

SPRINKLERED

☐ Yes

☐ Partial

☒ No

4 Special Detailed Requirements Based On Use and Occupancy (2021 IBC)

406.8 Repair Garages

☒ Project complies with 406.8 through 406.8.3

413 Combustible Storage

☒ 413.1 High-piled storage of combustible materials over 12'-0" or high-hazard commodities over 6'-0"

☒ Yes

☐ No

413.2 Storage of combustible materials in attics, under-floor, and concealed spaces

☐ Yes

☒ No

414 Hazardous Materials

☒ Project complies with 414.2.1 through 414.2.5 (IFC)Control Areas

☒ Number of Control Areas Provided: Entire Building is one control area

Location

☒ Inside

☐ Outside

Use

☒ Open

☐ Closed

☒ Storage Only

Types of Hazardous Materials (Table 307.1.(1) of IBC and 3206.2 of IFC)

☒ Allowable Quantity of Class IIB Liquids: 13,200 liquid gallons

☒ Actual Storage per control area: 28.13 gallons

☒ Allowable Quantity of Class IA Flammable Liquids: 30 liquid gallons

☒ Actual Storage per control area: 0 gallons

☒ Allowable Quantity of Class IB Flammable Liquids: 120 liquid gallons

☒ Actual Storage per control area: 6.44 gallons

☒ Allowable Amount of Inert Gas (Gaseous/ Liquidified): No limit

☒ Actual Storage per control area: 7.32 gallons

☒ High-Hazard Commodities per IFC 2018 3203.6 / 3206.2 (Rubber Tires)

☒ Allowable Quantity: 0-500 s.f.

☒ Actual Quantity: X≤500 s.f.

2 Codes

☒ 2021 International Building Code

☒ 2021 International Plumbing Code

☒ 2015 International Energy Conservation Code

☒ 2017 ICC/ANSI 117.1

☒ 2021 International Fire Code

☒ 2020 National Electrical Code

☒ 2021 International Fuel Gas Code

☒ 2021 International Mechanical Code

5 General Building Heights and Areas (2021 IBC)

504 Building Height and Areas and 506 Building Area (Per Table 504.3, 504.4, and 506.2)

☐ Allowable Building Height = 40'-0"

☒ Actual Building Height = 30'- 11 5/8"

☐ Allowable Number of Stories Above Grade Plane = 1

☒ Actual Number of Stories Above Grade Plane = 1

☐ Allowable Area Factor = 9,000 s.f.

☒ Actual Area = 3,293 s.f.

505.3 Equipment Platforms

☐ Project complies with 505.3 through 505.3.3

☒ Does not apply

508 Mixed Use and Occupancy

☐ Mixed Use Occupancy (Separated)

☐ Mixed Use Occupancy (Non-Separated)

☒ Does not apply

3 Use and Occupancy Classification(s) (2021 IBC)

☐ Assembly Group A-1

☐ High-Hazard Group H-2

☐ Residential Group R-2

☐ Assembly Group A-2

☐ High-Hazard Group H-3

☐ Residential Group R-3

☐ Assembly Group A-3

☐ High-Hazard Group H-4

☐ Residential Group R-4

☐ Assembly Group A-4

☐ High-Hazard Group H-5

☒ Storage Group S-1

☐ Assembly Group A-5

☐ Institutional Group I-1

☐ Storage Group S-2

☐ Business Group B

☐ Institutional Group I-2

☐ Utility & Misc Group U

☐ Educational Group E

☐ Institutional Group I-3

☐ Factory Group F-1

☐ Institutional Group I-4

☐ Factory Group F-2

☐ Mercantile Group M

☐ High-Hazard Group H-1

☐ Residential Group R-1

6 Types of Construction (2021 IBC)

601 General and 602 Construction Classification

☐ Type IA

☐ Type IB

☐ Type IIA

☐ Type IIB

☐ Type IIIA

☐ Type IIIB

☐ Type IV

☐ Type VA

☒ Type VB

Table 601 Fire Resistance Rating Requirements for Building Elements

Building Elements	Hours Required	Hours Provided
Primary Structural Frame	0	0
Bearing Walls (Exterior)	0	0
Bearing Walls (Interior)	0	N/A
Nonbearing Walls & Partitions (Exterior)	0	0
Nonbearing Walls & Partitions (Interior)	0	0
Floor Construction & Associated Secondary Members	0	0
Roof Construction & Associated Secondary Members	0	0

Table 705.5 Fire Resistance Requirements for Exterior Walls Based on Fire Separation Distance

Fire Separation Distance	Rear (North)	Right (East)	Front (South)	Left (West)
X < 5				
5 ≤ X < 10				
10 ≤ X < 30	=20'-0"			=21'-0"
X ≥ 30		>30'	>30'	

X≥30' for Group B and S-1 = 0 hours

10≤X<30' for Group B and S-1 = 0 hours

7 Fire And Smoke Protection Systems (2021 IBC)

718.4 Draftstopping in Attics

☒ Yes

☐ No

☐ Not Required

☒ Openings in the partitions shall be protected by self-closing doors with automatic latches constructed as required for the partitions.

☒ Installed in attics and concealed roof spaces such that any horizontal area does not exceed 3,000 s.f.

8 Interior Finishes (2021 IBC)

Table 803.13 Interior Wall and Ceiling Finish Requirements by Occupancy

Group	Exit Enclosures and Exit Passageways	Corridors	Rooms and Enclosed Spaces
S-1	B	B	C

804.4.2 Minimum Critical Radiant Flux

☐ Class I

☒ Class II

9 Fire Protection Systems (2021 IBC)

903 Automatic Sprinkler Systems

903.2.9.1 Repair Garages

☐ Yes

☐ Partial

☒ Not Required

906 Portable Fire Extinguishers

☒ Yes

☐ No

☒ Project complies with 906.1 through 906.10

☒ Project complies NFPA 10

907 Fire Alarm and Detection System

☐ Yes

☒ Not Required

10 Means of Egress (2021 IBC)

DT_2021 IBC Table 1004.5 Maximum Floor Area Allowance Per Occupant (Group S-1)

Occupancy Classification	Name	Number	Area	S.F. Per Occupants	No. of Occupants
S-1	Service	1	2186 SF	200	10.93
S-1	Toilet	2	46 SF	150	0.30
S-1	Storage	3	349 SF	300	1.16
S-1	Storage	4	500 SF	300	1.67
Subtotal			3081 SF		14.06

Please Note: The Group H-5 Fabrication and Manufacturing Load Factor of 200 square foot per occupant for manufacturing function of space was used for the above calculations because there is not a function of space occupant load factor for Repair Garages.

DT_2021 IBC Sections 1005.3.1 & 1005.3.2 Egress width Stairways and Other Egress Components (Group S-1)

Occupancy Classification	Name	Number	No. of Occupants	Other Egress Components	Required Capacity in Inches
S-1	Service	1	10.93	0.2	2.19
S-1	Toilet	2	0.30	0.2	0.06
S-1	Storage	3	1.16	0.2	0.23
S-1	Storage	4	1.67	0.2	0.33
Subtotal			14.06		2.81

10 Means of Egress (2021 IBC)

Tables 1006.2.1 Spaces with One Exit or Exit Access Doorway

Occupancy	Max Occupant Load	Max Occupant Load Provided	Number of Exits Required	Number of Exits Provided	Max. Common Path of Travel Allowable (Nonsprinkled)	Max. Provided Common Path of Travel (Nonsprinkled)
S-1	29	14.06	1	4	100'-0"	≤ 75'-0"

Table 1017.2 Exit Access Travel Distance

Occupancy	Without Sprinkler System (Feet)	With Sprinkler System	Max Travel Distance Provided (Feet)
S-1	200	N/A	52'-8"

Table 1006.3.3 Minimum Number of Exits or Access to Exits Per Story

Occupant Load Per Story	Minimum Number of Exits or Access to Exits from Story	Number of Exits or Access to Exits from Story Provided
1-500	2	4

www.ahoarch.com

Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Life Safety / Code Summary

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

LS100

Scale 12" = 1'-0"

11/21/2024 9:46:40 AM

29 Plumbing Systems (2021 IBC)

Table 2902.1 Minimum Number of Required Plumbing Fixtures

DT_Plumbing Fixture_Group S-1												
Total Occupant Load	Male	Female	Required Water Closets		Water Closets Provided	Required Lavatories		Lavatories Provided	Required Drinking Fountains	Drinking Fountains Provided	Required Service Sinks	Service Sinks Provided
			Male	Female		Male	Female					
14.06	7.03	7.03	0.07	0.07	1	0.07	0.07	1	0.01	1	1	1

2902.2 Separate Facilities

Separate facilities provided for each sex

☐ Yes ☒ Not Required per 2902.2 Exception 2

Plumbing Fixture Notes:
(1) High / Low drinking fountain provided for the entire building.
(1) Service Sink provided for the entire building.
(1) Family Assisted-Use Toilet Room containing (1) lavatory and (1) water closet provided for the entire building.

2902.2.1 Family or assisted use toilet facilities serving as separate facilities

☐ Yes ☐ No ☒ Not Required

2902.3 Employee and public toilet facilities

☒ Employee toilet combined with public toilet facilities

2902.3.1 Access

Route to public toilet facilities does not pass through kitchens, storage rooms, or closets and is accessible.

☒ Yes ☐ No

2902.3.3 Location of toilet facilities in occupancies other than covered mall buildings

Located not more than one story above or below the space required to be provided with toilet facilities

☒ Yes ☐ No

Path of travel to such facilities does not exceed 500 feet

☒ Yes ☐ No

2902.4 Signage

☒ Yes ☐ No

Legible sign designating the sex provided in visible location near entrance to toilet facility

☐ Yes ☒ Not Required per 2902.2.1

5 Fire Service Features (2021 IFC)

505.1 Address Identification

☒ Yes ☐ No ☐ Not Required ☐ Provided on Oil Change Building

☒ Project complies 505.1 Address Identification

506 Key Boxes

☒ Yes ☐ No ☐ Not Required

☒ Project complies 506.1 Where Required

32 High Piled Combustible Storage (2021 IFC)

3203.6 High-hazard commodities

☒ Yes ☐ No

☒ Project does contain high-hazard commodities (Rubber Tires)

Definitions per Chapter 2 of the International Fire Code

High-piled Combustible Storage. Storage of combustible materials in closely packed piles or combustible materials on pallets, in racks or on shelves where the top of storage is greater than 12'-0" in height. When required by the fire code official, high-piled combustible storage also includes certain high-hazard commodities, such as rubber tires, Group A plastics, flammable liquids, idle pallets, and similar commodities, where the top of storage is greater than 6'-0" in height.

☒ Project ~~does~~ contain high piled combustible storage over 6'-0" (<500 s.f. of rubber tire storage over 6 feet high).

Table 3206.2 General Fire Protection and Life Safety Requirements

Commodity Class	Size of High Piled Storage Area	All Storage Areas			
		Automatic Fire Extinguishing System	Fire Detection System	Building Access	Smoke and Heat Removal
High Hazard	0-500 s.f.	Not Required	Not Required	Not Required	Not Required

Solid-Piled Storage, Shelf Storage and Palletized Storage			
Max. Pile Dimension (Feet)	Max. Permissible Storage Height (Feet)	Max. Pile Volume (Cubic Feet)	
60 feet	Not Required	Not Required	

34 Tire Rebuilding and Tire Storage (2021 IFC)

3409 Indoor Storage Arrangement

- ☒ Project complies with 3409.1 Pile Dimensions
- ☒ Pile dimension less than 50'-0" in direction of wheel hole.
- ☒ Tires stored adjacent to or along one wall shall not extend more than 25'-0" from that wall.


57 Flammable and Combustible Liquids (2021 IFC)

5703.2 Fire Protection

☒ Project complies with 5703.2.1 portable fire extinguishers an hose lines. (See Section 9 Fire Protection Systems).

5703.4 Spill Control and Secondary Containment

☒ Not required. Project does not exceed maximum allowable quantity per control area.



www.ahoarch.com



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC. All Rights Reserved.

Life Safety / Code Summary

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A
LS101	
Scale	12" = 1'-0"

LIFE SAFETY SYMBOL LEGEND

Exit Sign

HC
EXIT
32"

Handicap Accessible
Egress Width

32"

Exit from room
(# = minimum clear
width in inches)

Maneuvering
clearances at
manual swinging
doors

#

Travel Distance

1 Hour Rated

11 Life Safety Plan_Main
3/16" = 1'-0"

Keynote Schedule	
Tag	Text
26	Fire Department Lock Box. Locate as directed by the Local Fire Marshal or AHJ. See Specification 104413 Fire Department Lock Box.
33	ADA compliant room / exit sign. See Details.
38	Eyewash station. See Plumbing.
51	Provide 20"x30" insulated attic access panel.
63	Service Desk. See Details on sheet G301.
213	Full height chain-link fence with 3'-0" x 7'-0" gate.
214	10K Lift (By Others).
216	Tire changer (By Others).
217	Wheel balancer (By Others).
218	Brake lathe (By Others).
219	Air compressor (By Others).
220	Scissor lift alignment (By Others). Verify dimensions of alignment pit with Owner / Alignment Lift Manufacturer prior to rough-in.
221	Scissor lift alignment console (By Others). Provide conduit in slab as required. See alignment lift specifications (By Others).
222	Alignment scarecrow (By Others).
223	Work bench (By Others).
224	Strut compressor (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.

Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.


Life Safety Plan -
Main

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A


LS102

Scale As indicated

11/21/2024 9:46:41 AM



1 Architectural Site Plan
N.T.S.





AHO ARCHITECTS, LLC

www.ahoarch.com



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.


Architectural Site Plan

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

AS100

Scale	N.T.S.
-------	--------

11/21/2024 9:46:32 AM



1 01. Floor Plan - Main
3/16" = 1'-0"

Keynote Schedule	
Tag	Text
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
20	4" diameter painted concrete-filled steel pipe bollard. Color as indicated on Finish Schedule. Paint embedded portion of bollard. Use primer and two finish coats. See Details on sheet A101. See Specification 055000 Metal Fabrications.
25	Control joint. For control joints in concrete floor slabs, coordinate location with equipment layout by others. Max. distance between control joints in slabs not to exceed 12'-0". Control joints in walls shall be 4'-0" max from wall intersection or corner and every 20'-0".
26	Fire Department Lock Box. Locate as directed by the Local Fire Marshal or AHJ. See Specification 104413 Fire Department Lock Box.
33	ADA compliant room / exit sign. See Details.
38	Eyewash station. See Plumbing.
44	Concrete apron. See Civil. Slope away from building with 3% slope.
45	See Structural for jamb reinforcing as required.
51	Provide 20"x30" insulated attic access panel.
63	Service Desk. See Details on sheet G301.
70	4'-0" high FRP on wet wall. See Specification 066400 Plastic Paneling (Fiberglass Reinforced Panels).
186	Paint 3" P-5 Safety Yellow around alignment pit. Verify paint is compatible with floor finish.
213	Full height chain-link fence with 3'-0" x 7'-0" gate.
214	10K Lift (By Others).
215	12K Lift (By Others).
216	Tire changer (By Others).
217	Wheel balancer (By Others).
218	Brake lathe (By Others).
219	Air compressor (By Others).
220	Scissor lift alignment (By Others). Verify dimensions of alignment pit with Owner / Alignment Lift Manufacturer prior to rough-in.
221	Scissor lift alignment console (By Others). Provide conduit in slab as required. See alignment lift specifications (By Others).
222	Alignment scarecrow (By Others).
223	Work bench (By Others).
224	Strut compressor (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Floor Plan - Main

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A


A100


Scale 3/16" = 1'-0"






1 02_Enlarged Plan_Main
3/4" = 1'-0"






DT_Sheet A104_Ceiling Joist Detail @ SV Toilet
1 1/2" = 1'-0"

Keynote Schedule	
Tag	Text
6	Painted 1/2" thick fire-rated plywood with 1/4" x 1 1/4" fire-rated painted wood batten strips at seams, secured to underside of roof trusses. Provide painted 1"x4" fire-rated wood trim at perimeter.
7	Painted 1/2" gypsum board ceiling, 5/8" Type X where indicated. See Specification Section 061000 Rough Carpentry.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
39	Provide attic draftstop partition and access door per IBC. Wall shall read "Seal All Penetrations" every 25'-0" o.c. Attic "Floor" area within draftstop areas shall not exceed 3,000 s.f. Draftstop materials shall not be less than 1/2" gypsum board adequately supported. The integrity of draftstop shall be maintained. Provide 1 opening per partition, protected by a self-closing door constructed as required for the partition with automatic latch. Door shall not be less than 20"x30" which is required for attic access specified in Section 1209.2 of the IBC. Provided max. 3,000 s.f. area is not exceeded, draftstop locations shall align with structural supports.
51	Provide 20"x30" insulated attic access panel.
113	Fluid applied vapor permeable air barrier. See Specification 072726 Fluid Applied Membrane Air Barrier.
114	Contractor to ensure overhead door, track, etc. meets the minimum vertical clearance required for equipment (By Others). Typical.
115	Dashed line indicates extent of overhead doors. Typical.
116	See Engineering drawings for Mechanical/Electrical/Plumbing fixtures and equipment. Typical.
142	Unfaced R-30 batt insulation. See Specification 072100 Thermal Insulation.
213	Full height chain-link fence with 3'-0" x 7'-0" gate.



01_RCP_Main
3/16" = 1'-0"



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.


Reflected Ceiling
Plan - Main

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A


A104

Scale As indicated







2 DT. Sheet A106_SSMR Roof Penetration Detail
1 1/2" = 1'-0"




3 DT. Sheet A106_SSMR Roof Curb Detail
1 1/2" = 1'-0"




4 Draft Template_Typical Ridge-Hip Detail
1" = 1'-0"



Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
39	Provide attic draftstop partition and access door per IBC. Wall shall read "Seal All Penetrations" every 25'-0" o.c. Attic "Floor" area within draftstop areas shall not exceed 3,000 s.f. Draftstop materials shall not be less than 1/2" gypsum board adequately supported. The integrity of draftstop shall be maintained. Provide 1 opening per partition, protected by a self-closing door constructed as required for the partition with automatic latch. Door shall not be less than 20"x30" which is required for attic access specified in Section 1209.2 of the IBC. Provided max. 3,000 s.f. area is not exceeded, draftstop locations shall align with structural supports.
42	Paint all roof penetrations to match roof color.
118	Stainless steel draw band.
119	Metal storm collar. Finish to match roof.
120	Rubber boot. Cut to suit pipe penetration.
121	Rivet boot to panel with continuous bead of sealant between boot and panel.
122	When pipe is fixed to structure and not designed to float with roof panel, cut hole in panel to allow for thermal expansion.



1 03. Roof Plan
3/16" = 1'-0"



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Roof Plan


Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

A108

Scale As indicated




EXTERIOR FINISH MATERIAL LEGEND




PAINTED SPLIT-FACE CMU

Color: SW7669 Summit Gray
Manuf: Sherwin Williams




STRUCTURAL HALF-HIGHS

Color: Richfield Blend
Manuf: Echelon




EXTERIOR PAINT

Color: SW6966 Blueblood
Manuf: Sherwin Williams



ROOF

Color: Royal Blue
Manuf: Berridge



HM DOORS

Color: SW7669 Summit Gray
Manuf: Sherwin Williams



STOREFRONT DOORS

Color: Clear Anodized Aluminum
Manuf: YKK

Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
15	1x pressure treated painted fascia board, continuous.
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
20	4" diameter painted concrete-filled steel pipe bollard. Color as indicated on Finish Schedule. Paint embedded portion of bollard. Use primer and two finish coats. See Details on sheet A101. See Specification 055000 Metal Fabrications.
22	Signage (By Others). Provide blocking as required. See Electrical.
25	Control joint. For control joints in concrete floor slabs, coordinate location with equipment layout by others. Max. distance between control joints in slabs not to exceed 12'-0". Control joints in walls shall be 4'-0" max from wall intersection or corner and every 20'-0".
26	Fire Department Lock Box. Locate as directed by the Local Fire Marshal or AHJ. See Specification 104413 Fire Department Lock Box.
68	1x pressure treated painted frieze board, continuous.

NOTE:
Align top of exterior wall packs with bottom of banding at 12'-0" a.f.f.



01_ Exterior Elevation_Front (South)
3/16" = 1'-0"



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.


Exterior Elevation -
Front (South)

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

A200


Scale 3/16" = 1'-0"

EXTERIOR FINISH MATERIAL LEGEND




PAINTED SPLIT-FACE CMU

Color: SW7669 Summit Gray
Manuf: Sherwin Williams




STRUCTURAL HALF-HIGHS

Color: Richfield Blend
Manuf: Echelon




EXTERIOR PAINT

Color: SW6966 Blueblood
Manuf: Sherwin Williams



ROOF

Color: Royal Blue
Manuf: Berridge



HM DOORS

Color: SW7669 Summit Gray
Manuf: Sherwin Williams




STOREFRONT DOORS


Color: Clear Anodized Aluminum
Manuf: YKK

Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
15	1x pressure treated painted fascia board, continuous.
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
25	Control joint. For control joints in concrete floor slabs, coordinate location with equipment layout by others. Max. distance between control joints in slabs not to exceed 12'-0". Control joints in walls shall be 4'-0" max from wall intersection or corner and every 20'-0".
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
68	1x pressure treated painted frieze board, continuous.

NOTE:
Align top of exterior wall packs with bottom of banding at 12'-0" a.f.f.



① 02_Exterior Elevation_Rear (North)
3/16" = 1'-0"



www.ahoarch.com



Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Exterior Elevation -
Rear (North)


Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

A201

Scale 3/16" = 1'-0"


11/21/2024 9:46:06 AM

EXTERIOR FINISH MATERIAL LEGEND




PAINTED SPLIT-FACE CMU

Color: SW7669 Summit Gray
Manuf: Sherwin Williams




STRUCTURAL HALF-HIGHS

Color: Richfield Blend
Manuf: Echelon




EXTERIOR PAINT

Color: SW6966 Blueblood
Manuf: Sherwin Williams



ROOF

Color: Royal Blue
Manuf: Berridge



HM DOORS

Color: SW7669 Summit Gray
Manuf: Sherwin Williams




STOREFRONT DOORS

Color: Clear Anodized Aluminum
Manuf: YKK

NOTE:

Align top of exterior wall packs with bottom of banding at 12'-0" a.f.f.



03 Exterior Elevation_Right (East)
3/16" = 1'-0"

Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties. (In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
15	1x pressure treated painted fascia board, continuous.
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
20	4" diameter painted concrete-filled steel pipe bollard. Color as indicated on Finish Schedule. Paint embedded portion of bollard. Use primer and two finish coats. See Details on sheet A101. See Specification 055000 Metal Fabrications.
25	Control joint. For control joints in concrete floor slabs, coordinate location with equipment layout by others. Max. distance between control joints in slabs not to exceed 12'-0". Control joints in walls shall be 4'-0" max from wall intersection or corner and every 20'-0".
26	Fire Department Lock Box. Locate as directed by the Local Fire Marshal or AHJ. See Specification 104413 Fire Department Lock Box.
44	Concrete apron. See Civil. Slope away from building with 3% slope.
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
68	1x pressure treated painted frieze board, continuous.



www.ahoarch.com



Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Exterior Elevation -
Right (East)


Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

A202

Scale	3/16" = 1'-0"
-------	---------------


11/21/2024 9:46:12 AM

EXTERIOR FINISH MATERIAL LEGEND




PAINTED SPLIT-FACE CMU

Color: SW7669 Summit Gray
Manuf: Sherwin Williams




STRUCTURAL HALF-HIGHS

Color: Richfield Blend
Manuf: Echelon




EXTERIOR PAINT

Color: SW6966 Blueblood
Manuf: Sherwin Williams



ROOF

Color: Royal Blue
Manuf: Berridge



HM DOORS

Color: SW7669 Summit Gray
Manuf: Sherwin Williams



STOREFRONT DOORS

Color: Clear Anodized Aluminum
Manuf: YKK


NOTE:

Align top of exterior wall packs with bottom of banding at 12'-0" a.f.f.

Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
15	1x pressure treated painted fascia board, continuous.
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
20	4" diameter painted concrete-filled steel pipe bollard. Color as indicated on Finish Schedule. Paint embedded portion of bollard. Use primer and two finish coats. See Details on sheet A101. See Specification 055000 Metal Fabrications.
25	Control joint. For control joints in concrete floor slabs, coordinate location with equipment layout by others. Max. distance between control joints in slabs not to exceed 12'-0". Control joints in walls shall be 4'-0" max from wall intersection or corner and every 20'-0".
26	Fire Department Lock Box. Locate as directed by the Local Fire Marshal or AHJ. See Specification 104413 Fire Department Lock Box.
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
68	1x pressure treated painted frieze board, continuous.



① 04_ Exterior Elevation Left (West)
3/16" = 1'-0"



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Exterior Elevation -
Left (West)


Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

A203

Scale 3/16" = 1'-0"



Keynote Schedule	
Tag	Text
6	Painted 1/2" thick fire-rated plywood with 1/4" x 1 1/4" fire-rated painted wood batten strips at seams, secured to underside of roof trusses. Provide painted 1"x4" fire-rated wood trim at perimeter.
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
15	1x pressure treated painted fascia board, continuous.
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
38	Eyewash station. See Plumbing.
39	Provide attic draftstop partition and access door per IBC. Wall shall read "Seal All Penetrations" every 25'-0" o.c. Attic "Floor" area within draftstop areas shall not exceed 3,000 s.f. Draftstop materials shall not be less than 1/2" gypsum board adequately supported. The integrity of draftstop shall be maintained. Provide 1 opening per partition, protected by a self-closing door constructed as required for the partition with automatic latch. Door shall not be less than 20"x30" which is required for attic access specified in Section 1209.2 of the IBC. Provided max. 3,000 s.f. area is not exceeded, draftstop locations shall align with structural supports.
44	Concrete apron. See Civil. Slope away from building with 3% slope.
68	1x pressure treated painted frieze board, continuous.
74	1/2" expansion joint with backer rod and sealant.
89	Concrete foundation. See Structural.
100	Concrete slab. See Structural.
109	Horizontal joint reinforcement at 16" o.c. vertical.
123	Blocking. See Structural.
124	Pre-engineered wood roof truss. See Structural.
125	Insulation baffle.
126	Unfaced R-38 batt insulation. See Specification 072100 Thermal Insulation.
127	2x pressure treated wood nailer.
128	Painted smooth-face 8" concrete-filled "U" block bond beam. Condition varies. See Structural.
129	"H" clips at mid-span on standing seam metal roof.
130	2 layers of #15 roofing felt.
131	5/8" pressure treated plywood decking. See Structural.
132	2x wood sub-fascia, continuous.
133	Field cut seam and form pan around eave flashing.
134	Eave flashing with drip edge.
135	Painted vented soffit with paintable PVC "H" jointers between panels, fastened to pressure treated 2"x4" wood blocking. See Specification Section 074293 Soffit Panels.
136	Pea gravel above through wall flashing.
137	Base flashing between first and second course to utilize BlockFlash. In addition to the pea gravel specified, provide a drainage mat in open masonry cell directly above the BlockFlash pan.
138	Drainable weeps at every third mortar joint.
139	10 mil vapor barrier. See Specification 072600 Vapor Retarders.
140	4" porous fill. See Geotechnical Report.
170	Fill first course of CMU with grout.
214	10K Lift (By Others).
215	12K Lift (By Others).
216	Tire changer (By Others).
217	Wheel balancer (By Others).
220	Scissor lift alignment (By Others). Verify dimensions of alignment pit with Owner / Alignment Lift Manufacturer prior to rough-in.
222	Alignment scarecrow (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Building Sections

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

A300

Scale As indicated



Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL


No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.


Building Sections

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A
A301	
Scale	As indicated

Keynote Schedule	
Tag	Text
9	Pre-finished standing seam metal roof system. See Specification 074113.16 Standing Seam Metal Roof Panels. See Finish Schedule for color.
10	Pre-finished metal gutter system. See Specification 077100 Roof Specialties.
12	(In locations indicated on the floor plan) Pre-finished metal downspout to discharge on grade unless otherwise indicated to be piped to storm. See Specification 077100 Roof Specialties.
13	Pre-finished metal hip and ridge cap by metal roofing manufacturer. Provide concealed ridge venting if indicated. Color to match roof. See Specification 074113.16 Standing Seam Metal Roof Panels.
20	4" diameter painted concrete-filled steel pipe bollard. Color as indicated on Finish Schedule. Paint embedded portion of bollard. Use primer and two finish coats. See Details on sheet A101. See Specification 055000 Metal Fabrications.
33	ADA compliant room / exit sign. See Details.
39	Provide attic draftstop partition and access door per IBC. Wall shall read "Seal All Penetrations" every 25'-0" o.c. Attic "Floor" area within draftstop areas shall not exceed 3,000 s.f. Draftstop materials shall not be less than 1/2" gypsum board adequately supported. The integrity of draftstop shall be maintained. Provide 1 opening per partition, protected by a self-closing door constructed as required for the partition with automatic latch. Door shall not be less than 20"x30" which is required for attic access specified in Section 1209.2 of the IBC. Provided max. 3,000 s.f. area is not exceeded, draftstop locations shall align with structural supports.
44	Concrete apron. See Civil. Slope away from building with 3% slope.
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
74	1/2" expansion joint with backer rod and sealant.
89	Concrete foundation. See Structural.
100	Concrete slab. See Structural.
139	10 mil vapor barrier. See Specification 072600 Vapor Retarders.
140	4" porous fill. See Geotechnical Report.
149	1/2" recess at scheduled door. See Structural.
194	Scheduled door. See plans for details.
214	10K Lift (By Others).
215	12K Lift (By Others).
216	Tire changer (By Others).
221	Scissor lift alignment console (By Others). Provide conduit in slab as required. See alignment lift specifications (By Others).
222	Alignment scarecrow (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.



1 Building Section 2
3/16" = 1'-0"




2 DT_Sheet A301_Slab on Grade @ OH Door -Service Bldg.
1" = 1'-0"

E2


Install siloxane on the exterior side of wall construction

Refer to structural drawings for reinforcing, grouting, and other information



Wall Type No.	Description	Width	Ref Test
E2	As shown	7 5/8"	-


I2



Wall Type No.	Description	Width	Ref Test
I2	As shown	6"	-


I3

Note: Stagger electrical outlet boxes, switches, etc. Seal around all penetrations in wall with acoustical sealant.



Wall Type No.	Description	Width	Ref Test
I3	As shown	6 1/2"	-


I4




Wall Type No.	Description	Width	Ref Test
I4	2 Hour rated wall assembly. (1 hour required.) 1 Hour rated ceiling assembly.	Varies	U905 (CMU) / P522 Ceiling

Keynote Schedule


Tag	Text
16	Painted structural half-highs. See Specification 042200 Concrete Unit Masonry.
17	Painted 8" split-face CMU (bond beam where indicated, see Structural). As required, provide painted smooth-face, grout filled "U" block bond beam at lightbars only. As required, paint CMU lintel above OH doors as indicated on finish schedule. See Structural. See Specification 042200 Concrete Unit Masonry.
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
19	Painted 8" split-face CMU (bond beam where indicated, see Structural). See Specification 042200 Concrete Unit Masonry.
68	1x pressure treated painted frieze board, continuous.
109	Horizontal joint reinforcement at 16" o.c. vertical.
112	Painted 1/2" gypsum board on 2x6 wood studs at 16" o.c. with kraft-face R-20 batt insulation (kraft in contact with gypsum board). See Details on sheet A400.
113	Fluid applied vapor permeable air barrier. See Specification 072726 Fluid Applied Membrane Air Barrier.
124	Pre-engineered wood roof truss. See Structural.
127	2x pressure treated wood nailer.
128	Painted smooth-face 8" concrete-filled "U" block bond beam. Condition varies. See Structural.
136	Pea gravel above through wall flashing.
137	Base flashing between first and second course to utilize BlockFlash. In addition to the pea gravel specified, provide a drainage mat in open masonry cell directly above the BlockFlash pan.
138	Drainable weeps at every third mortar joint.
145	2x pressure treated wood sill plate.
170	Fill first course of CMU with grout.
203	Acoustical sealant and backer rod. See Specification 079219 Acoustical Joint Sealants.
205	1 layer of 1/2" painted gypsum board on both sides of 2"x6" wood studs at 16" o.c. Infill with kraft-faced R-20 batt insulation. Kraft in contact with gypsum board.
206	Fire caulk both sides. Typical. See Specification 078443 Joint Firestopping.
241	5/8" Type X gypsum board over 1/2" resilient channels. Fire caulk both sides. Typical.
242	2x pressure treated wood top plate.



DT_Sheet A400_Gypsum Board Control Joint
1 1/2" = 1'-0"



DT_Sheet A400_Masonry Control Joint
1 1/2" = 1'-0"



DT_Sheet A400_Sealant Detail
6" = 1'-0"



Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Wall Types


Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

A400


Scale As indicated




① Service Bay Interior Elevation A
1/4" = 1'-0"



③ Service Bay Interior Elevation C
1/4" = 1'-0"



② Service Bay Interior Elevation B
1/4" = 1'-0"



④ Service Bay Interior Elevation D
1/4" = 1'-0"

Keynote Schedule	
Tag	Text
33	ADA compliant room / exit sign. See Details.
38	Eyewash station. See Plumbing.
56	Metal louver or vent. Color to match adjacent surface. See Mechanical.
63	Service Desk. See Details on sheet G301.
70	4'-0" high FRP on wet wall. See Specification 066400 Plastic Paneling (Fiberglass Reinforced Panels).
172	Ensure paint line occurs at top of door and window frames. Ensure all openings, alcoves and windows align with top of door frame. Typical in Oil and Service Bays.
213	Full height chain-link fence with 3'-0" x 7'-0" gate.
214	10K Lift (By Others).
215	12K Lift (By Others).
216	Tire changer (By Others).
217	Wheel balancer (By Others).
220	Scissor lift alignment (By Others). Verify dimensions of alignment pit with Owner / Alignment Lift Manufacturer prior to rough-in.
221	Scissor lift alignment console (By Others). Provide conduit in slab as required. See alignment lift specifications (By Others).
222	Alignment scarecrow (By Others).
224	Strut compressor (By Others).
232	Bracket mounted fire extinguisher. Provide sign at all fire extinguisher locations which may be visually obstructed. See Details on Sheet A602.



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Interior Elevations


Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

A600


Scale 1/4" = 1'-0"




1 Toilet 2 Interior Elevation A
3/4" = 1'-0"




2 Toilet 2 Interior Elevation B
3/4" = 1'-0"




3 Toilet 2 Interior Elevation C
3/4" = 1'-0"



4 Toilet 2 Interior Elevation D
3/4" = 1'-0"




Signage shall comply with Section 703 of the 2017 ICC/ANSI A117.1




Red and white vinyl sign at all fire extinguisher locations which may be visually obstructed (i.e. in Service)

Keynote Schedule	
Tag	Text
4	Robe hook mounted at 48" A.F.F. See Specification 102800 Toilet, Bath, and Laundry Accessories.
5	42" grab bar with blocking in walls as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
28	Framed mirror. See Specification 102800 Toilet, Bath, and Laundry Accessories.
29	Automatic Towel Dispenser (By others). Provide blocking in wall as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
30	Wall mounted soap dispenser (By Others). Provide blocking in wall as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
31	Jumbo Dual Roll Toilet Tissue dispenser (By Others). Provide blocking in wall as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
32	36" grab bar with blocking in walls as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
40	Under lavatory guard. See Specification 102800 Toilet, Bath, and Laundry Accessories.
43	24" vertical grab bar with blocking in walls as required. See Specification 102800 Toilet, Bath, and Laundry Accessories.
185	Flush valve on transfer side of water closet.



www.ahoarch.com



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.


Interior Elevations

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A


A601

Scale As indicated


11/21/2024 9:46:23 AM




DT-Sheet A605_Drinking Fountain_Plan View
1/2" = 1'-0"



DT_Sheet A605_Limits of Protruding Objects
1/2" = 1'-0"




DT_Sheet A605_Drinking Fountain_Front View
1/2" = 1'-0"




DT_Sheet A605_Clear Width @ Doorways
1/2" = 1'-0"


Mounting heights for portable fire extinguishers
(cabinet and bracket mounted) per
IBC Chapter 9)




DT_Sheet A605_Fire Extinguisher Mounting Heights
1" = 1'-0"



DT_Sheet A605_Spacing of Grab Bars
1 1/2" = 1'-0"



DT_Sheet A605_Level Change
12" = 1'-0"



DT_Sheet A605_Signage Mounting Heights
3/4" = 1'-0"

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Interior
Dimensional Info.

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

A605

Scale As indicated

FLOOR FINISH LEGEND

Sealed Concrete

Safety Yellow Paint.
See notes below.

Tile

CG = Corner Guard

Keynote Schedule	
Tag	Text
55	Stainless steel corner guard. See Specification 102600 Wall and Door Protection.
186	Paint 3" P-5 Safety Yellow around alignment pit. Verify paint is compatible with floor finish.

2 21_Floor Finish Plan_Main
3/16" = 1'-0"

AHO ARCHITECTS, LLC

www.ahoarch.com

Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Floor Finishes - Main

Project number24028

Date11/08/2024

Drawn byARC

Checked byN/A


A610

ScaleAs indicated


11/21/2024 9:46:24 AM

Door and Frame Schedule												
Number	Door						Frame			Glass	UL Label	Notes
	Width	Height	Thickness	Door Type	Door Material	Door Finish	Frame Type	Frame Material	Frame Finish			
1	3' - 0"	7' - 0"	0' - 1 3/4"	SF	Aluminum / Glass	Factory Finish	3	Aluminum	Factory Finish	Tempered		If required by the Fire Marshal or AHJ, add lettering that reads, "This door must remain unlocked when business is occupied."
2	10' - 0"	12' - 0"	0' - 2 1/8"	OH	Metal / Glass	Factory Finish	N/A	N/A	Factory Finish	Tempered		
3	10' - 0"	12' - 0"	0' - 2 1/8"	OH	Metal / Glass	Factory Finish	N/A	N/A	Factory Finish	Tempered		
4	10' - 0"	12' - 0"	0' - 2 1/8"	OH	Metal / Glass	Factory Finish	N/A	N/A	Factory Finish	Tempered		
5	10' - 0"	12' - 0"	0' - 2 1/8"	OH	Metal / Glass	Factory Finish	N/A	N/A	Factory Finish	Tempered		
6	10' - 0"	12' - 0"	0' - 2 1/8"	OH	Metal / Glass	Factory Finish	N/A	N/A	Factory Finish	Tempered		
7	3' - 0"	7' - 0"	0' - 1 3/4"	F	Hollow Metal	Painted	2	Hollow Metal	Painted	N/A		
8	3' - 0"	7' - 0"	0' - 1 3/4"	F	Hollow Metal	Painted	2	Hollow Metal	Painted	N/A		
9	4' - 0"	7' - 0"	0' - 1 3/4"	F	Hollow Metal	Painted	2	Hollow Metal	Painted	N/A		
10	3' - 0"	7' - 0"	0' - 1 3/4"	F	Hollow Metal	Painted	1	Hollow Metal	Painted	N/A		
11	3' - 0"	7' - 0"	0' - 1 3/4"	F	Hollow Metal	Painted	2	Hollow Metal	Painted	N/A		

WINDOW LEGEND



DOOR AND FRAME LEGEND



NOTE: Refer to floor plan for direction of door swing.

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC. All Rights Reserved.

Schedules


Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

A620


Scale 1/4" = 1'-0"



1 DT_Sheet A621_Door Head Detail_Wood
3" = 1'-0"




2 DT_Sheet A621_Exterior Door Head Detail_Masonry
3" = 1'-0"




3 DT_Sheet A621_Door Head Detail_Masonry (Interior)
3" = 1'-0"

Keynote Schedule	
Tag	Text
18	Unpainted structural half-highs. See Specification 042200 Concrete Unit Masonry.
109	Horizontal joint reinforcement at 16" o.c. vertical.
110	Sealant with backer rod. Match adjacent material color.
111	Aluminum storefront with insulated glazing. See Details on sheet A620.
123	Blocking. See Structural.
128	Painted smooth-face 8" concrete-filled "U" block bond beam. Condition varies. See Structural.
188	Kraft-faced batt insulation. Kraft in contact with gypsum board.
189	2x wood studs at 16" o.c.
190	1/2" painted gypsum board.
191	Double 2"x8" wood header.
192	Caulk all around on both sides.
193	Painted hollow metal frame with returns. See Finish Schedule for color.
194	Scheduled door. See plans for details.
196	Closed bottom structural half-high bond beam. See Structural.
197	Painted hollow metal frame, grouted solid.
198	Jamb anchors. Provide 3 per jamb.



4 DT_Sheet A621_Door Jamb Detail_Wood
3" = 1'-0"




5 DT_Sheet A621_Door Jamb Detail_Masonry
3" = 1'-0"


Material Schedule (Service Building Only)							
Abbreviation	Material Description	Manufacturer	Style Name or Number	Color (Description)	Size	Finish	Material Notes
CT-1	Ceramic Tile	Dal-Tile	Volume 1.0	BL72 Intensity Pebble	12"x12"	N/A	Use MAPEI Epoxy Grout
P-1	Paint - Color 1	Sherwin Williams	See Paint Schedule on G202	SW6966 Blueblood	N/A	See Paint Schedule on G202	
P-2	Paint - Color 2	Sherwin Williams	See Paint Schedule on G202	Custom Color (Dover Gray)	N/A	See Paint Schedule on G202	
P-3	Paint - Color 3	Sherwin Williams	See Paint Schedule on G202	SW7669 Summit Gray	N/A	See Paint Schedule on G202	
P-4	Paint - Color 4	Sherwin Williams	See Paint Schedule on G202	SW6959 Bluechip	N/A	See Paint Schedule on G202	
P-6	Paint - Color 6	Sherwin Williams	See Paint Schedule on G202	Safety Red	N/A	See Paint Schedule on G202	
P-7	Paint - Color 7	Sherwin Williams	See Paint Schedule on G202	SW7006 Extra White	N/A	See Paint Schedule on G202	
RB	Rubber Base	Ropee	Pinnacle	175 Slate	4"	N/A	
SC	Sealed Concrete	Sherwin Williams	See Paint Schedule on G202	Haze Gray	N/A	See Paint Schedule on G202	Add SharkGrip for added slip resistance
FRP-1	Fiberglass Reinforced Panels	Marlite	4'X8' Textured Panels	P430N Medium Gray	4'X8'	Pebbled	

Finish Schedule for Additional Items (Service Building Only)					
1.	Doors & Frames: Paint P-3	7.	Keynote 16 & 17 : P-1	15.	Soffit: P-1
2.	Bollards: P-6	8.	Keynote 15: P-1	16.	Door Hardware: Satin Chrome
3.	Exterior Pole Sign: By others.	9.	Keynote 68: P-1	17.	Window Gaskets: Light Gray
4.	Downspouts / Gutters: Match Roof Color	10.	Keynote 19: P-3	18.	Exterior Aluminum Storefront & Door: Clear Anodized
5.	Electrical covers to be brushed aluminum	11.	Knox Box: Aluminum	17.	Lintel at OH Doors: P-3
6.	Paint all louvers to match adjacent finish	12.	Roof: Royal Blue (Berridge)	18.	Not Used.

Finish Schedule										
Number	Name	Area	Floor Finish	Base Finish	Walls				Ceiling Finish	Remarks
					Rear (North)	Right (East)	Front (South)	Left (West)		
1	Service	2186 SF	SC	RB / None	P-3	P-1 / P-4	P-3	P-1 / P-4	P-7	Paint P-1 up to 7'-4" and P-4 from 7'-4" to ceiling.
2	Toilet	46 SF	SC	CT	CT / P-3	CT / P-3	CT / P-3	CT / P-3	P-7	CT wainscot 4'-4" high
3	Storage	349 SF	SC	None	P-3	Fence	P-3	P-3	P-7	
4	Storage	500 SF	SC	None	P-3	P-3	P-3	Fence	P-7	



6 DT_Sheet A621_Storefront Door Head Detail_Half-Highs
3" = 1'-0"



7 DT_Sheet A621_Storefront Door Jamb Detail_Masonry
3" = 1'-0"



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.


Finish Schedules &
Head, Jamb, and
Sill Details

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

A621


Scale As indicated

11/21/2024 9:46:26 AM



① 02_3D View_Front (South)

*See Civil for actual site conditions, including dumpster enclosure location.



② 03_3D View_Rear (North)

*See Civil for actual site conditions, including dumpster enclosure location.

Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

3D Views

Project number	24028
Date	11/08/2024
Drawn by	ARC
Checked by	N/A

R100

Scale

SCHEDULE OF SPECIAL INSPECTIONS				
IBC Code Section	Item	Inspection/Test/Certification	C or P	Extent/Comments
	1000.00	General Conditions		
	1000.01	Review of Structural Documents and Shop Drawings to determine differences not approved by Architect or Engineer of Record	Continuous	Structural Documents should take precedence over any shop drawings. Special Inspector should use the Architectural and Structural Documents as the primary documents for review of construction. Shop drawing should be used as secondary document to review details not shown on the Architectural and Structural Documents. Any discrepancy between the two documents should be resolved by the Architect or Engineer of Record before proceeding with construction.
	1000.02	The Special Inspector duties for missing details, conflicting details or coordination issues.	Continuous	Reasonable attempts have been made on the part of the design team to properly coordinate drawings. However in the event that a question arises on the project the Special Inspector shall obtain clarification from the Architect on all items. No changes shall be made to the drawings or construction without written conformation.
	1400.00	Fabricators		
1704.02.01	1400.01	Review the quality control procedures of the following fabricators for completeness and adequacy relative to the fabricator's scope of work: steel fabricator, lightgage truss fabricator, wood truss fabricator.	Periodic	
1704.02.02	1400.02	The following fabricators, if registered and approved by the building official, may submit "Certificates of Compliance" at the completion of their scope of work that their fabricated items were constructed in accordance with the approved construction documents: steel fabricator, lightgage truss fabricator, wood truss fabricator. Fabricators having successfully completed no fewer than 5 similar projects may also submit for approval with documentation of similar projects.	Periodic	
	2300.00	Soils and Deep Foundations		
1704.07	2300.01	Verify bearing capacities of soils beneath footings.	Periodic	As recommended in approved soils report and specified in earthwork specifications.
1704.07	2300.02	Verify assumed bearing capacities and determine settlements of soils beneath footings and building pad.	Periodic	As noted on the drawings, recommended by the geotechnical engineer, and specified in earthwork specifications.
1704.07.01	2300.03	Verify site preparation prior to beginning fill placement. Verify fill material type, placement method, lift thickness, and compaction of fill material. Verify in-place density of compacted fill.	Periodic	As recommended in approved soils report and specified in earthwork specifications.
1704.08	2300.04	Inspect installation of pile foundations including installation of test piles.	Continuous	As recommended in approved soils report and specified in pile specifications.
1704.09	2300.05	Inspect installation of drilled pier foundations and installation of test piers. Inspect reinforcing in each pier and test concrete.	Continuous	As recommended in approved soils report and specified in pile specifications.
1705.9	2300.06	Inspect helical pile installation.	Continuous	Record installation equipment used, pile dimensions, tip elevations, final depth, final installation torque.
	3300.00	Concrete Construction		
None	3300.06	Inspect concrete formwork except as noted above for proper dimensions. Verify that construction joints are properly keyed. Verify that slab recesses, if any, have been installed.	Periodic	Prior to each pour.
1704.04	3300.07	Inspect reinforcing steel except as noted above for installation including size, spacing and bar clearances. Verify that lap splices and embedment lengths are per the construction documents. Verify that dowels for work above are properly aligned and spaced to match other work.	Periodic	Prior to each pour.
None	3300.13	Inspect bolts	Periodic	
1704.04	3300.15	Verify each proposed concrete mix for the project.	Periodic	For each proposed mix
1704.04	3300.16	Sample all concrete for strength tests and test concrete for slump, air content, temperature, and other tests.	Continuous	During placement operations. Reference concrete specifications for specific tests and frequencies.
1704.04	3300.17	Inspect concrete placement except as noted above.	Continuous	
1704.04	3300.18	Inspect all concrete curing operations as noted in the extents column.	Periodic	Monitor during hot, cold and windy conditions. Reference concrete specifications.
	3300.25	Verify sawed joints in slabs on grade are comleted within 4 hours of the final set of the concrete	Continuous	
	4810.00	Masonry Construction		
1704.05.01 and .02	4810.03	Inspect proportions of site prepared mortar and grout. Inspect construction of mortar joints. Inspect reinforcement for correct size and spacing. Inspect work for correct location and type of embeds and anchor bolts. Inspect work for size and location of structural elements.	Periodic	At beginning of masonry construction and every _____ square feet of masonry thereafter.
1704.05.01 and .02	4810.05	Inspect masonry cells and cleanouts prior to placement of grout. Inspect grout proportions. Inspect placement of reinforcement.	Periodic	Prior to grouting of masonry.
1704.05.01 and .02	4810.06	Inspect grouting operations to ensure compliance with code and construction documents.	Continuous	During grouting.
1704.05.01, .02 and .03	4810.12	Inspect protection of masonry during cold weather and hot weather.	Periodic	During periods with temperatures below 40 degrees or above 90 degrees.
1704.05.01 and .02	4810.13	Inspect preparation of grout specimens, mortar specimens and / or prisms.	Continuous	During preparation of all specimens.
1704.05.01, .02 and .03	4810.14	Verify compliance with all required inspection provisions of the construction documents and approved submittals.	Periodic	As required for duration of project.
	5120.00	Steel Construction		
1704.03	5120.01	Inspection of the steel pieces		
1704.03.02	5120.02	Inspection of frame		
1704.03.03	5120.03			
1704.03	5120.04	Inspect high-strength bolts, nuts and washers: a. Identify markings to conform to ASTM standards specified in the construction documents. b. Inspect manufacturer's certificate of compliance.	Periodic	Reference project specifications and ASTM material specifications; AISC 335, (Sect A3.4); AISC LRFD (Sect A3.3).
1704.03	5120.05	Inspect high-strength bolting: Bearing-type connections.	Periodic	
1704.03	5120.07	Inspect and verify structural steel material: a. Identification markings to conform to ASTM standards specified in the approved construction documents. b. Manufacturers' certified mill test reports.	Periodic	Confirm that materials meet applicable ASTM specifications noted in construction documents.
1704.03	5120.08	Inspect and verify weld filler materials: a. Identification markings to conform to AWS specification in the approved construction documents. b. Manufacturer's certificate of compliance required.	Periodic	Confirm that materials meet applicable ASTM specifications noted in construction documents.
1704.03	5120.09	"Inspect welding: Structural Steel: 1) Complete and partial penetration groove 2) Multipass fillet welds. 3) Single-pass fillet welds > 5/16" "	Continuous	Per specifications and AWS D1.1
1704.03	5120.10	"Inspect welding: Structural Steel: 1) Single-pass fillet welds ≤ 5/16" 2) Floor and deck welds. "	Periodic	Per specifications and AWS D1.1
1704.03	5120.11			
1704.03	5120.12	"6. Inspect steel frame joint details for compliance with approved construction documents: a. Details such as bracing and stiffening. b. Member locations. c. Application of joint details at each connection."	Periodic	Inspect complete frame.
	5301.03	Verify deck support angles are provided for all opening greater than 100 square inches.	Periodic	
	5310.00	Metal Deck		
	5310.01	Verify depth and gauge of all deck elements	Periodic	
	5310.02	Verify adequate bearing of ends of decking	Periodic	
	6000.00	Wood		
1704.06	6000.01	Inspect fabricated wood trusses and shop built components.	Periodic	Inspect truss production in shop unless fabricator is approved by building official and submits certification of compliance at end of scope of work. Inspect ____% of trusses. Inspect 100% of trusses if discrepancies are observed.
1704.06	6000.02	Inspect site-built assemblies including site built trusses. Inspect erected trusses including bridging and attachments.	Periodic	Inspect all site-built trusses. Inspect erected trusses and installation of bridging.
1706.01	8000.00	Special Inspections for Wind Resistance		
1706.01.02	8000.01	Roof Cladding and Roof Framing Connections	Periodic	
1706.01.02	8000.02	Wall Connections to Roof and Floor Diaphragms and Framing	Periodic	
1706.01.02	8000.03	Roof and Floor Diaphragm Systems, including Collectors, Drag Struts, and Boundary Elements.	Periodic	
1706.01.02	8000.04	Vertical Windforce-Resisting Systems, including Braced Frames, Moment Frames, and Shearwalls	Periodic	
1706.01.02	8000.05	Windforce-Resisting System Connections to the Foundation.	Periodic	
1706.01.02	8000.06	Fabrication and installation of components and assemblies required to meet the impact-resistance requirements of Section 1609.1.4.	Periodic	

GENERAL NOTES

- Contractor shall compare structural drawings and architectural drawings. Any omissions or discrepancies between plans, details, and specifications shall be brought to the attention of the Architect or Engineer before bidding. In all cases, more stringent requirement governs. Architectural dimensions and elevations will control.
- Structural drawings or parts of the structural drawings may not be used as shop drawings without prior written approval.
- All or parts of these drawings were produced with computer aided drafting. Drawings are available from the Engineer in DWG format on request.
- Contractor proposed changes to details must be clearly noted on the first sheet of all shop drawings.
- Construction shown is stable after the building is complete including interior and exterior finishes. The Contractor is responsible for temporary bracing of the structure during construction.
- Review of submittal information shall be for general compliance with the contract documents and shall not include checking of detailed dimensions or detailed quantities.

DESIGN LOADS

- Reference code for loading 2021 IBC.
 - Building Classification II
 - Wind Load
 - Basic Wind Speed (3 sec gust) 108 mph
 - Wind Exposure C
 - Internal Pressure Coefficient +/- 0.18
 - Velocity Pressure (qz) -- psf
 - Roof Snow Load
 - Flat Roof Snow Load (Pf) 5 psf
 - Snow Exposure (Ce) 1.0
 - Importance Factor 1.0
 - Thermal Factor (Ct) 1.0
 - Seismic Load
 - Importance Factor 1.0
 - Mapped Spectral Response Accelerations
 - Ss 0.29g
 - S1 0.103
 - Site Class D
 - Spectral Response Coefficients
 - Sds 0.309
 - Sd1 0.164
 - Seismic Design Category C
 - Base Seismic-Force-Resisting System(s) and Response Modification Factor
 - Intermediate Reinforced Masonry Shear Walls 3.5
 - Design Base Shear xx kips
 - Seismic Response Coefficient (Cs) 0.xx
 - Analysis Procedure = Equivalent Lateral Force
 - Live Load
 - Roof Load 20 psf
 - Service Bay and slabs on grade 100 psf
 - Mezzanine 50 psf

FOUNDATIONS

- Foundation design for this project was based on soils information provided by Terracon
- Assumed bearing capacity _____ 2500 psf
- All footings are to bear on engineered fill.
- Install corner bars at all footing intersections and corners (Provide lap length e.w.)
- All footing elevations are given to the top of the footings.
- Footing steps shown on the plans are furnished as a guide for estimating quantities. Final elevations are to be set in the field. Bearing elevations must be approved by a Soils Engineer before any concrete is placed.
- Coordinate foundation elevations with plumbing requirements. Step footings as required to clear plumbing lines.
- Provide drainage for all retaining walls, see architectural for notes and details.

MASONRY

- All masonry work to be in accordance with "Building Code Requirements for Concrete Masonry Structures" TMS 402-2016 and "Specifications for Masonry Structures" TMS 602-2016.
- Fill all concrete masonry units with concrete or grout from the top of the footing to the finish floor or to 8" above finish grade whichever is higher.
- Use ladder type joint reinforcement (Dur-O-Wall SW DA3100 or better) at 16" on center in all cavity walls where brick is used for one or more of the wythes.
- Use truss type joint reinforcement (Dur-O-Wall SW DA3100 or better) at 16" o/c. in all other masonry walls.
- Provide joint reinforcement at 8" o/c. for all walls constructed with stack bond.
- Use Type "M" or Type "S" mortar in accordance with IBC Table 2103.7(1).
- Minimum compressive strength of concrete masonry f'm = 2500 psi. Submit for review test data on strength of units before starting any masonry work.
- Minimum compressive strength of grout f'm = 2500 psi. Use 3/8" max size aggregate. See Special Inspection Schedule for any testing requirements. Grout slump shall be 8" to 11".
- Use "Fine" grout for all reinforced piers and reinforced wall in accordance with ASTM C 476.
- Each grout lift shall not exceed 5'-0" unless cleanouts are provided in the bottom course.
- Fill cells under all lintels with grout.
- Provide lintels over all openings through wall. See lintel details for reinforcement.
- Unless otherwise noted provide control joints in all walls 4'-0" from wall intersections or corners and at 20'-0"
- Extend all horizontal steel and bond beams thru control joints.
- Vertical Reinforcement shall extend into the bond beam.
- Unless noted, all bars are to be located at the center of cell. Where bars are specified at each face, provide minimum ¾" clear space between reinforcement and CMU face shell.
- Anchor bolt into grouted cell locations only, unless noted otherwise.

REINFORCING STEEL AND CONCRETE

- All concrete work is to be in accordance with the "Building Code Requirements for Reinforced Concrete" (ACI 318-19).
- All detailing is to be in accordance with "ACI Detailing Manual" SP-66
- Use of Calcium Chloride, Chloride Ions, or other salts in concrete are prohibited.
- Concrete Properties: See Schedule
 - All concrete must obtain 7 day strength of 70% of design strength.
 - Concrete mixes may use up to 25% of cementious weight as fly ash.
 - Concrete mixes may use water reducers, accelerators or retarders with prior approval.
 - Do not provide air entrainment in concrete mixes for interior slabs.
- All steel reinforcement shall be of deformed bars of billet steel conforming to ASTM A615, Grade 60 in all concrete.
- Welded wire fabric shall be ASTM 185 and shall lap 2 cross wires or 6" whichever is greater on all sides. All laps shall be wired together.
- Provide (2) #4 bars x 4'-0" at re-entrant corner locations Typical. Locate 3" away from corner and space 1'-0" apart.
- All slabs on grade are 6", unless noted. Slabs are to be placed on 10 Mil, PVC vapor barrier over 4" of porous fill. Reinforce slabs with 6x6 W2.9 x W2.9 WWF placed 1" from top of slab. Unless otherwise noted slabs shall have joints placed a 12'-0" on centers. Joints may be control joints or construction joints. See Architectural Plans for floor slopes and recesses for hard tile.
- Minimum concrete cover for reinforcement:
 - Footings 3" bottom, 2" sides
 - Cast-In-Place Walls Surfaces exposed to weather or soil 2" - #6 and greater, 1-1/2" - #5 and smaller Other surfaces 3/4"
- Provide corner bars at all wall and footing intersections.
- No openings shall be allowed to penetrate any concrete work, unless it is shown on the structural framing plans without prior written approval. Contractor shall submit for review locations of proposed openings not shown 30 days prior to pouring any concrete.
- Provide a continuous water bar at all wall construction joints below ground level.
- Use 3/4" chamfer for all exposed corners unless noted.
- Testing samples for preparing strength test specimens of each concrete mixture placed each day shall be taken in accordance with (1) through (3).
 - At least once a day
 - At least once for each 150yd^3 of concrete
 - At least once for each 5000ft^2 of surface area for walls or slabs.

STRUCTURAL STEEL

- All detailing, fabricating, and erection of structural steel shall be in accordance with the AISC 360-10 "Specifications for Structural Steel Buildings". All reactions shown are ASD loads.
- All connections are to be detailed as Type 2 "simple frame connections".
- All structural steel W shapes shall be ASTM A992.
- All structural steel Tube sections shall be ASTM A500 Grade B.
- All structural steel Pipe sections shall be ASTM A501.
- All structural steel channels, angles and other sections shall be ASTM A36, unless noted.
- Headed Studs shall be Type B Shear Connectors.
- Shop and field connections shall be welded with E-70XX electrodes or bolted with 3/4" dia. A-325N or A-325F bolts, unless noted.
- Use 3/4" cap and bearing plates, unless noted.
- Use 3/4" dia x 1'-0" long ASTM 1554 Grade 36 anchor bolts, unless noted. In lieu of cast bolts, 3/4"x1'-0" long HAS rods epoxied with Hilti HVA epoxy, or equal, may be used with prior approval.
- Grout under baseplates with ASTM C 1107 cementitious 6000 psi Non-Shrink Grout.
- Structural steel shall be shop primed per SSPC paint system No. 7. Primer shall be SSPC paint with a minimum thickness of 2.0 MILS. Omit Paint at surfaces to be fireproofed.
- Provide L 3"x3"x1/4" frames around all roof opening through metal decking.

WOOD (STRUCTURAL)

- All floor framing and roof framing shall be #2KD SYP or approved equal.
- All floor framing shall be horizontally braced/blocked at midspan unless noted otherwise.
- All vertical framing shall be Spurce-Pine-Fir, #2.
- All wood exposed to weather or in contact with CMU or concrete shall be pressure treated in accordance with American Wood Preservers Association Manual of Recommended Practice
- All Fasteners and Nails in contact with pressure treated lumber shall be stainless steel Type 304. Submit all alternates for approval.
- Furnish design calculations sealed by a Professional Engineer licensed in the State of Project for all truss members.
- Truss connections to walls and framing shall be Designed and Specified by Truss Supplier.
- Field Modification or Fabrication of trusses is not allowed unless written approval is provided by Truss Supplier.
- Provide (4) studs at all beam and girder truss bearing locations.
- Roof decking shall be 5/8" APA rated sheathing, Exposure 1 with 32/16 span rating. Provide plyclips at all roof sheathing connections, unless noted otherwise.
- Floor and roof sheathing shall be nailed with 8d rinkshank nails at 6" o.c.
- All bolts connecting continuous horizontal sill plates to concrete, masonry, or steel shall have 3" flat washers.

CONCRETE SCHEDULE

Concrete Use	Design Strength	Max W/C Ratio	Slump Limits	Entrained Air Range	Weight	Notes
Basement Walls	4000 psi	n/a	6" to 8"	3% to 5%	150 pcf	Use HRWR
Slabs on Composite Metal Deck	4000 psi	n/a	6" to 8"	---	150 pcf	Use HRWR
Slabs on Grade/Grade Beams	4000 psi	n/a	6" to 8"	---	150 pcf	Use HRWR

BJW

STRUCTURAL
ENGINEERS

BARNETT JONES WILSON, LLC • FELL CITY • TUSCALOOSA • CHATTANOOGA • WWW.STRUCTENGS.COM

AHO ARCHITECTS, LLC

www.ahoarch.com

Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL		
No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

General Notes & Special Inspections

Project number24028

Date11/08/2024

Drawn byjcl

Checked byjcl

S0.1

Scale3/4" = 1'-0"

Shear Plate Connection Schedule

Length	# of bolts	End reaction	Min plate thickness
6"	2	8.2k	1/4"
9"	3	16.3k	1/4"
12"	4	26.1k	1/4"
15"	5	36.3k	1/4"
18"	6	46.3k	1/4"
21"	7	56.4k	1/4"

Reinforcing Steel Lap Splice & Development Length for Concrete Masonry

Bar Size	Bar in center of wall			Bar in each face of wall
	6" CMU	8" CMU	12" CMU	
#3	16"	16"	16"	16"
#4	21"	21"	21"	30"
#5	32"	26"	26"	46"
#6	61"	43"	40"	85"
#7	NA	60"	46"	115"
#8	NA	NA	61"	NA

- Notes:
- Lengths are for vertical splices in walls.
 - Bar length for center of wall are based on f'm of 1500 psi or greater.
 - Bar length for face of wall are based on f'm of 2000 psi or greater.
 - Refer to General Notes and details for masonry strength.


Components and Cladding Schedule a = 5.5'

Area(sf)	Zone 1,2,3 (+)(psf)	Zone 1 (-)(psf)	Zone 2,3 (-)(psf)	Zone 4,5 (+)(psf)	Zone 4 (-)(psf)	Zone 5 (-)(psf)
10	29.4	-32.1	-37.5	32.1	-34.8	-43.0
50	27.5	-28.3	-33.7	28.8	-31.5	-36.3
100	26.7	-26.7	-32.1	27.3	-30.0	-33.4


Reinforcing Steel Lap Splice Lengths

Bar Size	Column Splices	Bm, Ftg & Wall Splices	
		Top Bars	Other Bars
# 3	12"	19"	15"
# 4	15"	25"	19"
# 5	19"	31"	24"
# 6	23"	37"	29"
# 7	26"	54"	42"
# 8	30"	62"	48"
# 9	34"	70"	54"
# 10	38"	79"	61"
# 11	42"	87"	67"

- Notes:
- Top bars are any horizontal reinforcing steel that has another layer of steel more than 2" below the bars or reinforcing steel that has more than 12" of concrete below the bars.
 - All horizontal reinforcing bars in walls may be detailed as "Other Bars".
 - All corner bars may be detailed as "Other Bars".




Typical Joint Reinforcing at Corner



Typical Joint Reinforcing at Intersection

Typical Beam, Wall or Footing Reinforcing at Corners



Typical Beam, Wall or Footing Reinforcing at Intersections


Frame Connection Schedule

Length	# of bolts	End reaction	Min angle thickness
5-1/2"	2	37.1k	5/16"
8-1/2"	3	55.3k	5/16"
11-1/2"	4	72.7k	5/16"
14-1/2"	5	88.7k	5/16"
17-1/2"	6	104.0k	5/16"


Length	Size of Weld A	End reaction	Min angle thickness
5-1/2"	3/16"	37.1k	5/16"
8-1/2"	3/16"	55.3k	5/16"
11-1/2"	3/16"	72.7k	5/16"
14-1/2"	3/16"	88.7k	5/16"
17-1/2"	3/16"	104.0k	5/16"

Length	Size of Weld B	End reaction	Min angle thickness
5-1/2"	1/4"	14.6k	5/16"
8-1/2"	1/4"	32.2k	5/16"
11-1/2"	1/4"	53.4k	5/16"
14-1/2"	1/4"	76.6k	5/16"
17-1/2"	1/4"	101.0k	5/16"


Depth of beam	Min length of angle	Depth of beam	Min Length of angle
W12	5-1/2"	W24	11-1/2"
W14	5-1/2"	W27	11-1/2"
W16	5-1/2"	W30	14-1/2"
W18	8-1/2"	W33	14-1/2"
W21	8-1/2"	W36	17-1/2"




Typical Anchor Bolt Detail Typical Base Plate




Typical Construction Joint



Typical MasonryWall Control Joint




- Note:
- See architectural plan for spacing. If spacing is not shown place joints at 3 times the wall height but not greater than 20'-0" o.c., and at 4'-0" from corners
 - Extend all horizontal reinforcing including bond beam steel thru control joints.



Less than 4'-0" Less than 8'-0"

CMU Lintel Schedule

See sections on S5.1 for overhead door lintel



CMU Lintel Elevation

No.	Description	Date

© 2024 Aho Architects, LLC. All Rights Reserved.

Typical Details

Project number	24028
Date	11/08/2024
Drawn by	jci
Checked by	jd

S0.2

Scale 3/4" = 1'-0"

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Foundation & Roof
Framing Plan

Project number	24028
Date	11/08/2024
Drawn by	jcj
Checked by	jd


S1.1

Scale As indicated



Roof Perimeter
Blocking Detail

See 6/S5.1




ROOF FRAMING PLAN

1/8" = 1'-0"


Sheet Notes:

- See Sheet No 50.x for typical details and general notes.
- Reference all elevations to finish floor elevation (+) 0'-0"
- Truss bearing elevation = (+) 15'-5 1/2"
- Roof slope = 8'/12", unless noted
- Roof construction 5/8" plywood deck with H-clips. Attach with 8d nails @ 6" o.c..
- Refer to architectural drawings for all dimensions, slopes, elevations, etc., not illustrated on this plan. Coordinate all final dimensions and elevations with architectural.
- Truss loading: Top Chord Dead Load = 10 psf, Bottom Chord Dead Load = 10 psf, use Total dead load = 10psf for wind load calculations.
- Truss requirements: (note that all of these requirements must be included in the truss submittal prior to receiving approval)
 - Furnish design calculations sealed by a Professional Engineer licensed in the state of that the project is located for all truss members.
 - Truss manufacturer shall specify and provide all truss to truss and truss bearing connections, and not contain mention of "by others" in relation to design.
 - Truss manufacturer shall be responsible for providing and illustrating all temporary and permanent bracing required.




FOUNDATION PLAN


1/8" = 1'-0"




Section 10
3/4" = 1'-0"




Section 9
3/4" = 1'-0"




Section 7
3/4" = 1'-0"




Section 6
3/4" = 1'-0"




Section 5
3/4" = 1'-0"



Section 3
3/4" = 1'-0"



Section 2
3/4" = 1'-0"



Section 1
3/4" = 1'-0"

Express Oil Change & Tire Engineers

Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Sections and
Details

Project number	24028
Date	11/08/2024
Drawn by	jcj
Checked by	jd

S5.1

Scale 3/4" = 1'-0"

LEGEND

12x20

DUCT SIZE, FIRST FIGURE IS SIDE SHOWN INSIDE CLEAR DIMENSION UNLESS NOTED OTHERWISE

24x12

LOW PRESSURE, RECTANGULAR (GALVANIZED STEEL)

LOW PRESSURE, RECTANGULAR (ALUMINUM STEEL)

20"x8

ROUND (GALVANIZED STEEL)

20x10

MEDIUM PRESSURE, FLAT OVAL (GALVANIZED STEEL)

FLEXIBLE DUCT

R

DUCT RISE

D

DUCT DROP

EXISTING DUCTWORK TO REMAIN

DUCT TRANSITION

RECTANGULAR TO ROUND DUCT TRANSITION

TURNING VANES

FD

FIRE DAMPER AND SLEEVE, PROVIDE ACCESS DOOR

SD

SMOKE DAMPER AND SLEEVE, PROVIDE ACCESS DOOR

SDFD

COMBINATION FIRE/SMOKE DAMPER, PROVIDE ACCESS DOOR

MANUAL VOLUME DAMPER

STANDARD 45° BRANCH, SUPPLY OR RETURN, NO SPLITTER

STANDARD 45° BRANCH, SUPPLY OR RETURN, NO SPLITTER, WITH MANUAL VOLUME DAMPER

CONICAL SPIN-IN FITTING WITH BUTTERFLY DAMPER

GRILLE OR REGISTER, CEILING

A

ACCESS DOOR

D

CONDENSATE DRAIN PIPING

AD

AUXILIARY CONDENSATE DRAIN PIPING

R

REFRIGERANT PIPING (2 LINES TOTAL)

ELBOW, 90° (LONG RADIUS)

TEE

TEE, TURNED UP

TEE TURNED DOWN

ELBOW, TURNED DOWN

ELBOW, TURNED UP

①

WALL MOUNTED THERMOSTAT

②

WALL MOUNTED HUMIDISTAT

③

WALL MOUNTED TEMPERATURE SENSOR

④

WALL MOUNTED CARBON DIOXIDE SENSOR

⑤

WALL MOUNTED DEVICE W/ COVER GAURD

SMOKE DETECTOR

TIE NEW INTO EXISTING

UC

UNDERCUT DOOR 3/4 INCHES

SUPPLY AIR FLOW

RETURN OR EXHAUST AIR FLOW

NOTE: THIS LEGEND IS FOR REFERENCE ONLY. ALL SYMBOLS WHICH APPEAR WITHIN THE LEGEND MAY NOT APPLY TO THIS PROJECT.

ABBREVIATIONS

AB, CL'G

ABOVE CEILING

ABV.

ABOVE

AC

ALTERNATING CURRENT

A/C

AIR COMPRESSOR

AF

ABOVE FINISHED FLOOR

AHU

AIR HANDLING UNIT

AI

ANALOG INPUT

ALT.

ALTERNATE

AMP

AMPERE

AO

ANALOG OUTPUT

APPROX.

APPROXIMATELY

ARCH.

ARCHITECTURAL

AVG

AVERAGE

B

BOILER

BTU

BRITISH THERMAL UNIT

CFM

CUBIC FEET PER MINUTE

CH

CHILLER

CHWP

CHILLED WATER PUMP

CLG

CEILING

CT

COOLING TOWER

CU

CONDENSING UNIT

CWP

CONDENSER WATER PUMP

DEFL

DEFLECTION

DET

DETAIL

DI

DIGITAL INPUT

DIA

DIAMETER

Ø

DIAMETER

DO

DIGITAL OUTPUT

EDB

ENTERING DRY BULB

ELEC.

ELECTRICAL

ELEV.

ELEVATION

EWB

ENTERING WET BULB

EWT

ENTERING WATER TEMPERATURE

EXH

EXHAUST

EXIST.

EXISTING

°F

DEGREES FAHRENHEIT

GFF

GAS FIRED FURNACE

GPM

GALLONS PER MINUTE

FPM

FEET PER MINUTE

FPS

FEET PER SECOND

FT

FOOT OR FEET

HD.

HEAD

HP

HORSE POWER

HR

HOURS(S)

HT.

HEIGHT

HTR

HEATER

HVAC

HEATING, VENTILATION AND AIR CONDITIONING

HWP

HOT WATER PUMP

HX

HEAT EXCHANGER

HZ

FREQUENCY (HERTZ)

ID

INSIDE DIAMETER

IN.

INCHES

KW

KILOWATT

KWH

KILOWATT HOUR

MAX

MAXIMUM

MBH

1000 BTU PER HOUR

MECH.

MECHANICAL

MFR.

MANUFACTURER

MIN

MINIMUM

NO.

NUMBER

N/A

NOT APPLICABLE

NC

NOISE CRITERIA

O.D.

OUTSIDE DIAMETER

OA

OUTSIDE AIR

Ø

OVAL DUCTWORK

ORIG.

ORIGINAL

PH.

PHASE

PIU

POWERED INDUCTION UNIT

PRESS

PRESSURE

RTN

RETURN AIR

RTU

ROOFTOP AIR HANDLING UNIT

SDC

STAND ALONE DIGITAL CONTROLLER

SENS.

SENSIBLE

SQ.

SQUARE

SPLY

SUPPLY

TEMP

TEMPERATURE

VAV

VARIABLE AIR VOLUME

W

WATT



W/

WITH

W.P.D.

WATER PRESSURE DROP

4 LOUVER DETAIL NO SCALE




6 AIR DEVICE LEGEND NO SCALE

AIR QUANTITY DELIVERED BY DEVICE IN CFM (250 CFM)

DISTANCE TO COMBUSTIBLES				
MODEL NO.	SIDES	BACK	TOP	BELOW/ FRONT
DR 50	30	18	34	72

*MAINTAIN PER MANUFACTURER'S INSTALLATION REQUIREMENTS. DISTANCES MEASURED ABOVE/BELOW RAY HEAD SURFACE.



MANIFOLD CONTROL BOX MUST BE LOCATED TOWARDS THE LOWER END OF THE HEATER (TOWARDS THE FLOOR).

5 RADIANT HEATER MOUNTING DETAIL NO SCALE

POWER VENTILATOR SCHEDULE

EQUIPMENT NO.	MANUFACTURER/ MODEL NO.	CFM	E.S.P. (IN. W.C.)	RPM	MAX. SONES	ELECTRICAL			LOCATION	TYPE	DRIVE	WGT (LBS.)	REMARKS
						DISCONNECT	MOTOR STARTER	WATTS					
EF-1	COOK GC-146	70	0.35	849	1.5	BY DIV. 26	BY DIV. 23	32	115/1/60	CEILING	CENTRIFUGAL	DIRECT	15 1), 3), 5)
EF-2	COOK 16XP26	1750	0.35	1265	12.7	BY DIV. 26	BY DIV. 23	1/3 HP	115/1/60	WALL	PROPELLER	DIRECT	75 2), 3), 4), 5)
EF-3	COOK 14XP26	1300	0.35	1430	11.1	BY DIV. 26	BY DIV. 23	1/4 HP	115/1/60	WALL	PROPELLER	DIRECT	75 4), 5), 6)

- REMARKS:
- 1) PROVIDE OCCUPANCY SENSOR FOR FAN OPERATION.
 - 2) FAN SHALL RUN CONTINUOUSLY DURING OCCUPIED HOURS. INTERLOCK WITH LOCAL SWITCH. COORDINATE WITH ELECTRICAL.
 - 3) PROVIDE WITH FAN SPEED CONTROLLER.
 - 4) PROVIDE WITH FAN INLET GUARDS.
 - 5) PROVIDE WITH BACKDRAFT DAMPER.
 - 6) PROVIDE WITH DEDICATED WALL SWITCH.

GAS RADIANT HEATER SCHEDULE

EQUIPMENT NO.	MANUFACTURER/ MODEL NO.	HEATING CAPACITY (MBH)	WATTS	ELECTRICAL		WEIGHT (LBS)	MOUNTING HEIGHT	REMARKS
				DISCONNECT	VOLTS/PH/HZ.			
RH-1	RE-VERBER-RAY DX3L-20-75	75	5	BY DIV. 26	115/1/60	120	11' 7"	1), 2), 3), 4)
RH-2	RE-VERBER-RAY DX3L-20-75	75	5	BY DIV. 26	115/1/60	120	11' 7"	1), 2), 3), 4)
RH-3	RE-VERBER-RAY DR-50	50	17	BY DIV. 26	115/1/60	50	11' 7"	1), 2), 3), 4)

- REMARKS:
- 1) MAINTAIN DISTANCES FROM COMBUSTIBLES PER MANUFACTURERS INSTALLATION DETAILS.
 - 2) PROVIDE WITH 24V TRANSFORMER AND LOW VOLTAGE THERMOSTAT.
 - 3) ANGLE UNITS AT 30 DEGREES FROM HORIZONTAL. SUSPEND UNITS FROM STRUCTURE WITH 3/8" THREADED RODS.
 - 4) HEIGHT SHOWN MEASURED FROM BOTTOM OF HEATING RAY HEAD/TUBE.

ELECTRIC UNIT HEATER SCHEDULE


EQUIPMENT NO.	MANUFACTURER/ MODEL NO.	KW	STAGES	EAT (°F)	CFM	ELECTRICAL		MOUNTING	WGT (LBS)	REMARKS
						DISCONNECT	VOLTS/PH/HZ.			
EUH-1	MARKEL 3450	2	1	60	245	INTEGRAL	208/1/60	WALL	45	1)

- REMARKS:
- 1) PROVIDE WITH UNIT MOUNTED THERMOSTAT, CONTROL TRANSFORMER, AND DISCONNECT SWITCH.


DISTANCE TO COMBUSTIBLES					
MODEL NO.	# OF SIDE SHIELDS	MOUNTING ANGLE	SIDES	TOP	BELOW
DX3L-20	2	0°	9°	6°	60°

*MAINTAIN PER MANUFACTURER'S INSTALLATION REQUIREMENTS. DISTANCES MEASURED ABOVE/BELOW RAY HEAD SURFACE.


2 RADIANT HEATER HANGER DETAIL NO SCALE




GENERAL VENT REQUIREMENTS



3 RADIANT HEATER VENTING DETAILS NO SCALE




1 WALL EXHAUST FAN DETAIL NO SCALE



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



www.ahoarch.com



11/8/24

Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC. All Rights Reserved.

Mechanical
Legend, Schedules
and Details

Project number	24028
Date	11/08/2024
Drawn by	CRA
Checked by	JAB

M0.01

Scale 12" = 1'-0"

SECTION 233423 - POWER VENTILATORS

- A. POWER VENTILATORS WHICH ARE SCHEDULED OR REFERRED TO BY MODEL NUMBER OR CATALOGUE NUMBER ARE INTENDED TO INCLUDE ALL MATERIALS COVERED BY SUCH NUMBER, ANY REQUIRED ACCESSORIES FOR THE INSTALLATION OF THE FAN ARE TO BE BY THE SAME MANUFACTURER UNLESS OTHERWISE NOTED.
- B. WIRING AND ELECTRICAL CONNECTIONS SHALL BE IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL MATERIALS SHALL BE UL LISTED. FANS SHALL BE UL 705. FANS SHALL BEAR THE AMCA CERTIFIED RATING LABEL FOR SOUND AND AIR PERFORMANCE. FAN ASSEMBLY SHALL BEAR AN ENGRAVED ALUMINUM NAMEPLATE. FANS WHEELS SHALL BE BALANCED IN ACCORDANCE WITH AMCA STANDARD 204-96.
- C. EACH UNIT SHALL HAVE A PROTECTOR CONSTRUCTED OF GALVANIZED STEEL WITH 2 IN. OPENINGS MOUNTED VERTICALLY IN THE UNIT DISCHARGE. THE BIRDSCREEN SHALL PRODUCE MINIMAL EFFECT ON AIR AND SOUND PERFORMANCE.
- D. INSTALL FAN IN ACCORDANCE WITH MANUFACTURER'S INSTALLATION INSTRUCTIONS. INSTALL FANS WITH FLEXIBLE CONNECTIONS FOR SERVICE AND MAINTENANCE. MAKE FINAL DUCT CONNECTIONS TO FANS WITH FLEXIBLE CONNECTORS.
- E. BACK DRAFT DAMPER SHALL BE 6063T5 EXTRUDED ALUMINUM FRAME, .025 IN THICK FORMED ALUMINUM BLADES, .005 IN WIDE, .005 IN DEEP, .005 IN HIGH. THE DAMPER SHALL BE MOUNTED TO THE DUCT WITH TWO (2) SCREWS.
- F. COOK IS BASIS OF DESIGN. APPROVED MANUFACTURERS ARE GREENECH, PENN AND ACME.
- G. CEILING MOUNTED EXHAUST FAN - DIRECT DRIVE:
1. GC 100 SERIES: THE FAN WHEEL HOUSING AND INTEGRAL OUTLET DUCT SHALL BE INJECTION MOLDED FROM A SPECIALLY ENGINEERED RESIN EXCEEDING UL REQUIREMENTS FOR SMOKE AND HEAT GENERATION. THE OUTLET DUCT SHALL HAVE PROVISION FOR AN ALUMINUM BACKDRAFT DAMPER WITH CONTINUOUS ALUMINUM HINGE ROD. THE INLET BOX SHALL BE MINIMUM 22 GAUGE GALVANIZED STEEL. MOTOR SHALL BE UL LISTED TO COMPLY WITH THE NATIONAL ELECTRICAL CODE (NEC) AND MOTOR MOUNT/INLET. A FIELD WIRING COMPARTMENT WITH RECEPTACLE SHALL BE STANDARD. TO ACCOMMODATE DIFFERENT CEILING THICKNESS, AN ADJUSTABLE PREPUNCHED MOUNTING BRACKET SHALL BE PROVIDED. THE FOLLOWING HIGH IMPACT POLYURETHANE INJECTION MOLDING MATERIAL SHALL BE PROVIDED AS STANDARD. WHEEL SHALL BE CENTRIFUGAL FORWARD CURVED TYPE. INJECTION MOLDED OF POLYPROPYLENE RESIN.
 2. MOTOR SHALL BE OPEN Drip PROOF TYPE WITH PERMANENTLY LUBRICATED SEALED BEARINGS AND INCLUDE IMPEDANCE PROTECTION TO PROVIDE OVERLOAD PROTECTION AND DISCONNECT PLUG. MOTOR SHALL BE FURNISHED AT THE SPECIFIED VOLTAGE.
 3. FAN SHALL BE MODEL GC AS MANUFACTURED BY LOREN COOK COMPANY. GREENECH, ACME AND PENN VENTILATOR ARE APPROVED EQUAL.
- H. WALL MOUNTED PROPELLER FAN
1. THE FAN SHALL BE OF BOLTED AND WELDED CONSTRUCTION UTILIZING CORROSION RESISTANT FASTENERS. THE MOTOR DRIVES SHALL BE MOUNTED ON A TUBULAR STEEL POWER ASSEMBLY. THE POWER ASSEMBLY SHALL BE BOLTED TO A MINIMUM 14 GAUGE WALL PANEL WITH CONTINUOUSLY WELDED CORNERS AND AN INTEGRAL VENTURI. FAN SHALL BE ENCLOSED IN MINIMUM 18 GAUGE GALVANIZED STEEL WALL HOUSING WITH FACTORY INSTALLED SHUTTER AND INLET GUARD. ALL NON-GALVANIZED MATERIALS SHALL BE PROTECTED WITH AN EPOXY POLYURETHANE ELECTROSTATICALLY APPLIED, BAKED POLYESTER POWDER COATING. EACH COMPONENT SHALL BE SUBJECT TO A FIVE STAGE ENVIRONMENTALLY FRIENDLY WASH SYSTEM, FOLLOWED BY A MINIMUM 2 MIL THICK BAKED POWDER FINISH. PAINT MUST EXCEED 1,000 HOUR SALT SPRAY UNDER ASTM B117 TEST METHOD.
 2. PROPELLER: THE PROPELLER SHALL BE HIGH EFFICIENCY, LOW NOISE DESIGN WITH BLADES SECURELY FASTENED TO A MINIMUM 7 GAUGE HUB. THE HUB SHALL BE KEYPED AND LOCKED TO THE FAN SHAFT UTILIZING TWO SETSCREWS.
 3. MOTOR SHALL BE DESIGNED TO MEET CLASS B INSULATION RATED FOR CONTINUOUS DUTY AND FURNISHED AT THE SPECIFIED VOLTAGE, PHASE AND ENCLOSURE. BEARINGS SHALL BE DESIGNED AND TESTED SPECIFICALLY FOR USE IN AIR HANDLING APPLICATIONS. CONSTRUCTION SHALL BE HEAVY DUTY REGREASABLE BALL TYPE IN A CAST IRON PILLOW BLOCK HOUSING SELECTED FOR A MINIMUM L50 LIFE IN EXCESS OF 100,000 HOURS.
 4. BELTS AND DRIVES: BELTS SHALL BE OIL AND HEAT RESISTANT, STATIC CONDUCTING. DRIVES SHALL BE PRECISION MACHINED CAST IRON TYPE, KEYPED AND SECURELY ATTACHED TO THE WHEEL AND MOTOR SHAFTS. DRIVES SHALL BE SIZED FOR 150% OF THE INSTALLED MOTOR HORSEPOWER. THE VARIABLE PITCH MOTOR DRIVE MUST BE FACTORY SET TO THE SPECIFIED FAN RPM.
 5. FAN SHALL BE THE XLPH AS MANUFACTURED BY LOREN COOK COMPANY OR APPROVED EQUAL.

FINAL

© 2024 Aho Architects, LLC.
All Rights Reserved.

M0.02	
Scale	12" = 1'-0"



11/8/24

Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

SECTION 233113 - LOW PRESSURE DUCTWORK

- A. GENERAL
- DUCT SYSTEM SHALL BE FABRICATED WITH SHEET METAL THICKNESSES AND REINFORCED IN ACCORDANCE WITH SMACNA, AS SHOWN ON THE DRAWINGS AS DESCRIBED HEREIN. DUCTS 18 INCHES AND LARGER ON ANY SIDE SHALL BE STIFFENED BY BEADING ON NOT TO EXCEED 12 INCH CENTERS. UNLESS NOTED OTHERWISE THE MINIMUM PRESSURE/VELOCITY CLASSIFICATION SHALL BE 2 INCH W.G. PLUS OR MINUS, AT 2500 FT. PER MINUTE, DUCT SEAL CLASS "X". DUCT SIZES SHOWN ARE CLEAR INSIDE DIMENSIONS.
 - DUCTWORK HANGERS SHALL BE SUPPORTED BY FASTENERS ATTACHED TO STRUCTURAL STEEL. REPAIR FIRE PROOFING WHICH WAS REMOVED FOR DUCTWORK INSTALLATION. INSTALLATION TO BE DONE BY AN APPROVED QUALIFIED TRADESMAN.
 - INSTALL IN THE DUCTWORK DEVICES FURNISHED BY THE TEMPERATURE CONTROLS SUB-CONTRACTOR. INSTALL SMOKE DETECTORS IN DUCTWORK FURNISHED BY THE DIVISION 16 CONTRACTOR.
 - WATER AND OTHER PIPES SHALL NOT BE ALLOWED TO PASS THROUGH AIR RISERS OR DUCTS, UNLESS APPROVED BY THE ENGINEERS, AND WHEN THIS OCCURS, THE SIZE OF SAID DUCT OR RISER SHALL BE PROPORTIONATELY INCREASED. SANITARY WASTE AND VENT PIPING SHALL NOT PENETRATE ANY DUCTWORK.
- B. GALVANIZED STEEL DUCTWORK:
- GALVANIZED STEEL DUCTWORK SHALL CONFORM TO ASTM A653 (G90). ALL LONGITUDINAL SEAMS SHALL BE GROOVED, DOUBLE OR PITTSBURGH TYPE.
- C. DUCTWORK FITTINGS:
- FOR RECTANGULAR DUCTWORK, VANES SHALL BE PROVIDED IN ELBOWS WITH 90 DEGREE THROATS AND THROAT RADII LESS THAN 1-1/2 TIMES DUCT WIDTH. VANES SHALL BE LOCATED IN ACCORDANCE WITH ASHRAE STANDARDS. DOUBLE-VANE AIRFOIL-TYPE TURNING VANES SHALL BE PROVIDED FOR ALL SQUARE TURNS.
- D. HANGERS AND SUPPORTS:
- PROVIDE CONCRETE INSERTS OR STRUCTURAL STEEL FASTENERS APPROPRIATE FOR BUILDING MATERIALS. PROVIDE TRAPEZE AND RISER SUPPORTS AS REQUIRED. SUPPORT MATERIALS SHALL BE THE SAME AS DUCTWORK SUPPORTING.
 - HANGER, STRAPS AND RODS SHALL WITH SMACNA'S "HVAC DUCT CONSTRUCTION STANDARDS METAL AND FLEXIBLE" STANDARDS
 - DUCT ATTACHMENTS: SHEET METAL SCREWS, BLIND RIVETS OR SELF-TAPPING METAL SCREWS, COMPATIBLE WITH DUCT MATERIALS.
- E. SEALANT MATERIAL
- SEALANTS SHALL BE SOLVENT OR WATER BASED TYPE U.L. CLASSIFIED MEETING NFPA 90A CLASS 1 WITH ZERO FIRE AND SMOKE DEVELOPMENT RATING. SEALER SHALL BE UNITED SHEET METAL, UNITED DUCT SEALER, OR HARDCAST IRON GRIP NO. 801. TRANSVERSE SEAMS SHALL BE TAPED AND SEALED WITH TWO LAYERS OF UNITED SHEET METAL, UNI-CAST OR CAULKED WITH DUCT SEALER.
- F. FLEXIBLE CONNECTORS:
- INSTALL FLEXIBLE CONNECTORS AT ALL SUPPLY AND EXHAUST FANS AND OTHER AIR HANDLING UNITS WITH INLET AND OUTLET DUCT OR CASING CONNECTIONS. CONNECTORS SHALL NOT BE PAINTED. CONNECTORS SHALL NOT BE USED AS TRANSITION PIECES BETWEEN FAN AND DUCTWORK.
 - CONNECTORS SHALL BE NOT LESS THAN 4 INCHES LONG (IN CLEAR) AND PROPERLY ATTACHED TO DUCT AND FAN CONNECTION COLLAR BY 1 X 1/8 INCH DRAW BOLT (FABRICATED OF THE SAME MATERIAL AS ADJACENT DUCTWORK) FIRMLY CLAMPED AROUND COLLARS IN SUCH A MANNER AS TO BE AIRTIGHT AND SECURED TO COLLARS WITH SHEET METAL SCREWS.
 - FLEXIBLE CONNECTORS SHALL BE U.L. LISTED, NEOPRENE COATED HEAVY GLASS FABRIC. FABRIC SHALL BE VENTGLAS, MANUFACTURED BY VENTFABRICS, INC.
- G. FLEXIBLE DUCTWORK:
- FLEXIBLE DUCTS SHALL BE USED FOR STRAIGHT RUNS OF DUCT OR OFFSETS UP TO 45 DEGREES, BUT NOT EXCEEDING 48 INCHES IN LENGTH. THE USE OF FLEXIBLE DUCTS AS ELBOWS WITH MORE THAN A 45 DEGREE BEND WILL NOT BE PERMITTED.
 - FLEXIBLE DUCT SHALL BE U.L. LISTED AND LABELED AS CLASS 1, AIR DUCT CONNECTOR, IN ACCORDANCE WITH U.L. STANDARD 181 AND SHALL MEET THE REQUIREMENTS OF THE LATEST NFPA BULLETIN, NO. 90A AND NO. 90B FOR FLAME SPREAD AND SMOKE DEVELOPMENT RATING.
 - FLEXIBLE DUCT SHALL BE RATED FOR A MAXIMUM PRESSURE OF 6 INCH POSITIVE AND 3/4 INCH NEGATIVE AND 4000 FPM MAXIMUM VELOCITY. AIR DUCT SHALL CONSIST OF: CPE LINER, COATED SPRING STEEL WIRE HELIX, FIBERGLASS INSULATING BLANKET, FIBERGLASS SCRIM AND REINFORCED ALUMINUM VAPOR BARRIER. THERMAL CONDUCTANCE SHALL BE .23 OR LESS.
 - DUCT SHALL BE FLEXMASTER TYPE 8M OR PRIOR APPROVED EQUAL.
- A. VOLUME DAMPERS:
- SINGLE BLADE DAMPERS SHALL BE CONSTRUCTED OF .22 GAUGE GALVANIZED STEEL (BLADE AND FRAME). SINGLE BLADE DAMPERS SHALL BE LIMITED TO A 12 INCH HIGH BLADE. BLADE EDGES SHALL BE CRIMPED OR REINFORCED. DAMPER LEVERS SHALL INDICATE POSITIVELY THE OPEN AND CLOSED POSITION. END BEARINGS SHALL BE MOLDED SYNTHETIC. DAMPERS SHALL BE RUSKIN MD25 OR APPROVED EQUAL (RUSKIN MDRS25 FOR ROUND DUCTS).
 - MULTIBLADE DAMPERS SHALL BE CONSTRUCTED OF SHEET METAL THE SAME MATERIAL AS THE ADJACENT DUCTWORK. DAMPER FRAME SHALL BE NOT LESS THAN 18 GA. DAMPER BLADES NOT WIDER THAN 6 INCHES CRIMPED OR REINFORCED. DAMPER LEVERS SHALL INDICATE POSITIVELY THE OPEN AND CLOSED POSITION. END BEARINGS SHALL BE MOLDED SYNTHETIC. DAMPER SHALL BE RUSKIN MD35 OR APPROVED EQUAL.
- B. FIRE DAMPERS:
- FIRE DAMPERS SHALL BE UNDERWRITERS APPROVED AND LABELED (UL555). DAMPERS SHALL BE FABRICATED OF GALVANIZED STEEL AND SHALL BE OF SUCH A DESIGN AND LENGTH AS TO FUNCTION AS A WALL MOUNTING SLEEVE, WHICH SHALL BE A PART OF THE FIRE DAMPER. SLEEVES SHALL BE OF WELDED OR BOLTED CONSTRUCTION. CRIMPING OR TABS WILL NOT BE ACCEPTABLE SUBSTITUTES FOR WELDING OR BOLTING.
 - FIRE DAMPERS SHALL BE RUSKIN DIB23 SERIES FOR 1 2 HOUR RATING. FIRE DAMPERS SHALL BE RUSKIN DIB23 SERIES FOR 3 HOUR RATING. INSTALL STYLE A FIRE DAMPERS BEHIND DUCTED GRILLES AND REGISTERS IN RATED WALLS. INSTALL STYLE B OR C FIRE DAMPERS IN DUCTED OPENINGS IN RATED WALLS. AIR BALANCE AND PREFCO ARE APPROVED EQUAL.
- C. DAMPER HARDWARE:
- ALL HARDWARE SHALL BE SMACNA ACCEPTED. INSULATED DUCTWORK (CONCEALED) - VENTLOK 638 ELEVATED DIAL REGULATOR. INSULATED DUCTWORK (EXPOSED) - VENTLOK 644 - SELF LOCKING REGULATOR. UNINSULATED DUCTWORK - VENTLOK 555 OR 560 QUADRANTS.
- D. DUCT ACCESS DOORS:
- ACCESS DOORS SHALL BE HINGED, CONSTRUCTED OF THE SAME MATERIAL AS THE DUCTWORK. DOOR EDGES SHALL BE SEALED WITH 3/4 INCH WIDE X 1/8 INCH THICK NEOPRENE SPONGE GASKETING. DOOR HARDWARE SHALL BE VENTLOK #100 LATCHES. ACCESS DOORS ON INSULATED DUCTWORK SHALL BE DOUBLE WALL CONSTRUCTION WITH 1 INCH OF RIGID 3 PCF FIBERGLASS INSULATION.
 - PROVIDE DUCT ACCESS DOORS AT ALL DUCT MOUNTED DEVICES REQUIRING ADJUSTMENT OR RESETTNG. ACCESS DOORS SHALL BE APPROXIMATELY 18 INCHES HIGH BY 24 INCHES WIDE. IN SMALLER DUCTWORK, THE HEIGHT SHALL BE REDUCED TO BE 2 INCHES LESS THAN THAT OF THE DUCTWORK.

SECTION 230933 - TEMPERATURE CONTROLS

- A. GENERAL:
- FURNISH AND INSTALL AN ELECTRIC SYSTEM OF AUTOMATIC TEMPERATURE CONTROL AS SPECIFIED HEREIN AND AS SHOWN ON THE CONTRACT DRAWINGS AS MANUFACTURED BY HONEYWELL, JOHNSON CONTROLS, INVENYS, OR APPROVED EQUAL.
 - EXTRA COSTS INCURRED BY USE OF OTHER THAN BASE BID CONTROL SYSTEM, SUCH AS WIRING, CONTRACT DRAWINGS CHANGES, CHANGES IN DESIGN, ADDED SUPERVISION, ETC., SHALL BE THE RESPONSIBILITY OF THE TEMPERATURE CONTROL SUBCONTRACTOR (TCSC).
 - SYSTEM DOCUMENTS AND SHALL INCLUDE THE FOLLOWING: MANUFACTURER'S DATA SHEETS OF ALL PRODUCTS (ORIGINAL COPIES), COMPLETE DESCRIPTION OF OPERATION OF ALL CONTROL LOOPS, INCLUDING RECOMMENDED SETPOINTS AND RANGES OF ADJUSTMENT; FULLY LABELED ELEMENTARY DIAGRAM (ELECTRICAL LADDER DIAGRAM), AND LISTS OF ALL PROPOSED DEVICES AND EQUIPMENT.
- B. MOTOR OPERATORS: MOTOR OPERATOR SHALL BE SPRING RETURN TYPE, WHICH RETURNS MOTOR ACTUATOR SHAFT TO ITS FULL NORMAL MECHANICAL TRAVEL UPON POWER FAILURE. DAMPER MOTOR DRIVE MECHANISM WILL INCLUDE HOLDING BRAKE TO KEEP THE RETURN SPRING FROM DRAWING THE ACTUATOR FROM DRIVING TOWARD ITS NORMAL POSITION UNLESS POWER IS INTERRUPTED. SUPPLY AND INSTALL ELECTRIC MOTOR OPERATORS FOR ALL DAMPERS. UNIT SHALL BE HONEYWELL MS8105A SERIES OR APPROVED EQUAL.

C. AUTOMATIC DAMPERS: ALL CONTROL DAMPERS SHALL BE STANDARD PRODUCTS OF DAMPER OR TEMPERATURE CONTROL MANUFACTURERS UNLESS NOTED OTHERWISE. LOCAL FABRICATION OF DAMPERS IS NOT ALLOWED. DAMPERS SHALL BE OPPOSED BLADE TYPE. FURNISH FOR INSTALLATION BY THE MECHANICAL CONTRACTOR ALL MOTOR OPERATED DAMPERS. DAMPERS SHALL BE RUSKIN MODEL CD50. GREENHECK IN AN APPROVED EQUAL.

D. THERMOSTATS:

 - PROVIDE HVAC THERMOSTAT WITH THE FOLLOWING FEATURES: SEVEN DAY PROGRAMMING, TWO OCCUPIED/TWO UNOCCUPIED PERIODS PER DAY, AUTOMATIC HEAT/COOL CHANGEOVER WITH 2°F MINIMUM DEAD BAND, TWO STAGE HEATING, TWO STAGE COOLING, TOUCHSCREEN DISPLAY, AUXILIARY CONTACT, AND TEMPERATURE OVERRIDE. THERMOSTAT SHALL BE HONEYWELL VISIONPRO 8000 OR EQUAL.
 - PROVIDE HEATER AND VENTILATION THERMOSTAT WITH THE FOLLOWING FEATURES: SINGLE STAGE CONTROL, ON/OFF/AUTO SWITCHING, AND ADJUSTABLE SETPOINT CONTROL.

E. TEMPERATURE CONTROL WIRING:

 - ALL CONTROL WIRING AND CONDUIT REQUIRED TO COMPLETE THE TEMPERATURE CONTROL SYSTEM SHALL BE PROVIDED BY THE TEMPERATURE CONTROL SUB-CONTRACTOR. ALL WIRING SHALL CONFORM TO STANDARDS AND SPECIFICATIONS OUTLINED IN DIVISION 16. WIRE SIZE SHALL BE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS AND NATIONAL ELECTRIC CODE. MINIMUM CONDUIT SHALL BE 1/2 INCH DIAMETER. TCSC SHALL COORDINATE ALL CONTROL POWER REQUIREMENTS WITH ELECTRICAL CONTRACTOR PRIOR TO BID.
 - ELECTRIC CONNECTIONS BETWEEN THE VARIOUS UNIT CONTROL CABINETS SHALL BE MADE BY THE TCSC. ALL WIRING MUST BE TAGGED ON BOTH ENDS WITH PANEL NUMBER AND TERMINAL NUMBER.
 - THE TCSC IS RESPONSIBLE FOR ALL REQUIRED PROCESS AND ELECTRICAL CONNECTIONS TO ALL EQUIPMENT, CONTROL DEVICES, AND FIELD INSTRUMENTS. TCSC SHALL FURNISH AND INSTALL ALL CONDUITS, RACEWAYS, ETC., REQUIRED. TCSC SHALL FURNISH AND INSTALL ALL CONTROL AND INTERLOCK WIRING. TCSC SHALL FURNISH AND INSTALL ALL REQUIRED AUXILIARY STARTER CONTACTS OR RELAYS, ETC., FOR A COMPLETE ELECTRICAL INTERLOCK AND CONTROL WIRING SYSTEM.

F. INSTALLATION:

 - THE ENTIRE CONTROL SYSTEM, INCLUDING LOW VOLTAGE WIRING, WITH THE EXCEPTION OF DUCT MOUNTED AUTOMATIC DAMPERS AND SMOKE DETECTORS, SHALL BE INSTALLED BY THE TEMPERATURE CONTROL CONTRACTOR, WHO SHALL MAKE ALL TESTS AND ADJUSTMENTS. ALL CONTROLS SHALL BE FIELD-TESTED AND FIELD-CALIBRATED.
 - SET POINTS OF ALL CONTROLLING INSTRUMENTS ARE INDICATED AT A SPECIFIC POINT; HOWEVER, ALL SET POINTS SHALL BE ADJUSTABLE UP AND DOWN FROM THE POINT INDICATED.
 - CONTRACTOR SHALL SUBMIT TENTATIVE LOCATIONS OF ALL CONTROL DEVICES AND COMPONENTS (INCLUDING TEMPERATURE SENSORS) TO THE ARCHITECT FOR WRITTEN APPROVAL PRIOR TO INSTALLATION. CONTRACTOR SHALL PAY PARTICULAR ATTENTION TO LOCATION OF CONTROL DEVICES AND COMPONENTS TO LOCATION OF CONTROL DEVICES AND COMPONENTS. EFFECTS OF DRAFTS, RADIANT HEAT, VIBRATION, ETC ARE TO BE CONSIDERED WHEN INSTALLING CONTROL DEVICES AND COMPONENTS.
 - PRIOR TO ORDERING FACTORY ASSEMBLED EQUIPMENT WHICH CONTAINS INTEGRAL CONTROL DEVICES AND COMPONENTS, THE CONTRACTOR SHALL OBTAIN A WRITTEN STATEMENT FROM BOTH THE MANUFACTURER AND THE INSTALLING CONTRACTOR THAT THEY HAVE REVIEWED THE APPROPRIATE SUBMITTAL DATA AND ARE AWARE OF THE MAKE, MODEL, TYPE, SIZE, CHARACTERISTICS, ETC, OF THE FACTORY ASSEMBLED CONTROL DEVICES AND COMPONENTS WHICH THEY SHALL BE REQUIRED TO INTERFACE TO AND/OR CONTROL.
 - ALL CONTROL DEVICES (BOTH FIELD AND PANEL MOUNTED) SHALL BE LABELED TO INDICATE BOTH THEIR CONTROL SYSTEMS DESIGNATION, E.G., RTU-1 THERMOSTAT UNLESS INDICATED OTHERWISE, ABBREVIATIONS AND ACRONYMS FOR ALL ID TAGS AND PANEL FACEPLATES SHALL BE APPROVED BY THE ENGINEER.
 - ALL CONTROL DEVICES ARE TO BE MOUNTED IN ACCESSIBLE LOCATIONS. ALL DEVICES EXPOSED TO THE WEATHER SHALL BE HOUSED IN WEATHERPROOF ENCLOSURES.
 - AT THE COMPLETION OF THE JOB, TCSC SHALL CORRECT HIS DRAWINGS TO INCLUDE ANY CHANGES MADE DURING CONSTRUCTION. TCSC SHALL PROVIDE COLOR-CODED DRAWINGS INDICATED ALL TEMPERATURE ZONES AND EQUIPMENT (3 COPIES).

G. OPERATION TEST AND OWNER'S INSTRUCTION:


 - AT COMPLETION, TCSC SHALL OPERATE THE SYSTEM FOR A PERIOD OF AT LEAST THREE DAYS OF EIGHT HOURS EACH ON THE NEW SYSTEMS TO DEMONSTRATE FULFILLMENT OF THE REQUIREMENTS OF THE CONTRACT. DURING THIS TIME, ALL ADJUSTMENTS SHALL BE MADE TO THE EQUIPMENT SO THAT IT IS IN FIRST-CLASS OPERATING CONDITION. THE ENTIRE SYSTEM IS TO BE LEFT IN OPERATING CONDITION ACCEPTABLE TO THE ENGINEER.
 - UPON COMPLETION OF THE WORK AND ACCEPTANCE BY THE OWNER, TCSC SHALL PROVIDE ONE SCHEDULED FOUR-HOUR PERIOD OF FORMAL INSTRUCTION TO THE OWNER'S OPERATING PERSONNEL WHO HAVE RESPONSIBILITY FOR THE MECHANICAL SYSTEM.

H. SEQUENCE OF OPERATIONS:

 - EXHAUST FANS:
 - INTERLOCK EXHAUST FANS AS NOTED ON SCHEDULE.
 - UNIT HEATERS:
 - HEATERS SHALL ENERGIZE AS REQUIRED TO MAINTAIN SPACE TEMPERATURE.
 - HEATING SETPOINT SHALL BE 60°F (ADJUSTABLE).

SECTION 230933 - TESTING, ADJUSTING AND BALANCING

- A. THE TEST AND BALANCE CONTRACTOR SHALL BE AN INDEPENDENT CONTRACTOR THAT REGULARLY PERFORMS AIR AND WATER SYSTEMS TESTING AND BALANCING. MINIMUM QUALIFICATIONS FOR ACCEPTANCE SHALL BE GENERAL MEMBERSHIP IN NEBB OR AABC, EXCEPT THAT AFFILIATION WITH MANUFACTURERS, INSTALLING, CONTRACTORS, OR ENGINEERING FIRMS MAY NOT PRECLUDE ACCEPTANCE.
- B. PERFORM TESTING AND BALANCING PROCEDURES ON EACH SYSTEM ACCORDING TO THE PROCEDURES CONTAINED IN ASHRAE APPLICATIONS HANDBOOK, AABC OR NEBB NATIONAL STANDARDS.
- C. CUT INSULATION, DUCTS, PIPES, AND EQUIPMENT CABINETS FOR INSTALLATION OF TEST PROBES TO THE MINIMUM EXTENT NECESSARY TO ALLOW ADEQUATE PERFORMANCE OF PROCEDURES. AFTER TESTING AND BALANCING, CLOSE PROBE HOLES AND PATCH INSULATION WITH NEW MATERIALS IDENTICAL TO THOSE REMOVED. RESTORE VAPOR BARRIER AND FINISH ACCORDING TO THE INSULATION SPECIFICATIONS FOR THIS PROJECT.
- D. MARK EQUIPMENT SETTINGS WITH PAINT OR OTHER SUITABLE, PERMANENT IDENTIFICATION MATERIAL, INCLUDING DAMPER-CONTROL POSITIONS, VALVE INDICATORS, FAN-SPEED-CONTROL LEVERS, AND SIMILAR CONTROLS AND DEVICES, TO SHOW FINAL SETTINGS.
- E. SET HVAC SYSTEM AIRFLOW RATES WITHIN THE FOLLOWING TOLERANCES:
- SUPPLY, RETURN, AND EXHAUST FANS: PLUS 5 TO PLUS 10 PERCENT.
 - AIR OUTLETS AND INLETS: 0 TO MINUS 10 PERCENT.
- F. WITHIN 90 DAYS OF COMPLETING TESTING, ADJUSTING, AND BALANCING, PERFORM ADDITIONAL TESTING AND BALANCING TO VERIFY THAT BALANCED CONDITIONS ARE BEING MAINTAINED THROUGHOUT AND TO CORRECT UNUSUAL CONDITIONS. IF INITIAL TESTING, ADJUSTING, AND BALANCING PROCEDURES WERE NOT PERFORMED DURING NEAR-PEAK SUMMER AND WINTER CONDITIONS, PERFORM ADDITIONAL INSPECTIONS, TESTING, AND ADJUSTING DURING NEAR-PEAK SUMMER AND WINTER CONDITIONS.
- G. THE MECHANICAL CONTRACTOR'S RESPONSIBILITIES: FURNISH THE TEST AND BALANCE CONTRACTOR ONE COMPLETE SET OF ACCEPTED EQUIPMENT DATA AND ONE COMPLETE SET OF ACCEPTED MECHANICAL SHOP DRAWINGS. THE MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE FOR ADVISING THE TEST AND BALANCE CONTRACTOR OF ANY CHANGE(S) MADE TO THE SYSTEM(S) DURING THE CONSTRUCTION PROCESS. MECHANICAL CONTRACTOR SHALL PROVIDE DRAWINGS, SPECIFICATIONS, SHOP DRAWINGS, CONTROL DIAGRAMS, ETC. DETAILING THE CHANGES TO THE TEST AND BALANCE CONTRACTOR. REPLACE AND/OR INSTALL PULLEYS, BELTS, DAMPERS AND TRIM PUMP IMPELLERS AS REQUIRED FOR THE CORRECT BALANCE AS DIRECTED BY THE TEST AND BALANCE CONTRACTOR. ALLOCATE TIME IN THE CONSTRUCTION SCHEDULE FOR TEST AND BALANCE PROCEDURE. ASSIST THE TEST AND BALANCE CONTRACTOR IN COORDINATING WORK WITH THE OTHER TRADES, AND PREPARE THE SYSTEM FOR TESTING AND BALANCING.



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



11/8/24

Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.


Mechanical Specifications

Project number	24028
Date	11/08/2024
Drawn by	CRA
Checked by	JAB

M0.03

Scale 12" = 1'-0"



 Mechanical Floor Plan
1/4" = 1'-0"

- GENERAL NOTES:**
1. VERIFY EXISTING CONDITIONS IN FIELD PRIOR TO BEGINNING WORK.
 2. SPACE ABOVE CEILING IS LIMITED. CAREFUL COORDINATION WITH LIGHTING, ELECTRICAL, PLUMBING, STRUCTURAL, AND ARCHITECTURAL WORK IS CRITICAL TO DUCTWORK INSTALLATION.
 3. PROVIDE NECESSARY OFFSETS IN PIPING, ELECTRICAL CONDUIT, AND DUCTWORK AS REQUIRED TO ACCOMMODATE NEW WORK. DRAWINGS ARE DIAGRAMMATIC AND DO NOT SHOW ALL DETAILS NOR CHANGES IN DUCTWORK ELEVATIONS NECESSARY FOR COMPLETE INSTALLATION.
 4. COORDINATE CEILING AIR DEVICE LOCATIONS WITH LIGHTING PLAN AND ARCHITECT'S REFLECTED CEILING PLAN.
 5. DUCTWORK SHALL BE RUN TIGHT TO STRUCTURE. AVOID CROSSING OVER LIGHTS AND OTHER DUCTS DUE TO TIGHT CLEARANCES.
 6. LOUVERS SHALL BE RUSKIN ELF6375D OR APPROVED EQUAL. PROVIDE UNIT WITH BIRDSCREEN AND MILL ALUMINUM FINISH. COORDINATE EXACT HEIGHT AND COLOR OF LOUVER WITH ARCHITECT PRIOR TO ORDERING.
 7. MOUNT TEMPERATURE CONTROLS 48" ABOVE FINISHED FLOOR. COORDINATE EXACT LOCATION WITH ARCHITECT.
 8. OUTSIDE AIR VENTILATION INTAKES FOR OIL CHANGE AND SERVICE AREAS WILL BE PROVIDED BY OPEN ROLL-UP DOORS. DOORS SHALL BE OPEN WHILE VENTILATION SYSTEM IS ENABLED.
 9. MAINTAIN ALL MANUFACTURERS DISTANCES FOR INSTALLATION OF RADIANT HEATERS.

Express Oil Change & Tire Engineers
Service Building
Northport, Alabama


FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

**Mechanical
Floorplan**

Project number	24028
Date	11/08/2024
Drawn by	CRA
Checked by	JAB
M1.01	
Scale	As indicated



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262

www.ahoarch.com

11/8/24

Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Plumbing Legend,
Abbreviations and
Schedules

Project number	24028
Date	11/08/2024
Drawn by	CRA
Checked by	JAB
P0.01	
Scale	12" = 1'-0"

PLUMBING LEGEND, SYMBOLS AND ABBREVIATIONS					
	DOMESTIC COLD WATER		BALL VALVE	ABV	ABOVE
	DOMESTIC HOT WATER		VALVE IN VERTICAL	AFF	ABOVE FINISHED FLOOR
	DOMESTIC HOT WATER RETURN		CAP ON END OF PIPE	INV	INVERT
	SANITARY VENT		CLEANOUT - FLOOR TYPE	BFF	BELOW FINISHED FLOOR
	SANITARY WASTE		CLEANOUT - WALL TYPE	CW	COLD WATER
			P-TRAP	DN	DOWN
			PIPE TURNING DOWN	EX	EXISTING
			PIPE TURNING UP	HW	HOT WATER
			TEE DOWN	WS	WASTE STACK
			TEE UP	VS	VENT STACK
			TIE NEW INTO EXISTING	AC	ABOVE CEILING
			PLUMBING FIXTURE NUMBER	WHA	WATER HAMMER ARRESTOR
			RISER NUMBER	BFG	BELOW FINISHED GRADE
			WATER HAMMER ARRESTOR	TMV	THERMOSTATIC MIXING VALVE
			PLUG TYPE CLEANOUT	TP	TRAP PRIMER
			BALANCING VALVE	DS	DOWNSPOUT
			CHECK VALVE	UG	UNDER GROUND
			GATE VALVE		
			REDUCED PRESSURE ZONE BFP		
			THERMOSTATIC MIXING VALVE		
			FLOOR SINK		
			FLOOR DRAIN		
			ROOF DRAIN/OVERFLOW DRAIN		
			FOOD SERVICE EQUIPMENT		

PLUMBING FIXTURE CONNECTION SCHEDULE						
Equipment No.	Description	Hot Water	Cold Water	Waste	Vent	Remarks
WC-1	WATER CLOSET - ADA		1/2"	4"	2"	PRESSURE ASSIST TANK TYPE
EW-1	ELECTRIC WATER COOLER		1/2"	2"	2"	WALL MOUNT - ADA - BILEVEL
FD-1	FLOOR DRAIN			2"		PROVIDE WITH TRAP SEAL OR EQUAL
LAV-1	WALL MOUNTED LAV - ADA	1/2"	1/2"	2"	2"	PROVIDE WITH TRAP WRAP AND MIXING VALVE EQUAL TO ZW1070
SK-1	SERVICE SINK	1/2"	1/2"	2"	2"	ROUTE TO OIL INTERCEPTOR
EW-1	EMERGENCY EYEWASH	1/2"	1/2"	0"	2"	PROVIDE WITH MIXING VALVE;
HB-1	ANTI SIPHON HOSE BIBB (INDOOR)			3/4"		
WH-1	WALL HYDRANT - FREEZE PROOF			3/4"		

ELECTRIC WATER HEATER SCHEDULE												
EQUIPMENT NO.	MANUFACTURER	MODEL	SERVICE	ENTERING WATER TEMP (F)	LEAVING WATER TEMP (F)	RECOVERY RATE (GPH)	STORAGE CAPACITY	TANK DIMENSIONS		ELECTRICAL		COMMENTS
								DIAMETER	HEIGHT	WATER HEATER WATTAGE	NUMBER OF ELEMENTS	
EW-1	A. O. Smith	ECS-30X	BATHROOM	60 °F	120 °F	21	30.0 gal	1' - 8"	3' - 3"	4500 W	1	
NOTE: ROUTE T&P AND DRAIN PAN DISCHARGE TO OUTDOORS.												

INTERCEPTOR SCHEDULE									
EQUIPMENT NO.	MANUFACTURER	MODEL	FLOW RATE - INT	LIQUID HOLD CAPACITY	INLET/OUTLET	VENT	LENGTH	WIDTH	DEPTH
OIL-1	STRIEM	OS-25	25 GPM	21.0 gal	3"	2"	2' - 3"	1' - 11"	1' - 3"

NOTE: PROVIDE WITH HEAVY DUTY LID AND EXTENSIONS TO MATCH EXTERIOR GRADE.

WATER METER SIZING	
TOTAL LOAD (FIXTURE UNITS)	GPM
9.5	14.2

SECTION 22010 - PLUMBING GENERAL

- A. PROVIDE EQUIPMENT, LABOR, MATERIAL, ETC., REQUIRED TO MAKE A COMPLETE WORKING INSTALLATION. INSTALL THE WORK IN ACCORDANCE WITH DRAWINGS, SPECIFICATIONS AND THE STANDARDS AND CODES (LATEST EDITION) THAT APPLY TO THIS WORK. IN THE EVENT OF A CONFLICT, INSTALL WORK IN ACCORDANCE WITH THE MOST STRINGENT CODE REQUIREMENTS DETERMINED BY THE ENGINEER.
- C. OBTAIN AND PAY FOR ALL PERMITS AND INSPECTIONS INCLUDING: BUILDING PERMITS, HEALTH DEPARTMENT PERMITS AND SEWER TAP PERMITS. DELIVER TO ENGINEER CERTIFICATES OF INSPECTION AND APPROVAL ISSUED BY THE AUTHORITIES.
- D. ALL EQUIPMENT AND METHOD SHALL BE INSTALLED AND CONNECTED IN ACCORDANCE WITH THE BEST ENGINEERING PRACTICES AND IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.
- E. DISCONNECT, REMOVE AND RE-INSTALL PLUMBING SERVICES LOCATED ON OR CROSSING THROUGH CONTRACT LIMITS, ABOVE OR BELOW EXISTING STRUCTURING CONSTRUCTION OF PROJECT OR CONFLICTING WITH COMPLETED PROJECT OR ANY APPLICABLE CODES.
- F. PROVIDE CUTTING OF PAVEMENT, SIDEWALKS, DRIVEWAYS, ETC., EXCAVATING, TRENCHING, SHORING AND DE-WATERING. PROVIDE BACKFILL MATERIAL AND PERFORM BACKFILLING.
- G. RESTORE SITE TO ORIGINAL CONDITION OR NEW FINAL GRADES. PROVIDE PAVING, CONCRETE, SEED, OR SOD.
- H. DRAWINGS AND SPECIFICATIONS ARE COMPLEMENTARY. WORK CALLED FOR BY ONE IS BINDING AS IF CALLED FOR BY BOTH.
- I. DRAWINGS ARE DRAWN TO A SMALL SCALE AND ARE DIAGRAMMATIC ONLY. THE DRAWINGS INDICATE SIZE AND GENERAL ARRANGEMENT OF EQUIPMENT. DO NOT SCALE DRAWINGS FOR EXACT LOCATIONS. FIELD MEASUREMENTS TAKE PRECEDENCE.
- J. PROVIDE NECESSARY OFFSETS, ELBOWS AND FITTINGS AS REQUIRED TO AVOID CONFLICT WITH EQUIPMENT OF OTHER DIVISIONS AND TO OBTAIN PROPER HEADROOM AND CLEAR PASSAGEWAYS. THIS SHALL BE DONE AT NO ADDITIONAL COST TO THE OWNER.
- K. WORK UNDER THIS DIVISION SHALL BE FIRST CLASS WITH EMPHASIS ON NEATNESS AND WORKSMANSHIP. INSTALL WORK USING COMPETENT MECHANICS, UNDER SUPERVISION OF FOREMAN, ALL DULY CERTIFIED BY LOCAL AUTHORITIES.
- L. INSTALLATION SUBJECT TO ENGINEER'S OBSERVATION, FINAL APPROVAL, AND ACCEPTANCE. ENGINEER MAY REJECT UNSUITABLE WORK.
- M. ALL MATERIALS SHALL BE NEW. ALL MATERIALS AND EQUIPMENT FOR WHICH A UL STANDARD, AN AGA APPROVAL, AN AWWA STANDARD, FM LISTING OR ASME REQUIREMENTS IS ESTABLISHED, SHALL BE SO APPROVED AND LABELED OR STAMPED.
- N. THE DRAWINGS ARE BASED ON THE USE OF PRODUCTS SPECIFIED AND LISTED FIRST. IF ANY REVISION IN PIPING, CONDUIT WORK, FOUNDATIONS, ANCHOR BOLTS, CONNECTIONS, ETC., IS REQUIRED BY OTHER NAMED PRODUCTS OR APPROVED SUBSTITUTIONS, IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO MAKE SUCH REVISIONS AT NO ADDITIONAL EXPENSE TO THE OWNER.
- O. SUBMIT SIX (6) ORIGINAL COPIES OF COMPLETE SHOP DRAWINGS FOR ALL MATERIALS AND EQUIPMENT FURNISHED UNDER DIVISION 15 OF SPECIFICATIONS TO ENGINEER FOR REVIEW. SHOP DRAWINGS SHALL BEAR THE STAMP OF APPROVAL OF THE CONTRACTOR AS EVIDENCE THAT THE DRAWINGS HAVE BEEN CHECKED BY HIM, DRAWING SUBMITTED WITHOUT THIS STAMP OF APPROVAL WILL NOT BE CONSIDERED AND WILL BE RETURNED FOR PROPER RESUBMISSION.
- P. REVIEW OF SHOP DRAWINGS DOES NOT RELIEVE CONTRACTOR OF RESPONSIBILITY FOR ERRORS AND OMISSIONS IN SHOP DRAWINGS. CONTRACTOR IS RESPONSIBLE FOR DIMENSIONS AND SIZES OF EQUIPMENT. INFORM ENGINEER IN WRITINGS OF EQUIPMENT DIFFERING FROM THAT SHOWN.
- Q. PROVIDE MAINTENANCE AND OPERATING MANUALS BOUND IN 8 1/2" X 11" HARDBACK, THREE-POST BINDERS. MANUALS SHALL CONTAIN WRITTEN INSTRUCTIONS FOR EACH SYSTEM, SHOP DRAWINGS, SCHEMATIC DRAWINGS, EQUIPMENT CATALOG CUTS, MANUFACTURER'S INSTRUCTIONS, MANUFACTURERS WARRANTIES, AND VALVE TAG LIST.
- R. PROVIDE AS-BUILT PRINTS AT THE COMPLETION OF JOB. KEEP ONE SET OF PRINTS ON JOB AND RECORD DAY TO DAY CHANGES TO CONTRACT DRAWINGS WITH RED PENCIL. INDICATE ACTUAL LOCATION OF PIPING, VALVES, AND EQUIPMENT. TURN OVER PRINTS TO ENGINEER AT FINAL OBSERVATION.
- S. FURNISH ENGINEER WRITTEN WARRANTY, STATING THAT IF WORKSMANSHIP AND/OR MATERIALS EXECUTED UNDER THIS DIVISION IS PROVEN DEFECTIVE WITHIN ONE (1) YEAR AFTER FINAL ACCEPTANCE, SUCH DEFECTS AND OTHER WORK DAMAGED WILL BE REPAIRED AND/OR REPLACED.

SECTION 22050 - BASIC MATERIALS AND METHODS

- A. ACCESS PANELS:
1. ACCESS PANELS SHALL HAVE WELDED STEEL FRAME, ONE PIECE DOORS, AND SELF LATCHING DOOR LOCKS. LOCKS SHALL BE SCREW DRIVER OPERATED WITH CASE HARDENED STEEL CAM. PANELS SHALL BE MILCOR, DESCO, KARP OR EQUAL. KARP OR EQUAL. PROVIDE ACCESS PANELS IN WALLS AND CEILINGS AS NEEDED TO ALLOW ACCESS TO VALVES, EQUIPMENT, SHOCK ABSORBERS, TRAP PRIMERS, ETC. AND WHERE NOTED.
- B. FIRESTOPPING AND SOUNDSTOPPING:
1. PENETRATIONS THROUGH FLOORS AND FIRE RESISTANT WALLS SHALL BE SEALED TO THE RATED FIRE RESISTANCE EQUAL TO THE WALL. INSTALLATION SHALL BE DONE BY A QUALIFIED INSTALLER, APPROVED BY THE MANUFACTURER.
2. PROVIDE SOUND PROOFING THROUGH NON-RATED WALLS.
- C. PIPING SEALS:
1. PROVIDE MODULAR, RESILIENT SEALS AROUND PIPES PENETRATING ALL EXTERIOR WALLS, AND FLOORS BELOW GRADE. PIPING SEALS SHALL BE THUNDERLINE CORP. "LINK SEAL" LS SERIES.
- D. CUTTING AND PATCHING:
1. CONTRACTOR SHALL BE RESPONSIBLE FOR CUTTING AND PATCHING. CUT WALLS, FLOORS, CEILINGS, PARTITIONS, ETC., REQUIRED FOR THE INSTALLATION OF THIS WORK IN A NEAT AND CAREFUL MANNER. CORE DRILL FOR PIPE SLEEVES AND OTHER OPENINGS THROUGH FLOORS AND WALLS. SAWCUT LARGER OPENINGS. CUTTING SHALL BE KEPT TO A MINIMUM.
2. REPLACE OR REPAIR DUCTWORK, CONDUIT, PIPING, ETC., THAT IS CUT. PATCH AROUND OPENING CUT BY THIS CONTRACTOR OR PROVIDED BY OTHERS FOR HIM. PATCHING SHALL BE DONE BY AN APPROVED QUALIFIED CONTRACTOR, BUT SHALL BE PAID FOR BY THIS CONTRACTOR. FINISHED PATCHING SHALL RETAIN FIRE AND SMOKE RATINGS OF THE ASSEMBLY AND SHALL MATCH SURROUNDING FINISH.
- E. ANCHORS:
1. MOUNT ALL EQUIPMENT, BRACKETS, HANGERS, ANCHORS, ETC. TO SAFELY RESIST THE VIBRATION OR THRUST FORCES AND SUPPORT THE UNIT'S WEIGHT.
2. FLOOR MOUNTED ROTATING OR VIBRATING EQUIPMENT SHALL BE ANCHORED TO THE FLOOR USING GROUTED-IN PLACE OR CAST-IN PLACE ANCHOR BOLTS WITH THREE INCH HOOK AND SLEEVE. ANCHOR BOLTS SHALL BE OF THE SIZE RECOMMENDED BY THE MANUFACTURER.
3. FLOOR MOUNTED STATIC ITEMS, WALL AND CEILING MOUNTED EQUIPMENT BRACKET AND HANGERS SHALL BE INSTALLED USING DRILLED ANCHORS [OR CAST IN PLACE INSERTS]. ANCHORS SHALL BE PHILLIPS DRILL COMPANY "RED HEAD" OR MULTI-SET II. SIZE ANCHORS [AND INSERTS] FOR FOUR TIMES THE APPLIED LOAD. BOLTS USED OUTDOORS OR IN A WET ENVIRONMENT SHALL BE HOT DIP GALVANIZED.
- A. PIPE IDENTIFICATION:
1. IDENTIFICATION SHALL BE IN ACCORDANCE WITH ANSI-A13.1. PIPE MARKERS SHALL BE SETONS WEATHER-CODE OR EQUAL.
2. PROVIDE PIPE MARKERS AND DIRECTIONAL ARROWS ON PIPES AT BOTH SIDES OF PARTITIONS AND FLOORS SLABS, AT BRANCH LINE TAKE-OFFS, AT VALVES, AT INTERMEDIATE INTERVALS NOT IN EXCESS OF 20 FT. AND AT CONNECTIONS TO EQUIPMENT.
3. TAPE COLOR BAND IDENTIFYING MARKERS AND ARROWS ON EACH PIPE, BOTH INSULATED AND BARE PIPES. PIPE MARKERS AND ARROWS SHALL BE LOCATED WHERE READILY VISIBLE AND ON LOWER QUADRANTS OF OVERHEAD PIPES.
- B. VALVE TAG AND CHART:
1. VALVE TAGS SHALL BE SETON M4506, BLACK FILLED LETTERS WITH BRASS JACK CHAIN. ONE VALVE NUMBER SHALL BE STAMPED ON EACH TAG. IDENTIFY EACH VALVE TAG FOR THE UTILITY IT SERVES, SUCH AS "CW" FOR COLD WATER, HW FOR HOT WATER, ETC. VALVE CHARTS SHALL BE SETON. ATTACH A NUMBERED VALVE TAG TO EACH VALVE.
2. PROVIDE A TYPE WRITTEN CHART IN FRAME UNDER GLASS COVER, GIVING THE FULL LIST OF ALL VALVES INSTALLED UNDER THIS CONTRACT. CHART SHALL LIST VALVE NUMBER, TYPE OF UTILITY, AND LOCATION. MOUNT CHART WHERE DIRECTED BY OWNER. PROVIDE ONE ADDITIONAL COPY TO OWNER.
- C. EQUIPMENT IDENTIFICATION:
1. IDENTIFY EACH PIECE OF EQUIPMENT WITH A 1/8 INCH THICK ENGRAVED MELAMINE PLASTIC LAMINATE NAMEPLATE. LETTERS SHALL BE 1/2 INCH HIGH STANDARD STYLE. NAMES, ABBREVIATIONS, AND NUMBERING SHALL AGREE WITH THE CORRESPONDING EQUIPMENT DESIGNATIONS SHOWN ON THE DRAWINGS. USE BLACK LETTERS CUT IN A WHITE BACKGROUND FOR ALL EQUIPMENT ON STANDARD ELECTRICAL POWER.
2. FASTEN NAMEPLATES TO EQUIPMENT IN A CONSPICUOUS LOCATION USING SELF-TAPPING STAINLESS STEEL SCREWS. EXCEPT USE CONTACT EPOXY ADHESIVE WHERE SCREWS CANNOT OR SHOULD NOT PENETRATE SUBSTRATE.
- D. PIPE SLEEVES:
1. PROVIDE PIPE SLEEVES WHERE PIPES PASS THROUGH FLOORS AND WALLS ABOVE OR BELOW CEILINGS. PROVIDE PIPE SLEEVES IN NEW WALLS AND FLOORS AS THE WORK PROGRESSES. PROVIDE SPLIT PIPE SLEEVES IN NEW WALLS BUILT UP AROUND EXISTING PIPES. TACK WELD SPLIT SLEEVES TOGETHER.
2. SIZE PIPE SLEEVES TO ALLOW CONTINUOUS INSULATION, BUT NOT LESS THAN TWO PIPE SIZES LARGER THAN PIPE. SLEEVES IN WALLS SHALL BE FLUSH WITH WALL. SLEEVES IN FLOORS SHALL EXTEND 3/4 INCHES ABOVE FLOOR AND BE FLUSH WITH STRUCTURE BELOW.
3. SLEEVES IN CONCRETE WALLS, FLOORS OR MASONRY SHALL BE SCH 40 STEEL PIPE, MACHINE CUT. SLEEVES IN GYPSUM BOARD OR PLASTER WALLS SHALL BE 14 GAUGE, ROLLED GALVANIZED SHEET METAL, TACK WELDED ON THE LONGITUDINAL SEAM.
4. PROVIDE PLATES AROUND PIPES EXTENDING INTO EXPOSED AREAS WHERE THEY PASS THROUGH WALLS, FLOORS AND CEILINGS. SIZE PLATES TO COMPLETELY COVER PIPE SLEEVES. PLATES SHALL BE BEATON AND CADWELL, KEENEY OR GRINNELL, NICKEL PLATED STEEL, SPLIT PLATES WITH SET SCREW. CONCRETE FLOOR PLATE SHALL BE GRINNELL FIGURE 400.
- E. FLASHING:
1. PROVIDE FLASHING AT PIPING AND DUCT PENETRATIONS THROUGH ROOF AND ROOF MOUNTED STRUCTURES FURNISHED UNDER THIS DIVISION. FLASH IN ACCORDANCE WITH ROOFING MANUFACTURERS DETAILS. FLASHING MATERIALS SHALL BE IN ACCORDANCE WITH THE ROOFING MANUFACTURERS SYSTEM.
2. PROVIDE FLASHING AT PIPES PASSING THROUGH FLOORS WITH WATERPROOF MEMBRANE. FLASHING SHALL BE IN ACCORDANCE WITH WATERPROOFING MANUFACTURER'S DETAILS.

SECTION 220700 - PLUMBING INSULATION


- A. GENERAL:
1. ALL INSULATION, JACKETING, AND ADHESIVE SHALL HAVE COMPOSITE SURFACE BURNING CHARACTERISTIC RATING AS TESTED BY ASTM E 84, UL 723, OR NFPA 255 NOT EXCEEDING A FLAME SPREAD OF 25 OR SMOKE DEVELOPED OF 50.
2. SUBMITTALS SHALL USE PAGES FROM MIDWEST INSULATION CONTRACTORS ASSOCIATION - "COMMERCIAL AND INDUSTRIAL INSULATION STANDARDS" FOR DEFINING HOW INSULATION MATERIALS WILL BE APPLIED.
3. ALL PIPE INSULATION SHALL BE CONTINUOUS THROUGH WALLS, CEILINGS OR FLOOR OPENINGS, OR SLEEVES, EXCEPT WHERE FIRESTOP OR FIRESAFING MATERIALS ARE REQUIRED.
4. INSULATE ITEMS MOUNTED IN PIPING WITH THE SAME THICKNESS OF INSULATION AS SPECIFIED FOR PIPING.
5. REPAIR INSULATION DAMAGED BY WORK UNDER THIS CONTRACT TO MATCH EXISTING WORK OR REPLACE DAMAGED PORTION WITH INSULATION SPECIFIED FOR NEW WORK.
- B. DOMESTIC WATER PIPING:
1. INSULATION SHALL BE 850 DEG. F RATED AS MANUFACTURED BY OWENS CORNING, MANVILLE OR KNAUF. ROUTED OR MOLDED FITTING INSULATION SHALL BE HAMFAB.
2. INSULATION SHALL HAVE FACTORY-APPLIED, REINFORCED, FLAME RETARDANT, VAPOR BARRIER JACKET EQUAL TO OWENS-CORNING ASJ WITH SELF-SEALING LAP. BUTT JOINTS SHALL BE TAPED WITH FIELD-APPLIED ASJ TAPE 3 IN. WIDE.
3. INSULATION THICKNESSES SHALL BE IN ACCORDANCE WITH INTERNATIONAL ENERGY CONSERVATION CODE FOR PIPE SIZES NOTED ON PLAN.
4. ALL FITTINGS AND VALVES SHALL BE INSULATED WITH PREFORMED FIBER GLASS FITTINGS OR MITERED SECTIONS OF PIPE INSULATION. INSULATION SHALL BE OF EQUAL THICKNESS TO THE ADJACENT PIPE INSULATION.
5. METAL SHIELDS SHALL BE INSTALLED BETWEEN HANGERS OR SUPPORTS AND THE PIPING INSULATION. RIGID INSULATION INSERTS SHALL BE INSTALLED AS REQUIRED BETWEEN THE PIPE AND THE INSULATION SHIELDS. INSERTS SHALL BE OF EQUAL THICKNESS TO THE ADJACENT INSULATION AND SHALL BE VAPOR SEALED AS REQUIRED.
- C. ELASTOMERIC CLOSED CELL INSULATION:
1. INSULATION SHALL BE RUBATEX OR ARMSTRONG. SECURE INSULATION WITH CONTACT ADHESIVE IN ACCORDANCE WITH MANUFACTURERS INSTRUCTIONS. EXPOSED OR EXTERIOR INSTALLATIONS SHALL BE PAINTED WITH TWO COATS OF WATER BASED LATEX ENAMEL.
2. PROVIDE 1 IN. THICK INSULATION ON DX REFRIGERANT PIPING, COOLING COIL CONDENSATE PIPING, AND CAPS FOR ALL VALVE STEMS AND OPERATORS, GAUGE COCKS, THERMOMETER WELLS AND OTHER APPURTENANCES SUBJECT TO SWEATING.
- D. PIPING FINISHES:
1. METAL JACKETING SHALL BE, SMOOTH, 0.016 IN. THICK, TYPE T 3003 ALUMINUM WITH LAMINATED MOISTURE BARRIER. JACKETING SHALL BE CHILDERS, ALUMINUM ROLL JACKETING WITH POLYKRAFT MOISTURE BARRIER. COVER THE FOLLOWING INSULATED SYSTEMS WITH METAL JACKETING: PIPING INSTALLED OUTDOORS AND EXPOSED PIPING INDOORS WITHIN 8 FT. OF FINISHED FLOOR. METAL FITTING COVERS SHALL BE TWO PIECE ALUMINUM. COVERS SHALL BE ELL-JAC.
2. CONCEALED PIPING FINISH COVERING SHALL BE THE ALL SERVICE JACKET. FITTINGS SHALL BE COVERED BY WRAPPING THE FITTING WITH FIBER REINFORCED TAPE, WITH A 5 PERCENT OVERLAP. FITTING COVERS SHALL BE ONE PIECE 20 MIL PVC. COVERS SHALL BE CEEL-TITE 550 PVC-UVR BY CEEL-CO OR EQUALS.

SECTION 221001 - PLUMBING PIPING

- A. THE WORK REQUIRED UNDER THIS SECTION INCLUDES ALL WORK NECESSARY FOR A COMPLETE INSTALLATION OF SANITARY WASTE PIPING, STORM PIPING AND DOMESTIC WATER PIPING INSIDE THE BUILDING TO 5 FEET OUTSIDE THE BUILDING. SUBMIT SCHEDULE OF PIPE AND FITTINGS FOR EACH SERVICE.
- B. DOMESTIC WATER PIPING: WATER PIPING WITHIN THE SHALL BE COPPER TUBE, TYPE "L" HARD TEMPER, ASTM B-88. PIPING BELOW GROUND SHALL BE COPPER TUBE, TYPE "K" SOFT TEMPER, ASTM B-88. FITTINGS SHALL BE WROUGHT COPPER, SOLDER TYPE, ASTM B-75, ANSI B16.22. SOLDER UNIONS SHALL BE WROUGHT COPPER, WITH COPPER GROUND JOINT. ASTM B75, ANSI B16.22. DIELECTRIC, EPSO, 250 LB. WOG. SOLDER METAL SHALL CONFORM TO ASTM B32, LEAD-FREE.
- C. STORM, SANITARY WASTE, AND VENT PIPING: ABOVE GROUND: SCHEDULE 40 PVC-DWV ASTM D-2665 USING SOLVENT CEMENT ASTM D2565. HORIZONTAL PIPING FOR FUTURE ROUGH-INS MAY BE DWV COPPER, ASTM B-306. BELOW GROUND: SCHEDULE 40 PVC-DWV ASTM D-2665 USING SOLVENT CEMENT ASTM D-2564.
- D. STORM, SANITARY WASTE AND VENT FITTINGS: ABOVE GROUND: IINO HUB CAST IRON SOIL PIPE FITTINGS WITH COUPLING ASSEMBLY, CISPI STANDARD 3101. SCHEDULE 40 PVC-DWV, ASTM D-2855 USING SOLVENT CEMENT ASTM D-2564. BELOW GROUND: SCHEDULE 40 PVC-DWV, ASTM D-2855 USING SOLVENT CEMENT ASTM D-2564.
- E. BALL VALVES: VALVES SHALL BE NIBCO T-585-70, FULL PORT BALL TYPE WITH BRONZE BODY, CHROME PLATED BALL AND BRONZE THREADED ENDS, 600 PSI WOG OR NIBCO S-565-70 IN COPPER LINES. HAMMOND, CRANE, APOLLO, MILWAUKEE, OR APPROVED EQUAL.
- F. ALL PIPING SHALL BE ROUTED TO CONSERVE BUILDING SPACE, BE COORDINATED WITH ITEMS INSTALLED BY OTHER TRADES AND NOT INTERFERE WITH ACCESS TO OR OPERATION OF THE FACILITY.
- G. PROVIDE ROOF FLASHINGS FOR PIPE PENETRATIONS THROUGH ROOF, TO BE INSTALLED BY ROOFING CONTRACTOR.
- H. WATER PIPING WITHIN BUILDING SHALL BE SIZE INDICATED ON PLANS AND RISERS. IN THE EVENT NO SIZE IS SHOWN, PIPE SIZE OR SIZE REQUIRED BY THE PLUMBING CODE. PIPING SHALL BE SLOPED TOWARD A SYSTEM DRAIN AND TOWARD OUTLETS, TO PROVIDE FOR SYSTEM DRAIN-DOWN. IF INSTALLED NEAR EXTERIOR WALLS, PIPING SHALL BE LOCATED ON THE INTERIOR SIDE OF INSULATION. INSTALL PIPING TO PREVENT DIRECT CONTACT BETWEEN FERROUS AND NON-FERROUS MATERIALS. ALLOW FLEXIBILITY FOR EXPANSION IN PIPING.
- I. DOMESTIC WATER PIPING SYSTEM SHALL BE TESTED WITH POTABLE WATER AT A PRESSURE OF 125 PSIG OR 25 PSIG ABOVE DESIGN WORKING PRESSURE, WHICHEVER IS GREATER FOR 12 HOURS. TEST SHALL BE CONDUCTED WITH PLUMBING INSPECTOR UNLESS APPROVED OTHERWISE IN WRITING.
- J. WATER DISTRIBUTION PIPING SHALL BE DISINFECTED PRIOR TO OCCUPANCY OR SYSTEM START-UP WITH A CHLORINE SOLUTION 50 PPM. ALLOW SYSTEM TO STAND FOR SIX HOURS MINIMUM, THEN EXERCISE ALL VALVES TO ENSURE TREATMENT OF ALL BRANCHES AND COMPONENTS. SYSTEM SHALL BE FLUSHED WITH POTABLE WATER AFTER DISINFECTION AND PRIOR TO PLACEMENT INTO SERVICE.
- K. STORM, SANITARY WASTE AND VENT PIPING SHALL BE TESTED IN ACCORDANCE WITH WATER AND AIR TESTS AS SPECIFIED IN THE INTERNATIONAL PLUMBING CODE, IN ADDITION TO ANY TESTS REQUIRED BY THE LOCAL PLUMBING OFFICIAL. (10 FEET OF HEAD WITH NO APPARENT LEAKS. HOLD FOR 30 MINUTES MINIMUM). FLUSH ALL GRAVITY PIPING INCLUDING FLOOR DRAINS AND ROOF DRAINS PRIOR TO TURNING OVER TO THE OWNER.
- L. ALL PIPE SHALL BE CUT SQUARE. REAM PIPE AND TUBE ENDS AND REMOVE BURRS. CLEAN THE ENDS OF PIPES TO REMOVE OIL, GREASE AND OXIDES. PREPARE PIPING CONNECTIONS TO EQUIPMENT WITH FLANGES OR UNIONS.
- M. ALL SOLDERED PIPING AND EQUIPMENT CONNECTIONS SHALL BE PROPERLY PREPARED IN ACCORDANCE WITH GOOD PIPING PRACTICE. APPLY A THIN LAYER OF FLUX TO ONLY THE MALE TUBING. ROTATE INTO THE FITTING WITH ONE OR TWO REVOLUTIONS.
- N. DOMESTIC WATER PIPING: ROUTE PIPING IN ORDERLY MANNER, PLUMB AND PARALLEL TO BUILDING STRUCTURE, AND MAINTAIN GRADIENT. INSTALL PIPING TO ALLOW FOR EXPANSION AND CONTRACTION WITHOUT STRESSING PIPE, JOINTS, OR CONNECTED EQUIPMENT. PROVIDE CLEARANCE FOR INSTALLATION OF INSULATION AND ACCESS TO VALVES AND FITTINGS. PROVIDE ACCESS WHERE VALVES AND FITTINGS ARE NOT EXPOSED. INSTALL VALVES WITH STEMS UPRIGHT OR HORIZONTAL. PROVIDE DRAIN VALVES AT LOW POINTS IN SYSTEMS. TEST WATER PIPING BEFORE BEING INSULATED OR CONCEALED IN WALLS OR CEILING.
- O. STORM, SANITARY WASTE, AND VENT PIPING: HORIZONTAL SOIL, WASTE AND DRAINAGE LINES WITHIN BUILDING SHALL HAVE A MINIMUM UNIFORM SLOPE OF 1/8 INCH PER FOOT ON 3 INCH AND LARGER, AND 1/4 INCH PER FOOT ON LINES 2 INCH AND SMALLER. TURNS IN SANITARY, SOIL, AND DRAIN PIPING SHALL BE MADE USING 45 DEGREE ELBOWS, WYES, QUARTER, EIGHTH, SIXTEENTH BENDS, OR OTHER BENDS APPROVED BY THE PLUMBING CODE. DO NOT USE SANITARY TEES OR CROSSES EXCEPT WHERE DISCHARGING FROM HORIZONTAL TO VERTICAL. MAKE CHANGES IN PIPE SIZES WITH REDUCING FITTINGS AND RECESSED REDUCERS. DO NOT REDUCE LINE SIZE IN DIRECTION OF FLOW. PROVIDE CLEANOUTS IN ALL HORIZONTAL TURNS IN WASTE PIPING GREATER THAN 45 DEGREES. PROVIDE DEEP SEAL TRAPS ON ALL FLOOR DRAINS, AND TRAP PRIMERS/SEAL WHERE REQUIRED BY CODE OR AS INDICATED ON DRAWINGS. INDIRECT WASTE LINES DUMPING INTO FLOOR OR HUB DRAINS SHALL MAINTAIN A 2-INCH AIR GAP BETWEEN THE END OF THE WASTE LINE AND THE RIM OF THE FLOOR OR HUB DRAIN.

SECTION 22010 - GAS PIPING SYSTEMS

- A. PROVIDE COMPLETE INSTALLATION OF GAS PIPING FROM THE "POINT OF DELIVERY" UP TO AND INCLUDING CONNECTION TO ALL GAS-FIRED EQUIPMENT. CONNECT EQUIPMENT ITEMS FURNISHED UNDER OTHER SECTIONS OF SPECIFICATIONS. TEST IN ACCORDANCE WITH A.G.A., STANDARD GAS CODE, N.F.P.A. 54, AND APPLICABLE STATE AND LOCAL CODES.
- B. ROUTE GAS SERVICE ENTRANCE PIPING INTO BUILDING TO AVOID INTERFERENCE AND DAMAGE. PROVIDE MANUAL SHUTOFF VALVE, GAS COCK AND GAUGE. VALVES SHALL BE LABELED.
- C. PROVIDE ACCESS PANELS FOR VALVES AND OTHER ITEMS REQUIRING MAINTENANCE IN ENCLOSED SPACES. AVOID INSTALLING GAS APPURTENANCES IN ENCLOSED SPACES WHERE POSSIBLE. INSTALL IN ENCLOSED SPACES ONLY AS ALLOWED BY APPLICABLE CODES.
- D. SUBMIT MANUFACTURER'S LITERATURE ON ALL MATERIALS AND EQUIPMENT INCLUDING: PIPE, PIPE COATING, ANODES, VALVES, FLEXIBLE CONNECTORS, FITTINGS, REGULATORS, RELIEF VALVES, GAUGES, GAS SERVICE.
- E. COORDINATE INSTALLATION OF GAS SERVICE LINE WITH LOCAL GAS COMPANY. PAY ALL FEES.
1. PROVIDE 12 INCH ELEVATED METER MOUNTING PADS ON TOP OF A 4 INCH THICK CONCRETE PAD FOR SUPPORT OF GAS METER AND PIPING.
2. PROVIDE (TWO) 8 INCH DIAMETER PIPE BOLLARDS FOR GAS METER PROTECTION. BOLLARDS SHALL BE SIX FEET LONG (3 FEET BELOW GRADE), MOUNTED IN A 24 INCH DIAMETER HOLE, FILLED WITH 3,000 PSI CONCRETE.
- F. INTERIOR PIPING: CONNECT TO ENTERING LINE AND DISTRIBUTE GAS TO EQUIPMENT ITEMS REQUIRING GAS AND AS INDICATED. PERFORM WORK IN ACCORD WITH APPLICABLE A.G.A., N.F.P.A. 54, STATE AND LOCAL CODES. INSTALL GAS STOP VALVES AND DRIP LEGS AT EACH EQUIPMENT ITEM. PIPING SHALL BE ADEQUATELY DRAINED WITH A MINIMUM SLOPE OF 1/4 INCH PER 15 FEET AND DRIP LEGS (FULL SIZE OF PIPE) INSTALLED AT ADDITIONAL POINTS WHERE CONDENSATE MAY COLLECT. INSTALL PRESSURE REDUCING VALVES AS REQUIRED TO PROVIDE PRESSURE WITHIN EQUIPMENT MANUFACTURER'S REQUIREMENTS.
- G. EXTERIOR PIPING: EXTERIOR PIPING SHALL BE SCHEDULE 40 CARBON STEEL. PIPING 2 INCH AND SMALLER MAY USE THREADED FITTINGS. PIPING 2 INCH AND LARGER SHALL USE WELDED FITTINGS AND FLANGED VALVES. EXTERIOR PIPING SHALL BE COATED WITH AN ALKYD ENAMEL PRIMER (MINIMUM DRY THICKNESS 3 MILS). EXTERIOR PIPING SHALL BE SUPPORTED ON GALVANIZED B-LINE CHANNELS AND PIPE CLAMPS.
- H. UNDERGROUND PIPING:
1. UNDERGROUND PIPING SHALL BE CARBON STEEL - A53/A106 WELDED OR POLYETHYLENE.
2. UNDERGROUND STEEL PIPING SHALL HAVE AT LEAST 18 INCH OF PROPER BACKFILL COVER. UNDERGROUND PIPING SHALL BE PROTECTED FROM CORROSION. PROVIDE COATED PIPING AND EXPOSED PIPING INDOORS WITHIN 8 FT. OF FINISHED FLOOR. METAL FITTING COVERS SHALL BE TWO PIECE ALUMINUM. COVERS SHALL BE ELL-JAC.
3. GAS LINES ROUTED UNDER A BUILDING SHALL BE STEEL AND SHALL BE ENCASED IN A SCH 40 OUTER CONDUIT (AT LEAST 3 PIPE SIZES LARGER THAN THE GAS LINE). CONDUIT SHALL BE SEAL WELDED TO THE GAS PIPE INSIDE THE BUILDING. CONDUIT SHALL BE VENTED TO OUTDOORS. CONDUIT SHALL BE PROTECTED FROM CORROSION SIMILARLY TO UNDERGROUND PIPING.
- I. PIPE/TUBING:
1. STEEL PIPE: ASTM A53 GRADE A OR B, TYPE F, ERW OR SEAMLESS. SCHEDULE 40.
2. ASTM A106 SEAMLESS, SCHEDULE 40.
3. TUBING (STEEL) ASTM A539.
4. PLASTIC PIPE ASTM D2513 POLYETHYLENE. DRISCO PIPE 6500 OR PRIOR APPROVED EQUAL.
- J. FITTINGS:
1. WELDED (STEEL): WELDING FITTINGS SHALL BE CARBON STEEL BUTT WELDING TYPE CONFORMING TO ASTM-234. ELBOWS SHALL BE LONG RADIUS TYPE. WELDING TEES SHALL BE USED ON BRANCH CONNECTIONS EQUAL TO OR GREATER THAN 2 THE DIAMETER OF THE MAIN RUN. FITTINGS SHALL BE LADISH, TUBE-TURN OR WELDBRAND. CARBON STEEL REINFORCED BRANCH, WELDING FITTINGS UP TO 3 INCHES, BUT NOT GREATER THAN 2 THE DIAMETER OF THE MAIN RUN MAY BE USED. FITTINGS SHALL BE BONNEY FORGE OR PHOENIX FORGING.
2. THREADED (MALLEABLE, IRON): SCREWED FITTINGS SHALL BE MALLEABLE IRON ASTM A-197, CLASS 150 CONFORMING TO ANSI B16.3. DIMENSIONS CONFORMING TO FEDERAL SPEC WW-P-521. FITTINGS SHALL BE GRINNELL, FLAGG OR STOCKHAM.
3. HEAT FUSION/COMPRESSION (POLYETHYLENE): SOCKET TYPE FUSION SHALL MEET THE REQUIREMENTS OF ASTM 2683. FITTINGS SHALL BE LISTED AND MARKED ASTM D2513. BUTT TYPE FUSION FITTING SHALL MEET THE REQUIREMENTS OF ASTM D3261.
- K. UNIONS (DIELECTRIC): CLASS 250 MALLEABLE, SCREWED ASTM A-197.
- L. VALVES:
1. 1 INCH AND SMALLER: BALL VALVE - CLASS 125 BRASS FULL PART, 2 PIECE BODY, CHROME PLATED TO ANSI B16.1.
2. 2 INCHES AND SMALLER: PLUG COCK - CLASS 125 CAST IRON, SCREWED, FULL PORT AGA LISTED. ANSI B16.33 HOMESTEAD FIGURE 601.
3. 2 1/2 INCHES AND LARGER: PLUG VALVE - CLASS 125 FLANGED CAST IRON ASTM A126 CONFORMING TO ANSI B16.1.
- M. PIPE COATING: X-TRU COAT OR PRIOR APPROVED EQUAL INCLUDING JOINTS AND FITTINGS.
- N. PRESSURE REGULATORS: CAST IRON OR ALUMINUM BODY AND SPRING CASE WITH STAINLESS STEEL VALVE STEAM, SEAT RING AND VALVE PLUG, PLATED STEEL, SPRINGS, NEOPRENE DIAPHRAGM AND GASKETS AND THE DISC. REGULATING VALVES SHALL BE SIZED FOR THE FLOW INDICATED AND FOR INLET AND OUTLET PRESSURES INDICATED. OUTLET PRESSURE SHALL BE MAINTAINED UNDER THE DESIGN FLOW CONDITION AND AT NO FLOW. REGULATING VALVES TWO PSI AND BELOW SHALL HAVE LEAK LIMITING DEVICES. REGULATING VALVES OVER TWO PSI SHALL BE VENTED FULL SIZE TO OUTSIDE OF THE BUILDING. OTHER REGULATING VALVES REQUIRING ACCESS TO THE ATMOSPHERE SHALL BE EQUIPPED WITH VENT PIPING LEADING TO OUTSIDE. PROVIDE A PRESSURE RELIEF VALVE IF THE REGULATOR CONNECTION SIZE EXCEEDS TWO-INCHES. REGULATING VALVES SHALL BE FISHER, MAXITROL OR PRIOR APPROVED EQUAL MEETING ANSI Z21-18.
- O. PRESSURE GAGE: FOR MEDIUM PRESSURE GAS: 0-5 PSI RANGE. FOR LOW PRESSURE GAS: 0-30 INCH W.C. RANGE. USE LOW PRESSURE TYPE 2-1/2 INCH DIAL PRESSURE GAGE WITH APPROPRIATE RANGE, OCI MODEL CO 34, TRERICE, WEKSLER OR APPROVED EQUAL.



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



11/8/24

Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Plumbing
Specifications

Project number	24028
Date	11/08/2024
Drawn by	CRA
Checked by	JAB

P0.02

Scale 12" = 1'-0"

SECTION 221005 - PLUMBING SPECIALTIES


- A. THIS SPECIFICATION DESCRIBES THE REQUIREMENTS FOR LABOR AND MATERIALS REQUIRED FOR THE INSTALLATION OF PLUMBING SPECIALTIES INCLUDED AS PART OF THE BUILDING PLUMBING SYSTEM. MANUFACTURER'S LITERATURE INDICATING MODEL NUMBERS AND OPTIONS SHALL BE SUBMITTED FOR ALL FIXTURES AND EQUIPMENT. FORMAT SHALL INCLUDE A SCHEDULE OF THE SPECIALTIES SUBMITTED AND INCLUDE IDENTIFICATION NUMBER OF EACH ITEM, SUCH AS "FD-1 FLOOR DRAIN," A LIST OF EACH COMPONENT, ACCESSORY, AND OPTION OF THE ITEM BEING SUBMITTED. THIS SCHEDULE MUST BE INCLUDED IN THE FRONT OF THE SUBMITTAL PAGE.
- C. CLEANOUTS SHALL CONSIST OF A COATED CAST IRON BODY WITH THREADED TOP WITH SPIGOT OR NO-HUB CONNECTION AND GASKETED BRONZE CLOSURE PLUG WITH COUNTERSUNK SLOT. HEAD SHALL BE ADJUSTABLE IN HEIGHT; PROVIDE NON-SKID COVERS FOR FLOOR CLEANOUTS. PROVIDE THREAD SHIELD TO PROTECT ADJUSTMENT THREADS FROM CONCRETE AS REQUIRED. CLEANOUTS SHALL BE INSTALLED IN HORIZONTAL RUNS AT SPACING OF NO MORE THAN 75 FEET. INSTALL CLEANOUTS AT THE BASE OF EVERY SOIL AND WASTE STACK, AND AT EACH 90 DEGREE CHANGE IN DIRECTION. INSTALL CLEANOUTS WHICH ARE NOT EASILY ACCESSIBLE UP THROUGH FLOOR OR WALL AND PROVIDE APPLICABLE COVERS. INSTALL CLEANOUTS TO ALLOW AT LEAST 18" FOR RODDING.
- D. WATER HAMMER ARRESTORS SHALL BE CONSTRUCTED OF A STAINLESS STEEL OR COPPER SHELL, STAINLESS STEEL OR ELASTOMER BELLOW, WITH PRECHARGE OF AIR, NITROGEN, OR ARGON. ARRESTERS SHALL CONFORM TO ASSE STD. 1010, AND SHALL BE ZURN "SHOKTROL", JOSAM "ABSORBOTRON", WADE "SHOKSTOP", OR PRECISION PLUMBING PRODUCTS "SHOCK ARRESTOR". UNIT SHALL BE SIZED IN ACCORDANCE WITH TO PDJ STANDARDS. WATER HAMMER ARRESTORS SHALL BE SIZED TO ACTUAL PIPE SIZE AND INSTALLED AS NEAR THE SHOCK SOURCE AS PRACTICAL. INSTALL TO ALLOW UNOBSTRUCTED PATH FROM SHOCK SOURCE TO ARRESTOR.
- E. BALANCING VALVES (DOMESTIC HOT WATER RETURN): VALVES SHALL BE BELL AND GOSSETT OR SERIES CIRCUIT SETTER, PRESETTABLE BALANCE VALVE, VARIABLE ORIFICE FLOW METER AND POSITIVE SHUT-OFF SERVICE VALVE. EQUIPMENT WITH CAPPED READOUT VALVES FITTED WITH INTERNAL CHECK VALVES, 1/4 INCH NPT TAPPED AND PLUGGED DRAIN PORT. BRONZE BODY/BRASS BALL CONSTRUCTION WITH GLASS AND CARBON FILLER. SOLDER CONNECTIONS. VALVES TO HAVE DIFFERENTIAL PRESSURE READ-OUT PORTS ACROSS VALVE SEAT AREA. FURNISH WITH PREFORMED INSULATION TO PERMIT ACCESS FOR BALANCE AND READ-OUT. TACO IS AN APPROVED EQUAL.
- F. PRESSURE REDUCING VALVES: VALVES SHALL BE EQUAL TO WATTS SERIES U6B-GG BRONZE BODY SINGLE SEATED WITH COMPOSITION DANLSSS STEEL SPRING, DIRECT ACTING WITH STRAINER ON INLET SIDE, INTEGRAL BY-PASS CHECK VALVE, GAUGE, AND THREADED ENDS. INSTALL IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
- G. TRAP GUARD SEALS: PROVIDE AN ELASTOMERIC, NORMALLY CLOSED TRAP GUARD DEVICE TO PREVENT EVAPORATION OF THE TRAP SEAL AND TO PROTECT AGAINST SEWER GASES FROM BACKING UP INTO HABITABLE AREAS. DEVICE SHALL OPEN WITH FLUID AND ALLOWS LIQUID DRAINAGE TO FLOW THROUGH INTO THE BUILDING DRAIN. TRAP SEAL SHALL BE TRAP GUARD BY PRO-VENT SYSTEMS OR APPROVED EQUAL.
- H. FLOOR DRAIN (FD-1): DRAIN SHALL INCLUDE SUR-SET BUCKET, 9" DIAMETER MEDIUM DUTY CAST IRON GRATE, COATED CAST IRON BODY, BOTTOM OUTLET, SEEPAGE PAN, AND COMBINATION MEMBRANE CLAMP. DRAIN SHALL BE ZURN Z-554-NH OR EQUAL BY JAY R. SMITH, WADE, OR JOSAM. PROVIDE 3 FT. SQ. 6 MIL BUTYL MEMBRANE, AT EACH FLOOR DRAIN. CLAMP MEMBRANE. MEMBRANE SHALL BE RECESSED IN THE FLOOR SLAB WITH TOPPING POURED OVER IT. DRAINS INSTALLED IN ELEVATED BUILDING FLOORS SHALL BE SEALED IN SUCH A MANNER AS TO PREVENT LEAKAGE OF WATER AROUND TRAP AND BODY TO CEILING BELOW.
- I. HUB DRAIN (HD): DRAIN SHALL INCLUDE CAST IRON DEEP SEAL, "P" TRAP WITH INDIRECT WASTE FUNNEL INLET AND SIDE OUTLET THREADED AND WITH 1/2 INCH THREADED FLUSH CONNECTION. DRAIN SHALL BE JOSAM 8821-051 OR EQUAL BY ZURN, JAY R. SMITH, OR WADE.
- J. REDUCED PRESSURE ZONE BACKFLOW PREVENTER (ASSE 1015): BACKFLOW PREVENTER SHALL INCLUDE NPT BODY CONNECTIONS, QUARTER TURN, FULL PORT, RESILIENT SEATED BRONZE BALL VALVE, AND STRAINER. UNIT SHALL BE WATTS SERIES 909 QT OR EQUAL BY WILKINS, OR CONBRACO. BACKFLOW PREVENTERS SHALL BE INSTALLED IN ACCORDANCE WITH PER MANUFACTURER'S INSTRUCTIONS. AFTER INSTALLATION, BUT BEFORE SYSTEM IS PUT INTO SERVICE, TEST BACKFLOW PREVENTER FOR FUNCTIONALITY WITH TEST KIT AS RECOMMENDED BY MANUFACTURER. PIPE DISCHARGE FROM BACKFLOW PREVENTER VENT WITH CONNECTION-SIZE COPPER TUBING TO NEAREST FLOOR DRAIN. ENSURE AIR GAP IS PROVIDED IN RELIEF LINE EITHER BY AIR GAP FITTING OR ELEVATED DISCHARGE ABOVE DRAINS. BACKFLOW PREVENTER PIPING SHALL BE INSTALLED WITH UNIONS FOR REMOVAL.
- K. WALL HYDRANTS (WH-1): WALL HYDRANTS SHALL BE NICKEL BRONZE PLATED, INTEGRAL VACUUM BREAKER, 3/4 INCH HOSE THREAD, KEY OPERATOR, NON-FREEZE TYPE, HOUSED IN A RECESSED STAINLESS STEEL BOX WITH HINGED LOCKING COVER. HYDRANT SHALL BE JAY R. SMITH 5509 QT OR EQUAL BY WADE, JOSAM OR ZURN. INSTALL WALL HYDRANTS AS INDICATED ON DRAWINGS, MINIMUM HEIGHT 18" A.F.F. UNLESS OTHERWISE INDICATED.
- L. HOSE BIBB (HB-1): CHROME PLATED, 1/2 INCH HOSE THREAD OUTLET, LOCK SHIELD CAP WITH INTEGRAL VACUUM BREAKER. CHICAGO FAUCET NO. 362 OR T&S BRASS.
- M. THERMOSTATIC MIXING VALVES: MIXING VALVE SHALL BE THERMOSTATIC TYPE WITH LIQUID FILLED MOTOR AND LEAD-FREE BRONZE BODY CONSTRUCTION WITH REPLACEABLE CORROSION RESISTANT COMPONENTS. VALVE CONSTRUCTION SHALL BE SLIDING PISTON CONTROL MECHANISM. PISTON AND LINER SHALL BE OF STAINLESS STEEL MATERIAL. VALVES SHALL BE EQUIPPED WITH REMOVABLE UNION END STOP AND CHECK INLETS WITH STAINLESS STEEL STRAINERS. VALVE SHALL PROVIDE PROTECTION FROM HOT AND COLD SUPPLY LINE FAILURE AND THERMOSTAT FAILURE. PROVIDE WITH DIAL THERMOMETER AND SHUT OFF VALVE ON TEMPERED WATER OUTLET. MIXING VALVE SHALL BE LAWLOR 800 SERIES OR EQUAL BY HOLBY, SYMMONS, LEONARD, OR WATTS. INSTALL IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
- O. LIF SEPARATOR: STRIEM HIGH EFFICIENCY OIL/WATER SEPARATOR MODEL OS-25 SHALL BE LIFETIME GUARANTEED AND MADE IN THE USA. SEPARATOR SHALL BE CERTIFIED TO API601G125 AND CARRY A UPTC LISTING. SEPARATOR SHALL BE CONSTRUCTED OF POLYETHYLENE. SEPARATOR SHALL BE MANUFACTURED FOR ABOVE- OR BELOW-GRADE INSTALLATION. FIELD ADJUSTABLE RISER SYSTEM IS AVAILABLE AS AN OPTION TO BRING MANHOLE COVER TO GRADE. SEPARATOR FLOW RATE SHALL BE 25 GPM. SEPARATOR LIQUID HOLDING CAPACITY SHALL BE 21 GALLONS AND OIL CAPACITY SHALL BE 5.25 GALLONS. SOLIDS CAPACITY SHALL BE 6 GALLONS. COVER SHALL PROVIDE WATER/GAS-TIGHT SEAL AND HAVE A MAXIMUM 450 LBS. LOAD CAPACITY WHEN UNIT IS INSTALLED ABOVE-GRADE, AND 2,500 LBS. WHEN BURIED WITH SR16 RISER.

SECTION 223005 - PLUMBING EQUIPMENT


- A. ELECTRIC WATER HEATERS:
1. WATER HEATER SHALL COMPLY WITH UL 1453.
 2. STORAGE TANK CONSTRUCTION: ASME-CODE STEEL WITH 150 PSIG WORKING-PRESSURE RATING. STEEL JACKET WITH ENAMELED FINISH.
 3. TAPPINGS: FACTORY FABRICATED OF MATERIALS COMPATIBLE WITH TANK FOR PIPING CONNECTIONS, RELIEF VALVE, PRESSURE GAGE, THERMOMETER, DRAIN, ANODE RODS, AND CONTROLS AS REQUIRED. ATTACH TAPPINGS TO TANK SHELL BEFORE TESTING AND LABELING. TAPPINGS SHALL HAVE THREADED ENDS ACCORDING TO ASME B1.20.1, PIPE THREADS.
 4. INTERIOR FINISH: MATERIALS AND THICKNESSES COMPLYING WITH NSF 61, BARRIER MATERIALS FOR POTABLE-WATER TANK LININGS. EXTEND FINISH INTO AND THROUGH TANK FITTINGS AND OUTLETS.
 5. INSULATION: COMPLY WITH ASHRAE 90.1. SURROUND ENTIRE STORAGE TANK EXCEPT CONNECTIONS AND CONTROLS.
 6. HEATING ELEMENTS: ELECTRIC, SCREW-IN OR BOLT-ON, IMMERSION TYPE. STAGING AS NOTED IN SCHEDULE.
 7. TEMPERATURE CONTROL: ADJUSTABLE IMMERSION THERMOSTAT.
 8. SAFETY CONTROLS: AUTOMATIC, HIGH-TEMPERATURE-LIMIT AND LOW-WATER CUTOFF DEVICES OR SYSTEMS.
 9. DRAIN VALVE: ASSE 1005, CORROSION-RESISTANT METAL, FACTORY INSTALLED.
 10. ANODE RODS: FACTORY INSTALLED, MAGNESIUM.
 11. DIP TUBE: FACTORY INSTALLED. NOT REQUIRED IF COLD-WATER INLET IS NEAR BOTTOM OF STORAGE TANK.
 12. SPECIAL REQUIREMENT: NSF 5 CONSTRUCTION.
 13. ACCEPTABLE MANUFACTURERS ARE LOCHINVAR, A. O. SMITH, OR PRIOR APPROVAL EQUAL.
- B. THERMAL EXPANSION TANK (DOMESTIC WATER) 5 GALLON:
1. PRE-CHARGED HYDRO-PNEUMATIC STEEL EXPANSION TANK, CONSTRUCTED IN ACCORDANCE WITH SECTION VII of ASME BOILER AND PRESSURE CODE, WITH ALL WELDS CONFORMING TO ASME SECTION IX. TANK MUST BE STAMPED WITH A MAXIMUM WORKING PRESSURE OF 125 PSI, AND A MAXIMUM WORKING TEMPERATURE OF 200 DEGREES F. ALL INTERNAL WETTED PARTS MUST COMPLY WITH FDA REGULATIONS AND APPROVALS. AN INTERNAL BUTYL DIAPHRAGM WILL BE USED TO ISOLATE AIR FROM WATER. AMTROL OR APPROVED EQUAL ST SERIES.

SECTION 224005 - PLUMBING FIXTURES

- A. THIS SPECIFICATION DESCRIBES THE REQUIREMENTS FOR PLUMBING FIXTURES AND THEIR INSTALLATION. SUBMITTALS SHALL INCLUDE MANUFACTURER'S DATA SHEETS AND DIMENSIONAL INFORMATION ON ALL FIXTURES AND ACCESSORIES. FORMAT SHALL INCLUDE A SCHEDULE OF THE FIXTURES SUBMITTED AND INCLUDE IDENTIFICATION NUMBER OF EACH ITEM, SUCH AS "P-1 WATER CLOSET", AND LIST OF EACH COMPONENT AND ACCESSORY OF THE FIXTURE, INCLUDING MANUFACTURER'S MODEL NUMBER. THIS SCHEDULE MUST BE INCLUDED IN THE FRONT OF THE SUBMITTAL BOOKLET.
- C. VITREOUS WARE SHALL BE WHITE, REGULAR SECTION, OF WEIGHT REQUIRED, FREE FROM CRACKS, FLAWS, BUSTERS, CRAZES OR OTHER DEFECTS. PROVIDE WITH MOUNTING BRACKETS FOR WALL MOUNTED FIXTURES UNLESS FLOOR CARRIERS ARE INDICATED.
- D. STAINLESS STEEL SHALL HAVE MACHINE GROUND FINISH. DECKS AND SINK COMPARTMENT SIDES SHALL BE BUFFED. EXPOSED SURFACES SHALL HAVE NO. 4 SATIN FINISH. INTERIOR SURFACES SHALL BE DEADENED. EXPOSED METAL PARTS SHALL BE CHROMIUM PLATED AND PROTECTED DURING CONSTRUCTION BY A COAT OF GREASE.
- E. WATER CLOSET AND URINAL CARRIERS SHALL HAVE TAPERED THREAD FACE PLATE, PLASTIC COUPLING WITH TEST CAP, AND NEOPRENE RUBBER GASKET. LAVATORY, SINK AND URINAL CARRIERS SHALL HAVE RECTANGULAR STRUCTURAL STEEL UPRIGHTS. CARRIERS SHALL HAVE NECESSARY ACCESSORIES FOR PROPER INSTALLATION. CARRIERS SHALL BE ACCORDING TO ANSI A112.6.1M.
- F. WATER CLOSETS AND URINALS SHALL HAVE BOLT CAPS.
- G. SEATS SHALL BE WHITE, SOLID PLASTIC, WITH INTERNAL CHECK AND MOLDED STAINLESS STEEL HINGE WITHOUT VISIBLE METAL PARTS, EXCEPT AS HEREINAFTER SPECIFIED.
- H. CHROMIUM PLATED TRAPS SHALL BE BRASS WITH CHROMIUM PLATED NIPPLE TO WALL AND ESCUTCHEON.
- I. FITTINGS AND ACCESSORIES SPECIFIED DESIGNATE TYPE ONLY; PROVIDE MODIFICATIONS TO MAKE FITTINGS WORK PROPERLY WITH FIXTURE AND PIPING. PROVIDE NECESSARY TAILPIECE AND SHANKS.
- J. INSTALL EYEWASH STATION WITHIN 10 FEET OF HAZARD AREA, COMPLETELY UNOBSTRUCTED FROM VIEW OR ACCESS. ANCHOR TO FLOOR IN ACCORDANCE WITH MANUFACTURER'S REQUIREMENTS. PROVIDE AND INSTALL STRAINER AT DOMESTIC WATER INLET TO STATION. PROVIDE AND INSTALL ON WALL ABOVE STATION, A PLASTIC ENGRAVED SIGN READING "EMERGENCY USE ONLY", WHITE LETTERS ON RED BACKGROUND. PROVIDE MINIMUM 5 GALLON CONTAINER AND PROVIDE TIMED FLOW TEST FOR ALL EYEWASHES AND EMERGENCY SHOWERS. SUBMIT REPORT TO ARCHITECT OR ENGINEER PRIOR TO FINAL INSPECTION.
- K. FIXTURES
- WC-1 WATER CLOSET (17-1/2" HIGH, FLOOR MOUNT, TANK TYPE):
1. KOHLER K-3658 VITREOUS CHINA, 1.28 GALLON FLUSH; TANK WITH ELONGATED BOWL.
 2. KOHLER K-7637 3/8" POLISHED CHROME ANGLE SUPPLY WITH STOP.
 3. BENKE 527SS ELONGATED SELF-SUSTAINING WITH CHECK HINGES, OPEN FRONT, HEAVY DUTY SOLID PLASTIC SEAT.
- LAV-1 LAVATORY (ADA COMPLIANT, WALL HUNG):
1. AMERICAN STANDARD DELLYN WALL MOUNTED LAVATORY, VITREOUS CHINA, WITH OVER FLOW AND 4" FAUCET CENTERS, DRILLED FOR CONCEALED ARM CARRIER.
 2. ZURN Z-7443-VP SINGLE CONTROL FAUCET, LEVER HANDLE, 4" CENTER MOUNT, 1-1/4" GRID STRAINER.
 3. MCGUIRE 170 1/2" X 3/8" SWEAT LAVATORY SUPPLIES WITH WHEEL HANDLE STOPS.
 4. MCGUIRE 8902, 1-1/4 INCH X 1-1/2 INCH P-TRAP WITH ESCUTCHEON; ZURN GH, 1-1/4" OFFSET HANDICAP GRID DRAIN.
 5. TRAP AND SUPPLIES COVERED WITH TRAP WRAP EQUAL TO BROCHAR INDUSTRIES.
 6. ZURN Z-1231 LAVATORY CONCEALED ARM CARRIER.
- SK-1 LAUNDRY TUB (SINGLE COMPARTMENT):
1. FIAT MODEL NO. F1-1 SINGLE-MOLDED STONE LAUNDRY TUB WITH FREE DRAINING SOAP TRAY ON BACK LEDGE. INCLUDE FOUR WHITE BAKED ENAMEL ANGLE LEGS THAT SLIP INTO MOLDED SOCKETS. SELF-LEVELING LEGS WITH FLOOR ANCHORS.
 2. FIAT MODEL A-1 BRASS FAUCET WITH SWING SPOUT.
 3. MCGUIRE 170 1/2" X 3/8" SWEAT LAVATORY SUPPLIES WITH WHEEL HANDLE STOPS.
 4. MCGUIRE #150 TRAY PLUG WITH RUBBER STOPPER (1-1/2").
 5. MCGUIRE #8912 1-1/2" X 1-1/2", 17 GAUGE BRASS P-TRAP.
- EW-1 EYE/FACE WASH (PEDESTAL MOUNT):
1. STAINLESS STEEL BOWL WITH TWIN EYEWASH HEADS WITH FLIP TOP COVERS, CHROME PLATED WATER EYEWASH ASSEMBLY.
 2. INCLUDE UNIVERSAL EMERGENCY SIGN CONFORMING TO ANSI Z535.1.
 3. INCLUDE MIXING VALVE/TEMPERED WATER BLENDING SYSTEM.
 4. EQUAL TO GUARDIAN G1825. CONFORM TO ANSI Z358.1.
- EW-1 WATER COOLER (WALL MOUNT, BOTTLE FILLING STATION, ADA):
1. ELKAY LZ2SL8WSVRSK, HANDS FREE, ADA COMPLIANT DUAL STATION WITH BOTTLE FILLING STATION.
 2. MCGUIRE 8902 P-TRAP WITH ESCUTCHEON.
 3. MCGUIRE 170 STOP AND SUPPLY.
- L. ACCEPTABLE MANUFACTURERS: FIXTURES: VITREOUS CHINA - AMERICAN STANDARD, CRANE, ELJER, KOHLER. FIXTURES, STAINLESS STEEL - JUST, ELKAY. FLUSH VALVES - SLOAN, DELANEY, ZURN. TOILET SEATS - OLSONITE, SPERZEL, CHURCH, BENKE, BEMIS. FAUCETS - T&S BRASS, SPEAKMAN, CHICAGO, SYMMONS, ELJER. TERRAZZO - FIAT, CUTLER, FLORESTONE, STERN-WILLIAMS. TRIM, CHROMED BRASS - MCGUIRE. SANITARY DASH, BRIDGEPORT. SHOWER MIXING VALVES - POWERS, LEONARD, LAWLOR. SYMMONS, SPEAKMAN, ZURN. SHOWER HEADS - SYMMONS, SPEAKMAN, ZURN. ELECTRIC WATER COOLERS - ELKAY, HALSEY TAYLOR, SUNROC, OASIS, HAWS. USE ONLY WATER COOLERS WHICH DO NOT USE CFC'S FOR REFRIGERATION. SCRUB SINKS - ELJER, AMERICAN STANDARD, KOHLER, CRANE CARRIERS - J. R. SMITH, JOSAM, ZURN, WADE. EMERGENCY EQUIPMENT - GUARDIAN, HAWS, WESTERN, SPEAKMAN.
- M. INSTALL PLUMBING FIXTURE LEVEL AND PLUMB, IN ACCORDANCE WITH FIXTURE MANUFACTURER'S PUBLISHED LITERATURE, ROUGH-IN DRAWINGS, CODES REGULATIONS, AND REFERENCE STANDARDS. FASTEN PLUMBING FIXTURES SECURELY TO SUPPORTS OR BUILDING STRUCTURE. RIGIDLY SUPPORT WATER SUPPLIES BEHIND OR WITHIN WALL CONSTRUCTION. PROVIDE STOP VALVE IN THE WATER SUPPLY TO EACH FIXTURE IN AN ACCESSIBLE LOCATION. CONNECT WALL HUNG URINALS TO WASTE PIPING WITH RED BRASS NIPPLES. CONNECT FIXTURES TO WATER SUPPLY WITH COPPER OR BRASS (NO STEEL). EACH FIXTURE, FLOOR DRAIN AND PIECE OF EQUIPMENT REQUIRING CONNECTION TO DRAINAGE SYSTEM TO HAVE SEPARATE TRAPS INSTALLED AS CLOSE TO FIXTURE AS POSSIBLE. PROVIDE IRON OR STEEL BACKING FOR ALL WALL MOUNTED FIXTURES (OR WOOD BACKING ONLY IF BUILDING STRUCTURE IS WOOD). PROVIDE ESCUTCHEONS AT EACH WALL, FLOOR AND CEILING PENETRATION IN EXPOSED FINISHED LOCATIONS AND WITHIN CABINETS AND MILLWORK. APPLY SCP3154 PRIMER AND GENERAL ELECTRIC CO.'S NO. 1702 SILICONE SANITARY SEALANT AROUND PLUMBING FIXTURES TO CONCEAL VOIDS AT WALL AND CONTACT POINTS OF FIXTURE AFTER WALLS HAVE BEEN PAINTED. APPLY SCP3154 PRIMER AND GENERAL ELECTRIC CO.'S SILPRUF SEALANT ON PLAIN CONCRETE WALLS.



Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



11/8/24

Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date



© 2024 Aho Architects, LLC.
All Rights Reserved.

Plumbing Specifications

Project number	24028
Date	11/08/2024
Drawn by	CRA
Checked by	JAB

P0.03

Scale 12" = 1'-0"



Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

[illegible]



© 2024 Aho Architects, LLC.
All Rights Reserved.

Plumbing Floorplans

Project number	24028
Date	11/08/2024
Drawn by	CRA
Checked by	JAB

P1.01

Scale	As indicated
-------	--------------



Plumbing Floor Plan - Pressure
1/4" = 1'-0"

GENERAL NOTES:


- ① CONTRACTOR SHALL VERIFY EXISTING CONDITIONS IN FIELD PRIOR TO BEGINNING WORK.
- ② SPACE ABOVE CEILING IS LIMITED. CAREFUL COORDINATION WITH LIGHTING, ELECTRICAL, MECHANICAL, FIRE PROTECTION, STRUCTURAL AND ARCHITECTURAL WORK IS CRITICAL FOR COMPLETE PIPING INSTALLATION. CONTRACTOR SHALL PROVIDE NECESSARY OFFSETS IN NEW AND EXISTING PIPING AND ELECTRICAL CONDUIT AS REQUIRED TO ACCOMMODATE NEW WORK. CONTRACTOR SHALL ALLOW FOR ANY CONFLICTS ENCOUNTERED.
- ③ PIPING LAYOUTS ARE DIAGRAMMATIC AND DO NOT SHOW ALL ELEMENTS OF CONSTRUCTION. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CHANGES ON DIRECTION, ELEVATION AND MINOR OFFSETS NECESSARY FOR COMPLETE INSTALLATION OF ELEMENTS SHOWN.
- ④ ALL PRESSURE PIPING SHOWN IS ABOVE THE CEILING UNLESS OTHERWISE NOTED. ALL TRAP PRIMER LINES AND HOT WATER RETURN LINES SHALL BE 1/2" UNLESS OTHERWISE NOTED.
- ⑤ PRESSURE REGULATORS FOR GAS PIPING SHALL BE EQUAL TO MAXITROL 325 SERIES.
- ⑥ EXPOSED DOMESTIC WATER PIPING SHALL BE TYPE K COPPER. PIPING WITHIN WALLS AND CEILINGS SHALL BE PERMITTED TO BE PEX.





Plumbing Floor Plan - Gravity
1/4" = 1'-0"

GENERAL NOTES:

- ① CONTRACTOR SHALL VERIFY EXISTING CONDITIONS IN FIELD PRIOR TO BEGINNING WORK.
- ② PIPING LAYOUTS ARE DIAGRAMMATIC AND DO NOT SHOW ALL ELEMENTS OF CONSTRUCTION. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CHANGES ON DIRECTION, ELEVATION AND MINOR OFFSETS NECESSARY FOR COMPLETE INSTALLATION OF ELEMENTS SHOWN.
- ③ ALL WASTE PIPING SHOWN IS BELOW FINISHED FLOOR UNLESS OTHERWISE NOTED. ALL VENT PIPING SHOWN IS ABOVE CEILING UNLESS OTHERWISE NOTED.
- ④ REFER TO ARCHITECTURAL REFLECTED CEILING PLANS FOR LOCATIONS OF ALL CEILING MOUNTED DEVICES. REFER TO ARCHITECTURAL FLOOR PLANS FOR ALL DIMENSIONS.
- ⑤ COORDINATE ACCESS DOOR LOCATIONS WITH GENERAL CONTRACTOR AND ARCHITECT.






Northport, Alabama

[illegible]

Plumbing Risers

Scale






Engineering & Design Consultants
2111 Parkway Office Circle, Suite 125
Birmingham, AL 35244
(205) 733-6912 FAX: (205) 733-6913
Job No. 24262



www.ahoarch.com



11/8/24

Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date


© 2024 Aho Architects, LLC.
All Rights Reserved.

Plumbing Details


Project number	24028
Date	11/08/2024
Drawn by	CRA
Checked by	JAB

P3.01


Scale As indicated




6 DOMESTIC WATER ENTRANCE DETAIL
P3.01 NO SCALE




4 TYPICAL LAVATORY MIXING VALVE
P3.01 SCALE: NONE




1 TYPICAL GAS CONNECTION
P3.01 NO SCALE



2 WATER HEATER MOUNTING DETAIL
P3.01 NO SCALE




5 WALL CLEANOUT
P3.01 NO SCALE



7 OIL INTERCEPTOR DETAIL
P3.01 NO SCALE

NOTE:
USE A REGULATOR WHEN GAS
SUPPLY PRESSURE EXCEEDS
14" W.C.P. DO NOT EXCEED 14
W.C.P. TO THE APPLIANCE.



3 RADIANT HEATER GAS CONNECTION DETAIL
P3.01 NO SCALE

LIGHTING FIXTURE SCHEDULE

TYPE	MANUFACTURER	CATALOG NUMBER	LAMPS			MTG. TYPE	MTG. HT.	REC. DEPTH	DESCRIPTION
			QUANTITY	WATTS	TYPE				
L1	MAXLITE	(2)VT-4850U-40, VT-CONKIT, VT-ENDBRKT	18	100	LED	P	15'5" AFF	-	CONTINUOUS RUN OF (2) 4' LONG LINEAR LED FIXTURES WITH ALUMINUM VAPOR TIGHT HOUSING, 7600 LUMEN OUTPUT, 4000K COLOR TEMPERATURE. PROVIDE ALL REQUIRED ACCESSORIES FOR SUSPENDED MOUNTING. NOTE 1
	APPROVED EQUAL								
L3E	MAXLITE	LSU4U23WCSCREM	1	35	LED	S	C	-	4' SURFACE MOUNTED LED WRAPAROUND FIXTURE WITH CURVED PRISMATIC LENS, STEEL HOUSING, 4000K COLOR TEMPERATURE, 4253 LUMEN OUTPUT, AND EMERGENCY BATTERY PACK.
	APPROVED EQUAL								
L4	MAXLITE	M40U4W-CSBWRC MVCL40-55W	3	28	LED	W	12' AFF	-	FIXED WALL MOUNTED TRAPEZOIDAL LED FIXTURE WITH BLACK FINISH, DIE-CAST ALUMINUM HOUSING, 4000K SELECTABLE COLOR TEMPERATURE, 3512 LUMEN OUTPUT, WIDE DISTRIBUTION. UL LISTED FOR WET LOCATION. NOTE 4.
	APPROVED EQUAL								
L4E	MAXLITE	M40U4W-CSBWCREO MVCL40-55W	3	28	LED	W	12' AFF	-	FIXED WALL MOUNTED TRAPEZOIDAL LED FIXTURE WITH BLACK FINISH, DIE-CAST ALUMINUM HOUSING, 4000K SELECTABLE COLOR TEMPERATURE, 3512 LUMEN OUTPUT, WIDE DISTRIBUTION, ELECTRONIC DRIVER, AND EMERGENCY BATTERY PACK. UL LISTED FOR WET LOCATION. NOTE 4.
	APPROVED EQUAL								
BL	LITHONIA	ELM6L	FURNISHED WITH UNIT			W	9' AFF	-	SURFACE MOUNTED TWO HEAD LED EMERGENCY FIXTURE WITH WHITE THERMOPLASTIC HOUSING, SELF DIAGNOSTICS, AND EMERGENCY BATTERY PACK.
	APPROVED EQUAL								
XL	MAXLITE	EX-GW	FURNISHED WITH UNIT			W	AD	-	WHITE THERMOPLASTIC LED EXIT SIGN WITH SINGLE FACE, GREEN LETTERS, UNIVERSAL MOUNTING, SELF DIAGNOSTICS, AND EMERGENCY BATTERY PACK.
	APPROVED EQUAL								

ABBREVIATIONS: LI-LAY-IN C-CEILING LG-LENS GASKETING GMF-INTERNAL SLOW BLOW FUSE FL-FLUORESCENT MH-METAL HALIDE HO-HIGH OUTPUT
AFF-ABOVE FINISH FLOOR P-PENDENT FC-FROM CEILING R-RECESSED AM-ABOVE MIRROR W-WALL AD-ABOVE DOOR
S-SURFACE DTT-DOUBLE TWIN TUBE FLUORESCENT CA-CANOPY TC-TOP OF METAL CANOPY AW-ABOVE WINDOW VA-VERIFY WITH ARCHITECT

LIGHTING FIXTURE SCHEDULE GENERAL NOTES:

- FIXTURE OUTLET BOX LOCATIONS SHOWN ON THE DRAWINGS ARE DIAGRAMMATIC AND APPROXIMATE IN LOCATION. EXACT POSITION OF THE OUTLET BOX SHALL DEPEND ON THE FIXTURE AND THE MOUNTING DETAIL.
- MOUNTING AND SUPPORT DETAILS FOR LIGHTING FIXTURES SHALL BE SUBMITTED TO AND APPROVED BY THE ENGINEER BEFORE THE FIXTURES ARE INSTALLED. NO COMBUSTIBLE MATERIALS SHALL BE USED.
- WET LOCATION FIXTURES SHALL BE MOUNTED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATION SO AS TO ENSURE THE PREVENTION OF MOISTURE FROM ENTERING THE FIXTURE. IN ADDITION, EACH CONDUIT ENTRY WILL BE SEALED BY USE OF AN APPROVED SWEDGE FITTING WITH A NEOPRENE SEAL, AS MANUFACTURED BY JOHN REMKE COMPANY OR APPROVED EQUAL.
- OUTLET BOXES SERVING WET LOCATION FIXTURE SHALL BE CODE SIZE, WITH A WATERTIGHT SOLID CAST TOP. CONDUIT ENTRIES SHALL BE THREADED.
- FIXTURE MOUNTING HEIGHTS IN SCHEDULE ARE TYPICAL UNLESS NOTED OTHERWISE ON DRAWINGS.
- FOR LIGHTING PACKAGE PRICING, CONTACT THE FOLLOWING:

MIKE MCMAKEN
REXEL ENERGY SOLUTIONS
(M) 906-235-2979
MIKE.MCMAKEN@REXELENERGY.COM


STEPHEN MITCHELL
MAXLITE
(M) 908-256-3115
SMITCHELL@MAXLITE.COM

LIGHTING FIXTURE SCHEDULE NOTES:

- SEE MOUNTING DETAIL ON THIS SHEET FOR MORE INFORMATION.
- INSTALLED BY SIGN COMPANY.
- VERIFY MOUNTING HEIGHT WITH SIGN COMPANY BEFORE ROUGHING IN.
- FIXTURE SHALL BE MOUNTED SO THAT THE TOP OF THE FIXTURE IS AT 12' AFF TO ALIGN WITH BANDING ON EXTERIOR OF BUILDING.

GENERAL NOTES:


- VERIFY ALL DOOR SWINGS WITH ARCHITECTURAL BEFORE ROUGHING IN LIGHT SWITCHES TO ENSURE PROPER SWITCH LOCATION. VERIFY ALL CASEWORK DETAILS TO ENSURE THAT ALL OUTLETS ABOVE CASEWORK ARE AT THE PROPER HEIGHT.
- SERVICE TO THE BUILDING SHALL BE 120/240 VOLTS, 1PHASE, 3WIRE.
- ALL CONDUIT SHALL BE RUN CONCEALED UNLESS SPECIFICALLY SHOWN EXPOSED, OR INSTALLED IN EXPOSED CEILING.
- THE CONTRACTOR SHALL CHECK ALL LIGHTING FIXTURES FOR EXACT TYPE MOUNTING AND SPACE REQUIRED BEFORE ROUGHING IN.
- THE CONTRACTOR SHALL WORK CLOSELY WITH THE GENERAL CONTRACTOR AND VERIFY EXACT TYPE OF EQUIPMENT TO BE INSTALLED AND THE DIMENSIONS WHICH MAY AFFECT THE EXACT PLACEMENT OF ELECTRICAL WORK.
- VERIFY THE EXACT LOCATION OF ALL MOTORS AND EQUIPMENT BEFORE ROUGHING IN. LIKEWISE APPRAISE ALL TRADES OF THE LOCATIONS OF ELECTRICAL WORK THAT AFFECTS WALL THICKNESS, PLUMBING, MECHANICAL, ETC.
- ALL CONDUIT STUBBED OUT FOR FUTURE SHALL BE CAPPED AND HAVE LOCATION MARKED WITH A 2" SQUARE, PAINTED RED, WITH CONDUIT NAME AND SIZE SHOWN IN WHITE.
- ALL BRANCH CIRCUITS AND FEEDERS SHALL HAVE AN INSULATED GROUND WIRE PULLED IN THE CONDUIT WITH CURRENT CONDUCTOR UNLESS SPECIFICALLY NOTED OTHERWISE ON THE PLANS. THE GROUNDING CONDUCTOR SHALL BE SIZED ACCORDING TO TABLE 250-122 OF THE LATEST EDITION OF THE NATIONAL ELECTRICAL CODE UNLESS INDICATED TO BE LARGER IN THE SPECIFICATIONS OR PLANS.
- DO ALL WORK IN COMPLIANCE WITH ALL APPLICABLE CODES, LAWS AND ORDINANCES, THE NATIONAL ELECTRICAL CODE (HEREINAFTER REFERRED TO AS "CODE" OR "NEC"), THE AMERICANS WITH DISABILITIES ACT, AND THE REGULATIONS OF THE LOCAL AUTHORITIES HAVING JURISDICTION AND, WHERE APPLICABLE, UTILITY COMPANIES. OBTAIN AND PAY FOR ANY AND ALL REQUIRED PERMITS, INSPECTIONS, CERTIFICATES OF INSPECTIONS AND APPROVAL, AND THE LIKE, AND DELIVER SUCH CERTIFICATES TO THE OWNER.
- THE MAIN SERVICE SHALL HAVE THE GROUNDED CONDUCTOR (NEUTRAL) GROUNDED TO THE GROUNDING ELECTRODE SYSTEM AT THE SUPPLY SIDE OF THE SERVICE DISCONNECTING MEANS BY A GROUNDING ELECTRODE CONDUCTOR NOT SMALLER THAN THAT SHOWN IN TABLE 250-66 OF THE NEC. THE GROUNDED CONDUCTOR (NEUTRAL), THE GROUNDING ELECTRODE CONDUCTOR, AND THE EQUIPMENT GROUNDING CONDUCTOR CONNECTIONS SHALL BE MADE INSIDE THE SERVICE ENTRANCE EQUIPMENT.
- ALL CONDUCTORS SHALL BE COPPER, EXCEPT AS SHOWN ON DRAWINGS.
- MINIMUM CONDUCTOR SIZE SHALL BE #12.
- ALL CONDUIT INSTALLED INDOORS SHALL BE EMT, OTHERWISE SHALL BE IMC.
- SWITCH AND RECEPTACLE COVER PLATES SHALL BE STAINLESS STEEL.
- ALL DEVICES SHALL BE GRAY.
- ALL FUSES SHALL BE DUAL ELEMENT, TIME DELAY, RATED 100,000 AIC.
- ALL DISCONNECT SWITCHES SHALL BE HEAVY DUTY TYPE.
- ALL CONDUCTORS SHALL BE DUAL RATED THHN/THWN TYPE INSULATION.
- GUTTERS (WIREWAYS) SHALL BE SIZED AS SHOWN OR AS REQUIRED BY CODE. ALL GUTTERS SHALL HAVE HINGED COVERS WITH APPROVED FASTENING DEVICES & SHALL BE A STANDARD MANUFACTURED ITEM WITH U.L. LABEL. GUTTERS FROM AC DUCT MATERIAL ARE NOT ACCEPTABLE. GUTTERS SHALL BE AS MANUFACTURED BY HOFFMAN, SQUARE "D", B & C OR APPROVED EQUAL. GUTTER TAPS SHALL BE ILSCO TYPE GTA OF PTA WITH GTC OR PTC INSULATING COVERS.
- IT SHALL BE THE RESPONSIBILITY OF THIS CONTRACTOR, PRIOR TO BID, TO REAFFIRM WITH THE UTILITY COMPANIES INVOLVED, THAT THE LOCATION, ARRANGEMENT (AND THE POWER COMPANY: VOLTAGE, PHASE & METERING REQUIRED) AND CONNECTIONS AT THE UTILITY SERVICE ARE IN ACCORDANCE WITH THEIR REGULATIONS & REQUIREMENTS. IF THEIR REQUIREMENTS ARE AT A VARIANCE WITH THESE DRAWINGS & SPECIFICATIONS, THE CONTRACT PRICE SHALL INCLUDE ANY ADDITIONAL COST NECESSARY TO MEET THOSE REQUIREMENTS WITHOUT EXTRA COST TO THE OWNER AFTER A CONTRACT HAS BEEN ENTERED INTO.
- ON MANY PROJECTS, THE UTILITY COMPANY MAY LEVY CHARGES DUE TO LOCATION, SIZE OR TYPE OF SERVICE INVOLVED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THESE CHARGES, UNLESS SUCH CHARGES ARE NOT AVAILABLE PRIOR TO BID & CONTRACTOR SO DOCUMENTS AT BID OPENING. SHOULD THE THE COST NOT BE AVAILABLE, PRIOR TO BID, THE CONTRACTOR SHALL SUBMIT A LETTER SO STATING WITH HIS BID.
- ARRANGE WITH UTILITY COMPANIES FOR SUCH SERVICE AS SHOWN OR HEREIN SPECIFIED & INSTALLATION OF METER WHERE SHOWN. FURNISH WITH SHOP DRAWINGS, A SIGNED DOCUMENT FROM UTILITY COMPANIES DESCRIBING THE LOCATION & TYPE OF SERVICES TO BE FURNISHED AND ANY REQUIREMENTS THEY MAY HAVE. THIS DOCUMENT SHALL BE SIGNED FOR EACH UTILITY COMPANY BY A PERSON RESPONSIBLE FOR GRANTING SUCH SERVICES.
- PAY ALL CHARGES (IF ANY) IN CONNECTION THEREWITH, INCLUDING PERMANENT METER DEPOSIT. METER DEPOSIT WILL BE REFUNDED TO THE CONTRACTOR AT TIME OF OWNER'S ACCEPTANCE.



DETAIL
FIXTURE "L1" MOUNTING
NOT TO SCALE

GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THWGNBOTHAM@GW-ENG.COM | 205.317.3969



Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

General Notes &
Fixture Schedules

Project number	24028
Date	11/08/2024
Drawn by	TH
Checked by	GW
E100	
Scale	NO SCALE

GRAPHICAL ELECTRICAL SYMBOLS

BRANCH CIRCUIT SYMBOLS		
	BRANCH CIRCUIT	HOMERUN TO 20A, 1POLE CIRCUIT BREAKER IN PANELBOARD OR DEVICE NOTED. WIRE SIZE IS 2#12&1#12GRD-3/4"C.
	BRANCH CIRCUIT	CONCEALED IN CEILING OR WALL.
	BRANCH CIRCUIT	CONCEALED IN FLOOR.
	BRANCH CIRCUIT	EXISTING CONDUIT BARS DENOTE NEW CONDUCTORS.
	BRANCH CIRCUIT	EXPOSED.
	BRANCH CIRCUIT	RISER UP.
	BRANCH CIRCUIT	RISER DOWN.
BRANCH CIRCUIT NOTES		
	BRANCH CIRCUIT	3#12&1#12GRD-3/4"C
	BRANCH CIRCUIT	4#12&1#12GRD-3/4"C
	BRANCH CIRCUIT	2#10&1#10GRD-3/4"C
	BRANCH CIRCUIT	3#10&1#10GRD-3/4"C
SIZE CONDUIT PER NEC FOR GREATER NUMBER OF CONDUCTORS OR AS NOTED. THE NUMBER IN THE CIRCUIT INDICATES AWG WIRE SIZE AND THE HASHMARKS INDICATE THE NUMBER OF WIRES REQUIRED. EQUIPMENT GROUND CONDUCTOR SHALL BE SIZED IN ACCORDANCE WITH NEC TABLE 250-122. THE NUMBER OF HASH MARKS DO NOT INCLUDE EQUIPMENT GROUNDING CONDUCTOR.		

GENERAL SYMBOLS	
	JUNCTION BOX.
	WALL MOUNTED JUNCTION BOX.
	WALL MOUNTED JUNCTION BOX WITH FLEXIBLE CONNECTION TO EQUIPMENT.
	TWO GANG BOX WITH 3/4"C. STUB UP ABOVE ACCESSIBLE CEILING WITH COAXIAL CABLE AND TV JACKS. HOMERUN COAXIAL CABLE TO TBB.
	MANUAL MOTOR STARTER WITH THERMAL PROTECTION.
	SAFETY SWITCH, NON-FUSED.
	SAFETY SWITCH, FUSED.
	CIRCUIT BREAKER MOUNTED IN NEMA 1 ENCLOSURE UNLESS NOTED OTHERWISE
	LIGHTING PANEL AND/OR RECEPTACLE PANEL.
	POWER PANEL.
	TRANSFORMER.
	GROUND.

GENERAL ABBREVIATIONS	
H	MOUNTING HEIGHT ABOVE FINISHED FLOOR.
AF	ABOVE FINISHED FLOOR.
WP	WEATHER PROOF - NEMA 3R
RT	RAIN TIGHT - NEMA 4.
EP	EXPLOSION PROOF.
TP	TAMPER PROOF.
A	MOUNT ABOVE COUNTER.
BC	MOUNT BELOW COUNTER.
F	FLUSH MOUNTED.
SLD	SEE SINGLE LINE DIAGRAM.
GFI	GROUND FAULT INTERRUPTING.
C	CONDUIT.
EC	EMPTY CONDUIT.
CC	FLEXIBLE CONDUIT.
SFC	SEALTITE FLEXIBLE CONDUIT.
EMT	ELECTRICAL METALLIC TUBING.
IMC	INTERMEDIATE METALLIC CONDUIT.
RG	RIGID CONDUIT.
PVC	NONMETALLIC RIGID CONDUIT.
EX	EXISTING.
XR	EXISTING TO BE REMOVED
RL	EXISTING TO BE REMOVED AND RELOCATED.
RQ	EXISTING TO BE REMOVED. EXTEND CIRCUIT CONDUCTORS AS REQUIRED AND INSTALL FINISHED BLANK COVER.
RR	EXISTING TO BE REMOVED AND REPLACED WITH NEW.
RL'D	RELOCATED POSITION.
EM	EMERGENCY BATTERY PACK

LIGHTING FIXTURE & CONTROL SYMBOLS		
	CEILING OUTLET	FIXTURE TYPE "A" CIRCUIT #1.
	CEILING OUTLET	EXISTING.
	CEILING OUTLET	FLUORESCENT FIXTURE, SINGLE OR CONTINUOUS, LENGTHS AS SHOWN.
	CEILING OUTLET	FLUORESCENT STRIP.
	WALL OUTLET	BRACKET TYPE FIXTURE.
	WALL OUTLET	FLUORESCENT BRACKET TYPE FIXTURE.
	WALL OUTLET	A.C. TYPE, SINGLE POLE, 20A, 125/277V.
	WALL OUTLET	A.C. TYPE, THREE WAY, 20A, 125/277V.
	WALL OUTLET	A.C. TYPE, FOUR WAY, 20A, 125/277V.
	WALL OUTLET	180° DUAL TECH SENSOR LIGHTING MOTION DETECTOR, WALL MOUNTED. WATT STOPPER #DW-100.
	CEILING OUTLET	LIGHTING MOTION DETECTOR POWER PACK. INSTALL ABOVE ACCESSIBLE CEILING.
	SWITCH OUTLET	0-10V DIMMER UNLESS OTHERWISE NOTED.
SWITCH OUTLET NOTES		
"a" "b" ETC.	FIXTURE CORRESPONDS TO A SWITCH DENOTED WITH THE SAME LOWER CASE LETTER.	


EXIT LIGHT SYMBOLS	
	WALL OR CEILING MOUNTED, SINGLE FACE, NO ARROW.
	CEILING MOUNTED, DOUBLE FACE, LEFT OR RIGHT ARROWS.
	WALL OR CEILING MOUNTED, SINGLE FACE, LEFT OR RIGHT ARROW.
	WALL OR CEILING MOUNTED, SINGLE FACE, LEFT AND RIGHT ARROWS.
	CEILING MOUNTED, DOUBLE FACE, LEFT AND RIGHT ARROWS.

RECEPTACLE OUTLET SYMBOLS		
	WALL OUTLET	DUPLEX RECEPTACLE, 20A, 125V, 3WIRE, NEMA 5-20R.
	WALL OUTLET	DOUBLE DUPLEX RECEPTACLE, 20A, 125V, 3WIRE, NEMA 5-20R, SINGLE PLATE.
	WALL OUTLET	DUPLEX RECEPTACLE, 20A, 125V, NEMA 5-20R, GFCI, WEATHER-RESISTANT, WITH EXTRA DUTY IN-USE WEATHERPROOF COVER.
	WALL OUTLET	SINGLE RECEPTACLE, 20A, 250V, 3WIRE, NEMA 6-20R.
	WALL OUTLET	SINGLE RECEPTACLE, 20A, 250V, 3WIRE, NEMA L6-20R.
	FLOOR OUTLET	FLUSH MOUNTED IN-GRADE WITH DOUBLE DUPLEX RECEPTACLE, 20A, 125V, 3WIRE, NEMA 5-20R, FOUR SPACES FOR KEYSTONE CONNECTORS, AND BRUSHED BRASS COVER.
	CEILING OUTLET	DUPLEX RECEPTACLE, 20A, 125V, 3WIRE, NEMA 5-20R.
RECEPTACLE OUTLET NOTES		
"G"	GROUND FAULT INTERRUPTER.	
"GA"	GROUND FAULT INTERRUPTER, MOUNTED ABOVE COUNTER.	
"A"	MOUNTED ABOVE COUNTER.	
"BC"	MOUNTED BELOW COUNTER.	
"Df"	FOR DRINKING FOUNTAIN.	

VOICE/DATA OUTLET & CONDUIT SYMBOLS		
	VOICE/DATA OUTLET	WALL MOUNTED, WITH 3/4" CONDUIT HOMERUN TO NEAREST TELEPHONE CABINET OR BACKBOARD UNLESS NOTED OTHERWISE.
	VOICE/DATA OUTLET	TELEPHONE BACKBOARD - 3/4" PLYWOOD PAINTED WITH TWO COATS OF FIRE RETARDANT PAINT, 48"x96" HIGH, UNLESS SHOWN OTHERWISE.
VOICE/DATA OUTLET NOTES		
"A"	MOUNTED ABOVE COUNTER.	
"BC"	MOUNTED BELOW COUNTER.	

NOTES:

1. INDICATED MOUNTING HEIGHTS ARE FROM FINISHED FLOOR TO CENTERLINE OF OUTLET BOX, UNLESS OTHERWISE NOTED.
2. REFER TO ARCHITECTURAL DETAILS FOR ADDITIONAL REQUIREMENTS.
3. INSTALL OUTLETS THAT ARE IN CLOSE PROXIMITY ON THE SAME CENTERLINE.
4. MOUNTING HEIGHTS SHOWN HERE ARE TYPICAL UNLESS NOTED OTHERWISE ON DRAWINGS.



DETAIL
TYPICAL MOUNTING
HEIGHTS
NOT TO SCALE



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.


Symbol Legends
and Details

Project number	24028
Date	11/08/2024
Drawn by	TH
Checked by	GW
E101	
Scale	NO SCALE

GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
TH@GNBOTHAM@GW-ENG.COM | 205.317.3869

1. 48"x48" FREE STANDING TELEPHONE BACKBOARD. PROVIDE ACCESS AS REQUIRED BY CLEAR COM.
2. CONDUIT ELBOWS SHALL BE SWEEPING WITH NO HARD ANGLES.





1. COORDINATE SECONDARY SERVICE REQUIREMENTS WITH POWER COMPANY BEFORE BID. PROVIDE PER POWER COMPANY REQUIREMENTS.
2. EQUIPMENT WITH ALUMINUM FEEDERS SHALL BE PROVIDED WITH DUAL RATED TERMINALS.

NOTES:


1. SERVICE ENTRANCE RATED DISCONNECT SWITCH, NEMA 3R ENCLOSURE.
2. COORDINATE METERING WITH POWER COMPANY BEFORE ROUGHING IN.
3. SERVICE DISCONNECTS SHALL BE MOUNTED SUCH THAT CENTER OF OPERATING HANDLE SHALL NOT BE LESS THAN 4' AND NOT MORE THAN 6'-7" ABOVE GRADE.
4. PROVIDE ENGRAVED LABEL INDICATING MAXIMUM AVAILABLE FAULT CURRENT AND DATE OF CALCULATION. SEE DETAIL ON SHEET OC-E103.

5. PROVIDE LABEL INDICATING LOCATION OF SERVICE DISCONNECT "FED FROM SERVICE DISCONNECT # 1, LOCATED AT EXTERIOR OF OIL CHANGE BUILDING."
6. PROVIDE LABEL INDICATING LOCATION OF SERVICE DISCONNECT "FED FROM SERVICE DISCONNECT #2, LOCATED AT EXTERIOR OF OIL CHANGE BUILDING."
7. PROVIDE LABEL "SERVICE DISCONNECT SWITCH #1 FOR OIL CHANGE BUILDING."
8. PROVIDE LABEL "SERVICE DISCONNECT SWITCH #2 FOR SERVICE BUILDING."
9. GROUND TO EQUIPMENT GROUND BUS BAR ONLY. DO NOT GROUND NEUTRAL.



VOLTS	120/ 240	V 1 Phase, 3 Wire & Grd Bus Bar
-------	----------	---------------------------------

VOLTS	120/ 240	V 1 Phase, 3 Wire & Grd Bus Bar
-------	----------	---------------------------------



NOTES:

1. CONTRACTOR SHALL COORDINATE REQUIREMENTS SHOWN HERE WITH OWNER BEFORE ROUGHING IN. PROVIDE ELECTRICAL PER OWNER EQUIPMENT VENDOR REQUIREMENTS.

ALABAMA
LICENSED
No. 38353
PROFESSIONAL
ENGINEER
GIDEON M. WANNE
11/8/24

Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

[illegible]

Single Line Diagram & Panelboard Schedules

Drawn by	TH
Checked by	GW

E102

Scale	NO SCALE
-------	----------

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
 GWAMAE@GW-ENG.COM | 205.413.4112
 THIGGINBOTHAM@GW-ENG.COM | 205.317.3969



GROUNDING SYSTEM DETAIL

NOT TO SCALE


GROUNDING SYSTEM DETAIL – KEY NOTES

- ① BARE GROUNDING ELECTRODE CONDUCTOR, SEE SLD.
- ② 3/4"x10'-0" CLAD STEEL GROUND ROD, DRIVEN 24" BELOW GRADE, MINIMUM.
- ③ BARE GROUNDING ELECTRODE CONDUCTOR IN 2"PVC-40, SEE SLD.
- ④ EXOTHERMIC WELD CONNECTOR:
TWO CABLES TO GROUND ROD, CADWELD #GT OR #GY
CABLE TO CABLE TEE, CADWELD #TA
ONE CABLE TO GROUND ROD, CADWELD #GR
- ⑤ CAST BRONZE, UL LISTED GROUND CLAMP, 0-Z/GEDNEY TYPE-G.
- ⑥ BONDING JUMPER, SIZED BY EQUIPMENT MANUFACTURER PER NEC 250-66.
- ⑦ BONDING JUMPER TO GROUNDING BUSHING. AND BONDING JUMPERS FROM CONDUIT TO CONDUIT. ALL CONDUIT CONNECTED TO THE SERVICE ENTRANCE ENCLOSURE SHALL BE BONDED, SIZED PER NEC 250.
- ⑧ MAIN BONDING JUMPER, SIZED BY MANUFACTURER PER 250-66.
- ⑨ BONDING JUMPER.
- ⑩ 6 CONDUCTOR GROUND BUS, COPPER OR ALUMINUM RATED, ILSCO #PDE.


ELEVATION
LIFT POWER DETAIL
NOT TO SCALE




DETAIL
WIRING DESIGNATION
NOT TO SCALE




DETAIL
120/240V PANELBOARD INSTALLATION
& NAMEPLATE DETAIL
NOT TO SCALE




DETAIL
120/240V PANELBOARD
ELECTRICAL NAMEPLATE
NOT TO SCALE




DETAIL
ELECTRICAL NAMEPLATE
NOT TO SCALE



DETAIL
RECEPTACLE INSTALLATION
NOT TO SCALE



DETAIL
AVAILABLE FAULT CURRENT NAMEPLATE
NOT TO SCALE



LIFT LIMIT SWITCH
WIRING DETAIL
NOT TO SCALE



Express Oil Change & Tire Engineers

FINAL

[illegible]

© 2024 Aho Architects, LLC.
All Rights Reserved.

Details

Project number	24028
Date	11/08/2024
Drawn by	TH
Checked by	GW

E103

Scale	NO SCALE
-------	----------

GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THIGGINBOTHAM@GW-ENG.COM | 205.317.3969



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL


No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Site Plan - Electrical

Project number	24028
Date	11/08/2024
Drawn by	TH
Checked by	GW
E104	
Scale	1" = 20'-0"

GW ENGINEERING, LLC
4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
TNGCNBOTHAM@GW-ENG.COM | 205.317.3869



- NOTES:
1. VERIFY EXACT LOCATION OF STUB UP BEFORE ROUGH IN.
 2. HOMERUN TO PANELBOARD PP THROUGH LIGHTING CONTACTOR C-2.
 3. LOCATION OF MONUMENT SIGN SHOWN HERE IS FOR REFERENCE ONLY. VERIFY EXACT LOCATION OF MONUMENT SIGN WITH CIVIL PRIOR TO ROUGH IN.
 4. PROVIDE 1-1" EMPTY CONDUIT. HOMERUN TO PANEL PP FOR FUTURE EV CHARGING STATION. VERIFY EXACT LOCATION OF STUB UP WITH ARCHITECT AND CIVIL PRIOR TO INSTALLATION.

① Site Plan - Electrical
1" = 20'-0"

GENERAL NOTES:


- CONNECT ALL "BL", "XL" AND EMERGENCY BATTERY PACKS IN FIXTURES MARKED "EM" TO UNSWITCHED HOT LEG OF CIRCUIT.
- ENSURE L1 LIGHT FIXTURES DO NOT CONFLICT WITH OVERHEAD DOORS.
- FOR THE LIGHTING PACKAGE PRICING CONTACT THE FOLLOWING:

MIKE MCMAKEN
REXEL ENERGY SOLUTIONS
(M) 906-256-2979
MIKE.MCMAKEN@REXELENERGY.COM

STEPHEN MITCHELL
MAXLITE
(M) 908-256-3115
SMITCHELL@MAXLITE.COM
- ALL CONDUIT CROSSING OVERHEAD DOORS SHALL BE MOUNTED AS TIGHT TO THE STRUCTURE AS POSSIBLE TO AVOID CONFLICT WITH THE OVERHEAD DOOR TRACK.
- FOR LIGHTING, QUICK CONNECT CABLES SHALL NOT BE INSTALLED ABOVE CEILING. SURFACE MOUNT QUICK CONNECT CABLES BELOW CEILING.
- SERVICE BUILDING IS A MINOR REPAIR GARAGE AND IS UNCLASSIFIED. SEE MECHANICAL DRAWINGS FOR PROVIDED VENTILATION.

NOTES:

- HOMERUN TO CIRCUIT BREAKER IN PANELBOARD PP THROUGH LIGHTING CONTACTOR SV-1. SEE DETAIL ON SHEET E102.
- JUNCTION BOX FOR SIGN COMPANY PROVIDED FIXTURE SHALL BE MOUNTED 14'AFF. COORDINATE EXACT LOCATION WITH SIGN LIGHTING INSTALLER BEFORE ROUGHING IN.



1 Ground Floor Plan - Lighting
1/4" = 1'-0"



GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THGGINBOTHAM@GW-ENG.COM | 205.317.3969



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Floor Plan -
Lighting

Project number	24028
Date	11/08/2024
Drawn by	TH
Checked by	GW

E200

Scale 1/4" = 1'-0"

11/8/2024 4:38:12 PM

GENERAL NOTES:

1. CONTRACTOR SHALL VERIFY/COORDINATE LOCATION OF ALL POWER & DATA OUTLETS FOR EQUIPMENT. OBTAIN OWNER'S APPROVAL BEFORE ROUGH IN. NO EXCEPTIONS. NO ADDITIONAL COMPENSATION SHALL BE AWARDED FOR ANY ADDITIONAL WORK REQUIRED TO RELOCATE OUTLETS DUE TO CONTRACTOR'S FAILURE TO COORDINATE WITH OWNER.
2. ALL HORIZONTAL CONDUIT RUNS SHALL BE A MINIMUM OF 8" ABOVE FINISHED FLOOR EXCEPT FOR DROPS. ENSURE CONDUIT DOES NOT CONFLICT WITH OVERHEAD DOOR TRACK.
3. ALL CONDUIT CROSSING OVERHEAD DOORS SHALL BE MOUNTED AS TIGHT TO THE STRUCTURE AS POSSIBLE TO AVOID CONFLICT WITH THE OVERHEAD DOOR TRACK.
4. SERVICE BUILDING IS A MINOR REPAIR GARAGE AND IS UNCLASSIFIED. SEE MECHANICAL DRAWINGS FOR PROVIDED VENTILATION.
5. EXPRESS OIL CHANGE HAS OBTAINED EQUIPMENT AVAILABILITY AND SPECIAL VOLUME PRICING ON POWER EQUIPMENT AND LIGHTING CONTROL PACKAGES FROM REXEL. SEE CONTACTS BELOW FOR PRICING AND INFORMATION:


JEFFREY PARKER
REXEL
(M) 508-916-7758
JEFFREY.PARKER@REXELUSA.COM

COLIN BLACK
REXEL
COLIN.BLACK@REXELUSA.COM

MIKE MCMAKEN
REXEL ENERGY SOLUTIONS
(M) 906-235-2979
MIKE.MCMAKEN@REXELENERGY.COM

NOTES:

1. SEE AUXILIARY SINGLE LINE DIAGRAM ON SHEET SV-E102 FOR MORE INFORMATION ON TELEPHONE BACKBOARD. COORDINATE EXACT LOCATION.
2. PROVIDE UNISTRUT FOR CEILING MOUNTED RECEPTACLE. VERIFY EXACT LOCATION PRIOR TO ROUGH IN.
3. LOCATIONS SHOWN HERE ARE APPROXIMATE. FIELD COORDINATE EXACT LOCATION OF CONSOLE & CONDUIT WITH OWNER & ALIGNMENT LIFT SHOP DRAWINGS BEFORE ROUGH-IN.
4. PROVIDE 1 1/2" EMPTY CONDUIT FROM CONSOLE, STUBBED 8" UP ON INSIDE FACE OF EXTERIOR WALL.



1 Ground Floor Plan - Power
1/4" = 1'-0"



GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THGONBOTHAM@GW-ENG.COM | 205.317.3969



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Floor Plan - Power
& Voice/Data

Project number	24028
Date	11/08/2024
Drawn by	TH
Checked by	GW

E300

Scale 1/4" = 1'-0"



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Floor Plan - Elec.
Conn. to Mech.


Project number	24028
Date	11/08/2024
Drawn by	TH
Checked by	GW

E400

Scale 1/4" = 1'-0"

GW ENGINEERING, LLC
4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
TH@GIBOTHAM@GW-ENG.COM | 205.317.3969

- GENERAL NOTES:
- SERVICE BUILDING IS A MINOR REPAIR GARAGE AND IS UNCLASSIFIED. SEE MECHANICAL DRAWINGS FOR PROVIDED VENTILATION.
- NOTES:
- CONNECT TO 20A, 1 POLE CIRCUIT BREAKER IN PANELBOARD PPSV THROUGH LIGHTING CONTACTOR SV-1. SEE WIRING DIAGRAM ON SHET E102 FOR MORE INFORMATION.



Ground Floor Plan - Electrical Connecting to Mechanical
1/4" = 1'-0"



GENERAL REQUIREMENTS

- A. Carefully examine General Conditions, other specification Sections, and other drawings (in addition to electrical), in order to be fully acquainted with their effect on electrical work.
- B. Do all work in compliance with laws and ordinances and local authorities having jurisdiction and, where applicable, utility companies. Obtain and pay for any and all required permits, inspections, certificates of inspections and approval, and the like, and deliver such certificates to the Architect.
- C. Cooperate with other trades and contractors at job. Perform work in such manner and at such times as not to delay work of other trades. Complete all work as soon as the condition of the structure and installation of equipment will permit. Patch, in a satisfactory manner and by the proper craft, any work damaged by electrical work.
- D. All equipment (wiring devices, light fixtures, panelboards, disconnect switches, conductors, raceways, boxes, cabinets, circuit breakers, low voltage equipment, auxiliary systems, motors, machines, etc.) used for this project shall be tested by Underwriter's Laboratories, Inc and have "UL" nameplate.
- E. Coordinate placement of equipment above ceiling to facilitate proper clearance for serving of equipments.
- F. Take finish dimensions at the job site in preference to scale dimensions.
- G. Obtain from manufacturer's data on all equipment, the dimensions of which may affect electrical work. Use this data to coordinate proper service characteristics, entry locations, etc., and to ensure minimum clearances are maintained.
- H. The electrical contractor shall have had experience of at least the same size and scope as this project, on at least two other projects, within the last 5 years in order to be qualified to bid this project. This qualification shall also apply to his subcontractors.
- I. Workmen shall be experienced in their respective trade. Workmanship of installed work shall be first class and will be so judged by the Architect/Engineer. Substandard work shall be removed and replaced.
- J. The Bidders shall visit the site to thoroughly familiarize themselves with existing conditions prior to submitting their bid. No allowances will be made for lack of knowledge of existing conditions.
- K. Provide one Year warranty of conformance with drawings and specifications. In addition to the foregoing warranty, Contractor shall and does hereby warrant all materials and equipment furnished under this Division of the Specifications to be free from defects and to function or operate satisfactorily for one year after final acceptance of the work, and that any items not meeting this requirement will be made good by him without cost to owner, provided such defects or failures are not due to abuse, neglect, or lack of reasonable and ordinary maintenance.
- L. Unless otherwise specified, provide only new, standard first grade materials throughout, conforming to standards established by Underwriter's Laboratories, Inc., and so marked and labeled, together with manufacturer's brand or trademark. All equipment subject to approval of Architect/Engineer before installation. All like items shall be of one manufacture.
- M. Any equipment or materials shown on the drawings to be removed and reinstalled shall be cleaned and, if necessary repaired to like new condition prior to reinstallation.
- N. Where shown on the drawings or specified herein, furnish and install electrical equipment. Furnish all materials, hardware, equipment, labor and services required for the installation of complete and properly working installations as shown on the drawings and described herein.
- O. All work shall be executed in a workmanlike manner and shall present a neat and mechanical appearance upon completion. Care shall be exercised that all items are plumb, straight, level.
- P. Equipment grounding conductors shall be bonded at each enclosure and pole base. All equipment grounding conductors shall be connected to a common bus, bonded to the equipment enclosure.
- Q. An equipment grounding jumper shall be installed from the receptacle ground terminal to the outlet box.

CONDUITS

- A. Conduit: Rigid and IMC shall be galvanized outside and inside by hot dipping. EMT shall be Electro_Galvanized. Conduit shall be as manufactured by Republic, Wheatland, Triangle, Pittsburgh Standard, Youngstown, or Allied.
- B. Sealtight flexible metal conduit shall consist of flexible galvanized steel tubing with a liquidtight jacket of PVC. All flexible conduit shall have a copper bonding conductor wound into conduit body.
- C. Couplings and connectors on rigid and IMC shall be standard threaded type, galvanized outside and inside by hot dipping. Clamp type and threadless are not acceptable. Couplings and connectors, for rigid and IMC shall be as manufactured by Racco or Appleton.
- D. EMT connectors shall be steel, set screw unless required by code to be compression type, equipped with insulating throats. Connectors couplings shall be O-Z/Gedney 7000ST or 7000RST series, T & B 5123 - 5623 series, Midwest Electric series 1650, or equal series of Racco. Cast metal couplings will not be approved for any location.
- E. EMT couplings shall be steel, set screw unless required by code to be compression type. Couplings shall be O-Z/Gedney 6000S or 6000RS series, T & B 5120 - 5620 series, Midwest Electric series 660, or equal series of Racco. Cast metal connectors will not be approved for any location.
- F. Connectors raintight: Meyers or approved equal.
- G. Bushings on rigid and IMC shall be threaded malleable iron with integral noncombustible insulator. Rigid and IMC bushings shall be O-Z/Gedney "IBC" series, T & B BIM series, Midwest Electric series 1031 - 1043 or equal by Penn Union. Grounding bushings shall be O-Z/Gedney "IBC-L" series, T & B 3870 - 3999 series, Midwest Electric GLL series or equal by Penn Union.
- H. Watertight Flex Connectors: O-Z/Gedney, Racco, or Midwest Electric with insulating throat.
- I. EMT conduit with set screw shall be used for all branch circuits, power feeders, auxiliary, signaling and controls circuits in none hazardous dry locations for 2" and smaller. EMT may be used exposed where not subject to physical damage. EMT with compression fitting may be used in damp locations up to the 2" limit. Otherwise use rigid or intermediate hot dipped galvanized inside and out steel, threaded for screwed fitting only conduits unless specified on the drawings otherwise.
- J. Conduits shall be sized in accordance with the latest National Electrical Code except that conduits containing more than two conductors shall be sized based on 35% fill and 3/4" conduit shall contain no wire larger than #10 and no more than 6#12 or #10 wires. Conduit shall be sized larger than required above when so shown on the drawings or when required by local Code. Minimum size conduit shall be 3/4".
- K. Where conduit enters boxes, they shall be secured in place with approved insulating fittings.
- L. The use of running threads is absolutely prohibited. All conduit shall be jointed with approved conduit couplings. All couplings on IMC and rigid conduit shall be threaded.
- M. All conduits shall be supported within 3 feet of each coupling, fitting, outlet box, junction box, cabinet or equipment enclosure Conduit supports shall be independent of ducts, plumbing piping, ceiling supports, etc. Conduits shall not be supported by junction boxes, pull boxes, fixtures, etc.
- N. All exposed conduit threads, metal supports, etc., exposed to the elements or exterior of building shall be painted with rust preventive paint.

CONDUCTORS

- A. Conductors for general use, sized #10 and smaller, shall be solid copper. Conductors #8 and larger, and any size to motors or vibrating equipment shall be stranded copper.
- B. All conductor insulation shall be 600 volt THHN/THWN.
- C. Wire connections, #10 and smaller connections shall be made with insulated wire connectors with steel spring connector threads. Wire connectors shall be "Twister" Wire-Nut series as manufactured by Ideal Industries, Inc. or approved equal.
- D. On wire larger than #10, shall be made with approved solderless connectors and covered with Scotch #33 electrical tape so that the insulation is equal to conductor insulation.
- E. Connection of stranded conductors, #8 and larger, to bus bars in switchboards, panelboards, equipment enclosures, junction boxes, etc, shall be made with individual lugs, size as required by conductor, bolted to bus bar with full size bolts and nuts with lock washers.
- F. Conductors and conduits shall be continuous between outlets.
- G. No conductor shall be pulled until conduit is cleaned of all foreign matter.
- H. Where installed in panelboards, cabinets, wireways, switches and equipment wire and cable shall be neatly formed and tied.
- I. Conductors sized #10 AWG and below shall have permanently colored insulation. Conductors sized #8 AWG and above shall be color coded by either permanently colored insulation or by means of colored tape applied to the conductor within 12" of each termination and in each enclosure, junction box, etc.

JUNCTION BOXES

- A. Shall be standard type, with knockouts, made of hot dipped galvanized steel, Steel City, Racco, Appleton, or Bowers.
- B. Ceiling outlet boxes shall be 4" octagon 1-1/2" deep or larger as required due to number of wires.
- C. Boxes shall be provided with approved 3/8" fixture studs when required to support stem mounted light fixtures.
- D. Except when located in exposed concrete block, switch and receptacle boxes shall be 4" square with trim ring for single gang installation. Appropriate gang boxes shall be used for mounting ganged switches.
- E. When installed in exposed concrete block, switch and receptacle boxes shall be square type designed for exposed block installation.
- F. Outlet boxes shall be securely fastened to structural members and shall not be supported by dry wall, gypsum board, plaster, etc. The device or plate installed in conjunction with the outlet box shall not be used for support. There shall be no more knockouts opened in any outlet box than are required. Boxes shall be sealed during construction.
- G. Under no circumstances shall through-the-wall boxes be used. Back to back boxes shall be staggered at least 3 inches, except in fire rated partitions, in which case, back to back boxes shall be staggered at least 24 inches.
- H. Outlet boxes two gangs and wider shall not be supported by attachment clips or any means which supports the boxes from less than two opposite sides of the box. Such outlet boxes in stud walls shall be supported securely by support members spanning between studs.
- I. Outlet boxes installed in fire rated partitions shall be boxed in with wall board or other suitable fire rated material as required to maintain or restore the fire rating of the assembly.

WIRING DEVICES

- A. Manufacturers' Names: Shortened versions (shown in parentheses) of the following manufacturers' names are used in other Part 2 articles:
- Cooper Wiring Devices: a division of Cooper Industries, Inc. (Cooper).
 - Hubbell Incorporated; Wiring Device-Kellems (Hubbell).
 - Leviton Mfg. Company Inc. (Leviton).
 - Pass & Seymour/Legrand; Wiring Devices & Accessories (Pass & Seymour).
- B. Convenience Receptacles, 125 V, 20 A: Comply with NEMA WD 1, NEMA WD 6 configuration 5-20R, and UL 498.
- Products: Subject to compliance with requirements, provide one of the following:
 - Cooper; 5351 (single), 5352 (duplex).
 - Hubbell; HBL5351 (single), CR5352 (duplex).
 - Leviton; 5891 (single), 5352 (duplex).
 - Pass & Seymour; 5381 (single), 5352 (duplex).
- C. Duplex GFCI Convenience Receptacles, 125 V, 20 A:
- Products: Subject to compliance with requirements, provide one of the following:
 - Cooper; GF20.
 - Pass & Seymour; 2084.
- A. Switches, 120/277 V, 20 A:
- Products: Subject to compliance with requirements, provide one of the following:
 - Cooper; 2221 (single pole), 2222 (two pole), 2223 (three way), 2224 (four way).
 - Hubbell; CS1221 (single pole), CS1222 (two pole), CS1223 (three way), CS1224 (four way).
 - Leviton; 1221-2 (single pole), 1222-2 (two pole), 1223-2 (three way), 1224-2 (four way).
 - Pass & Seymour; 20AC1 (single pole), 20AC2 (two pole), 20AC3 (three way), 20AC4 (four way).
- B. Single and combination plate types to match corresponding wiring devices.
- Plate-Securing Screws: Metal with head color to match plate finish.
 - Material for Finished Spaces: stainless steel 302 **0.04-inch- (1-mm)** thick.
 - Material for Unfinished Spaces: Galvanized steel.
 - Material for Damp Locations: Cast aluminum with spring-loaded lift cover, and listed and labeled for use in "wet locations."
- F. Wet-Location, Weatherproof Cover Plates: NEMA 250, complying with type 3R weather-resistant, extra duty, die-cast aluminum with lockable in-use cover.
- G. Color: Wiring device catalog numbers in Section Text do not designate device color.
- Wiring Devices Connected to Normal Power System: Gray unless otherwise indicated or required by NFPA 70 or device listing.
 - Wiring Devices Connected to Emergency Power System: Red.
- H. Comply with NECA 1, including the mounting heights listed in that standard, unless otherwise noted.
- I. Coordination with Other Trades:
- Take steps to insure that devices and their boxes are protected. Do not place wall finish materials over device boxes and do not cut holes for boxes with routers that are guided by riding against outside of the boxes.
 - Keep outlet boxes free of plaster, drywall joint compound, mortar, cement, concrete, dust, paint, and other material that may contaminate the raceway system, conductors, and cables.
 - Install device boxes in brick or block walls so that the cover plate does not cross a joint unless the joint is troweled flush with the face of the wall.
 - Install wiring devices after all wall preparation, including painting, is complete.
- J. Conductors:
- Do not strip insulation from conductors until just before they are spliced or terminated on devices.
 - Strip insulation evenly around the conductor using tools designed for the purpose. Avoid scoring or nicking of solid wire or cutting strands from stranded wire.
 - The length of free conductors at outlets for devices shall meet provisions of NFPA 70, Article 300, without pigtails.
 - Existing Conductors:
 - Cut back and pigtail, or replace all damaged conductors.
 - Straighten conductors that remain and remove corrosion and foreign matter.
 - Pigtailing existing conductors is permitted provided the outlet box is large enough.
- K. Device Installation:
- Replace all devices that have been in temporary use during construction or that show signs that they were installed before building finishing operations were complete.
 - Keep each wiring device in its package or otherwise protected until it is time to connect conductors.
 - Do not remove surface protection, such as plastic film and smudge covers, until the last possible moment.
 - Connect devices to branch circuits using pigtails that are not less than 6 inches (152 mm) in length.
 - When there is a choice, use side wiring with binding-head screw terminals. Wrap solid conductor tightly clockwise, 2/3 to 3/4 of the way around terminal screw.
 - Use a torque screwdriver when a torque is recommended or required by the manufacturer.
 - When conductors larger than No. 12 AWG are installed on 15- or 20-A circuits, splice No. 12 AWG pigtails for device connections.
 - Tighten unused terminal screws on the device.
 - When mounting into metal boxes, remove the fiber or plastic washers used to hold device mounting screws in yokes, allowing metal-to-metal contact.

L. Receptacle Orientation:

- Install ground pin of vertically mounted receptacles up, and on horizontally mounted receptacles to the right.
- Install hospital-grade receptacles in patient-care areas with the ground pin or neutral blade at the top.

M. Device Plates: Do not use oversized or extra-deep plates. Repair wall finishes and remount outlet boxes when standard device plates do not fit flush or do not cover rough wall opening.

N. Dimmers:

- Install dimmers within terms of their listing.
- Verify that dimmers used for fan speed control are listed for that application.
- Install unshared neutral conductors on line and load side of dimmers according to manufacturers' device listing conditions in the written instructions.

O. Arrangement of Devices: Unless otherwise indicated, mount flush, with long dimension vertical and with grounding terminal of receptacles on top. Group adjacent switches under single, multigang wall plates.

P. Adjust locations of floor service outlets and service poles to suit arrangement of partitions and furnishings.

PANELBOARDS

A. Product Data: For each type of panelboard, switching and overcurrent protective device, transient voltage suppression device, accessory, and component indicated. Include dimensions and manufacturers' technical data on features, performance, electrical characteristics, ratings, and finishes.

B. Source Limitations: Obtain panelboards, overcurrent protective devices, components, and accessories from single source from single manufacturer.

- Comply with NEMA PB 1 including handling requirements.

D. Comply with NFPA 70.

E. Coordinate layout and installation of panelboards and components with other construction that penetrates walls or is supported by them, including electrical and other types of equipment, raceways, piping, encumbrances to workspace clearance requirements, and adjacent surfaces. Maintain required workspace clearances and required clearances for equipment access doors and panels.

F. Enclosures: Flush-and surface-mounted cabinets as shown on drawings.

- Rated for environmental conditions at installed location.
 - Outdoor Locations: NEMA 250, Type 4X (stainless steel).
 - Indoor location NEMA 1 with hinged Front Cover: Entire front trim hinged to box and with standard door within hinged trim cover.
- Finishes:
 - Back Boxes: Stainless Steel.
- Directory Card: Inside panelboard door, mounted in transparent card holder.

G. Phase, Neutral, and Ground Buses:

- Material: Hard-drawn copper, 98 percent conductivity.
- Equipment Ground Bus: Adequate for feeder and branch-circuit equipment grounding conductors; bonded to box.

H. Future Devices: Mounting brackets, bus connections, filler plates, and necessary appurtenances required for future installation of devices.

I. Panelboard Short-Circuit Current Rating: Fully rated to interrupt symmetrical short-circuit current available at terminals. See drawings for rating.

J. Manufacturers: Subject to compliance with requirements, provide products by either: Eaton, General Electric Company; Siemens, and Square D.

K. Branch Overcurrent Protective Devices for Circuit-Breaker Frame Sizes Larger Than 125 A: Bolt-on circuit breakers; plug-in circuit breakers where individual positive-locking device requires mechanical release for removal. Branch circuit breakers shall be HACR type. Molded-Case Circuit Breaker (MCCB): Comply with UL 489, with interrupting capacity to meet available fault currents.

L. Examine panelboards before installation. Reject panelboards that are damaged or rusted or have been subjected to water saturation.

M. Examine elements and surfaces to receive panelboards for compliance with installation tolerances and other conditions affecting performance of the Work.

N. Proceed with installation only after unsatisfactory conditions have been corrected.

O. Install panelboards and accessories according to NEMA PB 1.1.

P. Mount panelboard cabinet plumb and rigid without distortion of box. Mount recessed panelboards with fronts uniformly flush with wall finish and mating with back box.

Q. Install filler plates in unused spaces.

R. Arrange conductors in gutters into groups and bundle and wrap with wire ties after completing load balancing.

TEMPORARY POWER

A. The electrical contractor shall provide temporary electrical wiring for construction. The temporary service shall be single phase, three wire, 120/240 volts fused at main disconnect. All receptacles on this temporary service shall be protected by ground fault interruptible circuit breakers.



Express Oil Change & Tire Engineers
Service Building
Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

Specifications

Project number	24028
Date	11/08/2024
Drawn by	TH
Checked by	GW
E500	
Scale	NO SCALE

GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THWGNBOTHAM@GW-ENG.COM | 205.317.3869



Express Oil Change & Tire Engineers

Service Building

Northport, Alabama

FINAL

No.	Description	Date

© 2024 Aho Architects, LLC.
All Rights Reserved.

COMcheck

Project number	24028
Date	11/08/2024
Drawn by	TH
Checked by	GW
E600	
Scale	NO SCALE

GW ENGINEERING, LLC

4120 OVERLOOK CIRCLE, TRUSSVILLE, AL 35173
GWAMAE@GW-ENG.COM | 205.413.4112
THIGGINBOTHAM@GW-ENG.COM | 205.317.3969

COMcheck Software Version 4.1.5.5

Interior Lighting Compliance Certificate

Project Information

Energy Code: 2015 IECC

Project Title: Express Oil Change & Tire Engineers - Service Building

Project Type: New Construction

Construction Site: Northport, AL

Owner/Agent: Express Oil Change & Tire Engineers

Designer/Contractor: Taylor Higginbotham
GW Engineering
Trussville, AL 35173
205-317-3969
thigginbotham@gw-eng.com

Credits: 1.0 Required 1.0 Proposed
Reduced Lighting Power: 1.0 credit

Allowed Interior Lighting Power

A Area Category	B Floor Area (ft²)	C Allowed Watts / ft²	D Allowed Watts (B X C)
1-Service Bldg. (Automotive Facility)	2747	0.72	1978
Total Allowed Watts =			1978

Proposed Interior Lighting Power

A Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast	B Lamps/ Fixture	C # of Fixtures	D Fixture Watt.	E (C X D)
1-Service Bldg. (Automotive Facility)				
LED 7: Other:	1	18	100	1800
LED 8: Other:	1	1	35	35
Total Proposed Watts =			1835	

Interior Lighting PASSES: Design 7% better than code

Interior Lighting Compliance Statement

Compliance Statement: The proposed interior lighting design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed interior lighting systems have been designed to meet the 2015 IECC requirements in COMcheck Version 4.1.5.5 and to comply with any applicable mandatory requirements listed in the Inspection Checklist.

Taylor Higginbotham

Signature *Taylor Higginbotham*

11/08/2024

Date

Project Title: Express Oil Change & Tire Engineers - Service Building

Report date: 11/08/24

Data filename: C:\Users\Taylor Higginbotham\Documents\GW Engineering\2024 - AHO - EDC Guntersville, AL\Project Files\08 - Lighting Calculations & Cutsheets\SV Building\Comcheck - EDC Guntersville, AL - SV Bldg.cck

Page 1 of 7

COMcheck Software Version 4.1.5.5

Exterior Lighting Compliance Certificate

Project Information

Energy Code: 2015 IECC

Project Title: Express Oil Change & Tire Engineers - Service Building

Project Type: New Construction

Exterior Lighting Zone: 2 (Neighborhood business district (LZ2))

Construction Site: Northport, AL

Owner/Agent: Express Oil Change & Tire Engineers

Designer/Contractor: Taylor Higginbotham
GW Engineering
Trussville, AL 35173
205-317-3969
thigginbotham@gw-eng.com

Allowed Exterior Lighting Power

A Area/Surface Category	B Quantity	C Allowed Watts / Unit	D Tradable Wattage	E Allowed Watts (B X C)
Illuminated area of facade wall or surface	750 ft²	0.1	No	75
Entry canopy	9 ft²	0.25	Yes	2
Total Tradable Watts (a) =			2	
Total Allowed Watts =			77	
Total Allowed Supplemental Watts (b) =			600	

a) Wattage tradeoffs are only allowed between tradable areas/surfaces.
b) A supplemental allowance equal to 600 watts may be applied toward compliance of both non-tradable and tradable areas/surfaces.

Proposed Exterior Lighting Power

A Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast	B Lamps/ Fixture	C # of Fixtures	D Fixture Watt.	E (C X D)
Illuminated area of facade wall or surface (750 ft²): Non-tradable Wattage				
LED 2: L4: Other:	1	2	33	66
Entry canopy (9 ft²): Tradable Wattage	1	4	33	132
LED 3: L4E: Other:				
Total Tradable Proposed Watts =			132	

Exterior Lighting PASSES: Design 78% better than code

Exterior Lighting Compliance Statement

Compliance Statement: The proposed exterior lighting design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed exterior lighting systems have been designed to meet the 2015 IECC requirements in COMcheck Version 4.1.5.5 and to comply with any applicable mandatory requirements listed in the Inspection Checklist.

Taylor Higginbotham

Signature *Taylor Higginbotham*

11/08/2024

Date

Project Title: Express Oil Change & Tire Engineers - Service Building

Report date: 11/08/24

Data filename: C:\Users\Taylor Higginbotham\Documents\GW Engineering\2024 - AHO - EDC Guntersville, AL\Project Files\08 - Lighting Calculations & Cutsheets\SV Building\Comcheck - EDC Guntersville, AL - SV Bldg.cck

Page 2 of 7